User Login API

Authenticates a user and returns an access token. Use the token as the Bearer token on all other APIs.

URL

```
POST  https://10.10.11.54:8080/IdentityAccessMgmt/user/login
```

Headers

Header	Value	Mandatory
Content-Type	application/json	Yes
X-Original-Forwarded-For	Client IP address of the end user	Yes
X-Geolocation-Latitude	Latitude of the caller, e.g. 12.9716	Yes
X-Geolocation-Longitude	Longitude of the caller, e.g. 77.5946	Yes

Request body

```
{
  "userId": "las",
  "programMngrId": "LAS",
  "password": "<password>"
}
```

Request fields

Field	Type	Description	Example
userId	String	User id	las
programMngrId	String	Program manager the user is registered under. **Note:** the field name is programMngrId in this API.	LAS
password	String	Password of the user	<password>

Response body (HTTP 200)

```
{
  "transactionId": "7345430166900109312",
  "correlationId": "7341821415336603648",
  "timeStamp": "2025-06-30T07:07:03.512Z",
  "accessToken": "eyJhbGciOiJSUzI1NiIsInR5cCI..."
}
```

This API does not need an Authorization header. The program manager id must match the one the user is registered under.

Keep *transactionId* and *correlationId* for support and reconciliation.

Status codes

Code	Description
200	Login successful. The access token is returned in *accessToken*.
404	Resource not found.
500	Internal server error.

Error response

```
{
  "timestamp": "30-09-2026 06:20:47",
  "transactionId": "7510946730856935424",
  "correlationId": "string",
  "definedErrorCode": "The program manager not found",
  "status": 404,
  "errorCode": "The program manager not found",
  "errorMessage": "The program manager not found",
  "debugMessage": "The program manager not found"
}
```