Update Person Custom Field Value API

Updates the value of a single custom field of a registered person.

URL

```
PUT  https://10.10.11.54:8080/customermgmt/person/customField/value
```

Headers

Header	Value	Mandatory
Authorization	Bearer <access-token>	Yes
Content-Type	application/json	Yes
X-Original-Forwarded-For	Client IP address of the end user	Yes
X-Geolocation-Latitude	Latitude of the caller, e.g. 12.9716	Yes
X-Geolocation-Longitude	Longitude of the caller, e.g. 77.5946	Yes

Request body

```
{
  "personId": "88655489",
  "programManagerId": "ibkart",
  "customFieldId": "pan",
  "customFieldValue": "sdfghjkwertyu"
}
```

Request fields

Field	Type	Description	Example
personId	String	Unique identifier of the person	88655489
programManagerId	String	Program manager the person belongs to	ibkart
customFieldId	String	Identifier of the custom field to update. Must already be defined for the program manager.	pan
customFieldValue	String	New value for the custom field	sdfghjkwertyu

Response body (HTTP 200)

```
{
  "transactionId": "7345430166900109312",
  "correlationId": "7341821415336603648",
  "timeStamp": "2025-06-30T07:07:03.512Z"
}
```

Keep *transactionId* and *correlationId* for support and reconciliation.

Status codes

Code	Description
200	Custom field value updated successfully.
401	Missing or invalid access token.
404	Resource not found (for example, the person or program manager does not exist).
500	Internal server error.

Error response

```
{
  "timestamp": "30-09-2026 06:20:47",
  "transactionId": "7510946730856935424",
  "correlationId": "string",
  "definedErrorCode": "The program manager not found",
  "status": 404,
  "errorCode": "The program manager not found",
  "errorMessage": "The program manager not found",
  "debugMessage": "The program manager not found"
```

```
}
```