Update Person Custom Fields API

Updates the values of multiple custom fields of a registered person in a single call.

URL

```
PUT  https://10.10.11.54:8080/customermgmt/person/customFields
```

Headers

Header	Value	Mandatory
Authorization	Bearer <access-token>	Yes
Content-Type	application/json	Yes
X-Original-Forwarded-For	Client IP address of the end user	Yes
X-Geolocation-Latitude	Latitude of the caller, e.g. 12.9716	Yes
X-Geolocation-Longitude	Longitude of the caller, e.g. 77.5946	Yes

Request body

```
{
  "personId": "88655489",
  "programManagerId": "ibkart",
  "customFields": {
    "pan": "sdfghjkwertyu",
    "aadhar": "1234567890oiuhgf",
    "dpr": "qwertyuioikjhgfdxcv",
    "landDocument": "qudghavbhvhasv",
    "bankStamtemnt": "gvasdtqyfetgqvgewvqye",
    "invoice": "qyfsdgqvsdgqvvd"
  }
}
```

Request fields

Field	Type	Description	Example
personId	String	Unique identifier of the person	88655489
programManagerId	String	Program manager the person belongs to	ibkart
customFields	Object	Map of customFieldId to new value. Each custom field must already be defined for the program manager.	{ "pan": "sdfghjkwertyu", "aadhar": "1234567890oiuhgf" }

Response body (HTTP 200)

```
{
  "transactionId": "7345430166900109312",
  "correlationId": "7341821415336603648",
  "timeStamp": "2025-06-30T07:07:03.512Z"
}
```

Keep *transactionId* and *correlationId* for support and reconciliation.

Status codes

Code	Description
200	Custom fields updated successfully.
401	Missing or invalid access token.
404	Resource not found (for example, the person or program manager does not exist).
500	Internal server error.

Error response

```
{
  "timestamp": "30-09-2026 06:20:47",
  "transactionId": "7510946730856935424",
  "correlationId": "string",
```

```
  "definedErrorCode": "The program manager not found",
  "status": 404,
  "errorCode": "The program manager not found",
  "errorMessage": "The program manager not found",
  "debugMessage": "The program manager not found"
}
```