Open Regular Wallet API

Opens a regular wallet for a registered person. A person can hold multiple wallets, one per tag.

URL

```
POST  https://10.10.11.54:8080/regularWallet/
```

Headers

Header	Value	Mandatory
Authorization	Bearer <access-token>	Yes
Content-Type	application/json	Yes
X-Original-Forwarded-For	Client IP address of the end user	Yes
X-Geolocation-Latitude	Latitude of the caller, e.g. 12.9716	Yes
X-Geolocation-Longitude	Longitude of the caller, e.g. 77.5946	Yes

Request body

```
{
  "programMngrId": "ibkart",
  "personId": "919824561458",
  "groupId": "Merchant",
  "tagId": "savings wallet"
}
```

Request fields

Field	Type	Description	Example
programMngrId	String	Program manager id. **Note:** the field name is programMngrId in this API.	ibkart
personId	String	Registered person for whom the wallet is opened	919824561458
groupId	String	Group of the person	Merchant
tagId	String	Tag that identifies the type of wallet	savings wallet

Response body (HTTP 201 Created)

```
{
  "transactionId": "7345430166900109312",
  "correlationId": "7341821415336603648",
  "timeStamp": "2025-06-30T07:07:03.512Z"
}
```

Keep *transactionId* and *correlationId* for support and reconciliation.

Status codes

Code	Description
201	Wallet opened successfully.
401	Missing or invalid access token.
404	Resource not found (for example, the program manager or person does not exist).
409	The wallet already exists.
500	Internal server error.

Error response

```
{
  "timestamp": "30-09-2026 06:20:47",
  "transactionId": "7510946730856935424",
  "correlationId": "string",
  "definedErrorCode": "The program manager not found",
  "status": 404,
  "errorCode": "The program manager not found",
  "errorMessage": "The program manager not found",
```

```
  "debugMessage": "The program manager not found"
}
```