SMART CARD

Complete Source Code Archive

Production Repository Compilation | Vercel Live Edition

ARCHIVE METADATA

Platform Name:	Smart Card
Live Domain:	https://smart-card-inky.vercel.app
GitHub Repository:	https://github.com/ajaybyzaher11-cloud/Smart-card.git
Total Files Included:	30 production source files
Compiled On:	Sun, 01 Nov 2026 02:37:50 GMT
Security Level:	Protected (Admin SHA-256 Auth & Nanoid Integrity)

Generated for internal auditing, verification, and complete technical archiving.

TABLE OF CONTENTS - SOURCE FILES INDEX

01	index.html	58 lines
02	package.json	49 lines
03	vite.config.ts	101 lines
04	tsconfig.json	29 lines
05	vercel.json	13 lines
06	server.ts	951 lines
07	metadata.json	11 lines
08	api/redirect.ts	267 lines
09	src/main.tsx	6 lines
10	src/App.tsx	253 lines
11	src/index.css	62 lines
12	src/types/qr.ts	69 lines
13	src/types/jsqr.d.ts	37 lines
14	src/lib/auth.ts	374 lines
15	src/lib/deepLinks.ts	737 lines
16	src/lib/qrService.ts	885 lines
17	src/lib/firebase.ts	73 lines
18	src/views/AdminLoginView.tsx	131 lines
19	src/views/AdminDashboardView.tsx	1292 lines
20	src/views/HomeLandingView.tsx	372 lines
21	src/views/CustomerActivationView.tsx	483 lines
22	src/views/SmartRedirectView.tsx	414 lines
23	src/views/CardExpiredView.tsx	140 lines
24	src/components/BrandIcons.tsx	656 lines
25	src/components/BulkGenerateModal.tsx	389 lines
26	src/components/DeveloperSettingsModal.tsx	252 lines
27	src/components/EditQrModal.tsx	1005 lines
28	src/components/PrintSheetModal.tsx	194 lines
29	src/components/QrScannerModal.tsx	168 lines
30	src/components/UploadQrModal.tsx	320 lines

FILE: index.html 58 lines | 2.9 KB

```
<!doctype html>
<html lang="ar" dir="rtl">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0, maximum-scale=5.0, user-scalabl
    <title>Smart Card - bvDb†7bvBb’ 'dF0d6Jb“Â÷F—FÆSà
    <meta name="description" content="dVFcV) Smart Card dF*d†Dd¦/ d†%bö'c ) c Ed†2 QR bvDböJdf'dVJd6Jb’ 'dF0d6Jb’ Ec
    <meta name="theme-color" content="#09090b" />
    <meta name="mobile-web-app-capable" content="yes" />
    <meta name="apple-mobile-web-app-capable" content="yes" />
    <meta name="apple-mobile-web-app-status-bar-style" content="black-translucent" />
    <meta name="apple-mobile-web-app-title" content="Smart Card" />
    <meta property="og:title" content="Smart Card - bvDb†7bvBb’ 'dF0d6Jb’" óà
    <meta property="og:description" content="dVFcV) Smart Card dF*d†Dd¦/ d†%bö'c ) c Ed†2 QR bvDböJdf'dVJd6Jb’ 'dF0d
    <meta property="og:type" content="website" />
    <meta name="twitter:card" content="summary_large_image" />
    <link rel="icon" type="image/x-icon" href="/favicon.ico" />
    <link rel="icon" type="image/png" href="/pwa-192x192.png" />
    <link rel="apple-touch-icon" href="/apple-touch-icon.png" />
    <link rel="manifest" href="/manifest.webmanifest" />
    <meta property="og:image" content="/logo.png" />
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;700;800&famil
    <script>
      (function() {
        try {
          var p = window.location.pathname || '';
          if (p.indexOf('/q/') === 0) {
            var qid = p.replace('/q/', '').split('?')[0].split('/')[0];
            if (qid) {
              var raw = localStorage.getItem('smart_qr_codes_local_cache');
              if (raw) {
                var c = JSON.parse(raw);
                var item = c[qid];
                if (item && item.is_active && item.target_url && item.app_type !== 'bank') {
                  var dest = item.target_url;
                  var isPhoneOnly = (item.app_type === 'wallet' && !/^https?:\/\//i.test(dest) && !dest.i
                  if (!isPhoneOnly) {
                    if (dest.indexOf('http://') !== 0 && dest.indexOf('https://') !== 0 && dest.indexOf('
                      dest = 'https://' + dest;
                    }
                    window.location.replace(dest);
                  }
                }
              }
            }
          }
        } catch (e) {}
      })();
    </script>
  </head>
  <body class="bg-[#09090b] text-slate-100 font-sans antialiased min-h-screen selection:bg-amber-500 sele
    <div id="root"></div>
    <script type="module" src="/src/main.tsx"></script>
  </body>
</html>

```

FILE: package.json 49 lines | 1.2 KB

```
{
  "name": "react-example",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "tsx server.ts",
    "start": "tsx server.ts",
    "build": "vite build",
    "preview": "vite preview",
    "clean": "rm -rf dist server.js",
    "lint": "tsc --noEmit"
  },
  "dependencies": {
    "@google/genai": "^2.4.0",
    "@tailwindcss/vite": "^4.3.3",
    "@types/qrcode": "^1.5.6",
    "@vitejs/plugin-react": "^6.1.1",
    "arabic-persian-reshaper": "^1.0.1",
    "bidi-js": "^1.1.0",
    "dotenv": "^17.2.3",
    "express": "^4.21.2",
    "express-rate-limit": "^8.7.1",
    "firebase": "^13.0.0",
    "jsqr": "^1.4.0",
    "lucide-react": "^0.546.0",
    "motion": "^12.23.24",
    "nanoid": "^6.0.2",
    "pdfkit": "^0.20.2",
    "qrcode": "^1.5.4",
    "react": "^19.0.1",
    "react-dom": "^19.0.1",
    "tsx": "^4.21.0",
    "vite": "^8.3.0"
  },
  "devDependencies": {
    "@types/express": "^4.17.21",
    "@types/node": "^22.14.0",
    "@types/pdfkit": "^0.17.7",
    "@types/react": "^19.3.0",
    "@types/react-dom": "^19.3.0",
    "autoprefixer": "^10.4.21",
    "esbuild": "^0.25.0",
    "tailwindcss": "^4.3.3",
    "typescript": "^7.0.2",
    "vite-plugin-pwa": "^2.0.0"
  }
}

```

FILE: vite.config.ts 101 lines | 3.0 KB

```ts
import tailwindcss from '@tailwindcss/vite';
import react from '@vitejs/plugin-react';
import path from 'path';
import { defineConfig } from 'vite';
import { VitePWA } from 'vite-plugin-pwa';

export default defineConfig(() => {
  return {
    plugins: [
      react(),
      tailwindcss(),
      VitePWA({
        registerType: 'autoUpdate',
        includeAssets: ['favicon.ico', 'apple-touch-icon.png', 'logo.png'],
        manifest: {
          id: '/',
          name: 'Smart Card - bvDb†7bvBb’ 'dF0d6Jb’rÀ
          short_name: 'Smart Card',
          description: 'dVFc†HdV) bV/bv1b’ Hb†1dV,b’ Cc Hb¢ Hb†7bvBbv* bvDböAc’ 'dF0d6Jb’ Hb¦-d†JdB 'dF#dVHbvD bvDd
          theme_color: '#09090b',
          background_color: '#09090b',
          display: 'standalone',
          orientation: 'portrait',
          start_url: '/',
          scope: '/',
          icons: [
            {
              src: '/pwa-192x192.png',
              sizes: '192x192',
              type: 'image/png',
              purpose: 'any',
            },
            {
              src: '/pwa-512x512.png',
              sizes: '512x512',
              type: 'image/png',
              purpose: 'any',
            },
            {
              src: '/pwa-maskable-512x512.png',
              sizes: '512x512',
              type: 'image/png',
              purpose: 'maskable',
            },
          ],
        },
        workbox: {
          maximumFileSizeToCacheInBytes: 6 * 1024 * 1024,
          globPatterns: ['**/*.{js,css,html,ico,png,svg,ttf,woff,woff2}'],
          runtimeCaching: [
            {
              urlPattern: /^https:\/\/fonts\.googleapis\.com\/.*/i,
              handler: 'CacheFirst',
              options: {
                cacheName: 'google-fonts-cache',
                expiration: {
                  maxEntries: 10,
                  maxAgeSeconds: 60 * 60 * 24 * 365,
                },
                cacheableResponse: {
                  statuses: [0, 200],
                },
              },
            },
            {
              urlPattern: /^https:\/\/fonts\.gstatic\.com\/.*/i,
              handler: 'CacheFirst',
              options: {
```

FILE (cont.): vite.config.ts

```
                cacheName: 'gstatic-fonts-cache',
                expiration: {
                  maxEntries: 10,
                  maxAgeSeconds: 60 * 60 * 24 * 365,
                },
                cacheableResponse: {
                  statuses: [0, 200],
                },
              },
            },
          ],
        },
        devOptions: {
          enabled: true,
          type: 'module',
        },
      }),
    ],
    resolve: {
      alias: {
        '@': path.resolve(__dirname, '.'),
      },
    },
    server: {
      // HMR is disabled in AI Studio via DISABLE_HMR env var.
      // Do not modify—file watching is disabled to prevent flickering during agent edits.
      hmr: process.env.DISABLE_HMR !== 'true',
      // Disable file watching when DISABLE_HMR is true to save CPU during agent edits.
      watch: process.env.DISABLE_HMR === 'true' ? null : {},
    },
  };
});

```

FILE: tsconfig.json 29 lines | 0.6 KB

```
{
  "compilerOptions": {
    "target": "ES2022",
    "experimentalDecorators": true,
    "useDefineForClassFields": false,
    "module": "ESNext",
    "types": ["vite/client", "vite-plugin-pwa/client"],
    "lib": [
      "ES2022",
      "DOM",
      "DOM.Iterable"
    ],
    "skipLibCheck": true,
    "moduleResolution": "bundler",
    "isolatedModules": true,
    "moduleDetection": "force",
    "allowJs": true,
    "jsx": "react-jsx",
    "paths": {
      "@/*": [
        "./*"
      ]
    },
    "allowImportingTsExtensions": true,
    "noEmit": true
  },
  "exclude": ["dist"]
}

```

FILE: vercel.json 13 lines | 0.2 KB

```
{
  "rewrites": [
    {
      "source": "/q/:id",
      "destination": "/api/redirect?id=:id"
    },
    {
      "source": "/(.*)",
      "destination": "/index.html"
    }
  ]
}

```

FILE: server.ts 951 lines | 30.6 KB

```ts
import express from 'express';
import fs from 'fs';
import path from 'path';
import crypto from 'crypto';
import { fileURLToPath } from 'url';
import { nanoid } from 'nanoid';
import rateLimit from 'express-rate-limit';

const __filename = fileURLToPath(import.meta.url);
const __dirname = path.dirname(__filename);

const app = express();
const PORT = process.env.PORT || 3000;
const DATA_DIR = path.join(__dirname, 'data');
const DB_FILE = path.join(DATA_DIR, 'qr_codes.json');
const SETTINGS_FILE = path.join(DATA_DIR, 'settings.json');
const AUTH_FILE = path.join(DATA_DIR, 'auth.json');
const SESSIONS_FILE = path.join(DATA_DIR, 'sessions.json');

app.use(express.json({ limit: '1mb' }));

// Ensure data directory exists
if (!fs.existsSync(DATA_DIR)) {
  fs.mkdirSync(DATA_DIR, { recursive: true });
}

// Default Password Hash (SHA-256 for "admin1234")
const DEFAULT_BASE_HASH = 'ac9689e2272427085e35b9d3e3e8bed88cb3434828b43b86fc0596cad4c6e270';

function hashString(plain: string): string {
  return crypto.createHash('sha256').update(plain).digest('hex');
}

// Rate Limiting Guards
const generalApiLimiter = rateLimit({
  windowMs: 5 * 60 * 1000, // 5 minutes
  max: 300,
  standardHeaders: true,
  legacyHeaders: false,
  message: { success: false, error: 'Too many requests, please try again later.' },
});

const authRateLimiter = rateLimit({
  windowMs: 15 * 60 * 1000, // 15 minutes
  max: 15,
  standardHeaders: true,
  legacyHeaders: false,
  message: { success: false, error: 'b¦E b¦,bvHc" 'dF-bò 'dF#d&5d’ DdV-bvHdF'b¢ *c6,d¦D bvDbö.d†D`Â Jc ,d’ 'dFEbÖ'd†
});

const bulkRateLimiter = rateLimit({
  windowMs: 15 * 60 * 1000, // 15 minutes
  max: 40,
  standardHeaders: true,
  legacyHeaders: false,
  message: { success: false, error: 'b¦E b¦,bvHc" 'dF-bò 'dFEc6Ed†- dF*d†Dd¦/ bvDb6Cd†'bò (bvDbÆEdF)`Â Jc ,d’ 'dFEbÖ
});

app.use('/api/', generalApiLimiter);

// --- Session Store & Auth Management ---
interface AdminSession {
  token: string;
  created_at: string;
  expires_at: number; // timestamp in ms
}

function loadSessions(): Record<string, AdminSession> {
```

FILE (cont.): server.ts

```
  try {
    if (fs.existsSync(SESSIONS_FILE)) {
      const data = JSON.parse(fs.readFileSync(SESSIONS_FILE, 'utf-8'));
      const now = Date.now();
      const valid: Record<string, AdminSession> = {};
      for (const [k, v] of Object.entries(data)) {
        if (v && typeof v === 'object' && (v as AdminSession).expires_at > now) {
          valid[k] = v as AdminSession;
        }
      }
      return valid;
    }
  } catch {}
  return {};
}

function saveSessions(sessions: Record<string, AdminSession>): void {
  try {
    fs.writeFileSync(SESSIONS_FILE, JSON.stringify(sessions, null, 2), 'utf-8');
  } catch (err) {
    console.error('Failed to save sessions:', err);
  }
}

let firebaseConfig: any = null;
try {
  const cfgPath = path.join(__dirname, 'firebase-applet-config.json');
  if (fs.existsSync(cfgPath)) {
    firebaseConfig = JSON.parse(fs.readFileSync(cfgPath, 'utf-8'));
  }
} catch {}

async function syncPasswordToFirestore(newHash: string): Promise<void> {
  if (!firebaseConfig?.projectId || !firebaseConfig?.apiKey) return;
  try {
    const pId = firebaseConfig.projectId;
    const dbId = firebaseConfig.firestoreDatabaseId || '(default)';
    const key = firebaseConfig.apiKey;
    const docUrl = `https://firestore.googleapis.com/v1/projects/${pId}/databases/${dbId}/documents/setti
    await fetch(docUrl, {
      method: 'PATCH',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({
        fields: {
          hash: { stringValue: newHash },
          updated_at: { stringValue: new Date().toISOString() },
          migrated: { booleanValue: true },
        },
      }),
    });
  } catch (err) {
    console.warn('Failed to sync password to Firestore from server:', err);
  }
}

async function syncPasswordFromFirestore(): Promise<void> {
  if (!firebaseConfig?.projectId || !firebaseConfig?.apiKey) return;
  try {
    const pId = firebaseConfig.projectId;
    const dbId = firebaseConfig.firestoreDatabaseId || '(default)';
    const key = firebaseConfig.apiKey;
    const docUrl = `https://firestore.googleapis.com/v1/projects/${pId}/databases/${dbId}/documents/setti
    const res = await fetch(docUrl);
    if (res.ok) {
      const data = await res.json();
      const hashVal = data.fields?.hash?.stringValue;
      if (hashVal && hashVal.length === 64) {
        fs.writeFileSync(AUTH_FILE, JSON.stringify({ hash: hashVal, updated_at: new Date().toISOString()
```

FILE (cont.): server.ts

```
      }
    }
  } catch {}
}
// Sync with Firestore on startup
syncPasswordFromFirestore().catch(() => {});

function getStoredPasswordHash(): string {
  try {
    if (fs.existsSync(AUTH_FILE)) {
      const data = JSON.parse(fs.readFileSync(AUTH_FILE, 'utf-8'));
      if (data && typeof data.hash === 'string' && data.hash.length === 64) {
        return data.hash;
      }
    }
  } catch {}
  return DEFAULT_BASE_HASH;
}

function saveStoredPasswordHash(newHash: string): void {
  fs.writeFileSync(AUTH_FILE, JSON.stringify({ hash: newHash, updated_at: new Date().toISOString() }, nul
  syncPasswordToFirestore(newHash).catch(() => {});
}

// Cookie helper
function getCookieFromReq(req: express.Request, name: string): string | null {
  const cookieHeader = req.headers.cookie;
  if (!cookieHeader) return null;
  const match = cookieHeader.match(new RegExp('(^|;\\s*)' + name + '=([^;]*)'));
  return match ? decodeURIComponent(match[2]) : null;
}

// Server-Side Authentication Middleware for Admin APIs
function requireAdminAuth(req: express.Request, res: express.Response, next: express.NextFunction) {
  let token: string | null = null;

  // 1. Check Authorization: Bearer <token>
  const authHeader = req.headers.authorization;
  if (authHeader && authHeader.startsWith('Bearer ')) {
    token = authHeader.slice(7).trim();
  }

  // 2. Check X-Admin-Token header
  if (!token && typeof req.headers['x-admin-token'] === 'string') {
    token = req.headers['x-admin-token'].trim();
  }

  // 3. Check admin_session cookie
  if (!token) {
    token = getCookieFromReq(req, 'admin_session');
  }

  if (!token || token.length < 32) {
    return res.status(401).json({
      success: false,
      error: 'c¦Jc  EcV1bÓ¢ JbÆ( b¦3bÆJdB 'dF/bæHdB CdV3bFHdB #d†DbvK (Unauthorized Session)',
    });
  }

  const sessions = loadSessions();
  const session = sessions[token];
  if (!session || session.expires_at <= Date.now()) {
    return res.status(401).json({
      success: false,
      error: 'bvFb¦Gb¢ 5dF'bÖJb’ 'dF,dF3b–  d¦1bÆI b¦3bÆJdB 'dF/bæHdB EbÆ/bö'd² …6W76–öâ W‡ —&VB’rÀ
    });
  }

```

FILE (cont.): server.ts

```
  // Session valid
  next();
}

// --- Platform Settings ---
interface PlatformSettings {
  developer_whatsapp: string;
  developer_contact_url: string;
  developer_title?: string;
  support_message?: string;
  public_domain_url?: string;
}

const DEFAULT_SETTINGS: PlatformSettings = {
  developer_whatsapp: '01550523365',
  developer_contact_url: 'https://wa.me/201550523365',
  developer_title: 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
  support_message: 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’rÀ
  public_domain_url: 'https://smart-card-inky.vercel.app',
};

function loadSettings(): PlatformSettings {
  try {
    if (fs.existsSync(SETTINGS_FILE)) {
      const content = fs.readFileSync(SETTINGS_FILE, 'utf-8');
      return { ...DEFAULT_SETTINGS, ...JSON.parse(content) };
    }
  } catch (err) {
    console.error('Failed to read settings file:', err);
  }
  return DEFAULT_SETTINGS;
}

function saveSettings(settings: PlatformSettings): void {
  try {
    fs.writeFileSync(SETTINGS_FILE, JSON.stringify(settings, null, 2), 'utf-8');
  } catch (err) {
    console.error('Failed to write settings file:', err);
  }
}

if (!fs.existsSync(SETTINGS_FILE)) {
  saveSettings(DEFAULT_SETTINGS);
}

// --- QR Database ---
interface QrRecord {
  id: string;
  is_active: boolean;
  target_url: string | null;
  app_type?: string;
  label?: string;
  created_at: string;
  updated_at?: string;
  total_scans: number;
  expires_at?: string | null;
  subscription_months?: number;
}

function loadDatabase(): Record<string, QrRecord> {
  try {
    if (fs.existsSync(DB_FILE)) {
      const content = fs.readFileSync(DB_FILE, 'utf-8');
      return JSON.parse(content);
    }
  } catch (err) {
    console.error('Failed to read db file:', err);
  }
```

FILE (cont.): server.ts

```
  return {};
}

function saveDatabase(db: Record<string, QrRecord>): void {
  try {
    fs.writeFileSync(DB_FILE, JSON.stringify(db, null, 2), 'utf-8');
  } catch (err) {
    console.error('Failed to write db file:', err);
  }
}

if (!fs.existsSync(DB_FILE)) {
  saveDatabase({});
}

// Safe URL validator
function isSafeUrlScheme(url: string): boolean {
  if (!url) return false;
  const sanitized = url.trim().replace(/[\x00-\x1f\x7f]/g, '').toLowerCase();
  const dangerous = /^(?:javascript|data|vbscript|file|blob|about):/i;
  return !dangerous.test(sanitized);
}

function formatTikTokTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (!clean) return '';

  if (/^(?:https?:\/\/)?(?:vm|vt)\.tiktok\.com\//i.test(clean)) {
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }

  if (clean.includes('tiktok.com')) {
    const parts = clean.split('?');
    const pathPart = parts[0];
    const queryPart = parts[1] ? `?${parts[1]}` : '';

    const match = pathPart.match(/tiktok\.com\/(?:@)?([a-zA-Z0-9_.-]+)/i);
    if (match && match[1]) {
      const segment = match[1].replace(/^@/, '').toLowerCase().trim();
      const reservedRoutes = ['discover', 'explore', 'upload', 'live', 'tag', 'music', 'about', 'legal',
      if (!reservedRoutes.includes(segment)) {
        return `https://www.tiktok.com/@${segment}${queryPart}`;
      }
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }

  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.-]/g, '').toLowerCase().trim();

  if (username) {
    return `https://www.tiktok.com/@${username}`;
  }

  return clean;
}
```

FILE (cont.): server.ts

```
341
342 function formatInstagramTargetUrl(input: string): string {
343   if (!input) return '';
344   let clean = input
345     .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
346     .trim()
347     .replace(/^["']|["']$/g, '')
348     .trim();
349
350   if (clean.includes('instagram.com/')) {
351     const match = clean.match(/instagram\.com\/([a-zA-Z0-9._]+)/i);
352     if (match && match[1]) {
353       const user = match[1].replace(/^@/, '').toLowerCase().trim();
354       return `https://www.instagram.com/${user}/`;
355     }
356     if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
357       return `https://${clean}`;
358     }
359     return clean;
360   }
361   let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
362   username = username.replace(/[^\w.]/g, '').toLowerCase().trim();
363   if (username) {
364     return `https://www.instagram.com/${username}/`;
365   }
366   return clean;
367 }
368
369 function formatTelegramTargetUrl(input: string): string {
370   if (!input) return '';
371   let clean = input
372     .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
373     .trim()
374     .replace(/^["']|["']$/g, '')
375     .trim();
376
377   if (clean.includes('t.me/') || clean.includes('telegram.me/')) {
378     const match = clean.match(/(?:t\.me|telegram\.me)\/([a-zA-Z0-9_]+)/i);
379     if (match && match[1]) {
380       return `https://t.me/${match[1].replace(/^@/, '').toLowerCase().trim()}`;
381     }
382     if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
383       return `https://${clean}`;
384     }
385     return clean;
386   }
387   let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
388   username = username.replace(/[^\w]/g, '').toLowerCase().trim();
389   if (username) {
390     return `https://t.me/${username}`;
391   }
392   return clean;
393 }
394
395 function formatSnapchatTargetUrl(input: string): string {
396   if (!input) return '';
397   let clean = input
398     .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
399     .trim()
400     .replace(/^["']|["']$/g, '')
401     .trim();
402
403   if (clean.includes('snapchat.com/add/')) {
404     const match = clean.match(/snapchat\.com\/add\/([a-zA-Z0-9_.-]+)/i);
405     if (match && match[1]) {
406       return `https://www.snapchat.com/add/${match[1].replace(/^@/, '').toLowerCase().trim()}`;
407     }
408     if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
```

FILE (cont.): server.ts

```
      return `https://${clean}`;
    }
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.-]/g, '').toLowerCase().trim();
  if (username) {
    return `https://www.snapchat.com/add/${username}`;
  }
  return clean;
}

// --- AUTH APIS ---

// 1. Admin Login (Server authoritative verification & token generation)
app.post('/api/admin/login', authRateLimiter, (req, res) => {
  const { password } = req.body;
  if (!password || typeof password !== 'string') {
    return res.status(400).json({ success: false, error: 'bvDc ,bv! bV/bæ'dB CdFEb’ 'dFEc Hc r Ò“°
  }

  const attemptHash = hashString(password.trim());
  const storedHash = getStoredPasswordHash();

  if (attemptHash !== storedHash) {
    return res.status(401).json({ success: false, error: 'd6DdV) bvDdV1d†1 c¦Jc  5bÖJbÖ)' });
  }

  // Generate cryptographically secure session token
  const token = crypto.randomBytes(32).toString('hex');
  const sevenDays = 7 * 24 * 60 * 60 * 1000;
  const sessions = loadSessions();
  sessions[token] = {
    token,
    created_at: new Date().toISOString(),
    expires_at: Date.now() + sevenDays,
  };
  saveSessions(sessions);

  // Set HTTP-Only secure cookie
  res.cookie('admin_session', token, {
    httpOnly: true,
    secure: process.env.NODE_ENV === 'production',
    sameSite: 'lax',
    maxAge: sevenDays,
    path: '/',
  });

  return res.json({
    success: true,
    token,
    message: 'b¦E b¦3bÆJdB 'dF/bæHdB (df,bv-',
  });
});

// 2. Validate current session
app.get('/api/admin/session', (req, res) => {
  let token: string | null = null;
  const authHeader = req.headers.authorization;
  if (authHeader && authHeader.startsWith('Bearer ')) {
    token = authHeader.slice(7).trim();
  }
  if (!token && typeof req.headers['x-admin-token'] === 'string') {
    token = req.headers['x-admin-token'].trim();
  }
  if (!token) {
    token = getCookieFromReq(req, 'admin_session');
  }
```

FILE (cont.): server.ts

```
477
478   if (!token) {
479     return res.json({ success: true, authenticated: false });
480   }
481
482   const sessions = loadSessions();
483   const session = sessions[token];
484   const isValid = Boolean(session && session.expires_at > Date.now());
485   return res.json({ success: true, authenticated: isValid });
486 });
487
488 // 3. Admin Logout
489 app.post('/api/admin/logout', (req, res) => {
490   let token = getCookieFromReq(req, 'admin_session');
491   const authHeader = req.headers.authorization;
492   if (authHeader && authHeader.startsWith('Bearer ')) {
493     token = authHeader.slice(7).trim();
494   }
495   if (token) {
496     const sessions = loadSessions();
497     delete sessions[token];
498     saveSessions(sessions);
499   }
500   res.clearCookie('admin_session', { path: '/' });
501   res.json({ success: true, message: 'b¦E b¦3bÆJdB 'dF.c HbÂ (df,bv-' });
502 });
503
504 // 4. Update Password (Protected & requires current password verification)
505 app.post('/api/admin/password', requireAdminAuth, authRateLimiter, (req, res) => {
506   const { currentPassword, newPassword } = req.body;
507   if (!currentPassword || typeof currentPassword !== 'string') {
508     return res.status(400).json({ success: false, error: 'bvDc ,bv! bV/bæ'dB CdFEb’ 'dFEc Hc  'dF-bvDd¦)' });
509   }
510   if (!newPassword || typeof newPassword !== 'string' || newPassword.trim().length < 4) {
511     return res.status(400).json({ success: false, error: 'd6DdV) bvDdV1d†1 bvDbÆ/d¦/b’ JbÆ( b6Dbr *d&D c–F 4 b6-c A
512   }
513
514   const currentHash = getStoredPasswordHash();
515   const attemptCurrentHash = hashString(currentPassword.trim());
516
517   const isCurrentValid = attemptCurrentHash === currentHash || (currentHash === DEFAULT_BASE_HASH && atte
518   if (!isCurrentValid) {
519     return res.status(400).json({ success: false, error: 'd6DdV) bvDdV1d†1 bvDbÖ'dFJb’ :d¦1 cV-d¦-b’r Ò“°
520   }
521
522   const newHash = hashString(newPassword.trim());
523   saveStoredPasswordHash(newHash);
524
525   // Invalidate old sessions for maximum security
526   saveSessions({});
527
528   // Issue fresh session for the current admin
529   const token = crypto.randomBytes(32).toString('hex');
530   const sevenDays = 7 * 24 * 60 * 60 * 1000;
531   const sessions = loadSessions();
532   sessions[token] = {
533     token,
534     created_at: new Date().toISOString(),
535     expires_at: Date.now() + sevenDays,
536   };
537   saveSessions(sessions);
538
539   res.cookie('admin_session', token, {
540     httpOnly: true,
541     secure: process.env.NODE_ENV === 'production',
542     sameSite: 'lax',
543     maxAge: sevenDays,
544     path: '/',
```

FILE (cont.): server.ts

```
  });

  return res.json({
    success: true,
    token,
    message: 'b¦E bvDb¦-d&B dVF d6DdV) bvDdV1d†1 d†*bÖ/d¦+dv' d†*cFAd¦1dv' b†FbÆ'bÒ rÀ
  });
});

// --- QR & SETTINGS APIS ---

// Get all QR codes
app.get('/api/qr', (req, res) => {
  const db = loadDatabase();
  const list = Object.values(db).sort(
    (a, b) => new Date(b.created_at).getTime() - new Date(a.created_at).getTime()
  );
  res.json({ success: true, data: list });
});

// Get single QR code by ID
app.get('/api/qr/:id', (req, res) => {
  const { id } = req.params;
  const db = loadDatabase();
  const record = db[id];
  if (!record) {
    return res.status(404).json({ success: false, error: 'bvDc Ec" :d¦1 dVHbÆHbòr Ò“°
  }
  res.json({ success: true, data: record });
});

// Bulk Generate QR codes (PROTECTED with requireAdminAuth & bulkRateLimiter)
app.post('/api/qr/bulk', requireAdminAuth, bulkRateLimiter, (req, res) => {
  const count = parseInt(req.body.count, 10);
  const subscriptionMonths = typeof req.body.subscription_months === 'number' ? req.body.subscription_mon
  const providedExpiresAt = req.body.expires_at !== undefined ? req.body.expires_at : (
    subscriptionMonths > 0 ? new Date(Date.now() + subscriptionMonths * 30 * 24 * 60 * 60 * 1000).toISOSt
  );

  if (isNaN(count) || count < 1) {
    return res.status(400).json({ success: false, error: 'bvDc ,bv! bV/bæ'dB 1d&E cV-d¦- b6Cb†1 dVF cVAc r Ò“°
  }

  const safeCount = Math.min(count, 500);
  const db = loadDatabase();
  const newRecords: QrRecord[] = [];

  for (let i = 0; i < safeCount; i++) {
    let id = nanoid(10).replace(/[^a-zA-Z0-9_-]/g, 'x');
    while (db[id]) {
      id = nanoid(10).replace(/[^a-zA-Z0-9_-]/g, 'x');
    }

    const record: QrRecord = {
      id,
      is_active: false,
      target_url: null,
      created_at: new Date().toISOString(),
      total_scans: 0,
      subscription_months: subscriptionMonths,
      expires_at: providedExpiresAt,
    };

    db[id] = record;
    newRecords.push(record);
  }

  saveDatabase(db);
```

FILE (cont.): server.ts

```
  res.json({ success: true, data: newRecords, count: newRecords.length });
});

// Customer First-Scan Activation (Public)
app.post('/api/qr/:id/activate', (req, res) => {
  const { id } = req.params;
  const { target_url, app_type, expires_at, subscription_months } = req.body;

  if (!target_url) {
    return res.status(400).json({ success: false, error: 'bvDc ,bv! d6*bv(b' 'dF1bv(cr #d, 'dF1d&E bvDdV7dFHb,r Ò"°
  }

  // Validate URL scheme safety
  if (!isSafeUrlScheme(target_url)) {
    return res.status(400).json({ success: false, error: 'b†1d†*d†Cd†D bvDc 'b†7 c¦Jc  "dVF b6H c¦Jc  Ec6Ed†- b†G' }
  }

  const db = loadDatabase();
  let current = db[id];
  const now = new Date().toISOString();

  if (!current) {
    current = {
      id,
      is_active: true,
      target_url,
      app_type: app_type || 'website',
      created_at: now,
      updated_at: now,
      total_scans: 1,
      expires_at: expires_at !== undefined ? expires_at : null,
      subscription_months: subscription_months !== undefined ? subscription_months : 1,
    };
    db[id] = current;
    saveDatabase(db);
    return res.json({ success: true, data: current });
  }

  if (current.is_active) {
    return res.status(403).json({
      success: false,
      error: 'dv0br 'dFCd†/ dVAc–QdB Ec6(d&'d² (bvDd 9dBâ 'b¦5dB (bvDdV3bFHdB Db¦:d¦Jc  'dFHbÆGb'ârÀ
    });
  }

  current.is_active = true;
  current.target_url = target_url;
  current.app_type = app_type || 'website';
  current.updated_at = now;
  if (expires_at !== undefined) current.expires_at = expires_at;
  if (subscription_months !== undefined) current.subscription_months = subscription_months;

  saveDatabase(db);
  res.json({ success: true, data: current });
});

// Admin Exclusive Quick Edit (PROTECTED with requireAdminAuth)
app.put('/api/qr/:id', requireAdminAuth, (req, res) => {
  const { id } = req.params;
  const { target_url, app_type, label, expires_at, subscription_months } = req.body;

  if (target_url && !isSafeUrlScheme(target_url)) {
    return res.status(400).json({ success: false, error: 'bvDc 'b†7 d¦-b¦Hd¢ 9dFI b†1d†*d†Cd†D c¦Jc  "dVF' });
  }

  const db = loadDatabase();
  let current = db[id];
  const now = new Date().toISOString();
```

FILE (cont.): server.ts

```
681
682   if (!current) {
683     current = {
684       id,
685       is_active: true,
686       target_url: target_url || null,
687       app_type: app_type || 'website',
688       created_at: now,
689       total_scans: 0,
690     };
691     db[id] = current;
692   }
693
694   let normalizedTarget = target_url;
695   const effectiveType = app_type || current?.app_type || 'website';
696   if (normalizedTarget && typeof normalizedTarget === 'string') {
697     if (effectiveType === 'tiktok') normalizedTarget = formatTikTokTargetUrl(normalizedTarget);
698     else if (effectiveType === 'instagram') normalizedTarget = formatInstagramTargetUrl(normalizedTarget)
699     else if (effectiveType === 'telegram') normalizedTarget = formatTelegramTargetUrl(normalizedTarget);
700     else if (effectiveType === 'snapchat') normalizedTarget = formatSnapchatTargetUrl(normalizedTarget);
701   }
702
703   if (target_url !== undefined) current.target_url = normalizedTarget;
704   if (app_type !== undefined) current.app_type = app_type;
705   if (label !== undefined) current.label = label;
706   if (expires_at !== undefined) current.expires_at = expires_at;
707   if (subscription_months !== undefined) current.subscription_months = subscription_months;
708   current.is_active = true;
709   current.updated_at = now;
710
711   saveDatabase(db);
712   res.json({ success: true, data: current });
713 });
714
715 // Debounced scan counter
716 const recentScansDebounce = new Map<string, number>();
717
718 app.post('/api/qr/:id/scan', (req, res) => {
719   const { id } = req.params;
720   const db = loadDatabase();
721   const record = db[id];
722   if (record && record.is_active) {
723     const rawIp = (req.headers['x-forwarded-for'] as string) || req.socket.remoteAddress || 'unknown';
724     const clientIp = Array.isArray(rawIp) ? rawIp[0] : (rawIp.split(',')[0] || '').trim();
725     const debounceKey = `${id}_${clientIp}`;
726     const now = Date.now();
727     const lastScanTime = recentScansDebounce.get(debounceKey) || 0;
728
729     if (now - lastScanTime > 3000) {
730       recentScansDebounce.set(debounceKey, now);
731       record.total_scans = (record.total_scans || 0) + 1;
732       saveDatabase(db);
733     }
734   }
735   res.json({ success: true, total_scans: record ? (record.total_scans || 0) : 0 });
736 });
737
738 // Reset Scan Counter (PROTECTED with requireAdminAuth)
739 app.post('/api/qr/:id/reset-scans', requireAdminAuth, (req, res) => {
740   const { id } = req.params;
741   const { count } = req.body;
742   const db = loadDatabase();
743   const record = db[id];
744   if (!record) {
745     return res.status(404).json({ success: false, error: 'bvDd6Hbò :d¦1 dVHbÆHbòr Ò“°
746   }
747
748   record.total_scans = typeof count === 'number' && count >= 0 ? count : 0;
```

FILE (cont.): server.ts

```
  saveDatabase(db);
  res.json({ success: true, data: record, message: 'b¦E b¦9böJdB 'dF9bö'bò (df,bv-' });
});

// Delete QR Code (PROTECTED with requireAdminAuth)
app.delete('/api/qr/:id', requireAdminAuth, (req, res) => {
  const { id } = req.params;
  const db = loadDatabase();
  if (!db[id]) {
    return res.status(404).json({ success: false, error: 'bvDd6Hbò :d¦1 dVHbÆHbòr Ò“°
  }
  delete db[id];
  saveDatabase(db);
  res.json({ success: true, message: 'b¦E bÖ0d  'dFCd†/ dfGbv&d¦'d²r Ò“°
});

// Get platform settings
app.get('/api/settings', (req, res) => {
  const settings = loadSettings();
  res.json({ success: true, data: settings });
});

// Update platform settings (PROTECTED with requireAdminAuth)
app.post('/api/settings', requireAdminAuth, (req, res) => {
  const { developer_whatsapp, developer_contact_url, developer_title, support_message, public_domain_url
  const current = loadSettings();

  let formattedUrl = (developer_contact_url || '').trim();
  let cleanPhone = (developer_whatsapp || '').trim();

  if (!formattedUrl && cleanPhone) {
    let num = cleanPhone.replace(/[^\d]/g, '');
    if (num.startsWith('01')) num = '2' + num;
    formattedUrl = `https://wa.me/${num}`;
  }

  let cleanDomain = (public_domain_url !== undefined ? public_domain_url : current.public_domain_url || '
  if (cleanDomain.endsWith('/')) {
    cleanDomain = cleanDomain.slice(0, -1);
  }

  const updated: PlatformSettings = {
    developer_whatsapp: cleanPhone || current.developer_whatsapp,
    developer_contact_url: formattedUrl || current.developer_contact_url,
    developer_title: developer_title || current.developer_title || 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
    support_message: support_message || current.support_message || 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’
    public_domain_url: cleanDomain,
  };

  saveSettings(updated);
  res.json({ success: true, data: updated, message: 'b¦E bÖAc, %c–/bv/bv* bvDb¦Hbv5dB HbvDböHdVJdb (df,bv-' });
});

const FIRESTORE_PROJECT_ID = 'clean-plateau-dv4kj';
const FIRESTORE_DATABASE_ID = 'ai-studio-41f04a06-1999-41b9-b7be-e25b21dc1fd0';

// QR Code Instant Redirection Route
app.get('/q/:id', async (req, res, next) => {
  const { id } = req.params;
  const db = loadDatabase();
  let record = db[id];

  res.set('Cache-Control', 'no-store, no-cache, must-revalidate, proxy-revalidate, max-age=0');
  res.set('Pragma', 'no-cache');
  res.set('Expires', '0');

  // Firestore fallback lookup
  if (!record) {
```

FILE (cont.): server.ts

```
    try {
      const docUrl = `https://firestore.googleapis.com/v1/projects/${FIRESTORE_PROJECT_ID}/databases/${FI
      const firestoreRes = await fetch(docUrl);
      if (firestoreRes.ok) {
        const firestoreData = await firestoreRes.json();
        const f = firestoreData.fields || {};
        record = {
          id,
          is_active: f.is_active?.booleanValue ?? false,
          target_url: f.target_url?.stringValue ?? null,
          app_type: f.app_type?.stringValue ?? 'website',
          created_at: f.created_at?.stringValue ?? new Date().toISOString(),
          total_scans: parseInt(f.total_scans?.integerValue || '0', 10),
          expires_at: f.expires_at?.stringValue ?? null,
          subscription_months: parseInt(f.subscription_months?.integerValue || '1', 10),
        };
        db[id] = record;
        saveDatabase(db);
      }
    } catch (fsErr) {
      console.warn('Server Firestore fallback lookup error:', fsErr);
    }
  }

  if (!record) {
    return next();
  }

  const isPrefetch = req.headers['purpose'] === 'prefetch' ||
    req.headers['sec-purpose'] === 'prefetch' ||
    req.headers['x-purpose'] === 'preview';

  if (record.is_active && !isPrefetch) {
    const rawIp = (req.headers['x-forwarded-for'] as string) || req.socket.remoteAddress || 'unknown';
    const clientIp = Array.isArray(rawIp) ? rawIp[0] : (rawIp.split(',')[0] || '').trim();
    const debounceKey = `${id}_${clientIp}`;
    const now = Date.now();
    const lastScanTime = recentScansDebounce.get(debounceKey) || 0;

    if (now - lastScanTime > 3000) {
      recentScansDebounce.set(debounceKey, now);
      record.total_scans = (record.total_scans || 0) + 1;
      saveDatabase(db);

      if (recentScansDebounce.size > 2000) {
        for (const [k, time] of recentScansDebounce.entries()) {
          if (now - time > 15000) recentScansDebounce.delete(k);
        }
      }
    }
  }

  const isExpired = record.expires_at && new Date(record.expires_at).getTime() < Date.now();
  if (isExpired) {
    return next();
  }

  if (record.is_active && record.target_url && record.app_type !== 'bank' && !record.target_url.startsWit
    let target = record.target_url.trim();

    // Block dangerous schemes
    if (!isSafeUrlScheme(target) || target.startsWith('intent:')) {
      return next();
    }

    if (record.app_type === 'wallet') {
      const isWebPaymentLink = (/^https?:\/\//i.test(target) || target.startsWith('www.') || target.inclu
      if (!isWebPaymentLink) {
```

FILE (cont.): server.ts

```
        return next();
      }
      if (!target.startsWith('http://') && !target.startsWith('https://')) {
        target = `https://${target}`;
      }
    }

    // Normalize schemes and platforms
    if (record.app_type === 'tiktok' || target.includes('tiktok.com') || (!target.startsWith('http') && r
      target = formatTikTokTargetUrl(target);
    } else if (record.app_type === 'instagram' || target.includes('instagram.com') || (!target.startsWith
      target = formatInstagramTargetUrl(target);
    } else if (record.app_type === 'telegram' || target.includes('t.me') || (!target.startsWith('http') &
      target = formatTelegramTargetUrl(target);
    } else if (record.app_type === 'snapchat' || target.includes('snapchat.com') || (!target.startsWith('
      target = formatSnapchatTargetUrl(target);
    } else if (target.startsWith('instapay://send?to=')) {
      const handle = decodeURIComponent(target.replace('instapay://send?to=', ''));
      target = `https://ipn.eg/${encodeURIComponent(handle.replace('@instapay', ''))}`;
    } else if (target.startsWith('wa.me/')) {
      target = `https://${target}`;
    } else if (!target.startsWith('http://') && !target.startsWith('https://') && !target.startsWith('tel
      if (/^(?:\+?20|0)?1[0125]\d{8}$/.test(target)) {
        let num = target.replace(/[^\d]/g, '');
        if (num.startsWith('01')) num = '2' + num;
        target = `https://wa.me/${num}`;
      } else {
        target = `https://${target}`;
      }
    }

    if (req.query.preview === '1') {
      return next();
    }

    res.set('Cache-Control', 'no-store, no-cache, must-revalidate, private, max-age=0');
    return res.redirect(302, target);
  }

  next();
});

// Start dev server with Vite or static production
async function startServer() {
  const isProd = process.env.NODE_ENV === 'production';

  if (!isProd) {
    const { createServer } = await import('vite');
    const vite = await createServer({
      server: { middlewareMode: true },
      appType: 'spa',
    });
    app.use(vite.middlewares);
  } else {
    app.use(express.static(path.join(__dirname, 'dist')));
    app.get('*', (req, res) => {
      res.sendFile(path.join(__dirname, 'dist', 'index.html'));
    });
  }

  app.listen(PORT, () => {
    console.log(`Server running on http://0.0.0.0:${PORT}`);
  });
}

startServer();

```

FILE: metadata.json 11 lines | 0.3 KB

```
{
  "name": "Smart Card",
  "description": "dVFcV) Smart Card dF*d†Dd¦/ d†%bö'c ) c Ed†2 QR bvDböJdf'dVJd6Jb’ 'dF0d6Jb’ Ec’ 'dF*d†,d¦G bvDdV(b
  "requestFramePermissions": [
    "camera"
  ],
  "majorCapabilities": [
    "MAJOR_CAPABILITY_SERVER_SIDE_GEMINI_API"
  ]
}

```

FILE: api/redirect.ts 267 lines | 10.0 KB

```
const PROJECT_ID = 'clean-plateau-dv4kj';
const DATABASE_ID = 'ai-studio-41f04a06-1999-41b9-b7be-e25b21dc1fd0';
const API_KEY = 'AIzaSyAjyCP484AEQ52-9CDgp8TDkAw5woA1TFc';

export default async function handler(req: any, res: any) {
  // Always disable caching for QR scans
  res.setHeader('Cache-Control', 'no-store, no-cache, must-revalidate, proxy-revalidate, max-age=0');
  res.setHeader('Pragma', 'no-cache');
  res.setHeader('Expires', '0');

  // Extract ID from query (?id=...) or path
  const queryId = (req.query?.id || '').toString().trim();
  const urlPath = req.url || '';
  const pathMatch = urlPath.match(/\/q\/([a-zA-Z0-9_-]+)/);
  const id = queryId || (pathMatch ? pathMatch[1] : '');

  if (!id) {
    return res.writeHead(302, { Location: '/' }).end();
  }

  try {
    const docUrl = `https://firestore.googleapis.com/v1/projects/${PROJECT_ID}/databases/${DATABASE_ID}/d
    const response = await fetch(docUrl);

    if (!response.ok) {
      // Document not found or not in Firestore -> redirect to customer activation
      return res.writeHead(302, { Location: `/?activate=${id}` }).end();
    }

    const data = await response.json();
    const fields = data.fields || {};

    const isActive = fields.is_active?.booleanValue ?? false;
    const targetUrl = fields.target_url?.stringValue ?? '';
    const appType = fields.app_type?.stringValue ?? 'website';
    const expiresAtStr = fields.expires_at?.stringValue;

    // 1. If not active yet -> redirect directly to customer activation screen
    if (!isActive) {
      return res.writeHead(302, { Location: `/?activate=${id}` }).end();
    }

    // 2. Check expiration
    if (expiresAtStr) {
      const expiresAt = new Date(expiresAtStr).getTime();
      if (expiresAt < Date.now()) {
        return res.writeHead(302, { Location: `/?expired=${id}` }).end();
      }
    }

    // 3. Bank accounts always require copy screen
    if (appType === 'bank' || targetUrl.startsWith('bank://')) {
      return res.writeHead(302, { Location: `/?view=${id}` }).end();
    }

    // 4. Wallet: ONLY redirect directly if it is an actual HTTP/HTTPS payment web link!
    // If it's a phone number (010, 012, 011, 015), redirect to dedicated luxury copy view screen!
    const isWebPaymentLink = (/^https?:\/\//i.test(targetUrl) || targetUrl.startsWith('www.') || targetUr
    if (appType === 'wallet' && !isWebPaymentLink) {
      return res.writeHead(302, { Location: `/?view=${id}` }).end();
    }

    // Check for dangerous schemes (javascript:, data:, vbscript:)
    const sanitizedUrl = targetUrl.trim().replace(/[\x00-\x1f\x7f]/g, '');
    if (/^(?:javascript|data|vbscript|file|blob|about):/i.test(sanitizedUrl.toLowerCase())) {
      return res.writeHead(302, { Location: `/?view=${id}` }).end();
    }

```

FILE (cont.): api/redirect.ts

```
    // Never redirect to intent schemes
    if (targetUrl.startsWith('intent:')) {
      return res.writeHead(302, { Location: `/?view=${id}` }).end();
    }

function formatTikTokTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (!clean) return '';

  if (/^(?:https?:\/\/)?(?:vm|vt)\.tiktok\.com\//i.test(clean)) {
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }

  if (clean.includes('tiktok.com')) {
    const parts = clean.split('?');
    const pathPart = parts[0];
    const queryPart = parts[1] ? `?${parts[1]}` : '';

    const match = pathPart.match(/tiktok\.com\/(?:@)?([a-zA-Z0-9_.-]+)/i);
    if (match && match[1]) {
      const segment = match[1].replace(/^@/, '').toLowerCase().trim();
      const reservedRoutes = ['discover', 'explore', 'upload', 'live', 'tag', 'music', 'about', 'legal',
      if (!reservedRoutes.includes(segment)) {
        return `https://www.tiktok.com/@${segment}${queryPart}`;
      }
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }

  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.-]/g, '').toLowerCase().trim();

  if (username) {
    return `https://www.tiktok.com/@${username}`;
  }

  return clean;
}

function formatInstagramTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (clean.includes('instagram.com/')) {
    const match = clean.match(/instagram\.com\/([a-zA-Z0-9._]+)/i);
    if (match && match[1]) {
      const user = match[1].replace(/^@/, '').toLowerCase().trim();
      return `https://www.instagram.com/${user}/`;
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
```

FILE (cont.): api/redirect.ts

```
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.]/g, '').toLowerCase().trim();
  if (username) {
    return `https://www.instagram.com/${username}/`;
  }
  return clean;
}

function formatTelegramTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (clean.includes('t.me/') || clean.includes('telegram.me/')) {
    const match = clean.match(/(?:t\.me|telegram\.me)\/([a-zA-Z0-9_]+)/i);
    if (match && match[1]) {
      return `https://t.me/${match[1].replace(/^@/, '').toLowerCase().trim()}`;
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w]/g, '').toLowerCase().trim();
  if (username) {
    return `https://t.me/${username}`;
  }
  return clean;
}

function formatSnapchatTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (clean.includes('snapchat.com/add/')) {
    const match = clean.match(/snapchat\.com\/add\/([a-zA-Z0-9_.-]+)/i);
    if (match && match[1]) {
      return `https://www.snapchat.com/add/${match[1].replace(/^@/, '').toLowerCase().trim()}`;
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.-]/g, '').toLowerCase().trim();
  if (username) {
    return `https://www.snapchat.com/add/${username}`;
  }
  return clean;
}

    // 5. Direct Link (WhatsApp, Instagram, Facebook, TikTok, Website, Phone, InstaPay Link, or Wallet Pa
    let destination = sanitizedUrl;

    if (appType === 'tiktok' || destination.includes('tiktok.com') || (!destination.startsWith('http') &&
      destination = formatTikTokTargetUrl(destination);
    } else if (appType === 'instagram' || destination.includes('instagram.com') || (!destination.startsWi
```

FILE (cont.): api/redirect.ts

```
      destination = formatInstagramTargetUrl(destination);
    } else if (appType === 'telegram' || destination.includes('t.me') || (!destination.startsWith('http')
      destination = formatTelegramTargetUrl(destination);
    } else if (appType === 'snapchat' || destination.includes('snapchat.com') || (!destination.startsWith
      destination = formatSnapchatTargetUrl(destination);
    } else if (destination.startsWith('wa.me/')) {
      destination = `https://${destination}`;
    } else if (!destination.startsWith('http://') && !destination.startsWith('https://') && !destination.
      if (/^(?:\+?20|0)?1[0125]\d{8}$/.test(destination)) {
        let num = destination.replace(/[^\d]/g, '');
        if (num.startsWith('01')) num = '2' + num;
        destination = `https://wa.me/${num}`;
      } else {
        destination = `https://${destination}`;
      }
    }

    // Atomic increment scan counter in Firestore via REST API transform (non-blocking)
    const commitUrl = `https://firestore.googleapis.com/v1/projects/${PROJECT_ID}/databases/${DATABASE_ID
    fetch(commitUrl, {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({
        writes: [
          {
            transform: {
              document: `projects/${PROJECT_ID}/databases/${DATABASE_ID}/documents/qr_codes/${id}`,
              fieldTransforms: [
                {
                  fieldPath: 'total_scans',
                  increment: { integerValue: '1' }
                }
              ]
            }
          }
        ]
      })
    }).catch(() => {});

    // Send INSTANT HTTP 302 Redirection with HTML fallback body for universal mobile browser & app suppo
    res.writeHead(302, {
      Location: destination,
      'Content-Type': 'text/html; charset=utf-8'
    });
    return res.end(`<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8">
  <meta http-equiv="refresh" content="0;url=${destination}">
  <title>bÆ'c J d *bÒ 'dF1bv(crââãÂ÷F–FÆSà
  <script>location.replace(${JSON.stringify(destination)});</script>
</head>
<body style="background:#09090b;color:#facc15;font-family:sans-serif;display:flex;align-items:center;just
  <p>bÆ'c J b¦-d†JdFC bVDd’ 'dF1bv(cr Eb†'cF1b’âââ Æ  ‡&VcÒ"G¶FW7F–æ F–öçÒ" 7G–ÆSÒ&6öÆ÷#¢6f 63 S·FW‡BÖFV6÷& F–öã§VæF
</body>
</html>`);
  } catch (err) {
    console.error('Serverless redirect error:', err);
    // Fallback to client SPA
    return res.writeHead(302, { Location: `/?scan=${id}` }).end();
  }
}
```

FILE: src/main.tsx 6 lines | 0.2 KB

```tsx
import {createRoot} from 'react-dom/client';
import App from './App.tsx';
import './index.css';

createRoot(document.getElementById('root')!).render(<App />);

```

FILE: src/App.tsx 253 lines | 9.1 KB

```tsx
import { useState, useEffect, useRef } from 'react';
import { isAdminAuthenticated, logoutAdmin, validateAdminSession } from './lib/auth';
import { getQrCode, fetchPlatformSettings, recordQrScan, subscribeToSingleQrCode } from './lib/qrService'
import { processSmartLink, triggerSmartRedirect } from './lib/deepLinks';
import { AdminLoginView } from './views/AdminLoginView';
import { AdminDashboardView } from './views/AdminDashboardView';
import { CustomerActivationView } from './views/CustomerActivationView';
import { SmartRedirectView } from './views/SmartRedirectView';
import { CardExpiredView } from './views/CardExpiredView';
import { HomeLandingView } from './views/HomeLandingView';
import { PWAInstallBanner } from './components/PWAInstallBanner';
import { QrCodeRecord, PlatformSettings } from './types/qr';
import { Loader2 } from 'lucide-react';

export default function App() {
  const [currentPath, setCurrentPath] = useState<string>(() => window.location.pathname || '/');
  const searchParams = new URLSearchParams(typeof window !== 'undefined' ? window.location.search : '');
  const activateIdFromQuery = searchParams.get('activate');
  const viewIdFromQuery = searchParams.get('view');
  const expiredIdFromQuery = searchParams.get('expired');
  const scanIdFromQuery = searchParams.get('scan');

  const isQrScanPath = currentPath.startsWith('/q/') || Boolean(scanIdFromQuery || viewIdFromQuery || exp
  const qrIdFromPath = isQrScanPath
    ? (scanIdFromQuery || viewIdFromQuery || expiredIdFromQuery || activateIdFromQuery || currentPath.rep
    : null;

  const [activeRecord, setActiveRecord] = useState<QrCodeRecord | null>(null);
  const [domainUrl, setDomainUrl] = useState<string>(() => window.location.origin);
  const [settings, setSettings] = useState<PlatformSettings>({
    developer_whatsapp: '01550523365',
    developer_contact_url: 'https://wa.me/201550523365',
    developer_title: 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
    support_message: 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’rÀ
    public_domain_url: 'https://smart-card-inky.vercel.app',
  });

  // Sync domainUrl and fetch platform settings
  useEffect(() => {
    if (typeof window !== 'undefined') {
      setDomainUrl(window.location.origin);
      fetchPlatformSettings().then((s) => setSettings(s));
    }
  }, []);

  // Listen to popstate for browser back/forward buttons
  useEffect(() => {
    const handlePopState = () => {
      setCurrentPath(window.location.pathname || '/');
    };
    window.addEventListener('popstate', handlePopState);
    return () => window.removeEventListener('popstate', handlePopState);
  }, []);

  const navigate = (path: string) => {
    window.history.pushState({}, '', path);
    setCurrentPath(path);
    window.scrollTo(0, 0);
  };

  const isAdminPath = currentPath.startsWith('/admin') && currentPath !== '/admin/login';
  const isLoginPath = currentPath === '/admin/login';

  // Middleware: If accessing /admin and not authenticated, redirect to /admin/login
  useEffect(() => {
    if (isAdminPath) {
      if (!isAdminAuthenticated()) {
        navigate('/admin/login');
```

FILE (cont.): src/App.tsx

```
      } else {
        validateAdminSession().then((isValid) => {
          if (!isValid) {
            navigate('/admin/login');
          }
        });
      }
    } else if (isLoginPath && isAdminAuthenticated()) {
      navigate('/admin');
    }
  }, [currentPath, isAdminPath, isLoginPath]);

  const [isResolvingQr, setIsResolvingQr] = useState<boolean>(Boolean(isQrScanPath && qrIdFromPath));
  const hasRecordedScanRef = useRef<boolean>(false);

  // Load QR record when accessing /q/:id, record scan count LIVE, and instant redirect
  useEffect(() => {
    if (qrIdFromPath) {
      let isMounted = true;
      setIsResolvingQr(true);

      const fetchPromise = getQrCode(qrIdFromPath);
      const timeoutPromise = new Promise<null>((resolve) => setTimeout(() => resolve(null), 2500));

      Promise.race([fetchPromise, timeoutPromise])
        .then(async (record) => {
          if (!isMounted) return;

          if (record) {
            setActiveRecord(record);

            // If active: increment scan count LIVE in Firestore!
            if (record.is_active && !hasRecordedScanRef.current) {
              hasRecordedScanRef.current = true;

              // Check if not expired and direct link:
              const isExpired = record.expires_at && new Date(record.expires_at).getTime() < Date.now();
              if (!isExpired && record.target_url) {
                const linkInfo = processSmartLink(record.target_url, record.app_type);
                const isDirectRedirect = !linkInfo.isBankCard && !linkInfo.isInstaPayCard && !linkInfo.is
                if (isDirectRedirect) {
                  const target = linkInfo.schemeUrl || linkInfo.fallbackUrl;
                  if (target && target !== '#' && !target.startsWith('intent:')) {
                    try {
                      await Promise.race([
                        recordQrScan(record.id),
                        new Promise((resolve) => setTimeout(resolve, 150)),
                      ]);
                    } catch {}

                    // DIRECT INSTANT NAVIGATION - zero extra pages!
                    try {
                      window.location.replace(target);
                    } catch {
                      window.location.href = target;
                    }
                    return;
                  }
                }
              }

              // Otherwise record scan normally (for bank card, wallet, or expired)
              recordQrScan(record.id);
            }
          }
        })
        .catch((err) => {
          console.warn('QR resolution error:', err);
```

FILE (cont.): src/App.tsx

```
        })
        .finally(() => {
          if (isMounted) setIsResolvingQr(false);
        });

      // Real-time Firestore snapshot listener: instantly updates the UI if the admin edits the wallet nu
      const unsubLive = subscribeToSingleQrCode(qrIdFromPath, (liveRecord) => {
        if (!isMounted) return;
        if (liveRecord) {
          setActiveRecord(liveRecord);
          setIsResolvingQr(false);
        }
      });

      return () => {
        isMounted = false;
        unsubLive();
      };
    } else {
      setActiveRecord(null);
      setIsResolvingQr(false);
    }
  }, [qrIdFromPath]);

  // Compute effective domain URL (custom production domain if configured, else Vercel live domain)
  const effectiveDomainUrl = (settings.public_domain_url && settings.public_domain_url.trim())
    ? settings.public_domain_url.trim()
    : 'https://smart-card-inky.vercel.app';

  // Direct Scan Simulation: opens real /q/:id URL to trigger instant redirection
  const handleSimulateScan = (id: string) => {
    window.open(`${effectiveDomainUrl}/q/${id}`, '_blank');
  };

  // Route 1: QR Scan path /q/:id or direct action query
  if (isQrScanPath && qrIdFromPath) {
    // 1. While resolving: show sleek branded loader instead of blank black screen
    if (isResolvingQr && !activeRecord) {
      return (
        <div className="min-h-screen bg-[#09090b] flex flex-col items-center justify-center p-6 text-cent
          <div className="w-16 h-16 rounded-2xl bg-amber-400/10 border border-amber-400/30 flex items-cen
            <Loader2 className="w-8 h-8 text-amber-400 animate-spin" />
          </div>
          <p className="text-xs text-amber-200/80 font-bold">bÆ'c J d *bÒ 'dF(cv'd&) bvDc Cd¦)...</p>
        </div>
      );
    }

    // 2. If already active, check expiration
    if (activeRecord && activeRecord.is_active) {
      const isExpired = activeRecord.expires_at && new Date(activeRecord.expires_at).getTime() < Date.now
      if (isExpired) {
        return <CardExpiredView record={activeRecord} settings={settings} />;
      }
      return <SmartRedirectView record={activeRecord} />;
    }

    // 3. Direct First Scan Customer Activation (Always static, fast, and ready!)
    return (
      <CustomerActivationView
        qrId={qrIdFromPath}
        onActivated={(updated) => {
          setActiveRecord(updated);
        }}
      />
    );
  }

```

FILE (cont.): src/App.tsx

```tsx
  // Route 2: Admin Login
  if (isLoginPath) {
    return (
      <>
        <AdminLoginView
          onLoginSuccess={() => navigate('/admin')}
          onNavigateHome={() => navigate('/')}
        />
        <PWAInstallBanner />
      </>
    );
  }

  // Route 3: Admin Dashboard (Protected)
  if (isAdminPath) {
    return (
      <>
        <AdminDashboardView
          onLogout={() => {
            logoutAdmin();
            navigate('/admin/login');
          }}
          domainUrl={effectiveDomainUrl}
          onSimulateScan={handleSimulateScan}
        />
        <PWAInstallBanner />
      </>
    );
  }

  // Route 4: Home Landing View
  return (
    <>
      <HomeLandingView
        onGoToAdmin={() => {
          if (isAdminAuthenticated()) {
            navigate('/admin');
          } else {
            navigate('/admin/login');
          }
        }}
        onSimulateScan={handleSimulateScan}
        domainUrl={effectiveDomainUrl}
      />
      <PWAInstallBanner />
    </>
  );
}

```

FILE: src/index.css 62 lines | 1.4 KB

```
@import "tailwindcss";

@layer base {
  body {
    font-family: 'Tajawal', 'Plus Jakarta Sans', system-ui, -apple-system, sans-serif;
  }
}

/* 3D Lifelike Animations for Customer Selected Platform: Logo & Name Only */
@keyframes icon3DAlive {
  0%, 100% {
    transform: perspective(600px) translateZ(16px) translateY(0px) rotateY(-4deg) scale(1.15);
    filter: drop-shadow(0 8px 14px rgba(245, 158, 11, 0.45));
  }
  50% {
    transform: perspective(600px) translateZ(28px) translateY(-6px) rotateY(4deg) scale(1.25);
    filter: drop-shadow(0 14px 22px rgba(245, 158, 11, 0.7));
  }
}

@keyframes name3DAlive {
  0%, 100% {
    transform: translateY(0px) scale(1.02);
  }
  50% {
    transform: translateY(-2px) scale(1.08);
  }
}

.animate-icon-alive {
  animation: icon3DAlive 2.5s ease-in-out infinite;
  transform-style: preserve-3d;
  will-change: transform, filter;
}

.animate-name-alive {
  animation: name3DAlive 2.5s ease-in-out infinite;
  will-change: transform;
}

@media print {
  body {
    background: white !important;
    color: black !important;
  }
  .no-print {
    display: none !important;
  }
  .print-only {
    display: block !important;
  }
  .print-grid {
    display: grid !important;
    grid-template-columns: repeat(3, minmax(0, 1fr)) !important;
    gap: 16px !important;
  }
  .print-card {
    page-break-inside: avoid !important;
    border: 1px dashed #cbd5e1 !important;
  }
}

```

FILE: src/types/qr.ts 69 lines | 1.9 KB

```ts
export type AppType =
  | 'bank'
  | 'instapay'
  | 'wallet'
  | 'whatsapp'
  | 'instagram'
  | 'facebook'
  | 'telegram'
  | 'tiktok'
  | 'snapchat'
  | 'phone'
  | 'website'
  | 'other';

export interface BankDetails {
  bankName: string;
  accountName?: string;
  accountNumber: string;
  iban?: string;
  notes?: string;
}

export type SubscriptionPlan = 'monthly' | 'quarterly' | 'semi_annual' | 'annual' | 'unlimited' | 'custom

export interface QrCodeRecord {
  id: string; // Primary key, immutable nanoid(10)
  is_active: boolean; // default false, becomes true on first activation
  target_url: string | null; // Smart deep link, URL, or bank URI
  app_type?: AppType;
  created_at: string; // ISO timestamp
  updated_at?: string; // ISO timestamp
  total_scans?: number;
  last_scanned_at?: string;
  label?: string; // Optional friendly label or note by admin
  bank_details?: BankDetails;
  expires_at?: string | null; // ISO timestamp or null for permanent
  subscription_months?: number; // e.g. 1 for monthly, 3, 6, 12, or 0 for unlimited
}

export interface DeepLinkInfo {
  appType: AppType;
  appTitleAr: string;
  schemeUrl: string; // Native app URI scheme or direct target
  fallbackUrl: string; // Web fallback
  displayUrl: string;
  isBankCard?: boolean;
  bankDetails?: BankDetails;
  isInstaPayCard?: boolean;
  instaPayHandle?: string;
  isWalletCard?: boolean;
  walletProvider?: 'vodafone' | 'etisalat' | 'orange' | 'we' | 'generic';
  walletProviderNameAr?: string;
  walletProviderNameEn?: string;
  walletCompanyNameAr?: string;
  walletPhone?: string;
  walletFormattedPhone?: string;
  walletIntentUrl?: string;
  walletUssdCode?: string;
}

export interface PlatformSettings {
  developer_whatsapp: string; // e.g. "01550523365"
  developer_contact_url: string; // e.g. "https://wa.me/201550523365"
  developer_title?: string;
  support_message?: string;
  public_domain_url?: string; // Real production domain, e.g. "https://smartcard-app.onrender.com"
}

```

FILE (cont.): src/types/qr.ts

```
69
```

FILE: src/types/jsqr.d.ts 37 lines | 0.8 KB

```ts
declare module 'jsqr' {
  interface QRCodePoint {
    x: number;
    y: number;
  }

  interface QRCode {
    binaryData: number[];
    data: string;
    chunks: any[];
    version: number;
    location: {
      topRightCorner: QRCodePoint;
      topLeftCorner: QRCodePoint;
      bottomRightCorner: QRCodePoint;
      bottomLeftCorner: QRCodePoint;
      topRightFinderPattern: QRCodePoint;
      topLeftFinderPattern: QRCodePoint;
      bottomLeftFinderPattern: QRCodePoint;
      bottomRightAlignmentPattern?: QRCodePoint;
    };
  }

  interface Options {
    inversionAttempts?: 'dontInvert' | 'onlyInvert' | 'attemptBoth' | 'invertFirst';
  }

  function jsQR(
    data: Uint8ClampedArray,
    width: number,
    height: number,
    options?: Options
  ): QRCode | null;

  export default jsQR;
}

```

FILE: src/lib/auth.ts 374 lines | 12.1 KB

```ts
import { db } from './firebase';
import { doc, getDoc, setDoc } from 'firebase/firestore';

const ADMIN_TOKEN_KEY = 'smart_card_admin_session_token';
const ADMIN_TOKEN_EXPIRY_KEY = 'smart_card_admin_session_expiry';
const ADMIN_PASSWORD_HASH_KEY = 'smart_card_admin_pwd_hash';

// Default initial password hash (SHA-256 for "admin1234")
export const DEFAULT_BASE_HASH = 'ac9689e2272427085e35b9d3e3e8bed88cb3434828b43b86fc0596cad4c6e270';

const FIRESTORE_PROJECT_ID = 'clean-plateau-dv4kj';
const FIRESTORE_DATABASE_ID = 'ai-studio-41f04a06-1999-41b9-b7be-e25b21dc1fd0';
const FIRESTORE_API_KEY = 'AIzaSyAjyCP484AEQ52-9CDgp8TDkAw5woA1TFc';

const SEVEN_DAYS_MS = 7 * 24 * 60 * 60 * 1000;

// Clean insecure legacy keys if present
try {
  if (typeof window !== 'undefined') {
    localStorage.removeItem('dynamic_qr_admin_password');
    if (localStorage.getItem('dynamic_qr_admin_session') === 'authenticated_admin_token') {
      localStorage.removeItem('dynamic_qr_admin_session');
    }
  }
} catch {}

/**
 * Computes SHA-256 cryptographic hash of a string using Web Crypto API
 */
export async function hashPassword(plain: string): Promise<string> {
  const encoder = new TextEncoder();
  const data = encoder.encode(plain);
  const hashBuffer = await crypto.subtle.digest('SHA-256', data);
  const hashArray = Array.from(new Uint8Array(hashBuffer));
  return hashArray.map((b) => b.toString(16).padStart(2, '0')).join('');
}

/**
 * Gets the current active session token
 */
export function getAdminToken(): string | null {
  if (typeof window === 'undefined') return null;
  try {
    return localStorage.getItem(ADMIN_TOKEN_KEY) || sessionStorage.getItem(ADMIN_TOKEN_KEY);
  } catch {
    return null;
  }
}

/**
 * Authenticated fetch helper that automatically attaches Bearer token to requests
 */
export async function authFetch(input: RequestInfo | URL, init?: RequestInit): Promise<Response> {
  const token = getAdminToken();
  const headers = new Headers(init?.headers || {});
  if (token) {
    headers.set('Authorization', `Bearer ${token}`);
    headers.set('X-Admin-Token', token);
  }
  return fetch(input, {
    ...init,
    headers,
    credentials: 'include', // include HTTP-Only cookies
  });
}

/**
 * Checks if admin session is locally active and unexpired
```

FILE (cont.): src/lib/auth.ts

```
 */
export function isAdminAuthenticated(): boolean {
  if (typeof window === 'undefined') return false;
  const token = getAdminToken();
  if (!token || token.length < 16) return false;

  try {
    const expiryStr = localStorage.getItem(ADMIN_TOKEN_EXPIRY_KEY) || sessionStorage.getItem(ADMIN_TOKEN_
    if (expiryStr) {
      const expiry = parseInt(expiryStr, 10);
      if (!isNaN(expiry) && expiry <= Date.now()) {
        logoutAdmin();
        return false;
      }
    }
  } catch {}

  return true;
}

/**
 * Verifies active session with the backend server without breaking on static hosts (e.g. Vercel)
 */
export async function validateAdminSession(): Promise<boolean> {
  const token = getAdminToken();
  if (!token) return false;

  // First verify local session validity
  if (!isAdminAuthenticated()) return false;

  try {
    const controller = new AbortController();
    const timeoutId = setTimeout(() => controller.abort(), 2000);

    const res = await authFetch('/api/admin/session', {
      signal: controller.signal,
    });
    clearTimeout(timeoutId);

    const contentType = res.headers.get('content-type') || '';
    if (res.ok && contentType.includes('application/json')) {
      const data = await res.json();
      if (typeof data.authenticated === 'boolean') {
        if (!data.authenticated) {
          // Explicit invalidation by server
          logoutAdmin();
          return false;
        }
        return true;
      }
    }
  } catch {
    // If backend is unreachable or on a static host (like Vercel SPA), fallback to local valid token
  }

  // Session remains valid locally
  return true;
}

/**
 * Retrieves the currently active admin password hash directly from Cloud Database (Firestore).
 * Uses direct Firestore REST API for 100% reliable, unblockable fetching across all browsers,
 * Incognito tabs, and Brave Shields without third-party cookie or IndexedDB constraints.
 */
export async function getActivePasswordHash(): Promise<string> {
  // 1. Primary: Direct HTTPS REST query to Firestore cloud database
  try {
    const restUrl = `https://firestore.googleapis.com/v1/projects/${FIRESTORE_PROJECT_ID}/databases/${FIR
```

FILE (cont.): src/lib/auth.ts

```
    const controller = new AbortController();
    const timer = setTimeout(() => controller.abort(), 2500);
    const res = await fetch(restUrl, { signal: controller.signal, cache: 'no-store' });
    clearTimeout(timer);

    if (res.ok) {
      const data = await res.json();
      const hashVal = data.fields?.hash?.stringValue;
      if (typeof hashVal === 'string' && hashVal.length === 64) {
        try { localStorage.setItem(ADMIN_PASSWORD_HASH_KEY, hashVal); } catch {}
        try { sessionStorage.setItem(ADMIN_PASSWORD_HASH_KEY, hashVal); } catch {}
        return hashVal;
      }
    }
  } catch (err) {
    console.warn('REST auth fetch error, falling back to Firestore SDK:', err);
  }

  // 2. Secondary: Firestore SDK getDoc
  try {
    const snap = await getDoc(doc(db, 'settings', 'auth'));
    if (snap.exists() && snap.data()?.hash) {
      const h = snap.data().hash;
      if (typeof h === 'string' && h.length === 64) {
        try { localStorage.setItem(ADMIN_PASSWORD_HASH_KEY, h); } catch {}
        try { sessionStorage.setItem(ADMIN_PASSWORD_HASH_KEY, h); } catch {}
        return h;
      }
    }
  } catch (err) {
    console.warn('Firestore SDK auth error:', err);
  }

  // 3. Tertiary: Local storage cache
  try {
    const local = localStorage.getItem(ADMIN_PASSWORD_HASH_KEY) || sessionStorage.getItem(ADMIN_PASSWORD_
    if (local && local.length === 64) {
      return local;
    }
  } catch {}

  // 4. Default base password ("admin1234") if nothing is in DB yet
  return DEFAULT_BASE_HASH;
}

/**
 * Saves a valid session token locally
 */
function storeAdminSession(token: string): void {
  const expiry = String(Date.now() + SEVEN_DAYS_MS);
  try {
    localStorage.setItem(ADMIN_TOKEN_KEY, token);
    localStorage.setItem(ADMIN_TOKEN_EXPIRY_KEY, expiry);
  } catch {}
  try {
    sessionStorage.setItem(ADMIN_TOKEN_KEY, token);
    sessionStorage.setItem(ADMIN_TOKEN_EXPIRY_KEY, expiry);
  } catch {}
}

/**
 * Performs admin login:
 * Authoritatively validates against the active password in Cloud Firestore.
 * Once the password is changed, ONLY the new password is valid.
 */
export async function loginAdmin(passwordAttempt: string): Promise<boolean> {
  const clean = (passwordAttempt || '').trim();
  if (!clean) return false;
```

FILE (cont.): src/lib/auth.ts

```
205
206   const attemptHash = await hashPassword(clean);
207   const activeHash = await getActivePasswordHash();
208
209   // Try Server API first (if Express server is running)
210   try {
211     const controller = new AbortController();
212     const timeoutId = setTimeout(() => controller.abort(), 2500);
213
214     const serverRes = await fetch('/api/admin/login', {
215       method: 'POST',
216       headers: { 'Content-Type': 'application/json' },
217       credentials: 'include',
218       body: JSON.stringify({ password: clean }),
219       signal: controller.signal,
220     });
221     clearTimeout(timeoutId);
222
223     const contentType = serverRes.headers.get('content-type') || '';
224     if (serverRes.ok && contentType.includes('application/json')) {
225       const data = await serverRes.json();
226       if (data.success && data.token) {
227         storeAdminSession(data.token);
228         try {
229           localStorage.setItem(ADMIN_PASSWORD_HASH_KEY, attemptHash);
230           sessionStorage.setItem(ADMIN_PASSWORD_HASH_KEY, attemptHash);
231         } catch {}
232         return true;
233       }
234     }
235   } catch {
236     // Server fetch unavailable (e.g. static hosting on Vercel), fall through to database check
237   }
238
239   // Strict match against active database password hash:
240   // If password was updated in Firestore, ONLY that updated password works!
241   if (attemptHash === activeHash) {
242     let clientToken: string;
243     try {
244       clientToken = crypto.randomUUID ? crypto.randomUUID().replace(/-/g, '') + Date.now().toString(16) :
245     } catch {
246       clientToken = 'adm_token_' + Date.now().toString(36) + '_' + attemptHash.slice(0, 16);
247     }
248
249     storeAdminSession(clientToken);
250     try {
251       localStorage.setItem(ADMIN_PASSWORD_HASH_KEY, attemptHash);
252       sessionStorage.setItem(ADMIN_PASSWORD_HASH_KEY, attemptHash);
253     } catch {}
254
255     return true;
256   }
257
258   return false;
259 }
260
261 /**
262  * Secure password change requiring current password verification:
263  * Updates the password across the ENTIRE database:
264  * 1. Cloud Firestore database via REST API & Firestore SDK (`settings/auth` and replica `platform_settin
265  * 2. Server filesystem database (`data/auth.json`)
266  * 3. Client storage cache
267  */
268 export async function changeAdminPassword(
269   currentPasswordPlain: string,
270   newPasswordPlain: string
271 ): Promise<{ success: boolean; message: string }> {
272   const curClean = (currentPasswordPlain || '').trim();
```

FILE (cont.): src/lib/auth.ts

```
  const newClean = (newPasswordPlain || '').trim();

  if (!curClean) {
    return { success: false, message: 'bvDc ,bv! bV/bæ'dB CdFEb’ 'dFEc Hc  'dF-bvDd¦).' };
  }
  if (!newClean || newClean.length < 4) {
    return { success: false, message: 'd6DdV) bvDdV1d†1 bvDbÆ/d¦/b’ JbÆ( b6Dbr *d&D c–F 4 b6-c A b6H b61d&'dRâr Ó°
  }

  const curHashAttempt = await hashPassword(curClean);
  const activeHash = await getActivePasswordHash();

  // Validate current password (must match active database password)
  const isCurrentValid = curHashAttempt === activeHash || (activeHash === DEFAULT_BASE_HASH && curHashAtt
  if (!isCurrentValid) {
    return { success: false, message: 'd6DdV) bvDdV1d†1 bvDbÖ'dFJb’ :d¦1 cV-d¦-b’âr Ó°
  }

  const newHash = await hashPassword(newClean);
  const nowIso = new Date().toISOString();

  // 1. UPDATE CLOUD FIRESTORE DATABASE VIA REST API (Works directly on all platforms)
  try {
    const restUrl = `https://firestore.googleapis.com/v1/projects/${FIRESTORE_PROJECT_ID}/databases/${FIR
    await fetch(restUrl, {
      method: 'PATCH',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({
        fields: {
          hash: { stringValue: newHash },
          updated_at: { stringValue: nowIso },
          migrated: { booleanValue: true },
        },
      }),
    });
  } catch (err) {
    console.warn('REST cloud update warning:', err);
  }

  // 2. ALSO UPDATE VIA FIRESTORE SDK
  try {
    await setDoc(doc(db, 'settings', 'auth'), {
      hash: newHash,
      updated_at: nowIso,
      migrated: true,
    }, { merge: true });

    await setDoc(doc(db, 'platform_settings', 'auth'), {
      hash: newHash,
      updated_at: nowIso,
    }, { merge: true });
  } catch (err) {
    console.warn('SDK cloud update warning:', err);
  }

  // 3. UPDATE SERVER DATABASE (data/auth.json)
  try {
    const res = await authFetch('/api/admin/password', {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({
        currentPassword: curClean,
        newPassword: newClean,
      }),
    });
    const contentType = res.headers.get('content-type') || '';
    if (res.ok && contentType.includes('application/json')) {
      const data = await res.json();
```

FILE (cont.): src/lib/auth.ts

```
      if (data.token) {
        storeAdminSession(data.token);
      }
    }
  } catch {}

  // 4. UPDATE LOCAL CLIENT CACHE
  try {
    localStorage.setItem(ADMIN_PASSWORD_HASH_KEY, newHash);
    sessionStorage.setItem(ADMIN_PASSWORD_HASH_KEY, newHash);
  } catch {}

  return {
    success: true,
    message: 'b¦E b¦-böJb² CdFEb’ 'dFEc Hc  Ad¢ Bbv9bö) bvDb†JbvFbv* bvDc6-bv(d¦) (Firestore) d†,dVJc’ 'dF#bÆGc&) b†
  };
}

/**
 * Logout admin and invalidate session
 */
export function logoutAdmin(): void {
  try {
    authFetch('/api/admin/logout', { method: 'POST' }).catch(() => {});
  } catch {}

  try {
    localStorage.removeItem(ADMIN_TOKEN_KEY);
    localStorage.removeItem(ADMIN_TOKEN_EXPIRY_KEY);
    sessionStorage.removeItem(ADMIN_TOKEN_KEY);
    sessionStorage.removeItem(ADMIN_TOKEN_EXPIRY_KEY);
  } catch {}
}

```

FILE: src/lib/deepLinks.ts 737 lines | 23.5 KB

```ts
import { AppType, BankDetails, DeepLinkInfo } from '../types/qr';

/**
 * Checks whether the current window is embedded within an iframe
 * (e.g., inside the AI Studio Web Preview environment).
 */
export function isRunningInIframe(): boolean {
  try {
    return window.self !== window.top;
  } catch {
    return true;
  }
}

/**
 * Encodes bank details into a compact bank URI scheme for storage
 */
export function encodeBankDetails(details: BankDetails): string {
  const params = new URLSearchParams();
  if (details.bankName) params.set('b', details.bankName);
  if (details.accountNumber) params.set('acc', details.accountNumber);
  if (details.accountName) params.set('name', details.accountName);
  if (details.iban) params.set('iban', details.iban);
  if (details.notes) params.set('notes', details.notes);
  return `bank://account?${params.toString()}`;
}

/**
 * Decodes a bank URI scheme back into structured BankDetails
 */
export function decodeBankDetails(uri: string): BankDetails | null {
  if (!uri || !uri.startsWith('bank://')) return null;
  try {
    const query = uri.replace('bank://account?', '').replace('bank://?', '');
    const params = new URLSearchParams(query);
    return {
      bankName: params.get('b') || 'bÖ3bv( b†Fd6J',
      accountNumber: params.get('acc') || '',
      accountName: params.get('name') || '',
      iban: params.get('iban') || '',
      notes: params.get('notes') || '',
    };
  } catch {
    return null;
  }
}

/**
 * Validates that a URL does NOT contain dangerous or malicious execution schemes
 * (e.g., javascript:, vbscript:, data:, file:, etc.)
 */
export function isSafeUrlScheme(url: string): boolean {
  if (!url) return false;
  const sanitized = url.trim().replace(/[\x00-\x1f\x7f]/g, '').toLowerCase();
  const dangerous = /^(?:javascript|data|vbscript|file|blob|about):/i;
  return !dangerous.test(sanitized);
}

/**
 * Robustly sanitizes and extracts the true URL from raw inputs,
 * handling Android app share links (e.g. android-app://com.instapay.app/https/ipn.eg/...),
 * double protocols (https://android-app:// or https://https://), and custom schemes.
 */
export function cleanAndSanitizeUrl(input: string): string {
  let s = (input || '').trim();
  if (!s) return '';

  // Immediately reject dangerous script schemes
```

FILE (cont.): src/lib/deepLinks.ts

```
  if (!isSafeUrlScheme(s)) {
    return '';
  }

  // If already a bank URI scheme, leave as-is
  if (s.startsWith('bank://')) {
    return s;
  }

  // 1. Check if input contains an embedded web URL (common in Android share intents)
  // e.g., android-app://com.instapay.app/https/ipn.eg/S/shenoudazaher/instapay/7CGeaO
  const embeddedHttpMatch = s.match(/(https?:\/\/[^\s]+)/i) || s.match(/(https?\/[^\s]+)/i);
  if (embeddedHttpMatch && !s.startsWith('http://android-app') && !s.startsWith('https://android-app')) {
    let extracted = embeddedHttpMatch[1];
    if (extracted.startsWith('https/') || extracted.startsWith('http/')) {
      extracted = extracted.replace(/^https?\//, 'https://');
    }
    return extracted;
  }

  // 2. Double scheme like https://android-app://
  if (/^https?:\/\/+android-app:\/\//i.test(s)) {
    s = s.replace(/^https?:\/\/+android-app:\/\//i, 'android-app://');
    const innerUrl = s.match(/https?\/[^\s]+/i) || s.match(/https?:\/\/[^\s]+/i);
    if (innerUrl) {
      let clean = innerUrl[0];
      if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
        clean = clean.replace(/^https?\//, 'https://');
      }
      return clean;
    }
    const pkg = s.replace('android-app://', '').split('/')[0];
    return `https://play.google.com/store/apps/details?id=${pkg}`;
  }

  // 3. Fix double http(s) like https://https:// or https://http://
  s = s.replace(/^https?:\/\/+(https?:\/\/)/i, '$1');

  // 4. Raw android-app:// scheme
  if (s.startsWith('android-app://')) {
    const innerUrl = s.match(/https?\/[^\s]+/i) || s.match(/https?:\/\/[^\s]+/i);
    if (innerUrl) {
      let clean = innerUrl[0];
      if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
        clean = clean.replace(/^https?\//, 'https://');
      }
      return clean;
    }
    const pkg = s.replace('android-app://', '').split('/')[0];
    return `https://play.google.com/store/apps/details?id=${pkg}`;
  }

  // 5. Standard valid non-http schemes
  if (s.startsWith('tel:') || s.startsWith('mailto:')) {
    return s;
  }

  // 6. Custom scheme like instapay://send?to=
  if (s.startsWith('instapay://send?to=')) {
    const handle = decodeURIComponent(s.replace('instapay://send?to=', ''));
    return handle.replace(/@instapay$/i, '').trim();
  }

  return s;
}

/**
 * Normalizes Eastern Arabic numerals (f af&cfFeffgf†i) to standard ASCII numerals (0123456789)
```

FILE (cont.): src/lib/deepLinks.ts

```
 */
export function normalizeArabicNumerals(input: string): string {
  if (!input) return '';
  const arabicNumerals = ['f rÂ va', 'f"rÂ vc', 'fBrÂ ve', 'fbrÂ vg', 'f,rÂ vi'];
  return input.replace(/[f Öi]/g, (char) => {
    const idx = arabicNumerals.indexOf(char);
    return idx !== -1 ? String(idx) : char;
  });
}

/**
 * Checks if input is an external Quick Payment URL/link or deep link rather than a phone number
 */
export function isQuickPayUrl(input: string): boolean {
  const s = normalizeArabicNumerals(input || '').trim();
  if (/^https?:\/\//i.test(s)) return true;
  if (/^intent:\/\//i.test(s)) return true;
  if (/^(vfcash|orangecash|etisalatcash|wepay|ipn):\/\//i.test(s)) return true;

  const hasDomain = s.includes('.eg') || s.includes('.com') || s.includes('.net') || s.includes('.me') ||
  const digitsOnly = s.replace(/[^\d]/g, '');

  if (hasDomain && (s.includes('/') || s.includes('www.') || digitsOnly.length < 8)) {
    return true;
  }
  return false;
}

export interface DetectedWalletInfo {
  provider: 'vodafone' | 'orange' | 'etisalat' | 'we' | 'generic';
  nameAr: string;
  nameEn: string;
  companyNameAr: string;
  cleanPhone: string;
  formattedPhone: string;
  brandColor: string;
}

/**
 * Detects the Egyptian mobile wallet operator from the phone number prefix
 * 010 / f af  Óâ föF föæR 6 6€
 * 012 / f af" Óâ ÷& ævR 6 6€
 * 011 / f af  Óâ WF—6 Æ B 6 6€
 * 015 / f afR Óâ tR   •
 */
export function detectWalletInfo(rawPhone: string): DetectedWalletInfo {
  const normalized = normalizeArabicNumerals(rawPhone || '');
  let cleanPhone = normalized.replace(/[^\d]/g, '');

  // Strip international country codes (+20, 0020, 20)
  if (cleanPhone.startsWith('0020') && cleanPhone.length === 14) {
    cleanPhone = cleanPhone.slice(4);
  } else if (cleanPhone.startsWith('20') && cleanPhone.length === 12) {
    cleanPhone = cleanPhone.slice(2);
  }

  // Prepend missing leading zero (e.g. 1012345678 -> 01012345678)
  if (cleanPhone.length === 10 && cleanPhone.startsWith('1')) {
    cleanPhone = '0' + cleanPhone;
  }

  // Formatted display (010 1234 5678)
  let formattedPhone = cleanPhone;
  if (cleanPhone.length === 11) {
    formattedPhone = `${cleanPhone.slice(0, 3)} ${cleanPhone.slice(3, 7)} ${cleanPhone.slice(7)}`;
  }

  // 010 -> Vodafone Cash
```

FILE (cont.): src/lib/deepLinks.ts

```
  if (cleanPhone.startsWith('010')) {
    return {
      provider: 'vodafone',
      nameAr: 'j†Hbö'd Hdb Cbv4',
      nameEn: 'Vodafone Cash',
      companyNameAr: 'd Hbö'd Hdb EcV1 - Vodafone Egypt',
      cleanPhone,
      formattedPhone,
      brandColor: '#E60000',
    };
  }

  // 012 -> Orange Cash
  if (cleanPhone.startsWith('012')) {
    return {
      provider: 'orange',
      nameAr: 'b6Hc 'df, d6'cBrÀ
      nameEn: 'Orange Cash',
      companyNameAr: 'b6Hc 'df, dV5c  Ò ÷& ævR Vw— BrÀ
      cleanPhone,
      formattedPhone,
      brandColor: '#FF7900',
    };
  }

  // 011 -> Etisalat Cash
  if (cleanPhone.startsWith('011')) {
    return {
      provider: 'etisalat',
      nameAr: 'bv*cV'dF'b¢ Cbv4',
      nameEn: 'Etisalat Cash (e&)',
      companyNameAr: 'bVJ b&Fbò EcV1 (bv*cV'dF'b¢’ Ò Rb Vw— BrÀ
      cleanPhone,
      formattedPhone,
      brandColor: '#719E19',
    };
  }

  // 015 -> WE Pay
  if (cleanPhone.startsWith('015')) {
    return {
      provider: 'we',
      nameAr: 'd†J b†'d¢rÀ
      nameEn: 'WE Pay',
      companyNameAr: 'bvDdV5c Jb’ DdF'b¦5bvDbv* - Telecom Egypt (WE)',
      cleanPhone,
      formattedPhone,
      brandColor: '#592C82',
    };
  }

  return {
    provider: 'generic',
    nameAr: 'dV-d 8b’ Cbv4 bVDd6*c HdfJb’rÀ
    nameEn: 'Smart Cash Wallet',
    companyNameAr: 'bvDdV-d 8b’ 'dF0d6Jb’rÀ
    cleanPhone: cleanPhone || rawPhone,
    formattedPhone: cleanPhone || rawPhone,
    brandColor: '#EAB308',
  };
}

/**
 * Formats and normalizes TikTok username or links to the standard Universal / App Link format:
 * https://www.tiktok.com/@<clean_lowercase_username>
 * This guarantees the TikTok app opens directly to the profile on mobile devices,
 * or cleanly loads the profile page on the web, preventing it from just opening the app's home feed.
 */
```

FILE (cont.): src/lib/deepLinks.ts

```ts
export function formatTikTokTargetUrl(input: string): string {
  if (!input) return '';
  // 1. Remove all invisible zero-width and RTL/LTR formatting marks
  let clean = normalizeArabicNumerals(input)
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (!clean) return '';

  // 2. TikTok short video/profile share links (vm.tiktok.com / vt.tiktok.com)
  if (/^(?:https?:\/\/)?(?:vm|vt)\.tiktok\.com\//i.test(clean)) {
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }

  // 3. Full or partial tiktok.com URL
  if (clean.includes('tiktok.com')) {
    const parts = clean.split('?');
    const pathPart = parts[0];
    const queryPart = parts[1] ? `?${parts[1]}` : '';

    const match = pathPart.match(/tiktok\.com\/(?:@)?([a-zA-Z0-9_.-]+)/i);
    if (match && match[1]) {
      const segment = match[1].replace(/^@/, '').toLowerCase().trim();
      const reservedRoutes = ['discover', 'explore', 'upload', 'live', 'tag', 'music', 'about', 'legal',
      if (!reservedRoutes.includes(segment)) {
        return `https://www.tiktok.com/@${segment}${queryPart}`;
      }
    }
    // If it's a specific link with video ID or something, just ensure https://
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }

  // 4. Raw username (e.g. foodhunteregypt, @foodhunteregypt, FoodHunterEgypt, /@Foodhunteregypt)
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.-]/g, '').toLowerCase().trim();

  if (username) {
    return `https://www.tiktok.com/@${username}`;
  }

  return clean;
}

/**
 * Normalizes Instagram usernames/URLs to https://www.instagram.com/<clean_lowercase_username>/
 */
export function formatInstagramTargetUrl(input: string): string {
  if (!input) return '';
  let clean = normalizeArabicNumerals(input)
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (clean.includes('instagram.com/')) {
    const match = clean.match(/instagram\.com\/([a-zA-Z0-9._]+)/i);
    if (match && match[1]) {
      const user = match[1].replace(/^@/, '').toLowerCase().trim();
      return `https://www.instagram.com/${user}/`;
    }
```

FILE (cont.): src/lib/deepLinks.ts

```
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.]/g, '').toLowerCase().trim();
  if (username) {
    return `https://www.instagram.com/${username}/`;
  }
  return clean;
}

/**
 * Normalizes Telegram usernames/URLs to https://t.me/<clean_lowercase_username>
 */
export function formatTelegramTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (clean.includes('t.me/') || clean.includes('telegram.me/')) {
    const match = clean.match(/(?:t\.me|telegram\.me)\/([a-zA-Z0-9_]+)/i);
    if (match && match[1]) {
      return `https://t.me/${match[1].replace(/^@/, '').toLowerCase().trim()}`;
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w]/g, '').toLowerCase().trim();
  if (username) {
    return `https://t.me/${username}`;
  }
  return clean;
}

/**
 * Normalizes Snapchat usernames/URLs to https://www.snapchat.com/add/<clean_lowercase_username>
 */
export function formatSnapchatTargetUrl(input: string): string {
  if (!input) return '';
  let clean = input
    .replace(/[\u200B-\u200D\uFEFF\u200E\u200F\u202A-\u202E]/g, '')
    .trim()
    .replace(/^["']|["']$/g, '')
    .trim();

  if (clean.includes('snapchat.com/add/')) {
    const match = clean.match(/snapchat\.com\/add\/([a-zA-Z0-9_.-]+)/i);
    if (match && match[1]) {
      return `https://www.snapchat.com/add/${match[1].replace(/^@/, '').toLowerCase().trim()}`;
    }
    if (!clean.startsWith('http://') && !clean.startsWith('https://')) {
      return `https://${clean}`;
    }
    return clean;
  }
  let username = clean.replace(/^[/@]+/, '').split('?')[0].split('/')[0].trim();
  username = username.replace(/[^\w.-]/g, '').toLowerCase().trim();
  if (username) {
    return `https://www.snapchat.com/add/${username}`;
  }
```

FILE (cont.): src/lib/deepLinks.ts

```
  return clean;
}

/**
 * Analyzes user input and produces clean, universal URLs, deep links,
 * or bank details that work flawlessly across mobile and desktop.
 */
export function processSmartLink(rawInput: string, preferredType?: AppType): DeepLinkInfo {
  const sanitized = cleanAndSanitizeUrl(rawInput);
  const trimmed = sanitized.trim();

  // Handle Bank Type
  if (preferredType === 'bank' || trimmed.startsWith('bank://')) {
    const bankDetails = decodeBankDetails(trimmed) || {
      bankName: 'bÖ3bv( b†Fd6J',
      accountNumber: trimmed.replace(/^https?:\/\//, ''),
    };

    return {
      appType: 'bank',
      appTitleAr: bankDetails.bankName || 'bÖ3bv( b†Fd6J',
      schemeUrl: trimmed.startsWith('bank://') ? trimmed : encodeBankDetails(bankDetails),
      fallbackUrl: '#',
      displayUrl: bankDetails.accountNumber ? `${bankDetails.bankName}: ${bankDetails.accountNumber}` : '
      isBankCard: true,
      bankDetails,
    };
  }

  // Handle Smart Wallet (Vodafone Cash, Etisalat, Orange, WE Pay)
  if (preferredType === 'wallet') {
    const normalized = normalizeArabicNumerals(trimmed);
    let cleanTrimmed = normalized;
    if (cleanTrimmed.startsWith('tel:*9*7*')) {
      cleanTrimmed = cleanTrimmed.replace('tel:*9*7*', '').replace('#', '').replace('%23', '');
    }

    // 1. Check if input is a Web URL or Quick Payment Link (e.g. https://... or vf.eg or web.vodafone.co
    if (isQuickPayUrl(cleanTrimmed)) {
      let fullUrl = cleanTrimmed;
      if (!fullUrl.startsWith('http://') && !fullUrl.startsWith('https://') && !fullUrl.startsWith('inten
        fullUrl = `https://${fullUrl}`;
      }
      return {
        appType: 'wallet',
        appTitleAr: 'dV-d 8b’ Cbv4 (c 'b†7 bvDböAc’ 'dF3c Jc’’rÀ
        schemeUrl: fullUrl,
        fallbackUrl: fullUrl,
        displayUrl: fullUrl.replace(/^https?:\/\//, ''),
        isWalletCard: false, // Direct instant redirect to payment link!
      };
    }

    // 2. Otherwise, input is a wallet phone number (e.g. 010..., 012..., 011..., 015..., f af âââ•
    const detected = detectWalletInfo(cleanTrimmed);

    return {
      appType: 'wallet',
      appTitleAr: `${detected.nameAr} - ${detected.nameEn}`,
      schemeUrl: '', // Dedicated copy screen only - NO intent or USSD
      fallbackUrl: '',
      displayUrl: detected.cleanPhone,
      isWalletCard: true, // Show dedicated luxury card with logo, company name, phone, and copy button O
      walletProvider: detected.provider,
      walletProviderNameAr: detected.nameAr,
      walletProviderNameEn: detected.nameEn,
      walletCompanyNameAr: detected.companyNameAr,
      walletPhone: detected.cleanPhone,
```

FILE (cont.): src/lib/deepLinks.ts

```
      walletFormattedPhone: detected.formattedPhone,
    };
  }

  if (!trimmed) {
    return {
      appType: preferredType || 'website',
      appTitleAr: 'c 'b†7 d†Jb,rÀ
      schemeUrl: '',
      fallbackUrl: '',
      displayUrl: '',
    };
  }

  // 1. WhatsApp
  const isWhatsAppInput =
    preferredType === 'whatsapp' ||
    trimmed.includes('wa.me') ||
    trimmed.includes('whatsapp.com') ||
    trimmed.startsWith('whatsapp://') ||
    (!preferredType && /^(?:\+?20|0)?1[0125]\d{8}$/.test(rawInput.trim()));

  if (isWhatsAppInput) {
    let phoneDigits = '';
    let customText = '';

    if (trimmed.includes('wa.me/')) {
      const parts = trimmed.split('wa.me/')[1]?.split('?') || [];
      phoneDigits = parts[0]?.replace(/[^\d]/g, '') || '';
      if (parts[1]?.includes('text=')) {
        customText = new URLSearchParams(parts[1]).get('text') || '';
      }
    } else if (trimmed.includes('phone=')) {
      try {
        const urlObj = new URL(trimmed.startsWith('http') ? trimmed : `https://${trimmed}`);
        phoneDigits = urlObj.searchParams.get('phone')?.replace(/[^\d]/g, '') || '';
        customText = urlObj.searchParams.get('text') || '';
      } catch {
        phoneDigits = trimmed.replace(/[^\d]/g, '');
      }
    } else {
      phoneDigits = rawInput.trim().replace(/[^\d]/g, '');
    }

    // Auto format Egyptian numbers: 010... -> 2010...
    if (phoneDigits.startsWith('01') && phoneDigits.length === 11) {
      phoneDigits = '2' + phoneDigits;
    }

    const textQueryParam = customText ? `?text=${encodeURIComponent(customText)}` : '';
    const universalUrl = `https://wa.me/${phoneDigits}${textQueryParam}`;

    return {
      appType: 'whatsapp',
      appTitleAr: 'd†'b¦3bv( WhatsApp',
      schemeUrl: universalUrl,
      fallbackUrl: universalUrl,
      displayUrl: `wa.me/${phoneDigits}`,
    };
  }

  // 2. Phone Call
  const isPhone =
    preferredType === 'phone' ||
    trimmed.startsWith('tel:') ||
    (!preferredType && /^(\+|00)?\d{7,15}$/.test(rawInput.trim().replace(/[\s-]/g, '')));

  if (isPhone) {
```

FILE (cont.): src/lib/deepLinks.ts

```
    const cleanNumber = rawInput.trim().replace(/[^\d+]/g, '');
    const telUrl = `tel:${cleanNumber}`;
    return {
      appType: 'phone',
      appTitleAr: 'bv*cV'dB Gbv*d J',
      schemeUrl: telUrl,
      fallbackUrl: telUrl,
      displayUrl: cleanNumber,
    };
  }

  // 3. InstaPay Egypt (Quick Pay Link ONLY - Direct instant redirect)
  const isInstaPay =
    preferredType === 'instapay' ||
    trimmed.includes('ipn.eg') ||
    trimmed.includes('instapay');

  if (isInstaPay) {
    let paymentUrl = trimmed;
    if (paymentUrl.startsWith('ipn.eg/')) {
      paymentUrl = `https://${paymentUrl}`;
    } else if (!paymentUrl.startsWith('http://') && !paymentUrl.startsWith('https://')) {
      if (paymentUrl.includes('ipn.eg')) {
        paymentUrl = `https://${paymentUrl}`;
      } else {
        paymentUrl = `https://ipn.eg/${paymentUrl.replace(/^@/, '').replace(/@instapay$/i, '')}`;
      }
    }

    return {
      appType: 'instapay',
      appTitleAr: 'bVFc6*bv(bvJ InstaPay',
      schemeUrl: paymentUrl,
      fallbackUrl: paymentUrl,
      displayUrl: paymentUrl.replace(/^https?:\/\//, ''),
      isInstaPayCard: false, // Direct instant redirect to InstaPay quick payment link!
    };
  }



  // 4. Instagram
  const isInstagram =
    preferredType === 'instagram' ||
    trimmed.includes('instagram.com') ||
    (preferredType === undefined && rawInput.trim().startsWith('@') && !trimmed.includes('instapay'));

  if (isInstagram) {
    const universalUrl = formatInstagramTargetUrl(trimmed || rawInput);
    const match = universalUrl.match(/instagram\.com\/([a-zA-Z0-9._]+)/);
    const username = match ? match[1] : trimmed.replace(/^@/, '');

    return {
      appType: 'instagram',
      appTitleAr: 'bVFc6*bÆ1bvE Instagram',
      schemeUrl: universalUrl,
      fallbackUrl: universalUrl,
      displayUrl: `@${username}`,
    };
  }

  // 5. Facebook
  const isFacebook =
    preferredType === 'facebook' ||
    trimmed.includes('facebook.com') ||
    trimmed.includes('fb.me') ||
    trimmed.includes('fb.watch');

```

FILE (cont.): src/lib/deepLinks.ts

```
  if (isFacebook) {
    let cleanUrl = trimmed;
    if (!cleanUrl.startsWith('http://') && !cleanUrl.startsWith('https://')) {
      cleanUrl = `https://www.facebook.com/${cleanUrl.replace(/^www\./, '')}`;
    }
    return {
      appType: 'facebook',
      appTitleAr: 'd Jc6(d†C Facebook',
      schemeUrl: cleanUrl,
      fallbackUrl: cleanUrl,
      displayUrl: cleanUrl.replace(/^https?:\/\/(www\.)?facebook\.com\/?/, 'fb.com/'),
    };
  }

  // 6. Telegram
  const isTelegram =
    preferredType === 'telegram' ||
    trimmed.includes('t.me') ||
    trimmed.includes('telegram.me');

  if (isTelegram) {
    const universalUrl = formatTelegramTargetUrl(trimmed || rawInput);
    const match = universalUrl.match(/(?:t\.me|telegram\.me)\/([a-zA-Z0-9_]+)/);
    const handle = match ? match[1] : trimmed.replace(/^@/, '');

    return {
      appType: 'telegram',
      appTitleAr: 'b¦JdFJbÆ1bvE Telegram',
      schemeUrl: universalUrl,
      fallbackUrl: universalUrl,
      displayUrl: `t.me/${handle}`,
    };
  }

  // 7. TikTok (Direct App & Profile Universal Link)
  const isTikTok =
    preferredType === 'tiktok' ||
    trimmed.includes('tiktok.com');

  if (isTikTok) {
    const universalUrl = formatTikTokTargetUrl(trimmed || rawInput);
    const match = universalUrl.match(/tiktok\.com\/@([a-zA-Z0-9_.-]+)/i);
    const displayUser = match ? match[1] : trimmed.replace(/^@/, '');

    return {
      appType: 'tiktok',
      appTitleAr: 'b¦Jd2 *d†C TikTok',
      schemeUrl: universalUrl,
      fallbackUrl: universalUrl,
      displayUrl: `tiktok.com/@${displayUser}`,
    };
  }

  // 8. Snapchat
  const isSnapchat =
    preferredType === 'snapchat' ||
    trimmed.includes('snapchat.com');

  if (isSnapchat) {
    let user = trimmed;
    if (trimmed.includes('snapchat.com/add/')) {
      user = trimmed.split('snapchat.com/add/')[1]?.split('?')[0] || '';
    } else {
      user = rawInput.trim().replace(/^@/, '');
    }
    const universalUrl = `https://www.snapchat.com/add/${user}`;
    return {
      appType: 'snapchat',
```

FILE (cont.): src/lib/deepLinks.ts

```
      appTitleAr: 'c6Fbv( cF'b¢ 6æ  6† BrÀ
      schemeUrl: universalUrl,
      fallbackUrl: universalUrl,
      displayUrl: `snapchat.com/add/${user}`,
    };
  }

  // 9. Standard Web URL / Fallback
  let webUrl = trimmed;
  if (!webUrl.startsWith('http://') && !webUrl.startsWith('https://')) {
    webUrl = `https://${webUrl}`;
  }

  return {
    appType: preferredType || 'website',
    appTitleAr: 'c 'b†7 d†Jb,rÀ
    schemeUrl: webUrl,
    fallbackUrl: webUrl,
    displayUrl: webUrl.replace(/^https?:\/\//, ''),
  };
}

/**
 * Triggers instant direct opening of the target URL or app.
 * IMPORTANT: Checks if running inside an iframe (like AI Studio preview),
 * avoiding the X-Frame-Options: DENY iframe crash.
 */
export function triggerSmartRedirect(linkInfo: DeepLinkInfo): void {
  const target = linkInfo.schemeUrl || linkInfo.fallbackUrl;
  if (!target || target === '#' || target.startsWith('intent:') || !isSafeUrlScheme(target)) return;

  const inIframe = isRunningInIframe();

  if (inIframe) {
    // If inside an iframe (AI Studio preview):
    // Trying window.location.replace() to an external domain (e.g. wa.me, ipn.eg)
    // will be blocked by the browser with X-Frame-Options: DENY.
    // Instead, open in top window or new window:
    try {
      if (window.top) {
        window.top.location.href = target;
        return;
      }
    } catch {
      // Cross-origin top access blocked, open in new tab
    }
    window.open(target, '_blank', 'noopener,noreferrer');
  } else {
    // On real mobile device or standalone browser tab:
    try {
      window.location.replace(target);
    } catch {
      window.location.href = target;
    }
  }
}

```

FILE: src/lib/qrService.ts 885 lines | 26.3 KB

```
import QRCode from 'qrcode';
import jsQR from 'jsqr';
import { doc, getDoc, setDoc, updateDoc, deleteDoc, getDocs, collection, writeBatch, increment, onSnapsho
import { db } from './firebase';
import { AppType, QrCodeRecord, PlatformSettings } from '../types/qr';
import { processSmartLink } from './deepLinks';
import { authFetch } from './auth';

const LOCAL_STORAGE_KEY = 'smart_qr_codes_local_cache';
const SETTINGS_CACHE_KEY = 'smart_qr_platform_settings';

// Helper for offline caching with defensive sanitization
function getLocalCache(): Record<string, QrCodeRecord> {
  try {
    const raw = localStorage.getItem(LOCAL_STORAGE_KEY);
    if (!raw) return {};
    const parsed = JSON.parse(raw);
    const clean: Record<string, QrCodeRecord> = {};
    if (parsed && typeof parsed === 'object') {
      Object.keys(parsed).forEach((k) => {
        if (k && k !== 'undefined' && k !== 'null' && parsed[k]) {
          const recId = parsed[k].id || k;
          if (recId && recId !== 'undefined' && recId !== 'null') {
            clean[recId] = { ...parsed[k], id: recId };
          }
        }
      });
    }
    return clean;
  } catch {
    return {};
  }
}

function saveLocalCache(cache: Record<string, QrCodeRecord>) {
  try {
    localStorage.setItem(LOCAL_STORAGE_KEY, JSON.stringify(cache));
  } catch (e) {
    console.warn('LocalStorage save warning:', e);
  }
}

/**
 * Generates bulk unique QR codes with user-specified count and subscription duration
 */
export async function generateBulkQrCodes(count: number, subscriptionMonths = 1): Promise<QrCodeRecord[]>
  const safeCount = Math.max(1, count || 1);
  const now = new Date();
  const expiresAt = subscriptionMonths > 0
    ? new Date(now.getTime() + subscriptionMonths * 30 * 24 * 60 * 60 * 1000).toISOString()
    : null;

  let generatedRecords: QrCodeRecord[] = [];

  // Try Server API first if running on Node/Express full stack
  try {
    const res = await authFetch('/api/qr/bulk', {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({ count: safeCount, subscription_months: subscriptionMonths, expires_at: expir
    });

    const contentType = res.headers.get('content-type') || '';
    if (res.ok && contentType.includes('application/json')) {
      const json = await res.json();
      if (json.success && Array.isArray(json.data) && json.data.length > 0) {
        generatedRecords = json.data;
      }
```

FILE (cont.): src/lib/qrService.ts

```
    }
  } catch (err) {
    console.warn('Server bulk generate failed, generating client-side:', err);
  }

  // Fallback client-side generation if server temporarily unreachable or running on static host
  if (generatedRecords.length === 0) {
    const { nanoid } = await import('nanoid');
    for (let i = 0; i < safeCount; i++) {
      const id = nanoid(10).replace(/[^a-zA-Z0-9_-]/g, 'x');
      const record: QrCodeRecord = {
        id,
        is_active: false,
        target_url: null,
        created_at: now.toISOString(),
        total_scans: 0,
        subscription_months: subscriptionMonths,
        expires_at: expiresAt,
      };
      generatedRecords.push(record);
    }
  }

  // 1. ALWAYS Save to Local Cache immediately
  const cache = getLocalCache();
  generatedRecords.forEach((r) => {
    cache[r.id] = r;
  });
  saveLocalCache(cache);

  // 2. CRITICAL: ALWAYS Save EVERY generated code to Cloud Firestore!
  // This guarantees persistence across reloads, live polling, and all phones!
  try {
    const batch = writeBatch(db);
    for (const item of generatedRecords) {
      batch.set(doc(db, 'qr_codes', item.id), item);
    }
    await batch.commit();
  } catch (fsErr) {
    console.error('Firestore batch save error:', fsErr);
  }

  return generatedRecords;
}

/**
 * Fetch a single QR Code by ID (searches Firestore and Server API in parallel, with local cache fallback
 */
export async function getQrCode(id: string): Promise<QrCodeRecord | null> {
  const cleanId = id.trim();
  if (!cleanId) return null;

  // 0. Pre-injected server record for instantaneous 0ms resolution
  if (typeof window !== 'undefined' && (window as any).__INITIAL_QR_RECORD__) {
    const initialRec = (window as any).__INITIAL_QR_RECORD__;
    if (initialRec && initialRec.id === cleanId) {
      const cache = getLocalCache();
      cache[cleanId] = initialRec;
      saveLocalCache(cache);
      return initialRec;
    }
  }

  // 1. Fetch from Firestore and Server API concurrently
  const firestoreFetch = getDoc(doc(db, 'qr_codes', cleanId))
    .then((snap) => (snap.exists() ? (snap.data() as QrCodeRecord) : null))
    .catch(() => null);

```

FILE (cont.): src/lib/qrService.ts

```
  const serverFetch = fetch(`/api/qr/${encodeURIComponent(cleanId)}`)
    .then(async (res) => {
      const contentType = res.headers.get('content-type') || '';
      if (res.ok && contentType.includes('application/json')) {
        const json = await res.json();
        return (json.success && json.data) ? (json.data as QrCodeRecord) : null;
      }
      return null;
    })
    .catch(() => null);

  try {
    const results = await Promise.allSettled([firestoreFetch, serverFetch]);
    const fsRecord = results[0].status === 'fulfilled' ? results[0].value : null;
    const srvRecord = results[1].status === 'fulfilled' ? results[1].value : null;

    let bestRecord: QrCodeRecord | null = null;
    if (fsRecord && srvRecord) {
      const fsTime = new Date(fsRecord.updated_at || fsRecord.created_at || 0).getTime();
      const srvTime = new Date(srvRecord.updated_at || srvRecord.created_at || 0).getTime();
      bestRecord = srvTime > fsTime ? srvRecord : fsRecord;
    } else {
      bestRecord = fsRecord || srvRecord;
    }

    if (bestRecord) {
      const cache = getLocalCache();
      cache[cleanId] = bestRecord;
      saveLocalCache(cache);
      return bestRecord;
    }
  } catch (err) {
    console.warn('Concurrent QR fetch warning:', err);
  }

  // 2. Fallback to local cache only if network temporarily unreachable
  const cache = getLocalCache();
  if (cache[cleanId]) {
    return cache[cleanId];
  }

  // 3. Clean inactive record if completely new
  const newInactiveRecord: QrCodeRecord = {
    id: cleanId,
    is_active: false,
    target_url: null,
    created_at: new Date().toISOString(),
    total_scans: 0,
  };
  return newInactiveRecord;
}

/**
 * Strict lookup for an existing QR card in the database or cache.
 * Returns null if the card was never created/registered.
 */
export async function lookupExistingQrCode(id: string): Promise<QrCodeRecord | null> {
  const cleanId = id.trim();
  if (!cleanId) return null;

  // 1. Check local cache
  const cache = getLocalCache();
  if (cache[cleanId] && cache[cleanId].id) {
    return cache[cleanId];
  }

  // 2. Query Firestore and Server concurrently
  const firestoreFetch = getDoc(doc(db, 'qr_codes', cleanId))
```

FILE (cont.): src/lib/qrService.ts

```
    .then((snap) => (snap.exists() ? (snap.data() as QrCodeRecord) : null))
    .catch(() => null);

  const serverFetch = fetch(`/api/qr/${encodeURIComponent(cleanId)}`)
    .then(async (res) => {
      if (res.ok) {
        const json = await res.json();
        return (json.success && json.data) ? (json.data as QrCodeRecord) : null;
      }
      return null;
    })
    .catch(() => null);

  try {
    const results = await Promise.allSettled([firestoreFetch, serverFetch]);
    const fsRecord = results[0].status === 'fulfilled' ? results[0].value : null;
    const srvRecord = results[1].status === 'fulfilled' ? results[1].value : null;

    const found = fsRecord || srvRecord;
    if (found) {
      cache[cleanId] = found;
      saveLocalCache(cache);
      return found;
    }
  } catch {}

  return null;
}

/**
 * Fetch all QR codes for Admin view (Firestore + API + Local cache)
 */
export async function fetchAllQrCodes(): Promise<QrCodeRecord[]> {
  const mergedMap: Record<string, QrCodeRecord> = { ...getLocalCache() };

  // 1. Primary: Direct Cloud Firestore fetch
  try {
    const snap = await getDocs(collection(db, 'qr_codes'));
    if (!snap.empty) {
      snap.forEach((d) => {
        const data = d.data();
        const id = data?.id || d.id;
        if (id && id !== 'undefined' && id !== 'null') {
          const item: QrCodeRecord = {
            created_at: data.created_at || new Date().toISOString(),
            total_scans: data.total_scans || 0,
            is_active: Boolean(data.is_active),
            target_url: data.target_url || null,
            ...data,
            id,
          };
          mergedMap[id] = item;
        }
      });
    }
  } catch (fsErr) {
    console.warn('Firestore fetchAll warning:', fsErr);
  }

  // 2. Try Server API if available and returns JSON
  try {
    const res = await fetch('/api/qr');
    const contentType = res.headers.get('content-type') || '';
    if (res.ok && contentType.includes('application/json')) {
      const json = await res.json();
      if (json.success && Array.isArray(json.data)) {
        json.data.forEach((r: QrCodeRecord) => {
          if (!mergedMap[r.id] || new Date(r.updated_at || r.created_at).getTime() >= new Date(mergedMap[
```

FILE (cont.): src/lib/qrService.ts

```
            mergedMap[r.id] = r;
          }
        });
      }
    }
  } catch {
    // API unreachable
  }

  saveLocalCache(mergedMap);

  return Object.values(mergedMap)
    .filter((r): r is QrCodeRecord => Boolean(r && r.id && r.id !== 'undefined' && r.id !== 'null'))
    .sort(
      (a, b) => new Date(b.created_at || 0).getTime() - new Date(a.created_at || 0).getTime()
    );
}

/**
 * Customer first-time scan activation.
 * Saves directly to Firestore, local cache, and backend API.
 */
export async function activateQrCode(
  id: string,
  rawInput: string,
  preferredType?: AppType
): Promise<{ success: boolean; error?: string; record?: QrCodeRecord }> {
  const smartLink = processSmartLink(rawInput, preferredType);
  const now = new Date();
  const existing = await getQrCode(id);

  // Preserve existing expires_at if set, otherwise default to 1 month from activation
  const defaultExpiry = new Date(now.getTime() + 30 * 24 * 60 * 60 * 1000).toISOString();
  const expires_at = (existing && existing.expires_at !== undefined)
    ? existing.expires_at
    : defaultExpiry;
  const subscription_months = (existing && existing.subscription_months !== undefined)
    ? existing.subscription_months
    : 1;

  const effectiveTargetUrl = (smartLink.isWalletCard && smartLink.walletPhone)
    ? smartLink.walletPhone
    : (smartLink.schemeUrl || smartLink.fallbackUrl);

  const updatedRecord: QrCodeRecord = {
    id,
    is_active: true,
    target_url: effectiveTargetUrl,
    app_type: smartLink.appType,
    updated_at: now.toISOString(),
    created_at: existing?.created_at || now.toISOString(),
    total_scans: 1,
    expires_at,
    subscription_months,
  };

  // 1. Direct Cloud Firestore save with setDoc merge
  try {
    await setDoc(doc(db, 'qr_codes', id), updatedRecord, { merge: true });
  } catch (fsErr) {
    console.warn('Firestore direct activate write warning:', fsErr);
  }

  // 2. Sync to Server API
  try {
    fetch(`/api/qr/${encodeURIComponent(id)}/activate`, {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
```

FILE (cont.): src/lib/qrService.ts

```
      body: JSON.stringify({
        target_url: effectiveTargetUrl,
        app_type: smartLink.appType,
        expires_at,
        subscription_months,
      }),
    }).catch(() => {});
  } catch {}

  // 3. Update local cache
  const cache = getLocalCache();
  cache[id] = updatedRecord;
  saveLocalCache(cache);

  return { success: true, record: updatedRecord };
}

/**
 * Admin Quick Edit: Modify Target URL, label, and subscription expiry.
 * ID is strictly read-only and immutable.
 * Saves simultaneously to Firestore AND Server API.
 */
export async function adminUpdateQrCode(
  id: string,
  rawTargetUrl: string,
  preferredType?: AppType,
  label?: string,
  expiresAt?: string | null,
  subscriptionMonths?: number
): Promise<{ success: boolean; record?: QrCodeRecord }> {
  const smartLink = processSmartLink(rawTargetUrl, preferredType);
  const effectiveTargetUrl = (smartLink.isWalletCard && smartLink.walletPhone)
    ? smartLink.walletPhone
    : (smartLink.schemeUrl || smartLink.fallbackUrl || rawTargetUrl.trim());

  const current: QrCodeRecord = (await getQrCode(id)) || {
    id,
    created_at: new Date().toISOString(),
    total_scans: 0,
    is_active: true,
    target_url: null,
  };

  const updatedRecord: QrCodeRecord = {
    ...current,
    id,
    target_url: effectiveTargetUrl,
    app_type: smartLink.appType,
    is_active: true,
    label: label !== undefined ? label : current.label,
    expires_at: expiresAt !== undefined ? expiresAt : current.expires_at,
    subscription_months: subscriptionMonths !== undefined ? subscriptionMonths : current.subscription_mon
    updated_at: new Date().toISOString(),
  };

  // 1. ALWAYS write to Cloud Firestore with setDoc merge (Primary source of truth for Vercel & Productio
  try {
    await setDoc(doc(db, 'qr_codes', id), updatedRecord, { merge: true });
  } catch (fsErr) {
    console.warn('Firestore admin update warning:', fsErr);
  }

  // 2. ALWAYS sync to Server API if running full-stack Node/Express
  try {
    await authFetch(`/api/qr/${encodeURIComponent(id)}`, {
      method: 'PUT',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({
```

FILE (cont.): src/lib/qrService.ts

```
        target_url: effectiveTargetUrl,
        app_type: smartLink.appType,
        label,
        expires_at: expiresAt,
        subscription_months: subscriptionMonths,
      }),
    });
  } catch (err) {
    console.warn('Server admin update sync failed:', err);
  }

  // 3. Update local cache
  const cache = getLocalCache();
  cache[id] = updatedRecord;
  saveLocalCache(cache);

  return { success: true, record: updatedRecord };
}

/**
 * Quick Subscription Renewal: Extends subscription by N months (+30 days per month).
 * If card is still active, adds to existing expires_at. If expired, adds from now.
 */
export async function renewQrSubscription(
  id: string,
  monthsToAdd = 1
): Promise<{ success: boolean; record?: QrCodeRecord }> {
  const current = await getQrCode(id);
  if (!current) return { success: false };

  const nowMs = Date.now();
  let baseMs = nowMs;
  if (current.expires_at) {
    const existingMs = new Date(current.expires_at).getTime();
    if (existingMs > nowMs) {
      baseMs = existingMs;
    }
  }

  const addedDays = monthsToAdd * 30;
  const newExpiresAt = new Date(baseMs + addedDays * 24 * 60 * 60 * 1000).toISOString();

  const updatedRecord: QrCodeRecord = {
    ...current,
    expires_at: newExpiresAt,
    subscription_months: (current.subscription_months || 0) + monthsToAdd,
    updated_at: new Date().toISOString(),
  };

  try {
    await setDoc(doc(db, 'qr_codes', id), {
      expires_at: newExpiresAt,
      subscription_months: updatedRecord.subscription_months,
      updated_at: updatedRecord.updated_at,
    }, { merge: true });
  } catch (fsErr) {
    console.warn('Firestore renew write warning:', fsErr);
  }

  try {
    fetch(`/api/qr/${encodeURIComponent(id)}`, {
      method: 'PUT',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({
        expires_at: newExpiresAt,
        subscription_months: updatedRecord.subscription_months,
      }),
    }).catch(() => {});
```

FILE (cont.): src/lib/qrService.ts

```
  } catch {}

  const cache = getLocalCache();
  cache[id] = updatedRecord;
  saveLocalCache(cache);

  return { success: true, record: updatedRecord };
}

/**
 * Set custom expiration date or make card permanent (null)
 */
export async function setQrExpiration(
  id: string,
  expiresAt: string | null
): Promise<{ success: boolean; record?: QrCodeRecord }> {
  const current = await getQrCode(id);
  if (!current) return { success: false };

  const updatedRecord: QrCodeRecord = {
    ...current,
    expires_at: expiresAt,
    updated_at: new Date().toISOString(),
  };

  try {
    await setDoc(doc(db, 'qr_codes', id), {
      expires_at: expiresAt,
      updated_at: updatedRecord.updated_at,
    }, { merge: true });
  } catch (fsErr) {
    console.warn('Firestore set expiration warning:', fsErr);
  }

  try {
    fetch(`/api/qr/${encodeURIComponent(id)}`, {
      method: 'PUT',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({ expires_at: expiresAt }),
    }).catch(() => {});
  } catch {}

  const cache = getLocalCache();
  cache[id] = updatedRecord;
  saveLocalCache(cache);

  return { success: true, record: updatedRecord };
}

/**
 * Real-time Live Firestore Subscription for QR Codes
 * Pushes live updates whenever any scan or activation happens without page refresh!
 */
export function subscribeToQrCodes(
  callback: (records: QrCodeRecord[]) => void
): () => void {
  try {
    const qrCol = collection(db, 'qr_codes');
    const unsubscribe = onSnapshot(
      qrCol,
      (snapshot) => {
        const map: Record<string, QrCodeRecord> = { ...getLocalCache() };
        snapshot.forEach((d) => {
          const data = d.data();
          const id = data?.id || d.id;
          if (id && id !== 'undefined' && id !== 'null') {
            const item: QrCodeRecord = {
              created_at: data.created_at || new Date().toISOString(),
```

FILE (cont.): src/lib/qrService.ts

```
              total_scans: data.total_scans || 0,
              is_active: Boolean(data.is_active),
              target_url: data.target_url || null,
              ...data,
              id,
            };
            map[id] = item;
          }
        });
        const list = Object.values(map)
          .filter((item): item is QrCodeRecord => Boolean(item && item.id && item.id !== 'undefined' && i
          .sort(
            (a, b) => new Date(b.created_at || 0).getTime() - new Date(a.created_at || 0).getTime()
          );
        saveLocalCache(map);
        callback(list);
      },
      (err) => {
        console.warn('Firestore onSnapshot subscription warning:', err);
      }
    );
    return unsubscribe;
  } catch (err) {
    console.warn('subscribeToQrCodes error:', err);
    return () => {};
  }
}

/**
 * Real-time live subscription for a single QR code document.
 * Immediately pushes updates (e.g. when Admin changes number or wallet operator)
 * so customer screens or active view updates instantly without reload!
 */
export function subscribeToSingleQrCode(
  id: string,
  callback: (record: QrCodeRecord | null) => void
): () => void {
  const cleanId = id.trim();
  if (!cleanId) return () => {};

  try {
    const docRef = doc(db, 'qr_codes', cleanId);
    const unsubscribe = onSnapshot(
      docRef,
      (snapshot) => {
        if (snapshot.exists()) {
          const rec = snapshot.data() as QrCodeRecord;
          const cache = getLocalCache();
          cache[cleanId] = rec;
          saveLocalCache(cache);
          callback(rec);
        }
      },
      (err) => {
        console.warn('Single QR live subscription warning:', err);
      }
    );
    return unsubscribe;
  } catch (err) {
    console.warn('subscribeToSingleQrCode error:', err);
    return () => {};
  }
}

/**
 * Record a scan count authoritatively in Firestore & local cache
 */
export async function recordQrScan(id: string): Promise<void> {
```

FILE (cont.): src/lib/qrService.ts

```
  const cleanId = id.trim();
  if (!cleanId) return;

  // 1. Direct Firestore atomic increment with setDoc merge (bulletproof on Vercel)
  try {
    const qrRef = doc(db, 'qr_codes', cleanId);
    await setDoc(qrRef, {
      total_scans: increment(1),
      last_scanned_at: new Date().toISOString(),
    }, { merge: true });
  } catch (fsErr) {
    console.warn('Firestore scan increment warning:', fsErr);
  }

  // 2. Also notify backend API if available (keepalive preserves request during navigation)
  try {
    fetch(`/api/qr/${encodeURIComponent(cleanId)}/scan`, {
      method: 'POST',
      keepalive: true
    }).catch(() => {});
  } catch {}

  // 3. Update local cache
  const cache = getLocalCache();
  if (cache[cleanId]) {
    cache[cleanId].total_scans = (cache[cleanId].total_scans || 0) + 1;
    cache[cleanId].last_scanned_at = new Date().toISOString();
    saveLocalCache(cache);
  }
}

/**
 * Reset or manually adjust scan count
 */
export async function resetQrScanCount(id: string, count = 0): Promise<boolean> {
  try {
    const res = await authFetch(`/api/qr/${encodeURIComponent(id)}/reset-scans`, {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({ count }),
    });
    if (res.ok) {
      const cache = getLocalCache();
      if (cache[id]) {
        cache[id].total_scans = count;
        saveLocalCache(cache);
      }
      return true;
    }
  } catch (err) {
    console.warn('Failed to reset scan count:', err);
  }

  try {
    await updateDoc(doc(db, 'qr_codes', id), { total_scans: count });
  } catch {}

  const cache = getLocalCache();
  if (cache[id]) {
    cache[id].total_scans = count;
    saveLocalCache(cache);
  }
  return true;
}

/**
 * Delete a QR Code permanently from database and local cache
 */
```

FILE (cont.): src/lib/qrService.ts

```
export async function deleteQrCode(id: string): Promise<boolean> {
  try {
    const res = await authFetch(`/api/qr/${encodeURIComponent(id)}`, {
      method: 'DELETE',
    });
    if (res.ok) {
      const cache = getLocalCache();
      delete cache[id];
      saveLocalCache(cache);
      return true;
    }
  } catch (err) {
    console.warn('Server delete failed, updating local state:', err);
  }

  try {
    await deleteDoc(doc(db, 'qr_codes', id));
  } catch (fsErr) {
    console.warn('Firestore delete fallback warning:', fsErr);
  }

  const cache = getLocalCache();
  delete cache[id];
  saveLocalCache(cache);
  return true;
}

/**
 * Generate Classic QR Code Image Data URL (High Resolution for Printing)
 */
export async function generateQrDataUrl(qrUrl: string, width = 512): Promise<string> {
  return QRCode.toDataURL(qrUrl, {
    errorCorrectionLevel: 'M',
    margin: 2,
    width,
    color: {
      dark: '#000000',
      light: '#ffffff',
    },
  });
}

/**
 * Decode QR Code from an uploaded image file using jsQR
 */
export async function decodeQrFromImageFile(file: File): Promise<string | null> {
  return new Promise((resolve) => {
    const reader = new FileReader();
    reader.onload = (e) => {
      const img = new Image();
      img.onload = () => {
        const canvas = document.createElement('canvas');
        const ctx = canvas.getContext('2d');
        if (!ctx) {
          resolve(null);
          return;
        }

        canvas.width = img.width;
        canvas.height = img.height;
        ctx.drawImage(img, 0, 0, img.width, img.height);

        const imageData = ctx.getImageData(0, 0, canvas.width, canvas.height);
        const code = jsQR(imageData.data, imageData.width, imageData.height, {
          inversionAttempts: 'attemptBoth',
        });

        if (code && code.data) {
```

FILE (cont.): src/lib/qrService.ts

```
          resolve(code.data);
        } else {
          resolve(null);
        }
      };
      img.onerror = () => resolve(null);
      img.src = e.target?.result as string;
    };
    reader.onerror = () => resolve(null);
    reader.readAsDataURL(file);
  });
}

/**
 * Extract QR ID from scanned string or URL.
 */
export function extractQrIdFromUrl(rawText: string): string {
  const trimmed = rawText.trim();
  if (!trimmed) return '';

  const match = trimmed.match(/\/q\/([a-zA-Z0-9_-]+)/);
  if (match && match[1]) {
    return match[1];
  }

  if (/^[a-zA-Z0-9_-]{6,32}$/.test(trimmed)) {
    return trimmed;
  }

  const parts = trimmed.split('/');
  const lastPart = parts[parts.length - 1]?.split('?')[0];
  if (lastPart && /^[a-zA-Z0-9_-]+$/.test(lastPart)) {
    return lastPart;
  }

  return trimmed;
}

const DEFAULT_PLATFORM_SETTINGS: PlatformSettings = {
  developer_whatsapp: '01550523365',
  developer_contact_url: 'https://wa.me/201550523365',
  developer_title: 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
  support_message: 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’rÀ
  public_domain_url: 'https://smart-card-inky.vercel.app',
};

/**
 * Fetch platform settings from server with local fallback
 */
export async function fetchPlatformSettings(): Promise<PlatformSettings> {
  try {
    const res = await fetch('/api/settings');
    if (res.ok) {
      const json = await res.json();
      if (json.success && json.data) {
        try {
          localStorage.setItem(SETTINGS_CACHE_KEY, JSON.stringify(json.data));
        } catch {}
        return json.data;
      }
    }
  } catch (err) {
    console.warn('Failed to fetch settings from server, using local fallback:', err);
  }

  try {
    const snap = await getDoc(doc(db, 'settings', 'platform'));
    if (snap.exists()) {
```

FILE (cont.): src/lib/qrService.ts

```
      const data = { ...DEFAULT_PLATFORM_SETTINGS, ...snap.data() } as PlatformSettings;
      try {
        localStorage.setItem(SETTINGS_CACHE_KEY, JSON.stringify(data));
      } catch {}
      return data;
    }
  } catch {}

  try {
    const cached = localStorage.getItem(SETTINGS_CACHE_KEY);
    if (cached) return JSON.parse(cached);
  } catch {}

  return DEFAULT_PLATFORM_SETTINGS;
}

/**
 * Update platform settings (developer contact / WhatsApp link / Public Domain)
 */
export async function updatePlatformSettings(settings: Partial<PlatformSettings>): Promise<PlatformSettin
  let cleanPhone = (settings.developer_whatsapp || '').trim();
  let contactUrl = (settings.developer_contact_url || '').trim();
  let cleanDomain = (settings.public_domain_url !== undefined ? settings.public_domain_url : '').trim();
  if (cleanDomain.endsWith('/')) cleanDomain = cleanDomain.slice(0, -1);

  if (!contactUrl && cleanPhone) {
    let num = cleanPhone.replace(/[^\d]/g, '');
    if (num.startsWith('01')) num = '2' + num;
    contactUrl = `https://wa.me/${num}`;
  }

  const payload: PlatformSettings = {
    developer_whatsapp: cleanPhone || '01550523365',
    developer_contact_url: contactUrl || 'https://wa.me/201550523365',
    developer_title: settings.developer_title || 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
    support_message: settings.support_message || 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’rÀ
    public_domain_url: cleanDomain,
  };

  try {
    const res = await authFetch('/api/settings', {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify(payload),
    });

    if (res.ok) {
      const json = await res.json();
      if (json.success && json.data) {
        try {
          localStorage.setItem(SETTINGS_CACHE_KEY, JSON.stringify(json.data));
        } catch {}
        return json.data;
      }
    }
  } catch (err) {
    console.warn('Failed to save settings on server, updating local cache only:', err);
  }

  try {
    await setDoc(doc(db, 'settings', 'platform'), payload, { merge: true });
  } catch {}

  try {
    localStorage.setItem(SETTINGS_CACHE_KEY, JSON.stringify(payload));
  } catch {}
  return payload;
}
```

FILE (cont.): src/lib/qrService.ts

```
885
```

FILE: src/lib/firebase.ts 73 lines | 2.1 KB

```ts
import { initializeApp } from 'firebase/app';
import { getAuth } from 'firebase/auth';
import { doc, getDocFromServer, initializeFirestore } from 'firebase/firestore';
import firebaseConfig from '../../firebase-applet-config.json';

const app = initializeApp(firebaseConfig);

// CRITICAL: The app requires firebaseConfig.firestoreDatabaseId with auto-detect long polling for iframe
export const db = initializeFirestore(app, {
  experimentalAutoDetectLongPolling: true,
}, firebaseConfig.firestoreDatabaseId);
export const auth = getAuth(app);

export enum OperationType {
  CREATE = 'create',
  UPDATE = 'update',
  DELETE = 'delete',
  LIST = 'list',
  GET = 'get',
  WRITE = 'write',
}

export interface FirestoreErrorInfo {
  error: string;
  operationType: OperationType;
  path: string | null;
  authInfo: {
    userId?: string | null;
    email?: string | null;
    emailVerified?: boolean | null;
    isAnonymous?: boolean | null;
    tenantId?: string | null;
    providerInfo?: {
      providerId?: string | null;
      email?: string | null;
    }[];
  };
}

export function handleFirestoreError(error: unknown, operationType: OperationType, path: string | null):
  const errInfo: FirestoreErrorInfo = {
    error: error instanceof Error ? error.message : String(error),
    authInfo: {
      userId: auth.currentUser?.uid,
      email: auth.currentUser?.email,
      emailVerified: auth.currentUser?.emailVerified,
      isAnonymous: auth.currentUser?.isAnonymous,
      tenantId: auth.currentUser?.tenantId,
      providerInfo: auth.currentUser?.providerData?.map(provider => ({
        providerId: provider.providerId,
        email: provider.email,
      })) || [],
    },
    operationType,
    path,
  };
  console.error('Firestore Error:', JSON.stringify(errInfo));
  throw new Error(JSON.stringify(errInfo));
}

// Test connection on boot
async function testConnection() {
  try {
    await getDocFromServer(doc(db, 'test', 'connection'));
  } catch (error) {
    if (error instanceof Error && error.message.includes('the client is offline')) {
      console.warn('Firestore client is offline, check connection.');
    }
```

FILE (cont.): src/lib/firebase.ts

```
  }
}

testConnection().catch(() => {});

```

FILE: src/views/AdminLoginView.tsx 131 lines | 5.5 KB

```tsx
import { useState } from 'react';
import { Eye, EyeOff, ShieldCheck, ArrowRight, AlertCircle, Lock } from 'lucide-react';
import { loginAdmin } from '../lib/auth';

interface AdminLoginViewProps {
  onLoginSuccess: () => void;
  onNavigateHome: () => void;
}

export function AdminLoginView({ onLoginSuccess, onNavigateHome }: AdminLoginViewProps) {
  const [password, setPassword] = useState('');
  const [showPassword, setShowPassword] = useState(false);
  const [errorMsg, setErrorMsg] = useState<string | null>(null);
  const [loading, setLoading] = useState(false);

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    if (!password.trim()) return;

    setErrorMsg(null);
    setLoading(true);

    try {
      const ok = await loginAdmin(password.trim());
      if (ok) {
        onLoginSuccess();
      } else {
        setErrorMsg('d6DdV) bvDdV1d†1 c¦Jc  5bÖJbÖ). d¦1bÆI bvDb¦#d6/ d†%c–'bö) bvDdV-bvHdF).');
      }
    } catch {
      setErrorMsg('bÖ/b² .cv# b6+df'b  'dF*bÖBd" Edb CdFEb’ 'dFEc Hc âr“°
    } finally {
      setLoading(false);
    }
  };

  return (
    <div className="min-h-screen bg-[#09090b] text-white selection:bg-amber-500 selection:text-black flex
      {/* Background ambient gold glows */}
      <div className="absolute top-1/4 -left-20 w-80 h-80 bg-amber-500/10 rounded-full blur-3xl pointer-e
      <div className="absolute bottom-1/4 -right-20 w-80 h-80 bg-yellow-500/10 rounded-full blur-3xl poin

      {/* Back to Home Button */}
      <button
        onClick={onNavigateHome}
        className="absolute top-6 right-6 flex items-center gap-2 text-xs font-semibold text-amber-300/80
      >
        <ArrowRight className="w-4 h-4" />
        bvDc–Hbö) dFDc &d¦3d¦)
      </button>

      {/* Login Card */}
      <div className="w-full max-w-md bg-[#121216] border border-amber-500/30 rounded-3xl p-8 sm:p-10 sha
        <div className="text-center space-y-3 mb-8">
          <img
            src="/logo.png"
            alt="Smart Card"
            className="w-16 h-16 object-contain rounded-2xl mx-auto shadow-lg shadow-amber-500/25 border
          />
          <div>
            <span className="inline-block text-[11px] font-black uppercase tracking-wider text-amber-300
              dFHbÖ) bvDb¦-d6E
            </span>
            <h1 className="text-2xl font-black text-transparent bg-clip-text bg-gradient-to-r from-amber-
              Smart Card
            </h1>
            <p className="text-xs text-slate-400 mt-1">
              b¦3bÆJdB /bæHdB 'dF#böEdb r %bö'c ) bvDc Ed†2 d†'dF*d†,d¦G bvDc Cd
```

FILE (cont.): src/views/AdminLoginView.tsx

```
            </p>
          </div>
        </div>

        {errorMsg && (
          <div className="mb-6 p-3.5 bg-rose-500/20 border border-rose-500/40 rounded-2xl text-xs text-ro
            <AlertCircle className="w-4 h-4 text-rose-400 flex-shrink-0 mt-0.5" />
            <span className="leading-relaxed font-semibold">{errorMsg}</span>
          </div>
        )}

        <form onSubmit={handleSubmit} className="space-y-5">
          <div className="space-y-2">
            <label className="block text-xs font-bold text-amber-200/90">
              d6DdV) bvDdV1d†1 bvDc61d¦) dFDb6/dVF:
            </label>
            <div className="relative">
              <input
                type={showPassword ? 'text' : 'password'}
                value={password}
                onChange={(e) => setPassword(e.target.value)}
                placeholder="b6/bæD d6DdV) bvDdV1d†1..."
                className="w-full px-4 py-3.5 bg-black/50 border border-amber-500/25 rounded-2xl text-sm
                dir="ltr"
                required
                autoFocus
              />
              <button
                type="button"
                onClick={() => setShowPassword(!showPassword)}
                className="absolute left-3.5 top-3.5 text-slate-400 hover:text-amber-300 transition curso
                title={showPassword ? 'bV.d 'b r ¢ v%c†Gbv1'}
              >
                {showPassword ? <EyeOff className="w-4 h-4" /> : <Eye className="w-4 h-4" />}
              </button>
            </div>
          </div>

          <button
            type="submit"
            disabled={loading || !password.trim()}
            className="w-full py-3.5 px-4 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 hov
          >
            {loading ? (
              <span>bÆ'c J bvDb¦-d&B...</span>
            ) : (
              <>
                <ShieldCheck className="w-5 h-5 text-black" />
                <span>bö.d†D dFHbÖ) bvDb¦-d6E</span>
              </>
            )}
          </button>
        </form>

        <div className="mt-8 pt-6 border-t border-white/5 text-center flex items-center justify-center ga
          <Lock className="w-3.5 h-3.5 text-amber-400/60" />
          <span>b&Edf) d†EbÖEd¦)</span>
        </div>
      </div>
    </div>
  );
}
```

FILE: src/views/AdminDashboardView.tsx 1292 lines | 61.9 KB

```tsx
import { useState, useEffect } from 'react';
import {
  Plus,
  Upload,
  Camera,
  Printer,
  Search,
  Filter,
  QrCode as QrIcon,
  Download,
  Copy,
  Check,
  ExternalLink,
  LogOut,
  Lock,
  RefreshCw,
  Smartphone,
  Eye,
  Activity,
  BarChart3,
  CheckCircle2,
  Clock,
  Sparkles,
  KeyRound,
  Grid,
  List,
  SlidersHorizontal,
  Trash2,
  AlertTriangle,
  AlertCircle,
  MessageSquare,
  Phone,
  Settings,
  Globe,
  Edit3,
  Calendar,
  FileText,
  Code2
} from 'lucide-react';
import { fetchAllQrCodes, generateQrDataUrl, deleteQrCode, getQrCode, lookupExistingQrCode, fetchPlatform
import { logoutAdmin, changeAdminPassword } from '../lib/auth';
import { BulkGenerateModal } from '../components/BulkGenerateModal';
import { UploadQrModal } from '../components/UploadQrModal';
import { EditQrModal } from '../components/EditQrModal';
import { PrintSheetModal } from '../components/PrintSheetModal';
import { QrScannerModal } from '../components/QrScannerModal';
import { DeveloperSettingsModal } from '../components/DeveloperSettingsModal';
import { PWAHeaderButton } from '../components/PWAInstallBanner';
import { QrCodeRecord, PlatformSettings } from '../types/qr';
import { PlatformBrandIcon } from '../components/BrandIcons';

interface AdminDashboardViewProps {
  onLogout: () => void;
  domainUrl: string;
  onSimulateScan: (id: string) => void;
}

function formatDisplayTarget(url: string | null | undefined, appType?: string): string {
  if (!url) return '— (c¦Jc  Ec–Jdb (c–/)';
  if (appType === 'wallet') {
    if (url.startsWith('tel:*9*7*')) {
      const num = url.replace('tel:*9*7*', '').replace('#', '').replace('%23', '');
      return num ? `dV-d 8b“¢ G¶çV×Ö  ¢ vEbÖAc†) d6'cBs°
    }
    if (!url.startsWith('http://') && !url.startsWith('https://')) {
      return `dV-d 8b“¢ G·W&ÇÖ °
    }
  }
```

FILE (cont.): src/views/AdminDashboardView.tsx

```tsx
  if (url.startsWith('bank://')) {
    return 'b†JbvFbv* bÖ3bv( b†Fd6J';
  }
  return url;
}

export function AdminDashboardView({ onLogout, domainUrl, onSimulateScan }: AdminDashboardViewProps) {
  const [records, setRecords] = useState<QrCodeRecord[]>([]);
  const [loading, setLoading] = useState(true);
  const [searchTerm, setSearchTerm] = useState('');
  const [filterStatus, setFilterStatus] = useState<'all' | 'active' | 'inactive' | 'expired'>('all');
  const [viewMode, setViewMode] = useState<'grid' | 'table'>('grid');
  const [renewingId, setRenewingId] = useState<string | null>(null);

  // Modals state
  const [isBulkOpen, setIsBulkOpen] = useState(false);
  const [isUploadOpen, setIsUploadOpen] = useState(false);
  const [isScannerOpen, setIsScannerOpen] = useState(false);
  const [isPrintOpen, setIsPrintOpen] = useState(false);
  const [isPasswordModalOpen, setIsPasswordModalOpen] = useState(false);
  const [currentPassword, setCurrentPassword] = useState('');
  const [newPassword, setNewPassword] = useState('');
  const [confirmPassword, setConfirmPassword] = useState('');
  const [passwordError, setPasswordError] = useState<string | null>(null);
  const [passwordSaving, setPasswordSaving] = useState(false);
  const [passwordSuccess, setPasswordSuccess] = useState(false);

  // Developer Settings Modal State
  const [isSettingsModalOpen, setIsSettingsModalOpen] = useState(false);
  const [platformSettings, setPlatformSettings] = useState<PlatformSettings>({
    developer_whatsapp: '01550523365',
    developer_contact_url: 'https://wa.me/201550523365',
    developer_title: 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
    support_message: 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’rÀ
  });

  // Edit modal
  const [selectedEditRecord, setSelectedEditRecord] = useState<QrCodeRecord | null>(null);

  // Delete modal state
  const [codeToDelete, setCodeToDelete] = useState<string | null>(null);
  const [isDeleting, setIsDeleting] = useState(false);

  // QR Thumbnails cache
  const [qrThumbs, setQrThumbs] = useState<Record<string, string>>({});
  const [copiedId, setCopiedId] = useState<string | null>(null);

  const handleConfirmDelete = async () => {
    if (!codeToDelete) return;
    setIsDeleting(true);
    try {
      await deleteQrCode(codeToDelete);
      setRecords((prev) => prev.filter((r) => r.id !== codeToDelete));
      setCodeToDelete(null);
    } catch (err) {
      console.error('Delete failed:', err);
    } finally {
      setIsDeleting(false);
    }
  };

  const handleQuickRenew = async (id: string, months = 1) => {
    setRenewingId(id);
    try {
      const res = await renewQrSubscription(id, months);
      if (res.success && res.record) {
        setRecords((prev) => prev.map((r) => (r.id === id ? res.record! : r)));
      }
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
    } catch (err) {
      console.error('Quick renew failed:', err);
    } finally {
      setRenewingId(null);
    }
  };

  const loadData = async () => {
    setLoading(true);
    try {
      const data = await fetchAllQrCodes();
      const safeData = Array.isArray(data)
        ? data.filter((item): item is QrCodeRecord => Boolean(item && item.id && item.id !== 'undefined'
        : [];
      setRecords(safeData);

      // Pre-generate thumbnails for first batch
      const thumbs: Record<string, string> = {};
      for (const item of safeData.slice(0, 30)) {
        if (item && item.id) {
          thumbs[item.id] = await generateQrDataUrl(`${domainUrl}/q/${item.id}`, 200);
        }
      }
      setQrThumbs(thumbs);
    } catch (err) {
      console.error('Failed to load QR codes:', err);
    } finally {
      setLoading(false);
    }
  };

  useEffect(() => {
    loadData();
    fetchPlatformSettings().then((s) => {
      if (s) setPlatformSettings(s);
    });

    // Real-time Live Firestore onSnapshot: instant updates without refresh!
    const unsubscribe = subscribeToQrCodes((liveRecords) => {
      const safe = Array.isArray(liveRecords)
        ? liveRecords.filter((r): r is QrCodeRecord => Boolean(r && r.id && r.id !== 'undefined' && r.id
        : [];
      setRecords(safe);
      setLoading(false);
    });

    // Also periodic 4-second background refresh to guarantee live numbers
    const pollInterval = setInterval(() => {
      loadData();
    }, 4000);

    return () => {
      unsubscribe();
      clearInterval(pollInterval);
    };
  }, [domainUrl]);

  const handleCopyLink = (id: string) => {
    const fullUrl = `${domainUrl}/q/${id}`;
    navigator.clipboard.writeText(fullUrl);
    setCopiedId(id);
    setTimeout(() => setCopiedId(null), 2000);
  };

  const handleDownloadQr = async (record: QrCodeRecord) => {
    const fullUrl = `${domainUrl}/q/${record.id}`;
    const dataUrl = await generateQrDataUrl(fullUrl, 800);
    const link = document.createElement('a');
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
    link.href = dataUrl;
    link.download = `QR_${record.id}.png`;
    link.click();
  };

  const handleUpdatePassword = async (e: React.FormEvent) => {
    e.preventDefault();
    setPasswordError(null);
    const cleanCurrent = currentPassword.trim();
    const cleanNew = newPassword.trim();

    if (!cleanCurrent) {
      setPasswordError('bvDc ,bv! bV/bæ'dB CdFEb’ 'dFEc Hc  'dF-bvDd¦).');
      return;
    }

    if (cleanNew.length < 4) {
      setPasswordError('d6DdV) bvDdV1d†1 bvDbÆ/d¦/b’ JbÆ( b6F dF' b¦BdB 9db B .bvFbv*.');
      return;
    }

    if (cleanNew !== confirmPassword.trim()) {
      setPasswordError('d6DdV*br 'dFEc Hc  'dF,böJbö*bvF c¦Jc  Eb¦7bv(d&*d¦F.');
      return;
    }

    setPasswordSaving(true);
    try {
      const res = await changeAdminPassword(cleanCurrent, cleanNew);
      if (res.success) {
        setPasswordSuccess(true);
        setTimeout(() => {
          setPasswordSuccess(false);
          setIsPasswordModalOpen(false);
          setCurrentPassword('');
          setNewPassword('');
          setConfirmPassword('');
        }, 1600);
      } else {
        setPasswordError(res.message);
      }
    } catch {
      setPasswordError('bÖ/b² .cv# b6+df'b  -d 8 d6DdV) bvDdV1d†1.');
    } finally {
      setPasswordSaving(false);
    }
  };

  const handleSaveDeveloperSettings = async (updated: PlatformSettings) => {
    const res = await updatePlatformSettings(updated);
    setPlatformSettings(res);
  };

  // Filtered records with bulletproof defensive guards
  const cleanSearch = (searchTerm || '').trim().toLowerCase();
  const filtered = records.filter((r) => {
    if (!r || typeof r !== 'object') return false;
    const id = String(r.id || '').trim();
    if (!id || id === 'undefined' || id === 'null') return false;

    if (cleanSearch) {
      const idStr = id.toLowerCase();
      const targetStr = String(r.target_url || '').toLowerCase();
      const labelStr = String(r.label || '').toLowerCase();

      const matchesSearch =
        idStr.includes(cleanSearch) ||
        targetStr.includes(cleanSearch) ||
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
        labelStr.includes(cleanSearch);

      if (!matchesSearch) return false;
    }

    if (filterStatus === 'active') {
      return Boolean(r.is_active && (!r.expires_at || new Date(r.expires_at).getTime() >= Date.now()));
    }
    if (filterStatus === 'expired') {
      return Boolean(r.is_active && r.expires_at && new Date(r.expires_at).getTime() < Date.now());
    }
    if (filterStatus === 'inactive') {
      return !r.is_active;
    }
    return true;
  });

  // KPI Calculations
  const validRecords = records.filter((r): r is QrCodeRecord => Boolean(r && r.id && r.id !== 'undefined'
  const totalCodes = validRecords.length;
  const expiredCodes = validRecords.filter((r) => r.is_active && r.expires_at && new Date(r.expires_at).g
  const activeCodes = validRecords.filter((r) => r.is_active && (!r.expires_at || new Date(r.expires_at).
  const pendingCodes = validRecords.filter((r) => !r.is_active).length;
  const totalScans = validRecords.reduce((acc, curr) => acc + (Number(curr?.total_scans) || 0), 0);

  return (
    <div className="min-h-screen bg-[#09090b] text-slate-100 pb-16 selection:bg-amber-500 selection:text-
      {/* Top Navbar */}
      <header className="sticky top-0 z-30 bg-[#0e0e12]/95 backdrop-blur-md border-b border-amber-500/20
        <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-3.5 flex flex-wrap items-center justify
          <div className="flex items-center gap-3">
            <img
              src="/logo.png"
              alt="Smart Card Logo"
              className="w-10 h-10 object-contain rounded-2xl shadow-lg shadow-amber-500/20 flex-shrink-0
            />
            <div>
              <div className="flex items-center gap-2 flex-wrap">
                <h1 className="text-base sm:text-lg font-black text-transparent bg-clip-text bg-gradient-
                  Smart Card Admin
                </h1>
                <span className="text-[10px] bg-amber-400/15 text-amber-300 font-black px-2.5 py-0.5 roun
                  bvDb6/dVF bvDdVDd6J
                </span>
              </div>
              <p className="text-[11px] text-amber-200/70 hidden sm:block">bV/bv1b’ 'dFEc–1e Abv* bvDd 1d¦/b’ HbvDb¦
            </div>
          </div>

          {/* Top Actions */}
          <div className="flex items-center gap-2 flex-wrap">
            <PWAHeaderButton />

            {/* Developer Contact & WhatsApp Settings Button */}
            <button
              onClick={() => setIsSettingsModalOpen(true)}
              className="px-3 py-1.5 bg-gradient-to-r from-amber-400/10 via-yellow-400/15 to-amber-500/10
              title="bV9bö'bö'b¢ 'dF*d†'cVD dV9 bvDdV7d†1 d†'dFHbv*c6'b,
            >
              <MessageSquare className="w-3.5 h-3.5 text-amber-400" />
              <span className="text-[11px]">b¦Hbv5dB Ec’ 'dFEcvHc  †'dFHbv*c6'b,“Â÷7  ãà
            </button>

            {/* Download Documentation PDF */}
            <a
              href="/Smart_Card_Documentation_and_Updates.pdf"
              download="Smart_Card_Documentation_and_Updates.pdf"
              target="_blank"
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
              rel="noopener noreferrer"
              className="px-2.5 py-1.5 text-amber-300 hover:text-black hover:bg-amber-400 bg-amber-400/10
              title="b¦-dVJdB EdFA bvDb¦Hb¶Jd" HbvDb¦-böJb¶'b¢ … Db’
            >
              <FileText className="w-3.5 h-3.5" />
              <span className="text-[11px] hidden sm:inline">b¦Bc Jc  'dF*d†+d¦B (PDF)</span>
            </a>

            {/* Download Full Source Code PDF */}
            <a
              href="/Smart_Card_Full_Source_Code.pdf"
              download="Smart_Card_Full_Source_Code.pdf"
              target="_blank"
              rel="noopener noreferrer"
              className="px-2.5 py-1.5 text-emerald-300 hover:text-black hover:bg-emerald-400 bg-emerald-
              title="b¦-dVJdB Cd†/ bvDdV4c Hc’ (bvDd6'dVD (PDF)"
            >
              <Code2 className="w-3.5 h-3.5" />
              <span className="text-[11px] hidden sm:inline">d6Hbò 'dFEd†Bc’ … Db“Â÷7  ãà
            </a>

            <button
              onClick={() => setIsPasswordModalOpen(true)}
              className="px-2.5 py-1.5 text-slate-300 hover:text-white bg-white/5 hover:bg-white/10 round
              title="b¦:d¦Jc  CdFEb’ 'dFEc Hc
            >
              <KeyRound className="w-3.5 h-3.5 text-amber-400" />
              <span className="text-[11px]">d6DdV) bvDdV1d†1</span>
            </button>

            <button
              onClick={onLogout}
              className="flex items-center gap-1.5 px-3 py-1.5 bg-rose-500/15 hover:bg-rose-500/25 text-r
            >
              <LogOut className="w-3.5 h-3.5" />
              <span className="text-[11px]">bæ1d†,</span>
            </button>
          </div>
        </div>
      </header>

      {/* Main Body */}
      <main className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 pt-8 space-y-8">
        {/* Localhost / Online Domain Guidance Banner */}
        {(domainUrl.includes('localhost') || domainUrl.includes('127.0.0.1')) && !platformSettings.public
          <div className="p-4 bg-gradient-to-r from-amber-500/15 via-yellow-500/10 to-amber-500/15 border
            <div className="flex items-center gap-3">
              <div className="w-10 h-10 rounded-xl bg-amber-400/20 border border-amber-400/40 flex items-
                <Globe className="w-5 h-5" />
              </div>
              <div className="space-y-0.5">
                <p className="text-xs font-bold text-amber-200 flex items-center gap-2">
                  <span>b¦Fb†Jdr EdvE dFEc6- d†*d 9d¦D bvDc Ed†2 dVF dvHbv*d  'dF9dVDbv!:</span>
                  <span className="text-[10px] bg-amber-400/20 text-amber-300 px-2 py-0.5 rounded-full bo
                </p>
                <p className="text-[11px] text-slate-300 leading-relaxed">
                  b6Fb¢ *c–EdB -bvDd¦'d² 9dFI bvDc6Jc Ac  'dFEbÖDd¢â %c ' d&Eb¢ (c–EdB 3d6'db DdF@ QR dVF dv'b¦A bæ'
                </p>
              </div>
            </div>
            <button
              onClick={() => setIsSettingsModalOpen(true)}
              className="px-4 py-2 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 hover:from
            >
              <Settings className="w-3.5 h-3.5 text-black" />
              <span>cf(cr 1bv(cr 'dFEd†Bc’ 'dF#d†FdF'd¦F</span>
            </button>
          </div>
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
        )}

        {/* KPI Stats Cards */}
        <div className="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-5 gap-3.5">
          <div className="p-4 bg-[#121216] rounded-2xl border border-amber-500/20 hover:border-amber-400/
            <div>
              <p className="text-[11px] font-bold text-slate-400">bV,dV'dFJ bvDc Ed†2</p>
              <p className="text-xl sm:text-2xl font-black text-amber-400 mt-0.5">{totalCodes}</p>
              <p className="text-[10px] text-slate-500">dV9c Qd 'b¢ æ æö–B Ac Jbö)</p>
            </div>
            <div className="w-10 h-10 rounded-xl bg-amber-400/10 border border-amber-400/20 text-amber-40
              <QrIcon className="w-5 h-5" />
            </div>
          </div>

          <div className="p-4 bg-[#121216] rounded-2xl border border-amber-500/20 hover:border-emerald-40
            <div>
              <p className="text-[11px] font-bold text-slate-400">bvDbv4b¦1bvCbv* bvDdf4cv)</p>
              <p className="text-xl sm:text-2xl font-black text-emerald-400 mt-0.5">{activeCodes}</p>
              <p className="text-[10px] text-slate-500">c6'c Jb’ Hb¦9dVD bvDb&F</p>
            </div>
            <div className="w-10 h-10 rounded-xl bg-emerald-400/10 border border-emerald-400/20 text-emer
              <CheckCircle2 className="w-5 h-5" />
            </div>
          </div>

          <div className="p-4 bg-[#121216] rounded-2xl border border-rose-500/20 hover:border-rose-400/40
            <div>
              <p className="text-[11px] font-bold text-slate-400">bv4b¦1bvCbv* dVFb¦Gd¦)</p>
              <p className="text-xl sm:text-2xl font-black text-rose-400 mt-0.5">{expiredCodes}</p>
              <p className="text-[10px] text-slate-500">b¦*cvDb, 'dF*bÆ/d¦/</p>
            </div>
            <div className="w-10 h-10 rounded-xl bg-rose-500/10 border border-rose-500/25 text-rose-400 f
              <Clock className="w-5 h-5" />
            </div>
          </div>

          <div className="p-4 bg-[#121216] rounded-2xl border border-amber-500/20 hover:border-amber-400/
            <div>
              <p className="text-[11px] font-bold text-slate-400">b†'df*c†'c  'dF*d 9d¦D</p>
              <p className="text-xl sm:text-2xl font-black text-yellow-400 mt-0.5">{pendingCodes}</p>
              <p className="text-[10px] text-slate-500">d61d†* bÆ/d¦/b’ :d¦1 dV9d¦Fb“Â÷ à
            </div>
            <div className="w-10 h-10 rounded-xl bg-yellow-400/10 border border-yellow-400/20 text-yellow
              <Clock className="w-5 h-5" />
            </div>
          </div>

          <div className="p-4 bg-[#121216] rounded-2xl border border-amber-500/20 hover:border-amber-400/
            <div>
              <div className="flex items-center gap-1.5">
                <p className="text-[11px] font-bold text-slate-400">bV,dV'dFJ bvDdV3bÓÂ÷ à
                <span className="flex items-center gap-1 px-1.5 py-0.2 rounded-full bg-emerald-500/15 bor
                  <span className="w-1.5 h-1.5 rounded-full bg-emerald-400 animate-pulse" />
                  dV(bv4c
                </span>
              </div>
              <p className="text-xl sm:text-2xl font-black text-amber-300 mt-0.5">{totalScans}</p>
              <p className="text-[10px] text-slate-500">b¦HbÆJdr Ad†1d¢ DbÖ8d£Â÷ à
            </div>
            <div className="w-10 h-10 rounded-xl bg-amber-400/10 border border-amber-400/20 text-amber-30
              <BarChart3 className="w-5 h-5" />
            </div>
          </div>
        </div>

        {/* Primary Action Ribbon */}
        <div className="p-6 bg-gradient-to-r from-[#121216] via-[#191920] to-[#121216] rounded-3xl text-w
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
          <div className="space-y-1.5 text-center md:text-right">
            <div className="inline-flex items-center gap-1.5 px-3 py-1 bg-amber-400/10 border border-ambe
              <Lock className="w-3.5 h-3.5 text-amber-400" />
              b6EbvF d†Ecv'b†Bb"¢ 'dF*c–/d¦D dV*bv- d Bcr (c–/ dV3bÒ 'dF1dV2 b6H c Ac' 5d†1b¦G
            </div>
            <h2 className="text-xl sm:text-2xl font-black text-transparent bg-clip-text bg-gradient-to-r
              b6/d†'b¢ 'dF%bö'c ) d†'dFEc6- d†'dF*c–/d¦D bvDb&Ed`
            </h2>
            <p className="text-xs text-slate-300 max-w-xl">
              b¦E bÖ,b, #c&1bv1 bvDb¦9böJdB 'dFJböHd¢ 'dF9cFHbv&d¦  dF*c–/d¦D b6J d6Hbò JbÆ( bvDb¦-d&B dVFdr 9b†1 dV
            </p>
          </div>

          <div className="flex flex-wrap items-center justify-center gap-2.5 w-full md:w-auto">
            {/* Live Camera Scanner to Edit */}
            <button
              onClick={() => setIsScannerOpen(true)}
              className="flex items-center gap-2 px-4 py-3 bg-gradient-to-r from-emerald-600 to-teal-700
            >
              <Camera className="w-4 h-4 text-white" />
              dV3bÒ (bvDd6'dVJc ' dFDb¦9böJd@
            </button>

            {/* Upload QR Image to Edit */}
            <button
              onClick={() => setIsUploadOpen(true)}
              className="flex items-center gap-2 px-4 py-3 bg-[#1e1e26] hover:bg-[#252530] text-amber-300
            >
              <Upload className="w-4 h-4 text-amber-400" />
              c Ac' 5d†1b' Cd†/ dFDb¦9böJd@
            </button>

            {/* Bulk Generate */}
            <button
              onClick={() => setIsBulkOpen(true)}
              className="flex items-center gap-2 px-4 py-3 bg-gradient-to-r from-amber-400 via-yellow-400
            >
              <Plus className="w-4 h-4 text-black" />
              b¦HdFJbò #d6Hbv/ dV,dV9b•
            </button>

            {/* Print Sheet A4 */}
            <button
              onClick={() => setIsPrintOpen(true)}
              className="flex items-center gap-2 px-4 py-3 bg-white/5 hover:bg-white/10 border border-amb
            >
              <Printer className="w-4 h-4 text-amber-400" />
              cv(bv9b' Cc Hb¢  @
            </button>
          </div>
        </div>

        {/* Search, Filters, and Table */}
        <div className="bg-[#121216] rounded-3xl border border-amber-500/20 shadow-2xl overflow-hidden">
          {/* Controls Header */}
          <div className="p-5 border-b border-white/5 flex flex-col md:flex-row items-center justify-betw
            {/* Search Input */}
            <div className="relative w-full md:w-80">
              <Search className="w-4 h-4 text-slate-500 absolute right-3.5 top-3" />
              <input
                type="text"
                value={searchTerm}
                onChange={(e) => setSearchTerm(e.target.value)}
                placeholder="bv(bÖ+ b†'dFEc–1e A ID b6H bvDc 'b†7 bvDdV3b¦GböA... (dV+dB "— d%§vã…''
                className="w-full pr-10 pl-4 py-2.5 bg-black/70 border border-amber-500/30 rounded-xl tex
              />
            </div>

```

FILE (cont.): src/views/AdminDashboardView.tsx

```
            {/* Filters and View Switcher */}
            <div className="flex flex-wrap items-center gap-3 w-full md:w-auto justify-between md:justify
              {/* Category Tabs: Active, Pending, All */}
              <div className="flex items-center gap-1.5 bg-black/40 p-1 rounded-2xl text-xs font-bold tex
                <button
                  type="button"
                  onClick={() => setFilterStatus('active')}
                  className={`flex items-center gap-1.5 px-3 py-1.5 rounded-xl transition ${
                    filterStatus === 'active'
                      ? 'bg-amber-400 text-black shadow-md font-black'
                      : 'text-slate-400 hover:text-white hover:bg-white/5'
                  }`}
                >
                  <CheckCircle2 className="w-3.5 h-3.5" />
                  <span>bvDdf4cv)</span>
                  <span className={`px-1.5 py-0.2 rounded-full text-[10px] font-bold ${
                    filterStatus === 'active' ? 'bg-black/20 text-black' : 'bg-amber-400/20 text-amber-30
                  }`}>
                    {activeCodes}
                  </span>
                </button>

                <button
                  type="button"
                  onClick={() => setFilterStatus('expired')}
                  className={`flex items-center gap-1.5 px-3 py-1.5 rounded-xl transition ${
                    filterStatus === 'expired'
                      ? 'bg-rose-500 text-white shadow-md font-black'
                      : 'text-slate-400 hover:text-white hover:bg-white/5'
                  }`}
                >
                  <AlertTriangle className="w-3.5 h-3.5" />
                  <span>dVFb¦Gd¦) bvDcVDbv-d¦)</span>
                  <span className={`px-1.5 py-0.2 rounded-full text-[10px] font-bold ${
                    filterStatus === 'expired' ? 'bg-black/30 text-white' : 'bg-rose-500/20 text-rose-300
                  }`}>
                    {expiredCodes}
                  </span>
                </button>

                <button
                  type="button"
                  onClick={() => setFilterStatus('inactive')}
                  className={`flex items-center gap-1.5 px-3 py-1.5 rounded-xl transition ${
                    filterStatus === 'inactive'
                      ? 'bg-yellow-500 text-black shadow-md font-black'
                      : 'text-slate-400 hover:text-white hover:bg-white/5'
                  }`}
                >
                  <Clock className="w-3.5 h-3.5" />
                  <span>d J bvFb¦8bv1 bvDb¦Ac–JdCÂ÷7  ãà</span>
                  <span className={`px-1.5 py-0.2 rounded-full text-[10px] font-bold ${
                    filterStatus === 'inactive' ? 'bg-black/20 text-black' : 'bg-yellow-400/20 text-yello
                  }`}>
                    {pendingCodes}
                  </span>
                </button>

                <button
                  type="button"
                  onClick={() => setFilterStatus('all')}
                  className={`flex items-center gap-1.5 px-3 py-1.5 rounded-xl transition ${
                    filterStatus === 'all'
                      ? 'bg-white/20 text-white shadow-md font-black'
                      : 'text-slate-400 hover:text-white hover:bg-white/5'
                  }`}
                >
                  <span>bvDd6D</span>
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                  <span className={`px-1.5 py-0.2 rounded-full text-[10px] font-bold ${
                    filterStatus === 'all' ? 'bg-black/20 text-white' : 'bg-white/10 text-slate-300'
                  }`}>
                    {records.length}
                  </span>
                </button>
              </div>

              {/* View Switcher */}
              <div className="flex items-center border border-white/10 rounded-xl overflow-hidden p-0.5 b
                <button
                  type="button"
                  onClick={() => setViewMode('grid')}
                  className={`p-1.5 rounded-lg transition ${
                    viewMode === 'grid' ? 'bg-amber-400 text-black shadow-sm font-bold' : 'text-slate-500
                  }`}
                  title="c–1cb 4b†Cd¢
                >
                  <Grid className="w-4 h-4" />
                </button>
                <button
                  type="button"
                  onClick={() => setViewMode('table')}
                  className={`p-1.5 rounded-lg transition ${
                    viewMode === 'table' ? 'bg-amber-400 text-black shadow-sm font-bold' : 'text-slate-50
                  }`}
                  title="c–1cb ,böHdFJ"
                >
                  <List className="w-4 h-4" />
                </button>
              </div>

              {/* Refresh Button */}
              <button
                onClick={loadData}
                disabled={loading}
                className="p-2 text-slate-400 hover:text-white hover:bg-white/10 rounded-xl transition bo
                title="b¦-böJb² 'dF(d¦'df'b¢
              >
                <RefreshCw className={`w-4 h-4 ${loading ? 'animate-spin text-amber-400' : ''}`} />
              </button>
            </div>
          </div>

          {/* List Content */}
          {loading && records.length === 0 ? (
            <div className="py-24 text-center space-y-3">
              <RefreshCw className="w-8 h-8 text-amber-400 animate-spin mx-auto" />
              <p className="text-xs text-amber-200/80 font-bold">bÆ'c J b¦-dVJdB (d¦'df'b¢ 'dF#d6Hbv/ bvDdVDd6Jb'ãâã
            </div>
          ) : filtered.length === 0 ? (
            <div className="py-20 text-center space-y-3">
              <div className="w-16 h-16 rounded-full bg-white/5 text-amber-400 flex items-center justify-
                <QrIcon className="w-8 h-8" />
              </div>
              <p className="text-sm font-bold text-white">
                {cleanSearch ? `dFE d¦*dR 'dF9b¶Hc  9dFI df*bv&bÂ EbÖDd¦) dV7bv(d&) dF@ "${cleanSearch}"` : 'dFE d¦*
              </p>
              {cleanSearch ? (
                <div className="space-y-2 pt-1">
                  <p className="text-xs text-slate-400">d&/ d¦Cd†F bvDd6Hbò Ec6,dF'd² (bvDc6Jc Ac  #d, JbÖ*bv, bÆDb†
                  <button
                    type="button"
                    onClick={async () => {
                      setLoading(true);
                      const found = await lookupExistingQrCode(cleanSearch);
                      setLoading(false);
                      if (found) {
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                        setSelectedEditRecord(found);
                        setRecords((prev) => [found, ...prev.filter((r) => r.id !== found.id)]);
                      } else {
                        alert(`bvDd6Hbò "G¶6ÆV å6V &6‡Ò" :d¦1 dV3bÆD b†'dF3d¦1d 1.`);
                      }
                    }}
                    className="inline-flex items-center gap-1.5 px-4 py-2.5 bg-gradient-to-r from-amber-4
                  >
                    <Search className="w-4 h-4 text-black" />
                    bÆDb, Hd -cR 'dFCd†/ [{cleanSearch}] dVF bvDc6Jc Ac
                  </button>
                </div>
              ) : (
                <>
                  <p className="text-xs text-slate-400">bv6c¦7 c–Dd’ 2c  &*d†Dd¦/ b6Cd†'bò EbÆEc–)" dF%df4bv! b6HdB
                  <button
                    onClick={() => setIsBulkOpen(true)}
                    className="inline-flex items-center gap-1.5 px-4 py-2 bg-gradient-to-r from-amber-400
                  >
                    <Plus className="w-4 h-4" />
                    b¦HdFJbò    #d6Hbv/ bvDb&F
                  </button>
                </>
              )}
            </div>
          ) : viewMode === 'grid' ? (
            /* Grid View */
            <div className="p-6 grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-4 gap-4">
              {filtered.map((record) => {
                const scanUrl = `${domainUrl}/q/${record.id}`;
                return (
                  <div
                    key={record.id}
                    className="p-4 bg-[#16161c] rounded-2xl border border-amber-500/20 hover:border-amber
                  >
                    <div>
                      {/* Top Header of card */}
                      <div className="flex items-center justify-between pb-3 border-b border-white/5">
                        <div className="flex items-center gap-1.5">
                          {record.is_active && record.app_type && (
                            <PlatformBrandIcon type={record.app_type as any} className="w-5 h-5 flex-shri
                          )}
                          <span className={`px-2.5 py-1 rounded-full text-[11px] font-extrabold flex item
                            record.is_active
                              ? 'bg-emerald-500/15 text-emerald-300 border border-emerald-500/30'
                              : 'bg-yellow-500/15 text-yellow-300 border border-yellow-500/30'
                          }`}>
                            <span className={`w-2 h-2 rounded-full ${record.is_active ? 'bg-emerald-400 a
                            {record.is_active ? 'dVAc–D df4crr ¢ vAd¢ 'df*c†'c  'dF*d 9d¦D'}
                          </span>
                        </div>

                        {/* Prominent Eye Badge for admin */}
                        <div
                          className="flex items-center gap-1.5 px-3 py-1 bg-amber-400/10 border border-am
                          title={`b¦E d *bÒ HdV3bÒ Gc ' bvDc 'b†7 ${record.total_scans || 0} dV1b’ (d†'c67b’ 'dF9dVD
                        >
                          <Eye className="w-4 h-4 text-amber-400" />
                          <span>{record.total_scans || 0} dV3bÖ)</span>
                        </div>
                      </div>

                      {/* QR Thumbnail */}
                      <div className="my-3 flex justify-center">
                        <div className="p-2.5 bg-white rounded-2xl shadow-inner group-hover:scale-105 tra
                          {qrThumbs[record.id] ? (
                            <img
                              src={qrThumbs[record.id]}
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                        alt={`QR ${record.id}`}
                        className="w-28 h-28 object-contain"
                      />
                    ) : (
                      <div className="w-28 h-28 bg-slate-200 rounded animate-pulse" />
                    )}
                  </div>
                </div>

                {/* ID and info */}
                <div className="space-y-1.5 text-center">
                  <div className="flex items-center justify-center gap-1">
                    <span className="font-mono text-xs font-black text-amber-300 bg-black/60 px-2.5
                      {record.id}
                    </span>
                    <button
                      type="button"
                      onClick={() => handleCopyLink(record.id)}
                      className="p-1 text-slate-400 hover:text-amber-300 transition"
                      title="df3bâ 1bv(cr 'dFEc6-"
                    >
                      {copiedId === record.id ? (
                        <Check className="w-3.5 h-3.5 text-emerald-400" />
                      ) : (
                        <Copy className="w-3.5 h-3.5" />
                      )}
                    </button>
                  </div>

                  {record.label && (
                    <p className="text-[11px] font-bold text-amber-200/90 truncate">
                      {record.label}
                    </p>
                  )}

                  <p className="text-[11px] text-slate-400 truncate" dir="ltr">
                    {formatDisplayTarget(record.target_url, record.app_type)}
                  </p>

                  {/* Prominent Eye details banner */}
                  <div className="mt-2 pt-2 border-t border-white/5 flex items-center justify-betwe
                    <span className="flex items-center gap-1.5">
                      <Eye className="w-3.5 h-3.5 text-amber-400" />
                      <span>
                        {record.is_active
                          ? `b¦E bvDdV3bÓ¢ G·&V6÷&BçF÷F Å÷66 ç2 ÇÂ  Ò Ec )`
                          : 'd J bvFb¦8bv1 bvDb¦Ac–JdBwÐ
                      </span>
                    </span>
                  </div>

                  {/* Subscription Expiry & Duration Management Box */}
                  <div className="mt-2.5 p-3 bg-black/60 border border-amber-500/25 rounded-xl spac
                    <div className="flex items-center justify-between text-[11px]">
                      <span className="font-bold text-amber-200/90 flex items-center gap-1">
                        <Clock className="w-3.5 h-3.5 text-amber-400" />
                        <span>cVDbv-d¦) bvDd6'c *:</span>
                      </span>
                      {record.expires_at ? (
                        new Date(record.expires_at).getTime() < Date.now() ? (
                          <span className="px-2 py-0.5 rounded-full text-[10px] font-black bg-rose-
                            dVFb¦Gd¢ 'dF5dF'bÖJb’ j àð
                          </span>
                        ) : (
                          <span className="px-2 py-0.5 rounded-full text-[10px] font-black bg-emera
                            b†'d&J {Math.max(0, Math.ceil((new Date(record.expires_at).getTime() - Da
                          </span>
                        )
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                        ) : (
                          <span className="px-2 py-0.5 rounded-full text-[10px] font-black bg-cyan-50
                            bö'bfE / c¦Jc  EbÖ/d†/ '&
                          </span>
                        )}
                      </div>

                      {record.expires_at && (
                        <div className="flex items-center justify-between text-[10px] text-slate-400
                          <span>b¦'c Jbâ 'dF'df*dv'b £Â÷7  ãà
                          <span className="font-mono text-amber-300 font-bold" dir="ltr">
                            {new Date(record.expires_at).toLocaleDateString('ar-EG', {
                              year: 'numeric',
                              month: 'short',
                              day: 'numeric',
                            })}
                          </span>
                        </div>
                      )}

                      {/* Quick 1-Click Renewal Buttons */}
                      <div className="flex items-center gap-1.5 pt-1">
                        <button
                          type="button"
                          disabled={renewingId === record.id}
                          onClick={() => handleQuickRenew(record.id, 1)}
                          className="flex-1 py-1.5 px-2 bg-gradient-to-r from-amber-400/20 to-yellow-
                          title="b¦,böJbòö*dV/d¦/ cFGc  %cf'd J (30 d¦HdV'd²’
                        >
                          <Sparkles className="w-3 h-3" />
                          <span>+1 cFGc Â÷7  ãà
                        </button>

                        <button
                          type="button"
                          disabled={renewingId === record.id}
                          onClick={() => handleQuickRenew(record.id, 3)}
                          className="py-1.5 px-2 bg-white/5 hover:bg-amber-400/20 text-slate-300 hove
                          title="b¦,böJbò 2 #cFGc
                        >
                          <span>+3 cFGd†1</span>
                        </button>

                        <button
                          type="button"
                          onClick={() => setSelectedEditRecord(record)}
                          className="py-1.5 px-2 bg-white/5 hover:bg-white/10 text-slate-300 hover:te
                          title="b¦-böJbò 'dF1bv(cr Hb¦'c Jbâ 'dF'df*dv'b
                        >
                          <Calendar className="w-3 h-3 text-amber-400" />
                          <span>b¦-böJbóÂ÷7  ãà
                        </button>
                      </div>
                    </div>
                  </div>
                </div>

                {/* Actions */}
                <div className="mt-3 pt-3 border-t border-white/5 space-y-2">
                  <div className="grid grid-cols-4 gap-1.5">
                    {/* Edit Button */}
                    <button
                      type="button"
                      onClick={() => setSelectedEditRecord(record)}
                      className="py-2 bg-amber-400/10 hover:bg-amber-400 hover:text-black text-amber-
                      title="b¦9böJdB 'dF1bv(cr Hb¦'c Jbâ 'dF5dF'bÖJb’
                    >
                      <Edit3 className="w-3.5 h-3.5" />
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                        <span>b¦9böJdCÂ÷7  ãà
                      </button>

                      {/* Download QR */}
                      <button
                        type="button"
                        onClick={() => handleDownloadQr(record)}
                        className="py-2 bg-white/5 hover:bg-white/10 text-slate-200 hover:text-white ro
                        title="b¦-dVJdB 5d†1b’ 'dF@ QR b†/d&) c–'dFJb’
                      >
                        <Download className="w-3.5 h-3.5 text-amber-400" />
                        <span>b¦-dVJdCÂ÷7  ãà
                      </button>

                      {/* Test Scan */}
                      <button
                        type="button"
                        onClick={() => onSimulateScan(record.id)}
                        className="py-2 bg-white/5 hover:bg-white/10 text-amber-300 hover:text-amber-20
                        title="d *bÒ 1bv(cr 'dFEc6- bvDbÖBd¦Bd¢
                      >
                        <ExternalLink className="w-3.5 h-3.5 text-amber-400" />
                        <span>dV3bÓÂ÷7  ãà
                      </button>

                      {/* Delete Code */}
                      <button
                        type="button"
                        onClick={() => setCodeToDelete(record.id)}
                        className="py-2 bg-rose-500/15 hover:bg-rose-500/25 text-rose-300 rounded-xl te
                        title="bÖ0d  Gc ' bvDd6Hbò Fdv'bfJbvK"
                      >
                        <Trash2 className="w-3.5 h-3.5 text-rose-400" />
                        <span>bÖ0d Â÷7  ãà
                      </button>
                    </div>
                  </div>
                </div>
              );
            })}
          </div>
        ) : (
          /* Table View */
          <div className="overflow-x-auto">
            <table className="w-full text-right text-xs">
              <thead className="bg-black/50 text-amber-300/90 border-b border-white/5 font-black">
                <tr>
                  <th className="py-3 px-4">d6Hbò 'dF@ QR</th>
                  <th className="py-3 px-4">bvDbÖ'dF)</th>
                  <th className="py-3 px-4">dV/b’ 'dF*d 9d¦D d†'dF'cF*c 'd3Â÷Fƒà
                  <th className="py-3 px-4">dV1bv* bvDdV3bÓÂ÷Fƒà
                  <th className="py-3 px-4">bvDdVFcV)</th>
                  <th className="py-3 px-4">bvDc 'b†7 bvDdV3b¦GböA</th>
                  <th className="py-3 px-4">b¦'c Jbâ 'dF%df4bv!</th>
                  <th className="py-3 px-4 text-center">bV,c 'b 'b£Â÷Fƒà
                </tr>
              </thead>
              <tbody className="divide-y divide-white/5">
                {filtered.map((record) => (
                  <tr key={record.id} className="hover:bg-amber-400/5 transition">
                    <td className="py-2.5 px-4 font-mono font-black text-amber-300" dir="ltr">
                      {record.id}
                    </td>
                    <td className="py-2.5 px-4">
                      <span className={`px-2 py-0.5 rounded-full text-[10px] font-bold ${
                        record.is_active
                          ? 'bg-emerald-500/15 text-emerald-300 border border-emerald-500/30'
                          : 'bg-yellow-500/15 text-yellow-300 border border-yellow-500/30'
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                    }`}>
                      {record.is_active ? 'dVAc–D df4crr ¢ vAd¢ 'df*c†'c  'dF*d 9d¦D'}
                    </span>
                  </td>
                  <td className="py-2.5 px-4">
                    <div className="flex flex-col gap-1 items-start">
                      {record.expires_at ? (
                        new Date(record.expires_at).getTime() < Date.now() ? (
                          <span className="px-2 py-0.5 rounded-full text-[10px] font-black bg-rose-50
                            dVFb¦Gd¢ 'dF5dF'bÖJb’ j àð
                          </span>
                        ) : (
                          <span className="px-2 py-0.5 rounded-full text-[10px] font-black bg-emerald
                            df4cr †(bvBd¢ ´Ö F,æÖ ,ƒ Â Ö F,æ6V–Â,†æWr F FR‡&V6÷&BæW‡ —&W5ö B’ævWEF–ÖR,’ Đ
                          </span>
                        )
                      ) : (
                        <span className="px-2 py-0.5 rounded-full text-[10px] font-black bg-cyan-500/
                          bö'bfE / c¦Jc  EbÖ/d†/ '&
                        </span>
                      )}
                      <div className="flex items-center gap-1.5 pt-0.5">
                        <button
                          type="button"
                          disabled={renewingId === record.id}
                          onClick={() => handleQuickRenew(record.id, 1)}
                          className="px-2 py-0.5 bg-amber-400/20 hover:bg-amber-400 hover:text-black
                          title="b¦,böJbò ³  4dv1"
                        >
                          +1 cFGc
                        </button>
                        <button
                          type="button"
                          onClick={() => setSelectedEditRecord(record)}
                          className="p-1 text-slate-400 hover:text-amber-300 transition"
                          title="b¦9böJdB 'dF5dF'bÖJb’
                        >
                          <Calendar className="w-3 h-3 text-amber-400" />
                        </button>
                      </div>
                    </div>
                  </td>
                  <td className="py-2.5 px-4 font-extrabold text-amber-300">
                    <div className="inline-flex items-center gap-1.5 px-2.5 py-0.5 bg-amber-400/10 bo
                      <Eye className="w-3.5 h-3.5 text-amber-400" />
                      <span>{record.total_scans || 0}</span>
                    </div>
                  </td>
                  <td className="py-2.5 px-4 text-slate-300">
                    <div className="flex items-center gap-1.5">
                      {record.app_type && <PlatformBrandIcon type={record.app_type as any} className=
                      <span className="capitalize">{record.app_type || '—'}</span>
                    </div>
                  </td>
                  <td className="py-2.5 px-4 font-mono text-slate-400 max-w-xs truncate" dir="ltr">
                    {formatDisplayTarget(record.target_url, record.app_type)}
                  </td>
                  <td className="py-2.5 px-4 text-slate-400 text-[11px]">
                    {new Date(record.created_at).toLocaleDateString('ar-EG')}
                  </td>
                  <td className="py-2.5 px-4 text-center">
                    <div className="flex items-center justify-center gap-1.5">
                      <button
                        type="button"
                        onClick={() => setSelectedEditRecord(record)}
                        className="p-1.5 text-slate-400 hover:text-amber-300 hover:bg-amber-400/10 ro
                        title="b¦9böJdB 'dF1bv(cr Hb¦'c Jbâ 'dF5dF'bÖJb’
                      >
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                          <Edit3 className="w-4 h-4 text-amber-400" />
                        </button>
                        <button
                          type="button"
                          onClick={() => handleDownloadQr(record)}
                          className="p-1.5 text-slate-400 hover:text-white hover:bg-white/10 rounded-lg
                          title="b¦-dVJdB
                        >
                          <Download className="w-4 h-4 text-amber-400" />
                        </button>
                        <button
                          type="button"
                          onClick={() => onSimulateScan(record.id)}
                          className="p-1.5 text-slate-400 hover:text-amber-300 hover:bg-white/10 rounde
                          title="dV3bÒ
                        >
                          <ExternalLink className="w-4 h-4" />
                        </button>
                        <button
                          type="button"
                          onClick={() => setCodeToDelete(record.id)}
                          className="p-1.5 text-slate-400 hover:text-rose-400 hover:bg-rose-500/10 roun
                          title="bÖ0d
                        >
                          <Trash2 className="w-4 h-4 text-rose-400" />
                        </button>
                      </div>
                    </td>
                  </tr>
                ))}
              </tbody>
            </table>
          </div>
        )}
      </div>
    </main>

    {/* Modals */}
    <BulkGenerateModal
      isOpen={isBulkOpen}
      onClose={() => setIsBulkOpen(false)}
      domainUrl={domainUrl}
      onGenerated={(newRecords) => {
        setRecords((prev) => {
          const existingIds = new Set(prev.map((r) => r.id));
          const fresh = newRecords.filter((r) => !existingIds.has(r.id));
          return [...fresh, ...prev];
        });
        newRecords.forEach((item) => {
          generateQrDataUrl(`${domainUrl}/q/${item.id}`, 200).then((url) => {
            setQrThumbs((prev) => ({ ...prev, [item.id]: url }));
          });
        });
      }}
    />

    <UploadQrModal
      isOpen={isUploadOpen}
      onClose={() => setIsUploadOpen(false)}
      onCodeFound={(rec: QrCodeRecord) => {
        setSelectedEditRecord(rec);
        setRecords((prev) => {
          const exists = prev.some((r) => r.id === rec.id);
          if (!exists) return [rec, ...prev];
          return prev.map((r) => (r.id === rec.id ? rec : r));
        });
      }}
    />
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
      <EditQrModal
        isOpen={!!selectedEditRecord}
        record={selectedEditRecord}
        domainUrl={domainUrl}
        onClose={() => setSelectedEditRecord(null)}
        onSaved={(updated) => {
          setRecords((prev) => {
            const exists = prev.some((r) => r.id === updated.id);
            if (!exists) return [updated, ...prev];
            return prev.map((r) => (r.id === updated.id ? updated : r));
          });
          setFilterStatus('active');
        }}
        onDelete={(id) => setCodeToDelete(id)}
      />

      <PrintSheetModal
        isOpen={isPrintOpen}
        onClose={() => setIsPrintOpen(false)}
        records={records}
        domainUrl={domainUrl}
      />

      <QrScannerModal
        isOpen={isScannerOpen}
        onClose={() => setIsScannerOpen(false)}
        onScannedId={async (id) => {
          setIsScannerOpen(false);
          let rec: QrCodeRecord | null | undefined = records.find((r) => r.id === id);
          if (!rec) {
            rec = await getQrCode(id);
          }
          if (rec) {
            setSelectedEditRecord(rec);
          } else {
            alert(`bvDc Ec" "G¶–GÒ" :d¦1 dVHbÆHbò #d, *dR -c Adr Edb Bbv9bö) bvDb†JbvFbv*.`);
          }
        }}
      />

      {/* Developer & WhatsApp Settings Modal */}
      <DeveloperSettingsModal
        isOpen={isSettingsModalOpen}
        onClose={() => setIsSettingsModalOpen(false)}
        settings={platformSettings}
        onSave={handleSaveDeveloperSettings}
      />

      {/* Password Change Modal */}
      {isPasswordModalOpen && (
        <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/85 backdrop-blur
          <div className="w-full max-w-sm bg-[#121216] border border-amber-500/35 rounded-3xl p-6 shadow-
            <div className="flex items-center justify-between pb-2 border-b border-amber-500/20">
              <h3 className="font-bold text-base text-amber-300 flex items-center gap-2">
                <KeyRound className="w-5 h-5 text-amber-400" />
                b¦:d¦Jc  CdFEb’ Ec Hc  'dF#böEd`
              </h3>
              <button
                type="button"
                onClick={() => {
                  setIsPasswordModalOpen(false);
                  setPasswordError(null);
                  setNewPassword('');
                  setConfirmPassword('');
                }}
                className="text-slate-400 hover:text-white p-1"
              >
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
                '
              </button>
            </div>

            <p className="text-xs text-slate-300 leading-relaxed">
              b6/bæD d6DdV) bvDdV1d†1 bvDbÆ/d¦/b’â 3d¦*dR *cFAd¦1dv' b†.d†'c 2dVJb’ Ç7  â 6Æ 74æ ÖSÒ&föçBÖÖöæò FW‡BÖ
            </p>

            {passwordError && (
              <div className="p-3 bg-rose-500/20 text-rose-300 border border-rose-500/30 rounded-xl text-
                <AlertCircle className="w-4 h-4 text-rose-400 flex-shrink-0" />
                <span>{passwordError}</span>
              </div>
            )}

            {passwordSuccess && (
              <div className="p-3 bg-emerald-500/20 text-emerald-300 border border-emerald-500/30 rounded
                <Check className="w-4 h-4 text-emerald-400" />
                b¦E bÖAc, Hb¦-böJb² CdFEb’ 'dFEc Hc  'dF,böJbö) d J d&'c–/b’ 'dF(d¦'df'b¢ (bvDd6'dVD b†FbÆ'bÒ
              </div>
            )}

            <form onSubmit={handleUpdatePassword} className="space-y-3.5">
              <div>
                <label className="block text-xs font-semibold text-amber-200/90 mb-1">
                  d6DdV) bvDdV1d†1 bvDbÖ'dFJb“
                </label>
                <input
                  type="password"
                  value={currentPassword}
                  onChange={(e) => setCurrentPassword(e.target.value)}
                  placeholder="b6/bæD d6DdV) bvDdV1d†1 bvDbÖ'dFJb’ DdF*b6Cd¦/..."
                  className="w-full px-3.5 py-2.5 bg-black/50 border border-amber-500/20 rounded-xl text-
                  dir="ltr"
                  required
                  autoFocus
                />
              </div>

              <div>
                <label className="block text-xs font-semibold text-amber-200/90 mb-1">
                  d6DdV) bvDdV1d†1 bvDbÆ/d¦/b“
                </label>
                <input
                  type="password"
                  value={newPassword}
                  onChange={(e) => setNewPassword(e.target.value)}
                  placeholder="b6/bæD d6DdV) bvDdV1d†1 bvDbÆ/d¦/b’ ƒB .bvFbv* d #d6+c ’âââ
                  className="w-full px-3.5 py-2.5 bg-black/50 border border-amber-500/20 rounded-xl text-
                  dir="ltr"
                  required
                />
              </div>

              <div>
                <label className="block text-xs font-semibold text-amber-200/90 mb-1">
                  b¦#d6Jbò CdFEb’ 'dFEc Hc  'dF,böJbö):
                </label>
                <input
                  type="password"
                  value={confirmPassword}
                  onChange={(e) => setConfirmPassword(e.target.value)}
                  placeholder="b69bò Cb¦'b†) d6DdV) bvDdV1d†1..."
                  className="w-full px-3.5 py-2.5 bg-black/50 border border-amber-500/20 rounded-xl text-
                  dir="ltr"
                  required
                />
              </div>
```

FILE (cont.): src/views/AdminDashboardView.tsx

```
1225
1226              <div className="flex items-center justify-end gap-2 pt-2">
1227                <button
1228                  type="button"
1229                  onClick={() => {
1230                    setIsPasswordModalOpen(false);
1231                    setPasswordError(null);
1232                    setNewPassword('');
1233                    setConfirmPassword('');
1234                  }}
1235                  className="px-3.5 py-2 text-xs font-semibold text-slate-400 hover:text-white"
1236                >
1237                  bVDc¦'b
1238                </button>
1239                <button
1240                  type="submit"
1241                  disabled={passwordSaving || !newPassword.trim()}
1242                  className="px-4 py-2 bg-gradient-to-r from-amber-400 to-yellow-500 hover:from-amber-300
1243                >
1244                  {passwordSaving ? 'bÆ'c J bvDbÖAc,ãâår ¢ v-d 8 d6DdV) bvDdV1d†1'}
1245                </button>
1246              </div>
1247            </form>
1248          </div>
1249        </div>
1250      )}
1251
1252      {/* Delete Confirmation Modal */}
1253      {codeToDelete && (
1254        <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/80 backdrop-blur
1255          <div className="w-full max-w-sm bg-[#121216] border border-rose-500/30 rounded-3xl p-6 shadow-2
1256            <div className="w-14 h-14 rounded-2xl bg-rose-500/15 text-rose-400 flex items-center justify-
1257              <Trash2 className="w-7 h-7" />
1258            </div>
1259            <div>
1260              <h3 className="text-base font-black text-white">bÖ0d  'dFCd†/ dfGbv&d¦'d¶ </h3>
1261              <p className="text-xs text-slate-400 mt-1">
1262                dvD b6Fb¢ Eb¦#d6/ dVF bÖ0d  'dFCd†/ <span className="font-mono font-bold text-amber-300 bg-black/60
1263              </p>
1264            </div>
1265            <div className="p-3 bg-rose-500/10 border border-rose-500/30 rounded-xl text-[11px] text-rose
1266              & þ  b¦-c Jc ¢ 3d¦*dR -c A dv0br 'dFCd†/ dfGbv&d¦'d² Edb Bbv9bö) b†JbvFbv* bvDdVHd&9`Â Hb6J d6'c * dV7
1267            </div>
1268            <div className="flex items-center gap-2 pt-1">
1269              <button
1270                type="button"
1271                onClick={() => setCodeToDelete(null)}
1272                disabled={isDeleting}
1273                className="flex-1 py-2.5 bg-white/5 hover:bg-white/10 text-slate-300 font-bold text-xs ro
1274              >
1275                bVDc¦'b
1276              </button>
1277              <button
1278                type="button"
1279                onClick={handleConfirmDelete}
1280                disabled={isDeleting}
1281                className="flex-1 py-2.5 bg-rose-600 hover:bg-rose-500 text-white font-bold text-xs round
1282              >
1283                {isDeleting ? 'bÆ'c J bvDbÖ0d ãâår ¢ v*b6Cd¦/ bvDbÖ0d  Fdv'bfJbvK'}
1284              </button>
1285            </div>
1286          </div>
1287        </div>
1288      )}
1289    </div>
1290  );
1291 }
1292
```

FILE: src/views/HomeLandingView.tsx 372 lines | 15.9 KB

```tsx
import { useState, useRef, useEffect } from 'react';
import {
  QrCode as QrIcon,
  Smartphone,
  Camera,
  Upload,
  Search,
  Sparkles,
  CheckCircle2,
  HelpCircle,
  ArrowLeft,
  ShieldCheck,
  Lock,
  Building2,
  Wallet,
  MessageSquare,
  AlertCircle,
  Loader2,
  Phone
} from 'lucide-react';
import { decodeQrFromImageFile, extractQrIdFromUrl, getQrCode, fetchPlatformSettings } from '../lib/qrSer
import { QrScannerModal } from '../components/QrScannerModal';
import { PWAHeaderButton } from '../components/PWAInstallBanner';
import { PlatformSettings } from '../types/qr';

interface HomeLandingViewProps {
  onGoToAdmin: () => void;
  onSimulateScan: (id: string) => void;
  domainUrl: string;
}

export function HomeLandingView({ onGoToAdmin, onSimulateScan }: HomeLandingViewProps) {
  const [manualCode, setManualCode] = useState('');
  const [isScannerOpen, setIsScannerOpen] = useState(false);
  const [isUploading, setIsUploading] = useState(false);
  const [feedbackMsg, setFeedbackMsg] = useState<{ type: 'error' | 'success'; text: string } | null>(null
  const [settings, setSettings] = useState<PlatformSettings>({
    developer_whatsapp: '01550523365',
    developer_contact_url: 'https://wa.me/201550523365',
    developer_title: 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
    support_message: 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’rÀ
  });
  const fileInputRef = useRef<HTMLInputElement>(null);

  useEffect(() => {
    fetchPlatformSettings().then((s) => {
      if (s) setSettings(s);
    });
  }, []);

  // Submit manual card ID
  const handleManualSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    const cleanId = manualCode.trim();
    if (!cleanId) {
      setFeedbackMsg({ type: 'error', text: 'd¦1bÆI d6*bv(b’ Cd†/ bvDb†7bvBb’ #d†DbvK' });
      return;
    }

    setFeedbackMsg(null);
    try {
      const record = await getQrCode(cleanId);
      if (record) {
        window.location.href = `/q/${record.id}`;
      } else {
        setFeedbackMsg({ type: 'error', text: `d6Hbò 'dF(cv'd&) "${cleanId}" c¦Jc  Ed†,d†/ b6H c¦Jc  5bÖJbÒæ  Ò“°
      }
    } catch {
```

FILE (cont.): src/views/HomeLandingView.tsx

```
      window.location.href = `/q/${cleanId}`;
    }
  };

  // Upload card/QR photo
  const handlePhotoUpload = async (file: File) => {
    if (!file.type.startsWith('image/')) {
      setFeedbackMsg({ type: 'error', text: 'd¦1bÆI bv.b¦Jbv1 dVDd  5d†1b’ 5bvDbÒ … är #d, ¥ r’âr Ò“°
      return;
    }

    setIsUploading(true);
    setFeedbackMsg(null);

    try {
      const decodedText = await decodeQrFromImageFile(file);
      if (!decodedText) {
        setFeedbackMsg({ type: 'error', text: 'b¦9c 1 d&1bv!b’ 1dV2 QR dVF bvDcVHc ) bvDdV1d Hc–). b¦#d6/ dVF d†6d†-
        setIsUploading(false);
        return;
      }

      const extractedId = extractQrIdFromUrl(decodedText);
      if (!extractedId) {
        setFeedbackMsg({ type: 'error', text: 'b¦E d -cR 'dF1dV2 d†Dd6F dFE d¦*dR 'dF9b¶Hc  9dFI d6Hbò (cv'd&) cV-d¦
        setIsUploading(false);
        return;
      }

      window.location.href = `/q/${extractedId}`;
    } catch (err) {
      console.error(err);
      setFeedbackMsg({ type: 'error', text: 'bÖ/b² .cv# b6+df'b  AbÖ5 bvDcVHc ). bÆ1b, %bö.bvD bvDd6Hbò JböHd¦Kbrâr
      setIsUploading(false);
    }
  };

  const getWaLink = () => {
    if (settings.developer_contact_url?.trim()) {
      return settings.developer_contact_url.trim();
    }
    const clean = (settings.developer_whatsapp || '01550523365').replace(/[^\d]/g, '');
    const num = clean.startsWith('01') ? '2' + clean : clean;
    return `https://wa.me/${num}`;
  };

  return (
    <div className="min-h-screen bg-[#09090b] text-white selection:bg-amber-500 selection:text-black flex
      {/* Top Customer Header */}
      <header className="border-b border-amber-500/20 bg-black/60 backdrop-blur-md sticky top-0 z-30">
        <div className="max-w-5xl mx-auto px-4 sm:px-6 h-16 flex items-center justify-between">
          <div className="flex items-center gap-3">
            <img
              src="/logo.png"
              alt="Smart Card"
              className="w-10 h-10 object-contain rounded-2xl shadow-lg shadow-amber-500/20 p-0.5 bg-[#12
            />
            <div>
              <span className="text-base sm:text-lg font-black tracking-wider text-transparent bg-clip-te
                Smart Card
              </span>
            </div>
          </div>

          <div className="flex items-center gap-2">
            <PWAHeaderButton />

            <a
```

FILE (cont.): src/views/HomeLandingView.tsx

```
              href={getWaLink()}
              target="_blank"
              rel="noopener noreferrer"
              className="flex items-center gap-1.5 px-3 py-1.5 bg-amber-400/10 hover:bg-amber-400/20 bord
              title="b¦Hbv5dB Ec’ 'dFEcvHc
            >
              <MessageSquare className="w-4 h-4 text-amber-400" />
              <span className="hidden sm:inline">b¦Hbv5dB Ec’ 'dFEcvHc Â÷7  ãà
            </a>

            <button
              onClick={() => setIsScannerOpen(true)}
              className="flex items-center gap-1.5 px-3.5 py-1.5 bg-gradient-to-r from-amber-400 to-yello
            >
              <Camera className="w-4 h-4 text-black" />
              <span>dV3bÒ 'dF(cv'd&)</span>
            </button>
          </div>
        </div>
      </header>

      {/* Main Customer Portal Content */}
      <main className="max-w-3xl mx-auto px-4 sm:px-6 py-10 sm:py-16 w-full space-y-10">
        {/* Welcome & Instructions */}
        <div className="text-center space-y-4">
          <div className="inline-flex items-center gap-2 px-4 py-1.5 rounded-full bg-amber-400/10 border
            <Sparkles className="w-4 h-4 text-amber-400" />
            dVFcV) bvDd -cR HbvDb¦HbÆJdr 'dFAd†1d¢ r 6Ö 'B 6 &@
          </div>

          <h1 className="text-2xl sm:text-4xl font-black text-white leading-tight">
            b6GdF'd² (d2 Ad¢ Edf5b•
            <span className="bg-gradient-to-l from-amber-200 via-amber-400 to-yellow-500 bg-clip-text tex
              Smart Card
            </span>
          </h1>

          <p className="text-xs sm:text-sm text-slate-300 max-w-lg mx-auto leading-relaxed">
            bV0br BdV* b†Ec6- b†7bvBb¦C bvDc Cd¦) b6H d†'bÆGb¦C b6J dV4d6Db–  d¦Ed6Fd2 AbÖ5 bvDb†7bvBb’ Eb†'cF1b’ (b
          </p>
        </div>

        {/* Feedback message banner */}
        {feedbackMsg && (
          <div className={`p-4 rounded-2xl text-xs flex items-center gap-3 animate-in fade-in ${
            feedbackMsg.type === 'error'
              ? 'bg-rose-500/15 border border-rose-500/30 text-rose-300'
              : 'bg-emerald-500/15 border border-emerald-500/30 text-emerald-300'
          }`}>
            <AlertCircle className="w-4 h-4 flex-shrink-0" />
            <span className="flex-1 font-semibold">{feedbackMsg.text}</span>
          </div>
        )}

        {/* Hidden File Input for Image Upload */}
        <input
          type="file"
          ref={fileInputRef}
          accept="image/*"
          className="hidden"
          onChange={(e) => {
            const file = e.target.files?.[0];
            if (file) handlePhotoUpload(file);
          }}
        />

        {/* Quick Customer Action Cards */}
        <div className="bg-[#121216] border border-amber-500/30 rounded-3xl p-6 sm:p-8 space-y-6 shadow-[
```

FILE (cont.): src/views/HomeLandingView.tsx

```
          <div className="grid grid-cols-1 sm:grid-cols-2 gap-4">
            {/* Option 1: Live Camera Scan */}
            <button
              type="button"
              onClick={() => setIsScannerOpen(true)}
              className="p-5 rounded-2xl bg-gradient-to-tr from-amber-400/10 via-yellow-500/5 to-transpar
            >
              <div className="w-12 h-12 rounded-xl bg-amber-400/15 border border-amber-400/30 flex items-
                <Camera className="w-6 h-6 text-amber-400" />
              </div>
              <div>
                <h3 className="text-sm font-extrabold text-white">dV3bÒ Ad†1d¢ (bvDd6'dVJc '</h3>
                <p className="text-[11px] text-amber-200/70 mt-0.5">bvAb¦- d6'dVJc ' bvDdv'b¦A d†'d&1b2 'dF(cv'd&) d
              </div>
            </button>

            {/* Option 2: Upload Photo */}
            <button
              type="button"
              onClick={() => fileInputRef.current?.click()}
              disabled={isUploading}
              className="p-5 rounded-2xl bg-white/5 hover:bg-white/10 border border-white/10 hover:border
            >
              <div className="w-12 h-12 rounded-xl bg-white/10 flex items-center justify-center flex-shri
                {isUploading ? (
                  <Loader2 className="w-6 h-6 text-amber-400 animate-spin" />
                ) : (
                  <Upload className="w-6 h-6 text-amber-300" />
                )}
              </div>
              <div>
                <h3 className="text-sm font-extrabold text-white">
                  {isUploading ? 'bÆ'c J d -cR 'dF5d†1b’ãâãr ¢ v1d 9 cVHc ) bvDb†7bvBb’wÐ
                </h3>
                <p className="text-[11px] text-slate-400 mt-0.5">dVF b6Db†HdR 'dF5d†1 b6H dFBcv'b¢ 'dF4bv4b“Â÷ à
              </div>
            </button>
          </div>

          {/* Divider with text */}
          <div className="relative flex items-center justify-center py-2">
            <div className="absolute inset-0 flex items-center">
              <div className="w-full border-t border-amber-500/20" />
            </div>
            <span className="relative bg-[#121216] px-3 text-xs font-semibold text-amber-300/80">
              b6H bvCb¦( d6Hbò 'dF(cv'd&) bvDdV7b†Hc’ 9dFJdv'
            </span>
          </div>

          {/* Option 3: Manual Code Entry */}
          <form onSubmit={handleManualSubmit} className="space-y-3">
            <div className="flex flex-col sm:flex-row gap-2.5">
              <div className="relative flex-1">
                <input
                  type="text"
                  value={manualCode}
                  onChange={(e) => setManualCode(e.target.value)}
                  placeholder="bvCb¦( d6Hbò 'dF(cv'd&) bvDdV7b†Hc’ †Eb¶'dC¢ ³•ƒ&Õ  r’
                  className="w-full px-4 py-3 bg-black/50 border border-amber-500/20 rounded-xl text-sm f
                  dir="ltr"
                />
              </div>

              <button
                type="submit"
                disabled={!manualCode.trim()}
                className="px-6 py-3 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 hover:fr
              >
```

FILE (cont.): src/views/HomeLandingView.tsx

```
                <Search className="w-4 h-4" />
                d *bÒ 'dF(cv'd&)
              </button>
            </div>
            <p className="text-[11px] text-center text-slate-400">
              b¦,bò 'dFCd†/ dV7b†Hc–'d² (bæ7 d†'cf- c–Dd’ 'dF(cv'd&) bvDc Cd¦) b63d D c Ec" 'dF@ QR
            </p>
          </form>
        </div>

        {/* Customer Guidance & Feature Cards */}
        <div className="grid grid-cols-1 sm:grid-cols-3 gap-4 pt-2">
          <div className="p-4 bg-[#121216] border border-amber-500/20 rounded-2xl space-y-2 text-right">
            <div className="w-9 h-9 rounded-xl bg-amber-400/10 text-amber-400 flex items-center justify-c
              <Building2 className="w-5 h-5" />
            </div>
            <h4 className="text-xs font-extrabold text-white">bvDb¦-d†JdB 'dF(dfCd¢ 'dFEb†'cF1</h4>
            <p className="text-[11px] text-slate-400 leading-relaxed">
              df3bâ Ad†1d¢ Dc BdR 'dF-c6'b, HbvDb&Jb†'db ”$ â Ec’ %dVCbvFd¦) d *bÒ *cv(d¦B bvDb†Fd2 #d, –ç7F   ’ (cf
            </p>
          </div>

          <div className="p-4 bg-[#121216] border border-amber-500/20 rounded-2xl space-y-2 text-right">
            <div className="w-9 h-9 rounded-xl bg-amber-400/10 text-amber-400 flex items-center justify-c
              <Wallet className="w-5 h-5" />
            </div>
            <h4 className="text-xs font-extrabold text-white">dV-bvAc, 'dFCbv4 bvDbVDd6*c HdfJb“ÂöƒCà
            <p className="text-[11px] text-slate-400 leading-relaxed">
              b¦-d†JdB 3c Jc’ 9b†1 d Hbö'd Hdb Cbv4`Â #d†1df,`Â 'b¦5bvDbv*`Â HWE dV9 d6Hbò 'dF*bÖHd¦D bvDc61d¦9 bvDd
            </p>
          </div>

          <div className="p-4 bg-[#121216] border border-amber-500/20 rounded-2xl space-y-2 text-right">
            <div className="w-9 h-9 rounded-xl bg-amber-400/10 text-amber-400 flex items-center justify-c
              <MessageSquare className="w-5 h-5" />
            </div>
            <h4 className="text-xs font-extrabold text-white">bvDb¦Hbv5dB 'dFEb†'cF1 d†'dFHbv*c6'bƒÂöƒCà
            <p className="text-[11px] text-slate-400 leading-relaxed">
              d *bÒ EbÖ'bö+bv* d†'b¦3bv(`Â 5d -bv* bvDc6HcFJbvD dVJböJbv  b6H bvDbv*cV'dB 'dFGbv*d J d Hc 'd² /d†F b
            </p>
          </div>
        </div>

        {/* Customer FAQ / Help Section with Direct WhatsApp Support Button */}
        <div className="p-6 bg-[#121216] border border-amber-500/20 rounded-3xl text-right space-y-4">
          <div className="flex items-center justify-between flex-wrap gap-2">
            <div className="flex items-center gap-2 text-amber-400 text-xs font-bold">
              <HelpCircle className="w-4 h-4" />
              b¦Hbv,dr 5c–Hb†) d J dV3bÒ 'dF(cv'd&) b6H b¦E bÖ0d  'dFCd†/að
            </div>

            <a
              href={getWaLink()}
              target="_blank"
              rel="noopener noreferrer"
              className="inline-flex items-center gap-2 px-3.5 py-1.5 bg-gradient-to-r from-amber-400 to-
            >
              <MessageSquare className="w-3.5 h-3.5" />
              <span>b¦Hbv5dB Ec’ 'dFEcvHc ¢ ·6WGF–æw2æFWfVÆ÷ W%÷v† G6    ÇÂ s  SS S#33cRwÓÂ÷7  ãà
            </a>
          </div>

          <ul className="text-[11px] text-slate-300 space-y-1.5 list-disc list-inside leading-relaxed">
            <li>b¦#d6/ dVF b¦3dFJcr %cf'b ) d6'd Jb’ 9dFI bvDb†7bvBb’ Hc–/dR HbÆHbò 'df9d6'c6'b¢ Bd†Jb’ãÂöÆ“à
            <li>bV0br Cdf* b¦3b¦.böE d6'dVJc ' bvDdv'b¦A bvDc–'böJb–  b¦#d6/ dVF d†6d†- bvDb¦1d6Jc" „fö7W2’ 9dFI c E
            <li>d¦Ed6Fd2 /bv&dV'd² Cb¦'b†) bvDd6Hbò 'dFEcv(d†9 c–Dd’ 'dF(cv'd&) d J bvDbæ'df) b69dF'dr DdFHcVHdB 'dF
            <li>bV0br *dR Ec6- b6H bVDc¦'b  *d 9d¦D bvDb†7bvBb–  bv6c¦7 c–Dd’ 2c  *d†'cVD dV9 bvDdV7d†1 dFJb¦E bÖD b
          </ul>
```

FILE (cont.): src/views/HomeLandingView.tsx

```
        </div>
      </main>

      {/* Discrete Footer with Subtle Admin Login */}
      <footer className="border-t border-white/5 bg-black/60 py-6 px-4">
        <div className="max-w-5xl mx-auto flex flex-col sm:flex-row items-center justify-between gap-4 te
          <p>© {new Date().getFullYear()} Smart Card — bÆEd¦9 bvDbÖBd†B dV-d Hc†)</p>

          <button
            onClick={onGoToAdmin}
            className="flex items-center gap-1.5 text-slate-400 hover:text-amber-300 transition text-[11p
            title="b¦3bÆJdB /bæHdB 'dF%bö'c )"
          >
            <Lock className="w-3.5 h-3.5 text-amber-400" />
            <span>bö.d†D bvDbV/bv1b“Â÷7  ãà
          </button>
        </div>
      </footer>

      {/* Live Camera Scanner Modal */}
      <QrScannerModal
        isOpen={isScannerOpen}
        onClose={() => setIsScannerOpen(false)}
        onScannedId={(id) => {
          setIsScannerOpen(false);
          window.location.href = `/q/${id}`;
        }}
      />
    </div>
  );
}

```

FILE: src/views/CustomerActivationView.tsx 483 lines | 21.9 KB

```tsx
import { useState } from 'react';
import {
  Sparkles,
  CheckCircle2,
  AlertTriangle,
  Loader2,
  Building2,
  Wallet,
  ArrowRight,
  Check
} from 'lucide-react';
import { activateQrCode } from '../lib/qrService';
import {
  encodeBankDetails,
  processSmartLink,
  triggerSmartRedirect,
  detectWalletInfo,
  isQuickPayUrl,
  formatTikTokTargetUrl,
  formatInstagramTargetUrl,
  formatTelegramTargetUrl,
  formatSnapchatTargetUrl
} from '../lib/deepLinks';
import { AppType, QrCodeRecord } from '../types/qr';
import { PlatformBrandIcon, WalletProviderIcon } from '../components/BrandIcons';

interface CustomerActivationViewProps {
  qrId: string;
  onActivated: (updatedRecord: QrCodeRecord) => void;
}

export function CustomerActivationView({ qrId, onActivated }: CustomerActivationViewProps) {
  const [selectedType, setSelectedType] = useState<AppType>('whatsapp');
  const [rawInput, setRawInput] = useState('');
  const [bankName, setBankName] = useState('bvDb†Fd2 'dF#dvDd¢ 'dFEcV1d¢ „ä$R’r“°
  const [accountNumber, setAccountNumber] = useState('');
  const [accountName, setAccountName] = useState('');
  const [loading, setLoading] = useState(false);
  const [errorMsg, setErrorMsg] = useState<string | null>(null);
  const [activatedRecord, setActivatedRecord] = useState<QrCodeRecord | null>(null);

  const platforms: Array<{ type: AppType; label: string; placeholder: string; example: string }> = [
    {
      type: 'whatsapp',
      label: 'd†'b¦3bv(',
      placeholder: '01012345678 b6H 2010...',
      example: 'b6/bæD c BdR 'dFHbv*c6'b†  d†3d¦Ab¦- dV-bv/b¶*d2 Ad†1bvK c–Fbò Ec6- bvDd6'c *'
    },
    {
      type: 'instapay',
      label: 'bVFc6*bv(bvJ',
      placeholder: 'https://ipn.eg/S/... (c 'b†7 bvDböAc’ 'dF3c Jc’ Ad&7)',
      example: 'bvFc6. c 'b†7 bvDböAc’ 'dF3c Jc’ Edb *cv(d¦B bVFc6*bv(bvJ (bv7dF( böAc’ â EcF'c Cb’ 'dF1bv(cr’ HbvDc
    },
    {
      type: 'wallet',
      label: 'dV-d 8b’ Cbv4',
      placeholder: '010... b6H 012... b6H c 'b†7 bvDböAc’ 'dF3c Jc’ ‡GG 3¢òòââârÂ
      example: 'b6/bæD c 'b†7 bvDböAc’ 'dF3c Jc’ DdF*bÖHd¦D bvDd Hc J`Â #d, 1d&E dv'b¦A bvDdV-d 8b’ †Ad†/bvAd†F`Â #d
    },
    {
      type: 'bank',
      label: 'bÖ3bv( b†Fd6J',
      placeholder: 'c BdR 'dF-c6'b, 'dF(dfCd¢rÂ
      example: 'd¦9c 6 b†7bvBb’ (dfCd¦) c 3dVJb’ DdFEc6- dV9 c&1 dFFc6. c BdR 'dF-c6'b, Ad†1bvK'
    },
    {
      type: 'instagram',
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
      label: 'bVFc6*bÆ1bvE',
      placeholder: '@your_username b6H c 'b†7 bvDbÖ3bv(',
      example: 'bvCb¦( bv3dR -c6'b†C d†3d¦*dR Ab¦- b¦7b†Jd" %df3b¦,c 'dR 9dFI cVAbÖ*d2 Eb†'cF1b’r
    },
    {
      type: 'facebook',
      label: 'd Jc6(d†C',
      placeholder: 'c 'b†7 cVAbÖ*d2 #d, -c6'b†C c–Dd’ Ad¦3b†Hd2rÂ
      example: 'dV+bvD: https://facebook.com/yourpage'
    },
    {
      type: 'phone',
      label: 'bv*cV'dB Gbv*d J',
      placeholder: '01012345678 b6H +20...',
      example: 'd¦Ab¦- cF'cF) bvDbv*cV'dB Eb†'cF1b’ 9dFI dv'b¦A bvDc–Ed¦D b†1d&Ed2r
    },
    {
      type: 'telegram',
      label: 'b¦JdFJbÆ1bvE',
      placeholder: '@username b6H t.me/...',
      example: 'd¦Ab¦- b¦7b†Jd" *d¦Dd¦,c 'dR DdF*d†'cVD bvDdV(bv4c r
    },
    {
      type: 'tiktok',
      label: 'b¦Jd2 *d†C',
      placeholder: '@username b6H c 'b†7 b¦Jd2 *d†C',
      example: 'd¦Ab¦- b¦7b†Jd" *d¦C b¦Hd2 9dFI dVDd C bvDcF.cVJ'
    },
    {
      type: 'website',
      label: 'dVHd&9 d†Jb,rÂ
      placeholder: 'https://yourwebsite.com',
      example: 'b6J c 'b†7 d†Jb, *c :b, Ad¢ *d†,d¦G bvDc–EdF'b  %dFJdr †Eb¦,c   d&'bfEb’ 7c–'dV  bVDbâ’r
    },
  ];

  const currentPlatformInfo = platforms.find((p) => p.type === selectedType) || platforms[0];

  const handleActivate = async (e: React.FormEvent) => {
    e.preventDefault();

    let valueToSave = rawInput.trim();
    if (selectedType === 'bank') {
      if (!accountNumber.trim()) {
        setErrorMsg('d¦1bÆI d6*bv(b’ 1d&E bvDbÖ3bv( bvDb†Fd6J.');
        return;
      }
      valueToSave = encodeBankDetails({
        bankName,
        accountNumber: accountNumber.trim(),
        accountName: accountName.trim(),
      });
    } else if (selectedType === 'instapay') {
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 1bv(cr 'dF/d 9 bvDc61d¦9 dVF b¦7b†Jd" %df3b¦'b†'d¢âr“°
        return;
      }
      const hasLink = valueToSave.includes('ipn.eg') || valueToSave.startsWith('http://') || valueToSave.
      if (!hasLink) {
        setErrorMsg('b¦7b†Jd" %df3b¦'b†'d¢ Jb¦7dF( d†6c’ 1bv(cr 'dF/d 9 bvDc61d¦9 bvDdV(bv4c  †Eb¶D: https://ipn.eg/
        return;
      }
      if (valueToSave.startsWith('ipn.eg/')) {
        valueToSave = `https://${valueToSave}`;
      } else if (!valueToSave.startsWith('http://') && !valueToSave.startsWith('https://')) {
        valueToSave = `https://${valueToSave}`;
      }
    } else if (selectedType === 'wallet') {
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 1d&E dv'b¦A bvDdV-d 8b’ #d, 1bv(cr 'dF/d 9 bvDc61d¦9.');
        return;
      }
      if (!isQuickPayUrl(valueToSave)) {
        const detected = detectWalletInfo(valueToSave);
        valueToSave = detected.cleanPhone;
      }
    } else if (selectedType === 'tiktok') {
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 'c6E bvDdV3b¦.böE b6H c 'b†7 bÖ3bv( b¦Jd2 *d†C.');
        return;
      }
      valueToSave = formatTikTokTargetUrl(valueToSave);
    } else if (selectedType === 'instagram') {
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 'c6E bvDdV3b¦.böE b6H c 'b†7 bÖ3bv( bVFc6*bÆ1bvE.');
        return;
      }
      valueToSave = formatInstagramTargetUrl(valueToSave);
    } else if (selectedType === 'telegram') {
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 'c6E bvDdV3b¦.böE b6H c 'b†7 b¦JdFJbÆ1bvE.');
        return;
      }
      valueToSave = formatTelegramTargetUrl(valueToSave);
    } else if (selectedType === 'snapchat') {
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 'c6E bvDdV3b¦.böE b6H c 'b†7 bÖ3bv( c6Fbv( cF'b¢âr“°
        return;
      }
      valueToSave = formatSnapchatTargetUrl(valueToSave);
    } else {
      if (!valueToSave) {
        setErrorMsg('d¦1bÆI bV/bæ'dB 'dF1bv(cr #d, 'dF(d¦'df'b¢ 'dFEcvDd†(b’ Db¦Ac–JdB 'dFCbv1b¢âr“°
        return;
      }
    }

    setLoading(true);
    setErrorMsg(null);

    const smartLink = processSmartLink(valueToSave, selectedType);
    const destinationUrl = smartLink.schemeUrl || smartLink.fallbackUrl;

    try {
      const res = await activateQrCode(qrId, valueToSave, selectedType);

      // 1. If bank or wallet phone number: open dedicated card view
      if (selectedType === 'bank' || (selectedType === 'wallet' && smartLink.isWalletCard)) {
        if (res.record) {
          setActivatedRecord(res.record);
          onActivated(res.record);
        }
        setTimeout(() => {
          window.location.href = `/q/${qrId}`;
        }, 500);
        return;
      }

      // 2. For direct redirect (WhatsApp, InstaPay Quick Pay Link, Wallet Payment Link, Instagram, etc.)
      // Direct instant redirection with zero intermediate screens!
      if (destinationUrl) {
        try {
          window.location.replace(destinationUrl);
        } catch {
          window.location.href = destinationUrl;
        }
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
        return;
      } else if (res.record) {
        setActivatedRecord(res.record);
        onActivated(res.record);
        setTimeout(() => {
          window.location.href = `/q/${qrId}`;
        }, 500);
      }
    } catch (err) {
      console.error('Activation failed:', err);
      if (destinationUrl && selectedType !== 'bank' && selectedType !== 'wallet') {
        try {
          window.location.replace(destinationUrl);
        } catch {
          window.location.href = destinationUrl;
        }
      } else {
        setErrorMsg('bÖ/b² .cv# b6+df'b  *d 9d¦D bvDd6'c *`Â Jc ,d’ 'dFEbÖ'd†Db’ Ec ) b6.c I.');
      }
    } finally {
      setLoading(false);
    }
  };

  return (
    <div className="min-h-screen bg-[#09090b] text-white selection:bg-amber-500 selection:text-black flex
      <div className="w-full max-w-lg relative z-10">
        {!activatedRecord ? (
          <div className="bg-[#121216] border border-amber-500/30 rounded-3xl p-5 sm:p-8 shadow-[0_0_40px
            {/* Clean Header with Logo */}
            <div className="text-center space-y-2">
              <img src="/logo.png" alt="Smart Card" className="w-16 h-16 object-contain mx-auto mb-2 drop
              <div className="inline-flex items-center gap-1.5 px-3 py-1 bg-amber-400/15 text-amber-300 b
                <Sparkles className="w-3.5 h-3.5 text-amber-400" />
                b¦Ac–JdB (cv'd&) Smart Card dF#d†D dV1b•
              </div>
              <h1 className="text-2xl sm:text-3xl font-black text-transparent bg-clip-text bg-gradient-to
                Smart Card
              </h1>
              <p className="text-xs sm:text-sm text-slate-300">
                bv.b¦1 bvDb¦7b†Jd" #d, 'dFEdf5b’ 'dF*d¢ *c :b, Ad¢ 1b†7dv' b†Gc ' bvDd6'c * (bv.b¦Jbv1 d†'bÖ/ d Bcr’
              </p>
            </div>

            {/* Error Banner */}
            {errorMsg && (
              <div className="p-3.5 bg-rose-500/20 border border-rose-500/40 rounded-2xl text-xs text-ros
                <AlertTriangle className="w-4 h-4 text-rose-400 flex-shrink-0 mt-0.5" />
                <span>{errorMsg}</span>
              </div>
            )}

            {/* Form */}
            <form onSubmit={handleActivate} className="space-y-6">
              {/* Step 1: Platform Selection (Strict Single Select) */}
              <div className="space-y-3">
                <label className="text-xs font-black text-amber-200 block">
                  1. bv.b¦1 bvDdVFcV) b6H bvDb†Fd3
                </label>
                <div className="grid grid-cols-2 sm:grid-cols-5 gap-2.5">
                  {platforms.map((p) => {
                     const isSelected = selectedType === p.type;
                     return (
                       <button
                         key={p.type}
                         type="button"
                         onClick={() => setSelectedType(p.type)}
                         className={`relative flex flex-col items-center justify-center p-3 rounded-2xl b
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
                        isSelected
                          ? 'bg-[#181822] border-amber-500/30'
                          : 'bg-[#14141a] text-slate-300 border-white/10 hover:bg-[#1a1a24] hover:bord
                      }`}
                    >
                      {/* 3D Animated Icon (Movement applied strictly to logo) */}
                      <div
                        className={`w-11 h-11 flex items-center justify-center rounded-xl p-1 transiti
                          isSelected
                            ? 'animate-icon-alive'
                            : 'bg-black/40 hover:scale-105'
                        }`}
                      >
                        <PlatformBrandIcon
                          type={p.type}
                          className="w-9 h-9"
                        />
                      </div>

                      {/* 3D Animated Platform Label (Movement applied strictly to name) */}
                      <span
                        className={`text-[11px] font-black truncate w-full text-center transition-all
                          isSelected
                            ? 'animate-name-alive text-amber-300 drop-shadow-[0_1px_4px_rgba(250,204,2
                            : 'text-slate-300'
                        }`}
                      >
                        {p.label}
                      </span>
                    </button>
                  );
                })}
              </div>
            </div>

            {/* Step 2: Dynamic Input Field */}
            {selectedType === 'bank' ? (
              <div className="p-4 bg-black/50 border border-amber-500/20 rounded-2xl space-y-3">
                <div className="flex items-center gap-2 text-xs font-black text-amber-200">
                  <PlatformBrandIcon type="bank" className="w-5 h-5" />
                  <span>2. b†JbvFbv* bvDbÖ3bv( bvDb†Fd6J:</span>
                </div>
                <div className="space-y-1">
                  <label className="text-xs font-bold text-slate-300">bv3dR 'dF(dfC:</label>
                  <select
                    value={bankName}
                    onChange={(e) => setBankName(e.target.value)}
                    className="w-full px-3 py-2.5 bg-[#09090b] border border-amber-500/20 rounded-xl te
                  >
                    <option value="bvDb†Fd2 'dF#dvDd¢ 'dFEcV1d¢ „ä$R’#æ'dF(dfC bvDb6GdFJ bvDdV5c J (NBE)</option>
                    <option value="b†Fd2 EcV1 (Banque Misr)">b†Fd2 EcV1 (Banque Misr)</option>
                    <option value="bvDb†Fd2 'dF*bÆ'c J bvDböHdFJ (CIB)">bvDb†Fd2 'dF*bÆ'c J bvDböHdFJ (CIB)</optio
                    <option value="b†Fd2 Bcv1 bvDd†7dfJ (QNB)">b†Fd2 Bcv1 bvDd†7dfJ (QNB)</option>
                    <option value="b†Fd2 'dFBbvGc ) (Banque du Caire)">b†Fd2 'dFBbvGc ) (Banque du Caire)</option
                    <option value="b†Fd2 'dF%c6Cdf/c Jb’ „ ÆW„& æ²’#æ(dfC bvDbV3d6Fbö1d¦) (AlexBank)</option>
                    <option value="b†Fd2 Ad¦5dB 'dF%c6DbvEd¢#æ(dfC d JcVD bvDbV3dF'dVJ</option>
                    <option value="b†Fd2 "bæ1">b†Fd2 "bæ1</option>
                  </select>
                </div>

                <div className="space-y-1">
                  <label className="text-xs font-bold text-slate-300">c BdR 'dF-c6'b, 'dF(dfCd¢ †%dF2bvEd¢“£ÂöÆ &P
                  <input
                    type="text"
                    value={accountNumber}
                    onChange={(e) => setAccountNumber(e.target.value)}
                    placeholder="dV+bvD: 12345678901234"
                    className="w-full px-3.5 py-2.5 bg-black/60 border border-amber-500/20 rounded-xl t
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
                    dir="ltr"
                    required
                  />
                </div>

                <div className="space-y-1">
                  <label className="text-xs font-bold text-slate-300">bv3dR 5bv-b, 'dF-c6'b, †'bæ*d¦'c J):</label
                  <input
                    type="text"
                    value={accountName}
                    onChange={(e) => setAccountName(e.target.value)}
                    placeholder="dV+bvD: b6-dV/ dV-dV/ c–Dd¢
                    className="w-full px-3.5 py-2 bg-black/60 border border-amber-500/20 rounded-xl tex
                  />
                </div>
              </div>
            ) : selectedType === 'wallet' ? (
              <div className="space-y-3">
                <div className="flex items-center gap-2 text-xs font-black text-amber-200">
                  <PlatformBrandIcon type="wallet" className="w-5 h-5" />
                  <span>2. b6/bæD c BdR 'dFEbÖAc†) b6H c 'b†7 bvDböAc’ 'dF3c Jc“£Â÷7  ãà
                </div>
                <div className="relative">
                  <input
                    type="text"
                    value={rawInput}
                    onChange={(e) => setRawInput(e.target.value)}
                    placeholder="010... b6H 012... b6H c 'b†7 bvDböAc’ ‡GG 3¢òòâââ
                    className="w-full px-4 py-3.5 bg-black/50 border border-amber-500/20 rounded-2xl te
                    dir="ltr"
                    required
                    autoFocus
                  />
                </div>

                {/* Real-time detection card for wallet */}
                {rawInput.trim() ? (
                  isQuickPayUrl(rawInput) ? (
                    <div className="p-3.5 bg-amber-500/10 border border-amber-500/30 rounded-2xl flex i
                      <div className="w-10 h-10 rounded-xl bg-amber-400/20 border border-amber-400/30 f
                        <Sparkles className="w-5 h-5" />
                      </div>
                      <div className="text-right text-xs">
                        <p className="font-bold text-amber-300">c 'b†7 böAc’ 3c Jc’ DdFEbÖAc†) &¡</p>
                        <p className="text-[11px] text-slate-300">c6Jb¦E b¦-d†JdB 'dF9dVJdB *dFBbv&d¦'d² Hd Hc Jbv
                      </div>
                    </div>
                  ) : (() => {
                    const detected = detectWalletInfo(rawInput);
                    return (
                      <div className="p-3.5 bg-black/60 border border-white/10 rounded-2xl flex items-c
                        <div className="w-18 h-12 rounded-xl bg-black/60 border border-white/10 p-1 fle
                          <WalletProviderIcon provider={detected.provider} size={48} className="w-full
                        </div>
                        <div className="text-right text-xs min-w-0">
                          <div className="flex items-center gap-1.5 flex-wrap">
                            <span className="font-black text-amber-300 text-sm">{detected.nameAr}</span
                            <span className="text-[11px] font-bold text-slate-300">({detected.nameEn})<
                          </div>
                          <p className="text-[11px] text-slate-400 mt-0.5">
                            c6Jb¦E c–1cb 5d -b’ Abv.c ) dV.cV5b’ (cF9bv1 <strong>{detected.companyNameAr}</strong>
                          </p>
                        </div>
                      </div>
                    );
                  })()
                ) : (
                  <div className="p-3 bg-black/40 rounded-xl border border-white/5 text-[11px] text-amb
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
                    Ø=Ü¡ <strong>bæJbv1bv* bvDdV-d 8b“£Â÷7G&öæsà
                    <br />• dFH bÖ7d¦* <strong>c 'b†7 böAc’ 3c Jc“Â÷7G&öæsâ DdFEbÖAc†) (https://...) dvJbÖHdB 'dF9
                    <br />• dFH bÖ7d¦* <strong>c BdR 'dFEd†(bvJdCÂ÷7G&öæsâ ƒ    Ad†/bvAd†F d6'cB ò   " #d†1bvFbÂ C
                  </div>
                )}
              </div>
            ) : (
              <div className="space-y-2">
                <div className="flex items-center gap-2 text-xs font-black text-amber-200">
                  <PlatformBrandIcon type={selectedType} className="w-5 h-5" />
                  <span>2. b6/bæD b†JbvFbv* {currentPlatformInfo.label}:</span>
                </div>
                <div className="relative">
                  <input
                    type="text"
                    value={rawInput}
                    onChange={(e) => setRawInput(e.target.value)}
                    placeholder={currentPlatformInfo.placeholder}
                    autoCapitalize="none"
                    autoCorrect="off"
                    spellCheck={false}
                    className="w-full px-4 py-3.5 bg-black/50 border border-amber-500/20 rounded-2xl te
                    dir="ltr"
                    required
                    autoFocus
                  />
                </div>
                <p className="text-[11px] text-amber-200/70 leading-relaxed">
                  Ø=Ü¡ {currentPlatformInfo.example}
                </p>
              </div>
            )}

            {/* Submit Button */}
            <button
              type="submit"
              disabled={loading || (selectedType === 'bank' ? !accountNumber.trim() : !rawInput.trim())
              className="w-full py-4 px-6 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 h
            >
              {loading ? (
                <>
                  <Loader2 className="w-5 h-5 animate-spin text-black" />
                  <span>bÆ'c J b¦Ac–JdB 'dFCbv1b¢ãâãÂ÷7  ãà
                </>
              ) : (
                <>
                  <PlatformBrandIcon type={selectedType} className="w-6 h-6" />
                  <span>b¦#d6Jbò Hb¦Ac–JdB Cbv1b¢ ‡¶7W'&VçE Æ Ff÷&Ô–æfòÆ &VÇÒ’ 'dF"db ƒÝè Â÷7  ãà
                </>
              )}
            </button>
          </form>
        </div>
      ) : (
        /* Celebration View */
        <div className="bg-[#121216] border border-amber-500/30 rounded-3xl p-8 shadow-2xl text-center
          <div className="w-16 h-16 rounded-full bg-amber-400/20 border-2 border-amber-400 text-amber-4
            <CheckCircle2 className="w-8 h-8 animate-pulse text-amber-400" />
          </div>

          <div className="space-y-1.5">
            <h2 className="text-xl font-black text-transparent bg-clip-text bg-gradient-to-r from-amber
              b¦E b¦Ac–JdB Cbv1b¦C b†FbÆ'bÒ ƒÍø•
            </h2>
            <p className="text-xs text-slate-300">
              bÆ'c J dfBdFC bVDd’ 4bv4b’ 'dFCbv1b¢ 'dFEb†'cF1b’ 'dF"dbââà
            </p>
          </div>
```

FILE (cont.): src/views/CustomerActivationView.tsx

```
          </div>
        )}
      </div>
    </div>
  );
}

```

FILE: src/views/SmartRedirectView.tsx 414 lines | 19.2 KB

```tsx
import { useEffect, useState } from 'react';
import {
  Zap,
  ExternalLink,
  Smartphone,
  RefreshCw,
  MessageSquare,
  Instagram,
  Facebook,
  CreditCard,
  Phone,
  Send,
  Video,
  Globe,
  Building2,
  Copy,
  Check,
  Wallet,
  ArrowRight,
  ShieldCheck,
  Sparkles
} from 'lucide-react';
import { processSmartLink, triggerSmartRedirect, isRunningInIframe, detectWalletInfo } from '../lib/deepL
import { recordQrScan } from '../lib/qrService';
import { QrCodeRecord } from '../types/qr';
import { PlatformBrandIcon, WalletProviderIcon } from '../components/BrandIcons';

interface SmartRedirectViewProps {
  record: QrCodeRecord;
}

export function SmartRedirectView({ record }: SmartRedirectViewProps) {
  const [copiedField, setCopiedField] = useState<string | null>(null);
  const [hasAttemptedRedirect, setHasAttemptedRedirect] = useState(false);
  const [inIframe, setInIframe] = useState(false);

  const linkInfo = processSmartLink(record.target_url || '', record.app_type);

  useEffect(() => {
    // Record scan count authoritatively in Firestore & local cache
    recordQrScan(record.id);

    const isIframe = isRunningInIframe();
    setInIframe(isIframe);

    // If it is NOT a bank card, wallet card, or instapay card: instant auto-redirect!
    if (!linkInfo.isBankCard && linkInfo.appType !== 'bank' && !linkInfo.isWalletCard && !linkInfo.isInst
      if (!isIframe) {
        triggerSmartRedirect(linkInfo);
        setHasAttemptedRedirect(true);
      } else {
        setHasAttemptedRedirect(true);
      }
    }
  }, [record.id]);

  const handleCopy = (text: string, fieldKey: string) => {
    navigator.clipboard.writeText(text);
    setCopiedField(fieldKey);
    setTimeout(() => setCopiedField(null), 2000);
  };

  const handleDirectLaunch = () => {
    const target = linkInfo.schemeUrl || linkInfo.fallbackUrl;
    if (!target) return;

    if (inIframe) {
      window.open(target, '_blank', 'noopener,noreferrer');
```

FILE (cont.): src/views/SmartRedirectView.tsx

```
    } else {
      triggerSmartRedirect(linkInfo);
    }
  };

  // 1. BANK CARD VIEW: If the QR code is configured for Bank Transfer
  if (linkInfo.isBankCard || record.app_type === 'bank') {
    const bank = linkInfo.bankDetails || {
      bankName: 'bÖ3bv( b†Fd6J',
      accountNumber: record.target_url || '',
    };

    return (
      <div className="min-h-screen bg-[#09090b] text-white selection:bg-amber-500 selection:text-black fl
        <div className="w-full max-w-md bg-[#121216] border border-amber-500/30 rounded-3xl p-6 sm:p-8 sh
          {/* Header */}
          <div className="text-center space-y-2">
            <div className="w-16 h-16 rounded-2xl bg-gradient-to-tr from-amber-400 via-yellow-500 to-ambe
              <Building2 className="w-8 h-8 text-black" />
            </div>
            <div className="inline-flex items-center gap-1.5 px-3 py-1 bg-amber-400/15 border border-ambe
              <ShieldCheck className="w-3.5 h-3.5 text-amber-400" />
              b†JbvFbv* bvDb¦-d†JdB 'dF(dfCd¢ 'dFEc–*dV/b•
            </div>
            <h1 className="text-xl sm:text-2xl font-black text-transparent bg-clip-text bg-gradient-to-r
              {bank.bankName || 'bÖ3bv( b†Fd6J'}
            </h1>
          </div>

          {/* Bank Account Info Card */}
          <div className="bg-black/50 border border-amber-500/20 rounded-2xl p-4 sm:p-5 space-y-4">
            {/* Account Number */}
            <div className="space-y-1.5">
              <div className="flex items-center justify-between text-xs text-amber-200/80 font-semibold">
                <span>c BdR 'dF-c6'b, 'dF(dfCd££Â÷7  ãà
                <span className="text-[10px] text-slate-400">bv6c¦7 dFDdf3bâ 'dFAd†1d£Â÷7  ãà
              </div>
              <div className="flex items-center justify-between bg-black/60 border border-amber-500/30 ro
                <span className="font-mono text-base sm:text-lg font-black text-amber-300 tracking-wider
                  {bank.accountNumber || '—'}
                </span>
                <button
                  type="button"
                  onClick={() => handleCopy(bank.accountNumber || '', 'acc')}
                  className="flex items-center gap-1 px-3 py-1.5 bg-gradient-to-r from-amber-400 to-yello
                >
                  {copiedField === 'acc' ? (
                    <>
                      <Check className="w-4 h-4 text-black" />
                      <span>b¦E bvDdf3bâ Â÷7  ãà
                    </>
                  ) : (
                    <>
                      <Copy className="w-4 h-4 text-black" />
                      <span>df3bãÂ÷7  ãà
                    </>
                  )}
                </button>
              </div>
            </div>

            {/* Account Name */}
            {bank.accountName && (
              <div className="space-y-1 pt-2 border-t border-white/5">
                <span className="text-xs text-slate-400">bv3dR 'dFEc6*d Jbò ò 5bv-b, 'dF-c6'bƒ£Â÷7  ãà
                <p className="font-bold text-sm text-white">{bank.accountName}</p>
              </div>
            )}
```

FILE (cont.): src/views/SmartRedirectView.tsx

```
137
138             {/* IBAN */}
139             {bank.iban && (
140               <div className="space-y-1.5 pt-2 border-t border-white/5">
141                 <div className="flex items-center justify-between text-xs text-slate-400">
142                   <span>bvDb&Jb†'db 'dF/d†Dd¢ „”$ â“£Â÷7  ãà
143                 </div>
144                 <div className="flex items-center justify-between bg-black/60 border border-amber-500/20
145                   <span className="font-mono text-xs text-amber-200 select-all truncate" dir="ltr">
146                     {bank.iban}
147                   </span>
148                   <button
149                     type="button"
150                     onClick={() => handleCopy(bank.iban || '', 'iban')}
151                     className="p-1.5 text-amber-400 hover:text-white transition"
152                     title="df3bâ 'dF"d¦(bvF"
153                   >
154                     {copiedField === 'iban' ? <Check className="w-4 h-4 text-emerald-400" /> : <Copy clas
155                   </button>
156                 </div>
157               </div>
158             )}
159           </div>
160
161           {/* Quick Payment Apps Launchers */}
162           <div className="space-y-2">
163             <p className="text-xs text-center text-slate-400 font-medium">bvDb¦-d†JdB 'dFEb†'cF1 c–(c  'dF*cv(d¦Bbv*
164             <div className="grid grid-cols-2 gap-2">
165               <a
166                 href="https://ipn.eg"
167                 target="_blank"
168                 rel="noopener noreferrer"
169                 className="flex items-center justify-center gap-1.5 p-3 bg-amber-400/10 hover:bg-amber-40
170               >
171                 <CreditCard className="w-4 h-4 text-amber-400" />
172                 <span>d *bÒ –ç7F   “Â÷7  ãà
173               </a>
174               <button
175                 type="button"
176                 onClick={() => handleCopy(bank.accountNumber || '', 'acc')}
177                 className="flex items-center justify-center gap-1.5 p-3 bg-white/5 hover:bg-white/10 bord
178               >
179                 <Copy className="w-4 h-4 text-amber-400" />
180                 <span>df3bâ Db¦7b†Jd" 'dF(dfC</span>
181               </button>
182             </div>
183           </div>
184         </div>
185       </div>
186     );
187   }
188
189   // 2. WALLET VIEW (Vodafone Cash, Etisalat Cash, Orange Cash, WE Pay)
190   if (linkInfo.isWalletCard || (record.app_type === 'wallet' && linkInfo.isWalletCard !== false)) {
191     const rawPhone = linkInfo.walletPhone || linkInfo.displayUrl || record.target_url || '';
192     const detected = detectWalletInfo(rawPhone);
193     const phone = detected.cleanPhone || rawPhone;
194     const formattedPhone = detected.formattedPhone || phone;
195     const provider = detected.provider || 'vodafone';
196     const providerNameAr = detected.nameAr;
197     const providerNameEn = detected.nameEn;
198     const companyName = detected.companyNameAr;
199     let brandBorder = 'border-red-500/40 shadow-[0_0_50px_rgba(230,0,0,0.22)]';
200     let badgeClass = 'bg-red-500/15 text-red-300 border-red-500/30';
201     let brandGradient = 'from-red-200 via-red-400 to-rose-500';
202
203     if (provider === 'orange') {
204       brandBorder = 'border-orange-500/40 shadow-[0_0_50px_rgba(255,121,0,0.22)]';
```

FILE (cont.): src/views/SmartRedirectView.tsx

```
      badgeClass = 'bg-orange-500/15 text-orange-300 border-orange-500/30';
      brandGradient = 'from-orange-200 via-orange-400 to-amber-500';
    } else if (provider === 'etisalat') {
      brandBorder = 'border-emerald-500/40 shadow-[0_0_50px_rgba(113,158,25,0.22)]';
      badgeClass = 'bg-emerald-500/15 text-emerald-300 border-emerald-500/30';
      brandGradient = 'from-emerald-200 via-emerald-400 to-green-500';
    } else if (provider === 'we') {
      brandBorder = 'border-purple-500/40 shadow-[0_0_50px_rgba(102,45,145,0.28)]';
      badgeClass = 'bg-purple-500/15 text-purple-300 border-purple-500/30';
      brandGradient = 'from-purple-200 via-purple-400 to-indigo-400';
    } else if (provider === 'generic') {
      brandBorder = 'border-amber-500/40 shadow-[0_0_50px_rgba(212,175,55,0.2)]';
      badgeClass = 'bg-amber-400/15 text-amber-300 border-amber-400/30';
      brandGradient = 'from-amber-200 via-amber-400 to-yellow-500';
    }

    const isCopied = copiedField === 'wallet';

    return (
      <div className="min-h-screen bg-[#09090b] text-white selection:bg-amber-500 selection:text-black fl
        <div className={`w-full max-w-md bg-[#121216] border rounded-3xl p-6 sm:p-8 space-y-6 text-center

          {/* Official Company Logo */}
          <div className="relative inline-block mx-auto">
            <div className="w-48 h-24 sm:w-56 sm:h-28 rounded-2xl bg-black/60 border border-white/15 p-3
              <WalletProviderIcon provider={provider} size={140} className="w-full h-full max-h-20 object
            </div>
          </div>

          {/* Provider and Company Titles */}
          <div className="space-y-2">
            <div className={`inline-flex items-center gap-1.5 px-3 py-1 rounded-full text-[11px] font-bla
              <Sparkles className="w-3.5 h-3.5" />
              <span>{companyName}</span>
            </div>

            {/* Arabic Wallet Name */}
            <h1 className={`text-2xl sm:text-3xl font-black text-transparent bg-clip-text bg-gradient-to-
              {providerNameAr}
            </h1>

            {/* English Wallet Name */}
            <p className="text-xs sm:text-sm font-bold text-slate-300 tracking-wider">
              {providerNameEn}
            </p>
          </div>

          {/* Phone Number Display Box */}
          <div className="bg-black/60 border border-white/10 rounded-2xl p-4 sm:p-5 space-y-3">
            <div className="flex items-center justify-between text-xs text-slate-400 font-medium">
              <span>c BdR 'dFEbÖAc†) dF*bÖHd¦D bvDb6Ed†'dC£Â÷7  ãà
              <span className="text-[10px] text-amber-400/90 font-bold">b£'dv2 dFDb¦-d†JdB 'dFAd†1d£Â÷7  ãà
            </div>

            <div className="flex items-center justify-between bg-black/80 border border-amber-500/30 roun
              <span className="font-mono text-xl sm:text-2xl font-black text-amber-300 tracking-wider sel
                {formattedPhone}
              </span>

              {/* Compact Inline Copy Button */}
              <button
                type="button"
                onClick={() => handleCopy(phone, 'wallet')}
                className={`flex items-center gap-1.5 px-3.5 py-2 text-xs font-black rounded-lg transitio
                  isCopied
                    ? 'bg-emerald-500 text-black hover:bg-emerald-400'
                    : 'bg-gradient-to-r from-amber-400 to-yellow-500 hover:from-amber-300 hover:to-amber-
                }`}
```

FILE (cont.): src/views/SmartRedirectView.tsx

```
                title="df3bâ 'dF1d&E"
              >
                {isCopied ? <Check className="w-4 h-4 text-black" /> : <Copy className="w-4 h-4 text-blac
                <span>{isCopied ? 'b¦E bvDdf3bâ r ¢ vFc6.'}</span>
              </button>
            </div>
          </div>

          {/* Prominent Primary Copy Button - The ONLY action on this screen as requested */}
          <div className="space-y-4 pt-1">
            <button
              type="button"
              onClick={() => handleCopy(phone, 'wallet')}
              className={`w-full py-4 px-6 text-sm sm:text-base font-black rounded-2xl shadow-xl transiti
                isCopied
                  ? 'bg-emerald-500 hover:bg-emerald-400 text-black shadow-emerald-500/25 ring-2 ring-eme
                  : 'bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 hover:from-amber-300 hov
              }`}
            >
              {isCopied ? (
                <>
                  <Check className="w-5 h-5 text-black animate-bounce" />
                  <span>b¦E df3bâ 1d&E bvDdV-d 8b’ (df,bv- '  (bÆ'dv2 dFDcVB)</span>
                </>
              ) : (
                <>
                  <Copy className="w-5 h-5 text-black" />
                  <span>df3bâ 1d&E dV-d 8b’ ‡· &÷f–FW$æ ÖT 'Ò“Â÷7  ãà
                </>
              )}
            </button>

            {/* Clear, simple instructions */}
            <div className="p-3.5 bg-black/40 rounded-2xl border border-white/5 text-right space-y-2 text
              <p className="font-bold text-amber-300 flex items-center gap-1.5">
                <span>Ø=Ü¡</span>
                <span>cv1d¦Bb’ 'dF*bÖHd¦D:</span>
              </p>
              <ol className="list-decimal list-inside space-y-1 pr-1 text-slate-300">
                <li>bv6c¦7 c–Dd’ 2c  Ç7G&öæsæFc6. c BdR 'dFEbÖAc†)</strong> b69dF'drãÂöÆ“à
                <li>bvAb¦- b¦7b†Jd" EbÖAc†*d2 'dF.bv5b’ ‡· &÷f–FW$æ ÖT 'Ò’ãÂöÆ“à
                <li>bvDcVB bvDc BdR HbÖ/bò 'dFEb†Dc¢ 'dFEcvDd†( d†#d6Qbò 9dVDd¦) bvDb¦-d†JdBãÂöÆ“à
              </ol>
            </div>
          </div>
        </div>
      </div>
    );
  }

  // 3. INSTAPAY IPA CARD VIEW
  if (linkInfo.isInstaPayCard) {
    const handle = linkInfo.instaPayHandle || record.target_url || '';
    return (
      <div className="min-h-screen bg-[#09090b] text-white selection:bg-amber-500 selection:text-black fl
        <div className="w-full max-w-md bg-[#121216] border border-amber-500/30 rounded-3xl p-6 sm:p-8 sh
          <div className="w-18 h-18 rounded-2xl bg-black/60 border border-amber-500/40 p-2 flex items-cen
            <PlatformBrandIcon type="instapay" className="w-12 h-12" />
          </div>

          <div>
            <div className="inline-flex items-center gap-1.5 px-3 py-1 bg-amber-400/15 border border-ambe
              <Sparkles className="w-3.5 h-3.5 text-amber-400" />
              c–Fd†'db 'dF/d 9 bvDdF-c†J (IPA)
            </div>
            <h1 className="text-xl sm:text-2xl font-black text-transparent bg-clip-text bg-gradient-to-r
              bVFc6*bv(bvJ InstaPay
            </h1>
```

FILE (cont.): src/views/SmartRedirectView.tsx

```
            <p className="text-xs text-amber-200/70 mt-1">bvFd&1 dFFc6. c–Fd†'db 'dF/d 9 d†'dF*bÖHd¦D d J b¶HbvFdÓÂ÷
          </div>

          <div className="bg-black/50 border border-amber-500/20 rounded-2xl p-4 space-y-2">
            <span className="text-xs text-slate-400">c–Fd†'db 'dF/d 9 bvDdF-c†J bvDbæ'cR (d£€Â÷7  ãà
            <div className="flex items-center justify-between bg-black/60 border border-amber-500/30 roun
              <span className="font-mono text-base sm:text-lg font-black text-amber-300 tracking-wide tru
                {handle}
              </span>
              <button
                type="button"
                onClick={() => handleCopy(handle, 'instapay')}
                className="flex items-center gap-1.5 px-3.5 py-2 bg-gradient-to-r from-amber-400 to-yello
              >
                {copiedField === 'instapay' ? <Check className="w-4 h-4 text-black" /> : <Copy className=
                <span>{copiedField === 'instapay' ? 'b¦E bvDdf3bâ r ¢ vFc6.'}</span>
              </button>
            </div>
          </div>

          <div className="space-y-3 pt-1">
            <a
              href="https://ipn.eg"
              target="_blank"
              rel="noopener noreferrer"
              className="w-full py-3.5 px-4 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 h
            >
              <CreditCard className="w-4 h-4 text-black" />
              <span>d *bÒ 1bv(cr Ed†Bc’ %df3b¦'b†'d¢ –ç7F   “Â÷7  ãà
            </a>

            <p className="text-[11px] text-slate-400 leading-relaxed">
              Ø=Ü¡ bvFc6. bvDc–Fd†'db +dR 'd *bÒ 'dF*cv(d¦B d†'cf:cr 9dFI &amp;quot;bV1c6'dB Fd&Hbòg V÷C² HbvDcVB bvDc–F
            </p>
          </div>
        </div>
      </div>
    );
  }

  // 4. INSTANT DIRECT REDIRECTION SPLASH (WhatsApp, Instagram, Facebook, TikTok, Website, YouTube, etc.)
  const targetLink = linkInfo.schemeUrl || linkInfo.fallbackUrl;

  return (
    <div className="min-h-screen bg-[#09090b] text-white flex flex-col items-center justify-center p-6 te
      <div className="relative mb-6">
        <div className="w-20 h-20 rounded-2xl bg-amber-400/10 border border-amber-400/30 flex items-cente
          <PlatformBrandIcon type={linkInfo.appType} className="w-12 h-12 animate-pulse" />
        </div>
      </div>

      <div className="space-y-2 mb-6">
        <h2 className="text-xl sm:text-2xl font-black text-transparent bg-clip-text bg-gradient-to-r from
          bÆ'c J d *bÒ ¶Æ–æ´–æfòæ   F—FÆT 'Ò Eb†'cF1b’ââà
        </h2>
        <p className="text-xs text-slate-400 font-medium">
          dF-c†) d†'bÖ/b’ Hc6Jb¦E b¦-d†JdFC b¦Dd&'bfJbvK &¡
        </p>
      </div>

      {targetLink && (
        <a
          href={targetLink}
          target={inIframe ? '_blank' : '_self'}
          rel="noopener noreferrer"
          className="text-xs text-amber-400/90 hover:text-amber-300 underline font-semibold transition py
        >
          bV0br DdR Jd *bÒ 'dF*cv(d¦B b¦Dd&'bfJbvK`Â 'cf:cr Gdf' dFDdV*bv(c–)
```

FILE (cont.): src/views/SmartRedirectView.tsx

```
        </a>
      )}
    </div>
  );
}

```

FILE: src/views/CardExpiredView.tsx 140 lines | 6.9 KB

```tsx
import { RefreshCw, MessageSquare, AlertCircle, Clock, ShieldAlert } from 'lucide-react';
import { QrCodeRecord, PlatformSettings } from '../types/qr';
import { PlatformBrandIcon } from '../components/BrandIcons';

interface CardExpiredViewProps {
  record: QrCodeRecord;
  settings: PlatformSettings;
}

export function CardExpiredView({ record, settings }: CardExpiredViewProps) {
  const formattedExpiry = record.expires_at
    ? new Date(record.expires_at).toLocaleDateString('ar-EG', {
        year: 'numeric',
        month: 'long',
        day: 'numeric',
      })
    : 'c¦Jc  EbÖ/bòs°

  // Format WhatsApp Link
  let cleanPhone = (settings.developer_whatsapp || '01550523365').trim();
  let contactUrl = settings.developer_contact_url || '';
  if (!contactUrl && cleanPhone) {
    let num = cleanPhone.replace(/[^\d]/g, '');
    if (num.startsWith('01')) num = '2' + num;
    contactUrl = `https://wa.me/${num}`;
  }

  const renewalMessage = encodeURIComponent(
    `dV1bÖ(bvK`Â #d†/ b¦,böJbò 'cF*c 'd2 'dFCbv1b¢ 'dF0d6J c BdS¢ ,G·&V6÷&Bæ–GÒ–
  );
  const whatsappRenewalUrl = `${contactUrl}${contactUrl.includes('?') ? '&' : '?'}text=${renewalMessage}`

  return (
    <div className="min-h-screen bg-[#09090b] text-white flex flex-col justify-between items-center p-4 s
      {/* Ambient background glows */}
      <div className="absolute top-1/4 left-1/2 -translate-x-1/2 -translate-y-1/2 w-96 h-96 bg-amber-500/
      <div className="absolute bottom-10 right-10 w-72 h-72 bg-yellow-600/10 rounded-full blur-3xl pointe

      {/* Header */}
      <header className="w-full max-w-md pt-4 pb-2 flex items-center justify-between z-10">
        <div className="flex items-center gap-2">
          <img src="/logo.png" alt="Smart Card" className="w-8 h-8 object-contain rounded-lg border borde
          <span className="text-xs font-black tracking-wider text-amber-200/90 font-mono">Smart Card</spa
        </div>
        <span className="px-3 py-1 bg-rose-500/15 border border-rose-500/30 text-rose-400 rounded-full te
          <ShieldAlert className="w-3.5 h-3.5" />
          <span>bv4b¦1bvC dVFb¦Gd£Â÷7  ãà
        </span>
      </header>

      {/* Central Content Card */}
      <main className="w-full max-w-md my-auto py-6 z-10">
        <div className="bg-[#121216]/95 border border-amber-500/30 rounded-3xl p-6 sm:p-8 text-center spa
          {/* Top highlight bar */}
          <div className="absolute top-0 left-0 right-0 h-1 bg-gradient-to-r from-amber-500 via-rose-500

          {/* Expired / Clock Icon */}
          <div className="relative mx-auto w-24 h-24 rounded-3xl bg-gradient-to-br from-rose-500/20 via-a
            <Clock className="w-12 h-12 text-amber-400 stroke-[1.5]" />
            <div className="absolute -top-1 -right-1 w-4 h-4 bg-rose-500 rounded-full border-2 border-[#1
              <span className="text-[9px] text-white font-black">!</span>
            </div>
          </div>

          {/* Title & Description */}
          <div className="space-y-2">
            <h1 className="text-2xl sm:text-3xl font-black text-transparent bg-clip-text bg-gradient-to-r
              bvFb¦Gb¢ Ab¦1b' 'cF*c 'd2 'dFCbv1b
```

FILE (cont.): src/views/CardExpiredView.tsx

```
            </h1>
            <p className="text-xs sm:text-sm text-slate-300 leading-relaxed font-normal">
              dFBbò 'df*dv* d *c ) bvDbv4b¦1bvC bvDdV-bö/b’ Ddv0dr 'dF(cv'd&) bvDc Cd¦). dF*bÆ/d¦/ bvDbv4b¦1bvC d†%c
            </p>
          </div>

          {/* Card Info Box */}
          <div className="bg-black/40 border border-white/10 rounded-2xl p-4 text-right space-y-2.5">
            <div className="flex items-center justify-between text-xs pb-2 border-b border-white/5">
              <span className="text-slate-400 font-medium">c BdR 'dF(cv'd&) bvDc Cd¦):</span>
              <span className="font-mono font-black text-amber-400 text-sm tracking-wider">
                {record.id}
              </span>
            </div>

            <div className="flex items-center justify-between text-xs pb-2 border-b border-white/5">
              <span className="text-slate-400 font-medium">b¦'c Jbâ 'df*dv'b  'dF5dF'bÖJb“£Â÷7  ãà
              <span className="font-semibold text-rose-300">{formattedExpiry}</span>
            </div>

            {record.app_type && (
              <div className="flex items-center justify-between text-xs">
                <span className="text-slate-400 font-medium">bvDd†,dv) bvDdV1b¦(cv):</span>
                <span className="inline-flex items-center gap-1.5 text-slate-200 font-medium">
                  <PlatformBrandIcon type={record.app_type} className="w-4 h-4" />
                  <span>{record.app_type}</span>
                </span>
              </div>
            )}
          </div>

          {/* Action Buttons */}
          <div className="space-y-3 pt-2">
            {/* Primary WhatsApp Renewal Button */}
            <a
              href={whatsappRenewalUrl}
              target="_blank"
              rel="noopener noreferrer"
              className="w-full py-4 px-6 rounded-2xl bg-gradient-to-r from-amber-400 via-yellow-500 to-a
            >
              <MessageSquare className="w-5 h-5 fill-black" />
              <span>b¦,böJbò 'cF*c 'd2 'dFCbv1b¢ 9b†1 d†'b¦3bv(</span>
            </a>

            {/* Check Renewal / Reload */}
            <button
              onClick={() => window.location.reload()}
              className="w-full py-3 px-4 rounded-xl bg-white/5 hover:bg-white/10 border border-white/10
            >
              <RefreshCw className="w-3.5 h-3.5" />
              <span>bV0br *dR 'dF*bÆ/d¦/ bv6c¦7 dFDb¦-d&B d†%c–'bö) bvDb¦HbÆJdsÂ÷7  ãà
            </button>
          </div>

          {/* Contact Details Footnote */}
          <div className="pt-2 text-[11px] text-slate-400 flex items-center justify-center gap-1">
            <span>dFDbö9dR 'dF3c Jc“£Â÷7  ãà
            <span className="text-amber-300 font-mono font-bold" dir="ltr">
              {settings.developer_whatsapp || '01550523365'}
            </span>
          </div>
        </div>
      </main>

      {/* Footer */}
      <footer className="w-full max-w-md py-4 text-center text-[10px] text-slate-500 z-10 font-mono">
        Smart Card © {new Date().getFullYear()} — bÆEd¦9 bvDbÖBd†B dV-d Hc†)
      </footer>
```

FILE (cont.): src/views/CardExpiredView.tsx

```
    </div>
  );
}

```

FILE: src/components/BrandIcons.tsx 656 lines | 24.1 KB

```tsx
import React from 'react';
import { AppType } from '../types/qr';

interface BrandIconProps {
  className?: string;
  size?: number;
}

/**
 * 1. Official WhatsApp App Squircle Icon
 * Uses official squircle app icon asset provided by user (1792666710853_e8958abe.jpg)
 */
export function WhatsAppIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <img
      src="/whatsapp-app-logo.png"
      alt="WhatsApp"
      width={size}
      height={size}
      className={`${className} object-contain rounded-xl select-none drop-shadow-sm`}
      loading="eager"
      decoding="async"
    />
  );
}

/**
 * 2. Official Facebook App Squircle Icon
 * Matches the official Facebook 3D squircle app icon (user uploaded 1792666781397.jpg)
 */
export function FacebookIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="fb_squircle_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse
          <stop stopColor="#1977F3" />
          <stop offset="1" stopColor="#0D61D9" />
        </linearGradient>
        <linearGradient id="fb_glass_sheen" x1="0" y1="0" x2="100" y2="50" gradientUnits="userSpaceOnUse"
          <stop stopColor="white" stopOpacity="0.22" />
          <stop offset="1" stopColor="white" stopOpacity="0" />
        </linearGradient>
      </defs>
      {/* Squircle Base */}
      <rect width="100" height="100" rx="22" fill="url(#fb_squircle_grad)" />
      {/* Specular Highlight */}
      <path d="M0 22C0 9.85 9.85 0 22 0h56c12.15 0 22 9.85 22 22v12C68 38 32 38 0 32V22z" fill="url(#fb_g
      {/* Bold Facebook 'f' reaching right to the bottom edge */}
      <path
        d="M66.5 100V61.5H79.5L81.5 46.5H66.5V36.9C66.5 32.6 67.7 29.6 74 29.6H82V16.2C80.6 16 75.8 15.6
        fill="white"
      />
    </svg>
  );
}

/**
 * 3. Official Google Phone / Dialer Squircle Icon
 * Matches the official Google Phone app icon (user uploaded 1792666875207.jpg)
 */
export function PhoneCallIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
```

FILE (cont.): src/components/BrandIcons.tsx

```tsx
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="phone_white_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse
          <stop stopColor="#FFFFFF" />
          <stop offset="1" stopColor="#F8FAFC" />
        </linearGradient>
        <filter id="phone_soft_shadow" x="-10%" y="-10%" width="120%" height="120%">
          <feDropShadow dx="0" dy="2" stdDeviation="3" floodColor="#0F172A" floodOpacity="0.08" />
        </filter>
      </defs>
      {/* Pure White Squircle Base with Soft Inset Border */}
      <rect width="100" height="100" rx="22" fill="url(#phone_white_grad)" stroke="#E2E8F0" strokeWidth="
      {/* Google Dual-Tone Blue Phone Handset */}
      <g transform="translate(18, 18) scale(0.64)">
        {/* Dark Blue Upper Earpiece & Grip (#1A73E8) */}
        <path
          d="M34.5 10.5C31.2 3.1 22.6 0 15.2 3.3L4.8 7.9C1.8 9.2 0 12.3 0 15.6C0 54.5 31.5 86 70.4 86C73.
          display="none"
        />
        {/* Crisp Vector Geometry matching uploaded dialer image */}
        {/* Top/Backgrip section in Deep Google Blue */}
        <path
          d="M48 10C42 10 32 16 28 26L21 44C16 57 26 73 39 83L49 90C59 96 73 98 83 91L92 84C97 80 99 74 9
          display="none"
        />
        {/* Precise Handset Paths */}
        {/* Upper/Earpiece in #1A73E8 */}
        <path
          d="M42.8 6.5C36.2 1.3 26.6 2.6 21.4 9.2L12.5 20.6C7.8 26.5 7.4 34.6 11.5 41C19.8 54.1 31.9 66.2
          display="none"
        />
        {/* Clean Material Dialer Handset */}
        {/* Top Dark Blue (#1A73E8) */}
        <path
          d="M32.5 12C28.2 5.5 19.5 3.8 13 8.1L5.8 12.9C1.9 15.5 0 20 0 24.6C0 60.7 29.3 90 65.4 90C70 90
          fill="#1A73E8"
        />
        {/* Bottom Curved Highlight (#4285F4) */}
        <path
          d="M65.4 90C29.3 90 0 60.7 0 24.6C0 22.3.5 20.1 1.4 18 10 52 38 80 72 88.6c-2.1.9-4.3 1.4-6.6 1
          fill="#4285F4"
          fillOpacity="0.8"
        />
        <path
          d="M20 35.5C25.3 45.2 32.9 52.8 42.6 58.1L35 68C22 58 12 48 2 35l9.5-6.5L20 35.5z"
          fill="#4285F4"
        />
      </g>
    </svg>
  );
}

/**
 * 4. Official InstaPay App Squircle Icon
 * Uses high-resolution squircle app icon asset provided by user
 */
export function InstaPayIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <img
      src="/instapay-app-logo.png"
```

FILE (cont.): src/components/BrandIcons.tsx

```tsx
      alt="InstaPay"
      width={size}
      height={size}
      className={`${className} object-contain rounded-xl select-none drop-shadow-sm`}
      loading="eager"
      decoding="async"
    />
  );
}

/**
 * 5. Official Instagram App Squircle Icon
 */
export function InstagramIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <radialGradient id="ig_squircle_grad" cx="20%" cy="100%" r="130%">
          <stop offset="0%" stopColor="#FFDC80" />
          <stop offset="20%" stopColor="#F77737" />
          <stop offset="40%" stopColor="#F56040" />
          <stop offset="60%" stopColor="#FD1D1D" />
          <stop offset="80%" stopColor="#E1306C" />
          <stop offset="90%" stopColor="#C13584" />
          <stop offset="100%" stopColor="#833AB4" />
        </radialGradient>
        <linearGradient id="ig_glass_sheen" x1="0" y1="0" x2="100" y2="50" gradientUnits="userSpaceOnUse"
          <stop stopColor="white" stopOpacity="0.25" />
          <stop offset="1" stopColor="white" stopOpacity="0" />
        </linearGradient>
      </defs>
      {/* Squircle Base */}
      <rect width="100" height="100" rx="22" fill="url(#ig_squircle_grad)" />
      <path d="M0 22C0 9.85 9.85 0 22 0h56c12.15 0 22 9.85 22 22v12C68 38 32 38 0 32V22z" fill="url(#ig_g
      {/* Camera Outer Rounded Rect */}
      <rect x="23" y="23" width="54" height="54" rx="15" stroke="white" strokeWidth="6" />
      {/* Camera Center Lens */}
      <circle cx="50" cy="50" r="13" stroke="white" strokeWidth="6" />
      {/* Camera Flash Dot */}
      <circle cx="66" cy="34" r="3.5" fill="white" />
    </svg>
  );
}

/**
 * 6. Official TikTok App Squircle Icon
 */
export function TikTokIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="tiktok_base_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse
          <stop stopColor="#16161A" />
          <stop offset="1" stopColor="#08080A" />
```

FILE (cont.): src/components/BrandIcons.tsx

```tsx
        </linearGradient>
      </defs>
      {/* Carbon Matte Squircle */}
      <rect width="100" height="100" rx="22" fill="url(#tiktok_base_grad)" stroke="#27272A" strokeWidth="
      {/* 3D Cyan Layer */}
      <path
        fill="#00F2FE"
        d="M68.5 35.5c-4.4-1.2-8-4.4-9.2-8.8h-8.4v38c0 5.6-4.4 10-10 10s-10-4.4-10-10 4.4-10 10-10c1.2 0
      />
      {/* 3D Red Layer */}
      <path
        fill="#FE2C55"
        d="M69.7 34.7c-4.4-1.2-8-4.4-9.2-8.8h-7.2v38c0 5.6-4.4 10-10 10s-10-4.4-10-10 4.4-10 10-10c1.2 0
      />
      {/* White Core */}
      <path
        fill="#FFFFFF"
        d="M68.5 35.1c-4.4-1.2-8-4.4-9.2-8.8h-8v38c0 5.6-4.4 10-10 10s-10-4.4-10-10 4.4-10 10-10c1.2 0 2.
      />
    </svg>
  );
}

/**
 * 7. Official Telegram App Squircle Icon
 */
export function TelegramIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="tg_squircle_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse
          <stop stopColor="#2CB5E8" />
          <stop offset="1" stopColor="#1D96D2" />
        </linearGradient>
        <linearGradient id="tg_glass_sheen" x1="0" y1="0" x2="100" y2="50" gradientUnits="userSpaceOnUse"
          <stop stopColor="white" stopOpacity="0.25" />
          <stop offset="1" stopColor="white" stopOpacity="0" />
        </linearGradient>
      </defs>
      {/* Squircle Base */}
      <rect width="100" height="100" rx="22" fill="url(#tg_squircle_grad)" />
      <path d="M0 22C0 9.85 9.85 0 22 0h56c12.15 0 22 9.85 22 22v12C68 38 32 38 0 32V22z" fill="url(#tg_g
      {/* Origami Paper Plane */}
      <path
        d="M23 49.5L69 31C71.1 30.1 73.1 31.5 72.5 33.7L64.5 71.5C64 74 61.8 74.8 59.8 73.5L48 64.6L42 70
        fill="white"
      />
    </svg>
  );
}

/**
 * 8. Official Vodafone Cash Icon
 * Uses official transparent brand logo provided by user (/wallets/vodafone-cash.png)
 */
export function VodafoneCashIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  const [hasError, setHasError] = React.useState(false);

  if (hasError) {
    return (
      <svg
```

FILE (cont.): src/components/BrandIcons.tsx

```
        viewBox="0 0 100 100"
        width={size}
        height={size}
        className={`${className} select-none drop-shadow-md`}
        fill="none"
        xmlns="http://www.w3.org/2000/svg"
      >
        <defs>
          <linearGradient id="vf_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse">
            <stop stopColor="#E60000" />
            <stop offset="1" stopColor="#A80000" />
          </linearGradient>
        </defs>
        <rect width="100" height="100" rx="22" fill="url(#vf_grad)" />
        <circle cx="50" cy="42" r="18" fill="white" />
        <circle cx="50" cy="42" r="11" fill="#E60000" />
        <rect x="22" y="72" width="56" height="16" rx="8" fill="white" />
        <text x="50" y="84" textAnchor="middle" fill="#E60000" fontSize="10.5" fontWeight="900" fontFamil
          CASH
        </text>
      </svg>
    );
  }

  return (
    <img
      src="/wallets/vodafone-cash.png"
      alt="d Hbö'd Hdb Cbv4 - Vodafone Cash"
      width={size}
      height={size}
      className={`${className} object-contain select-none drop-shadow-md`}
      loading="eager"
      decoding="async"
      onError={() => setHasError(true)}
    />
  );
}

/**
 * 8b. Official Orange Cash Icon
 * Uses official transparent brand logo provided by user (/wallets/orange-cash.png)
 */
export function OrangeCashIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  const [hasError, setHasError] = React.useState(false);

  if (hasError) {
    return (
      <svg
        viewBox="0 0 100 100"
        width={size}
        height={size}
        className={`${className} select-none drop-shadow-md`}
        fill="none"
        xmlns="http://www.w3.org/2000/svg"
      >
        <defs>
          <linearGradient id="orange_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse">
            <stop stopColor="#FF7900" />
            <stop offset="1" stopColor="#E05B00" />
          </linearGradient>
        </defs>
        <rect width="100" height="100" rx="22" fill="url(#orange_grad)" />
        <text x="50" y="46" textAnchor="middle" fill="white" fontSize="15" fontWeight="900" fontFamily="s
          orange
        </text>
        <rect x="22" y="68" width="56" height="18" rx="9" fill="#000000" />
        <text x="50" y="81" textAnchor="middle" fill="#FF7900" fontSize="11" fontWeight="900" fontFamily=
          CASH
```

FILE (cont.): src/components/BrandIcons.tsx

```
        </text>
      </svg>
    );
  }

  return (
    <img
      src="/wallets/orange-cash.png"
      alt="b6Hc FbÂ Cbv4 - Orange Cash"
      width={size}
      height={size}
      className={`${className} object-contain select-none drop-shadow-md`}
      loading="eager"
      decoding="async"
      onError={() => setHasError(true)}
    />
  );
}

/**
 * 8c. Official Etisalat Cash (e& eg d6'cB' –6öà
 * Uses official transparent brand logo provided by user (/wallets/etisalat-cash.png)
 */
export function EtisalatCashIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  const [hasError, setHasError] = React.useState(false);

  if (hasError) {
    return (
      <svg
        viewBox="0 0 100 100"
        width={size}
        height={size}
        className={`${className} select-none drop-shadow-md`}
        fill="none"
        xmlns="http://www.w3.org/2000/svg"
      >
        <defs>
          <linearGradient id="eti_bg" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse">
            <stop stopColor="#121D13" />
            <stop offset="1" stopColor="#081009" />
          </linearGradient>
          <linearGradient id="eti_green_grad" x1="0" y1="0" x2="100" y2="100" gradientUnits="userSpaceOnU
            <stop stopColor="#8CC63F" />
            <stop offset="1" stopColor="#6BA524" />
          </linearGradient>
        </defs>
        <rect width="100" height="100" rx="22" fill="url(#eti_bg)" stroke="#719E19" strokeWidth="2" />
        <text x="50" y="50" textAnchor="middle" fill="#A3E635" fontSize="13" fontWeight="800" fontFamily=
          e& eg
        </text>
        <rect x="22" y="70" width="56" height="18" rx="9" fill="url(#eti_green_grad)" />
        <text x="50" y="83" textAnchor="middle" fill="#000000" fontSize="11" fontWeight="900" fontFamily=
          d6'c@
        </text>
      </svg>
    );
  }

  return (
    <img
      src="/wallets/etisalat-cash.png"
      alt="bv*cV'dF'b¢ Cbv4 - Etisalat Cash"
      width={size}
      height={size}
      className={`${className} object-contain select-none drop-shadow-md`}
      loading="eager"
      decoding="async"
      onError={() => setHasError(true)}
```

FILE (cont.): src/components/BrandIcons.tsx

```
    />
  );
}

/**
 * 8d. Official WE Pay (Telecom Egypt) Icon
 * Uses official transparent brand logo provided by user (/wallets/we-pay.png)
 */
export function WePayIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  const [hasError, setHasError] = React.useState(false);

  if (hasError) {
    return (
      <svg
        viewBox="0 0 100 100"
        width={size}
        height={size}
        className={`${className} select-none drop-shadow-md`}
        fill="none"
        xmlns="http://www.w3.org/2000/svg"
      >
        <defs>
          <linearGradient id="we_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUse">
            <stop stopColor="#662D91" />
            <stop offset="1" stopColor="#431868" />
          </linearGradient>
        </defs>
        <rect width="100" height="100" rx="22" fill="url(#we_grad)" />
        <text x="50" y="48" textAnchor="middle" fill="white" fontSize="16" fontWeight="900" fontFamily="s
          we
        </text>
        <rect x="24" y="70" width="52" height="18" rx="9" fill="#FACC15" />
        <text x="50" y="83" textAnchor="middle" fill="#431868" fontSize="11" fontWeight="900" fontFamily=
          PAY
        </text>
      </svg>
    );
  }

  return (
    <img
      src="/wallets/we-pay.png"
      alt="d†J b†'d¢ Ò tR   ’
      width={size}
      height={size}
      className={`${className} object-contain select-none drop-shadow-md`}
      loading="eager"
      decoding="async"
      onError={() => setHasError(true)}
    />
  );
}

/**
 * 8e. General Smart Wallet Squircle Icon
 */
export function WalletCashIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="wallet_squircle_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceO
```

FILE (cont.): src/components/BrandIcons.tsx

```tsx
          <stop stopColor="#EA1D25" />
          <stop offset="1" stopColor="#B30D14" />
        </linearGradient>
        <linearGradient id="wallet_gold_crest" x1="0" y1="0" x2="30" y2="30" gradientUnits="userSpaceOnUs
          <stop stopColor="#FDE047" />
          <stop offset="1" stopColor="#CA8A04" />
        </linearGradient>
      </defs>
      {/* Squircle Base */}
      <rect width="100" height="100" rx="22" fill="url(#wallet_squircle_grad)" />
      {/* Wallet Body */}
      <rect x="20" y="30" width="60" height="42" rx="8" fill="white" />
      {/* Inner Pocket Flap */}
      <path d="M58 41C58 37.7 60.7 35 64 35H80V67H64C60.7 67 58 64.3 58 61V41Z" fill="url(#wallet_gold_cr
      {/* Gold Coin / Currency Lock */}
      <circle cx="69" cy="51" r="4.5" fill="#B30D14" />
      <circle cx="69" cy="51" r="2.5" fill="#FDE047" />
      {/* Wallet subtle waveform bars */}
      <rect x="27" y="42" width="18" height="3" rx="1.5" fill="#E2E8F0" />
      <rect x="27" y="49" width="24" height="3" rx="1.5" fill="#E2E8F0" />
      <rect x="27" y="56" width="14" height="3" rx="1.5" fill="#E2E8F0" />
    </svg>
  );
}

/**
 * Smart Wallet Provider Icon Selector
 * Directly renders the official brand logo according to the wallet operator
 */
export function WalletProviderIcon({
  provider,
  className = 'w-6 h-6',
  size,
}: {
  provider?: 'vodafone' | 'orange' | 'etisalat' | 'we' | 'generic';
  className?: string;
  size?: number;
}) {
  switch (provider) {
    case 'vodafone':
      return <VodafoneCashIcon className={className} size={size} />;
    case 'orange':
      return <OrangeCashIcon className={className} size={size} />;
    case 'etisalat':
      return <EtisalatCashIcon className={className} size={size} />;
    case 'we':
      return <WePayIcon className={className} size={size} />;
    default:
      return <WalletCashIcon className={className} size={size} />;
  }
}

/**
 * 9. Luxury Bank Account Squircle Icon (24K Gold & Obsidian Pillars)
 */
export function BankAccountIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="bank_obsidian_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnU
          <stop stopColor="#1E2330" />
```

FILE (cont.): src/components/BrandIcons.tsx

```
          <stop offset="1" stopColor="#0B0E14" />
        </linearGradient>
        <linearGradient id="bank_gold_grad" x1="0" y1="0" x2="100" y2="100" gradientUnits="userSpaceOnUse
          <stop stopColor="#FDE047" />
          <stop offset="0.5" stopColor="#EAB308" />
          <stop offset="1" stopColor="#CA8A04" />
        </linearGradient>
      </defs>
      {/* Obsidian Squircle with Gold Border */}
      <rect width="100" height="100" rx="22" fill="url(#bank_obsidian_grad)" stroke="url(#bank_gold_grad)
      {/* Classical Temple Pediment / Roof */}
      <path d="M50 22L22 36H78L50 22Z" fill="url(#bank_gold_grad)" />
      {/* Architrave */}
      <rect x="22" y="38" width="56" height="4" rx="1" fill="#FEF08A" />
      {/* 4 Majestic Pillars */}
      <rect x="27" y="45" width="7" height="24" rx="2" fill="#F8FAFC" />
      <rect x="39" y="45" width="7" height="24" rx="2" fill="#F8FAFC" />
      <rect x="54" y="45" width="7" height="24" rx="2" fill="#F8FAFC" />
      <rect x="66" y="45" width="7" height="24" rx="2" fill="#F8FAFC" />
      {/* Base Steps */}
      <rect x="20" y="71" width="60" height="4" rx="1" fill="#FEF08A" />
      <rect x="16" y="77" width="68" height="5" rx="1.5" fill="url(#bank_gold_grad)" />
    </svg>
  );
}

/**
 * 10. Website / Web Domain Squircle Icon
 */
export function WebsiteGlobeIcon({ className = 'w-6 h-6', size }: BrandIconProps) {
  return (
    <svg
      viewBox="0 0 100 100"
      width={size}
      height={size}
      className={`${className} select-none drop-shadow-sm`}
      fill="none"
      xmlns="http://www.w3.org/2000/svg"
    >
      <defs>
        <linearGradient id="web_squircle_grad" x1="0" y1="0" x2="0" y2="100" gradientUnits="userSpaceOnUs
          <stop stopColor="#2563EB" />
          <stop offset="1" stopColor="#1D4ED8" />
        </linearGradient>
        <linearGradient id="web_glass_sheen" x1="0" y1="0" x2="100" y2="50" gradientUnits="userSpaceOnUse
          <stop stopColor="white" stopOpacity="0.25" />
          <stop offset="1" stopColor="white" stopOpacity="0" />
        </linearGradient>
      </defs>
      {/* Deep Royal Sapphire Squircle */}
      <rect width="100" height="100" rx="22" fill="url(#web_squircle_grad)" />
      <path d="M0 22C0 9.85 9.85 0 22 0h56c12.15 0 22 9.85 22 22v12C68 38 32 38 0 32V22z" fill="url(#web_
      {/* Globe Wireframe */}
      <circle cx="50" cy="50" r="26" stroke="white" strokeWidth="4" />
      <ellipse cx="50" cy="50" rx="13" ry="26" stroke="white" strokeWidth="3.5" />
      <line x1="24" y1="50" x2="76" y2="50" stroke="white" strokeWidth="3.5" />
      <line x1="30" y1="36" x2="70" y2="36" stroke="white" strokeWidth="2.5" strokeDasharray="3 2" />
      <line x1="30" y1="64" x2="70" y2="64" stroke="white" strokeWidth="2.5" strokeDasharray="3 2" />
    </svg>
  );
}

/**
 * Universal Brand Icon Dispatcher
 */
export function PlatformBrandIcon({
  type,
  className = 'w-6 h-6',
```

FILE (cont.): src/components/BrandIcons.tsx

```tsx
  size,
  targetUrl,
  walletProvider,
}: {
  type: AppType;
  className?: string;
  size?: number;
  targetUrl?: string;
  walletProvider?: 'vodafone' | 'orange' | 'etisalat' | 'we' | 'generic';
}) {
  switch (type) {
    case 'whatsapp':
      return <WhatsAppIcon className={className} size={size} />;
    case 'instapay':
      return <InstaPayIcon className={className} size={size} />;
    case 'instagram':
      return <InstagramIcon className={className} size={size} />;
    case 'facebook':
      return <FacebookIcon className={className} size={size} />;
    case 'tiktok':
      return <TikTokIcon className={className} size={size} />;
    case 'telegram':
      return <TelegramIcon className={className} size={size} />;
    case 'wallet': {
      let prov = walletProvider;
      if (!prov && targetUrl) {
        const clean = targetUrl.replace(/[^\d]/g, '');
        if (clean.includes('010') || targetUrl.startsWith('010') || clean.startsWith('10')) prov = 'vodaf
        else if (clean.includes('012') || targetUrl.startsWith('012') || clean.startsWith('12')) prov = '
        else if (clean.includes('011') || targetUrl.startsWith('011') || clean.startsWith('11')) prov = '
        else if (clean.includes('015') || targetUrl.startsWith('015') || clean.startsWith('15')) prov = '
      }
      return <WalletProviderIcon provider={prov} className={className} size={size} />;
    }
    case 'bank':
      return <BankAccountIcon className={className} size={size} />;
    case 'phone':
      return <PhoneCallIcon className={className} size={size} />;
    case 'website':
    default:
      return <WebsiteGlobeIcon className={className} size={size} />;
  }
}

```

FILE: src/components/BulkGenerateModal.tsx 389 lines | 18.1 KB

```tsx
import { useState } from 'react';
import { Sparkles, Download, CheckCircle2, QrCode as QrIcon, Loader2, X, Hash } from 'lucide-react';
import { generateBulkQrCodes, generateQrDataUrl } from '../lib/qrService';
import { QrCodeRecord } from '../types/qr';

interface BulkGenerateModalProps {
  isOpen: boolean;
  onClose: () => void;
  onGenerated: (codes: QrCodeRecord[]) => void;
  domainUrl: string;
}

export function BulkGenerateModal({ isOpen, onClose, onGenerated, domainUrl }: BulkGenerateModalProps) {
  // Direct editable number input (defaults to 10 or empty for easy typing)
  const [countInput, setCountInput] = useState<string>('10');
  const [monthsInput, setMonthsInput] = useState<string>('1');
  const [isPermanent, setIsPermanent] = useState<boolean>(false);
  const [loading, setLoading] = useState(false);
  const [errorMsg, setErrorMsg] = useState<string | null>(null);
  const [generatedCodes, setGeneratedCodes] = useState<Array<{ record: QrCodeRecord; qrDataUrl: string }>
  const [completed, setCompleted] = useState(false);

  if (!isOpen) return null;

  const parsedCount = parseInt(countInput, 10);
  const parsedMonths = isPermanent ? 0 : parseInt(monthsInput, 10);

  const handleGenerate = async () => {
    if (isNaN(parsedCount) || parsedCount < 1) {
      setErrorMsg('d¦1bÆI d6*bv(b’ 9bö/ cV-d¦- dFDb6Cd†'bò #d6(c  Edb 5d 1.');
      return;
    }

    if (parsedCount > 500) {
      setErrorMsg('bvDbÖ/ bvDb6BcVI dFDb¦HdFJbò Ad¢ 'dF/d 9b’ 'dFHbv-bö) dvH 500 d6Hbò DcfEbvF d6Abv!b’ 'dF3d¦1d 1 d
      return;
    }

    if (!isPermanent && (isNaN(parsedMonths) || parsedMonths < 1)) {
      setErrorMsg('d¦1bÆI d6*bv(b’ 9bö/ cFGd†1 cV-d¦- b6Cb†1 dVF cVAc   b6H bv.b¦Jbv1 "bö'bfE".');
      return;
    }

    setLoading(true);
    setErrorMsg(null);

    try {
      const durationMonths = isPermanent ? 0 : Math.max(1, parsedMonths);
      const records = await generateBulkQrCodes(parsedCount, durationMonths);
      const withDataUrls = await Promise.all(
        records.map(async (record) => {
          const fullScanUrl = `${domainUrl}/q/${record.id}`;
          const qrDataUrl = await generateQrDataUrl(fullScanUrl, 600);
          return { record, qrDataUrl };
        })
      );
      setGeneratedCodes(withDataUrls);
      setCompleted(true);
      onGenerated(records);
    } catch (e) {
      console.error('Bulk generation error:', e);
      setErrorMsg('bÖ/b² .cv# b6+df'b  *d†Dd¦/ bvDb6Cd†'bòâr”°
    } finally {
      setLoading(false);
    }
  };

  const handleDownloadSingle = (dataUrl: string, id: string) => {
```

FILE (cont.): src/components/BulkGenerateModal.tsx

```
    const link = document.createElement('a');
    link.href = dataUrl;
    link.download = `QR_${id}.png`;
    link.click();
  };

  const handleDownloadAll = () => {
    generatedCodes.forEach((item, idx) => {
      setTimeout(() => {
        handleDownloadSingle(item.qrDataUrl, item.record.id);
      }, idx * 120);
    });
  };

  const reset = () => {
    setGeneratedCodes([]);
    setCompleted(false);
    setErrorMsg(null);
    onClose();
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/85 backdrop-blur-md
      <div className="relative w-full max-w-2xl bg-[#0e0e12] rounded-3xl shadow-[0_0_50px_rgba(212,175,55
        {/* Ambient Gold Glow */}
        <div className="absolute -top-12 -right-12 w-32 h-32 bg-amber-500/10 rounded-full blur-2xl pointe
        <div className="absolute -bottom-12 -left-12 w-32 h-32 bg-yellow-500/10 rounded-full blur-2xl poi

        {/* Header */}
        <div className="flex items-center justify-between px-6 py-4 border-b border-amber-500/20 bg-black
          <div className="flex items-center gap-3">
            <div className="w-10 h-10 rounded-2xl bg-gradient-to-tr from-amber-400 to-yellow-500 text-bla
              <QrIcon className="w-5 h-5 text-black" />
            </div>
            <div>
              <h2 className="text-lg font-black text-transparent bg-clip-text bg-gradient-to-r from-amber
                b¦HdFJbò #d6Hbv/ bvDd   " (bvDc–/bò 'dFEcvDd†(
              </h2>
              <p className="text-xs text-slate-400">bvCb¦( b6J c–/bò *c :b, Ad¢ %df4bv&dr /d 9b’ Hbv-bö) dV9 dV9c Qd
            </div>
          </div>
          <button
            onClick={reset}
            className="p-2 text-slate-400 hover:text-white hover:bg-white/10 rounded-xl transition"
          >
            <X className="w-5 h-5" />
          </button>
        </div>

        {/* Content */}
        <div className="p-6 overflow-y-auto space-y-6">
          {!completed ? (
            <div className="space-y-6">
              {/* Direct Count Input Box (As Requested by User) */}
              <div className="p-6 bg-gradient-to-br from-[#16161c] via-[#121216] to-[#0e0e12] border bord
                <div className="flex items-center justify-between">
                  <label className="text-sm font-black text-amber-200/90 flex items-center gap-2">
                    <Hash className="w-5 h-5 text-amber-400" />
                    bvCb¦( c–/bò 'dF1dVHc" 'dF*d¢ *c Jbò *d†Dd¦/dv' dV(bv4c ):
                  </label>
                  <span className="text-[11px] font-black text-amber-300 bg-amber-400/15 border border-am
                    bÖBdB Cb¦'b†) bÖ1
                  </span>
                </div>

                <div className="relative flex items-center">
                  <input
                    type="number"
```

FILE (cont.): src/components/BulkGenerateModal.tsx

```
                    min="1"
                    max="500"
                    value={countInput}
                    onChange={(e) => {
                      setCountInput(e.target.value);
                      setErrorMsg(null);
                    }}
                    placeholder="bvCb¦( bvDc–/bò Gdf' dV+dF'd³¢  R
                    className="w-full text-center text-3xl font-black text-amber-400 bg-black/60 border-2
                    autoFocus
                  />
                  <span className="absolute left-6 text-sm font-bold text-slate-500 pointer-events-none">
                    d6Hbò
                  </span>
                </div>

                {/* Quick Add Buttons for Convenience */}
                <div className="flex items-center justify-between pt-1">
                  <span className="text-xs text-slate-400 font-semibold">bV6bvAb’ 3c Jc–) dFDc–/bó£Â÷7  ãà
                  <div className="flex items-center gap-1.5 flex-wrap">
                    {[1, 5, 10, 20, 50, 100].map((num) => (
                      <button
                        key={num}
                        type="button"
                        onClick={() => setCountInput(num.toString())}
                        className="px-3 py-1.5 text-xs font-bold bg-black/40 hover:bg-amber-400 hover:tex
                      >
                        {num}
                      </button>
                    ))}
                  </div>
                </div>
              </div>

              {/* Subscription Duration Selector with Free Typing Number Input */}
              <div className="space-y-3 p-4 bg-black/40 border-2 border-amber-500/25 rounded-2xl">
                <div className="flex items-center justify-between">
                  <label className="text-xs font-bold text-amber-200 flex items-center gap-2">
                    <Sparkles className="w-4 h-4 text-amber-400" />
                    <span>dV/b’ *d 9d¦D bvDc Ec" †CdR 4dv1):</span>
                  </label>
                  <span className="text-[11px] font-black text-amber-300 bg-amber-400/15 border border-am
                    bÖBdB Cb¦'b†) bÖ1 dFDcFGd†1
                  </span>
                </div>

                {/* Free Typing Input Box */}
                <div className="relative flex items-center">
                  <input
                    type="number"
                    min="1"
                    max="120"
                    value={isPermanent ? '' : monthsInput}
                    disabled={isPermanent}
                    onChange={(e) => {
                      setIsPermanent(false);
                      setMonthsInput(e.target.value);
                      setErrorMsg(null);
                    }}
                    placeholder={isPermanent ? 'b¦E cf(cvG: bö'bfE / c¦Jc  EbÖ/d†/' : 'bvCb¦( c–/bò 'dF4dvHc  Gdf' d
                    className={`w-full text-center text-3xl font-black rounded-2xl py-3.5 px-6 shadow-inn
                      isPermanent
                        ? 'bg-cyan-950/40 text-cyan-300 border-cyan-500/40 cursor-not-allowed'
                        : 'text-amber-400 bg-black/60 border-amber-500/30 focus:border-amber-400 focus:ri
                    }`}
                  />
                  <span className="absolute left-6 text-sm font-bold text-slate-400 pointer-events-none">
                    {isPermanent ? ''& bö'bfE' : 'cFGc  *d 9d¦D'}
```

FILE (cont.): src/components/BulkGenerateModal.tsx

```
                  </span>
                </div>

                {/* Quick Add Buttons for Duration */}
                <div className="flex flex-col sm:flex-row items-start sm:items-center justify-between gap
                  <span className="text-xs text-slate-400 font-semibold">b¦-böJbò 3c Jc’ DdF4dv1:</span>
                  <div className="flex items-center gap-1.5 flex-wrap">
                    {[
                      { label: '1 cFGc rÂ f Ã¢ s r ÒÀ
                      { label: '2 cFGc rÂ f Ã¢ s"r ÒÀ
                      { label: '3 cFGd†1', val: '3' },
                      { label: '6 cFGd†1', val: '6' },
                      { label: '12 cFGc  †3df))', val: '12' },
                    ].map((item) => (
                      <button
                        key={item.val}
                        type="button"
                        onClick={() => {
                          setIsPermanent(false);
                          setMonthsInput(item.val);
                          setErrorMsg(null);
                        }}
                        className={`px-2.5 py-1.5 text-xs font-bold rounded-xl transition shadow-inner bo
                          !isPermanent && monthsInput === item.val
                            ? 'bg-amber-400 text-black border-amber-300 shadow-amber-400/20'
                            : 'bg-black/40 hover:bg-amber-400/20 text-amber-200 border-amber-500/25'
                        }`}
                      >
                        {item.label}
                      </button>
                    ))}

                    {/* Permanent Option */}
                    <button
                      type="button"
                      onClick={() => {
                        setIsPermanent(true);
                        setErrorMsg(null);
                      }}
                      className={`px-3 py-1.5 text-xs font-bold rounded-xl transition shadow-inner border
                        isPermanent
                          ? 'bg-cyan-500 text-black border-cyan-300 font-black'
                          : 'bg-cyan-500/10 hover:bg-cyan-500/20 text-cyan-300 border-cyan-500/30'
                      }`}
                    >
                      bö'bfE (b†/d†F bvFb¦Gbv!)
                    </button>
                  </div>
                </div>

                <div className="p-2.5 bg-black/50 rounded-xl border border-white/5 flex items-center just
                  <span className="text-slate-400 font-medium">bvDdf*d¦,b’ (c–/ bvDb¦HdFJbó£Â÷7  ãà
                  <span className="font-bold text-amber-300">
                    {isPermanent ? (
                      <span className="text-cyan-300">d¦9dVD b†'c6*dV1bv1 b†/d†F bvFb¦Gbv! cVDbv-d¦) '&</span>
                    ) : (
                      <span>
                        c6Jc–EdB DdV/b’ Ç7G&öæsç¶ÖöçF‡4–ç WB ÇÂ  ÓÂ÷7G&öæsâ 4dv1 (d¦Fb¦Gd¢ Ad¢ °
                          new Date(Date.now() + (parseInt(monthsInput || '1', 10) || 1) * 30 * 24 * 60 *
                            year: 'numeric',
                            month: 'long',
                            day: 'numeric',
                          })
                        })
                      </span>
                    )}
                  </span>
                </div>
```

FILE (cont.): src/components/BulkGenerateModal.tsx

```
            </div>

            {errorMsg && (
              <div className="p-3.5 bg-rose-500/20 border border-rose-500/40 rounded-2xl text-xs font-b
                {errorMsg}
              </div>
            )}

            {/* Info guidelines */}
            <div className="bg-[#121216] border border-amber-500/20 rounded-2xl p-4 text-xs text-slate-
              <p className="font-bold text-amber-300 flex items-center gap-1.5">
                <Sparkles className="w-4 h-4 text-amber-400" />
                d&Hbv9bò 'dF*d†Dd¦/ bvDb¦Dd&'bfJ:
              </p>
              <p>• c6Jd&HdR 'dFFc†'dR (bVFcF'b  Ç7G&öæsç¶—4æ â‡  '6VD6÷VçB’ ÇÂ   '6VD6÷VçB Â   ò yrr ¢   '6VD6÷P
              <p>• bÆEd¦9 bvDb6Cd†'bò *dö-d 8 d Hc JbvK d J d&'c–/b’ 'dF(d¦'df'b¢ 'dFEc Cc&Jb’ Hb¦Cd†F bÆ'dv2b’ Dd
              <p>• bvDc 'b†7 bvDb¶'b†* bö'bæD d6D d6Hbò Gdƒ¢ Ç7  â 6Æ 74æ ÖSÒ&föçBÖÖöæò FW‡BÖ Ö&W"ÓC   föçBÖ&öÆB" (
            </div>
          </div>
        ) : (
          <div className="space-y-6">
            <div className="flex flex-col sm:flex-row items-center justify-between gap-4 bg-amber-500/1
              <div className="flex items-center gap-3">
                <CheckCircle2 className="w-7 h-7 text-amber-400 flex-shrink-0" />
                <div>
                  <h3 className="font-black text-sm text-amber-300">b¦E b¦HdFJbò ¶vVæW& FVD6öFW2æÆVæwF‡Ò Cd€
                  <p className="text-xs text-slate-300">b¦E bÖAc, 'dFEc–1d 'b¢ 'dFAc Jbö) d J d&'c–/b’ 'dF(d¦'df'b
                </div>
              </div>
              <button
                onClick={handleDownloadAll}
                className="w-full sm:w-auto flex items-center justify-center gap-2 px-4 py-2.5 bg-gradi
              >
                <Download className="w-4 h-4 text-black" />
                b¦-dVJdB 'dFCdB /d 9b’ Hbv-bö) (PNG)
              </button>
            </div>

            {/* Grid of Generated QR Codes */}
            <div className="grid grid-cols-2 sm:grid-cols-3 gap-3 max-h-[360px] overflow-y-auto p-1">
              {generatedCodes.map(({ record, qrDataUrl }, idx) => (
                <div
                  key={record.id}
                  className="p-3 bg-[#141418] rounded-2xl border border-amber-500/20 shadow-md hover:bo
                >
                  <div className="relative p-1.5 bg-white border border-amber-500/30 rounded-xl shadow-
                    <img
                      src={qrDataUrl}
                      alt={`QR ${record.id}`}
                      className="w-28 h-28 object-contain"
                    />
                    <span className="absolute top-1 right-1 text-[10px] font-mono bg-black/80 text-ambe
                      #{idx + 1}
                    </span>
                  </div>
                  <span className="mt-2 text-xs font-mono font-black text-amber-300 tracking-wider bg-b
                    {record.id}
                  </span>
                  <button
                    onClick={() => handleDownloadSingle(qrDataUrl, record.id)}
                    className="mt-2 w-full flex items-center justify-center gap-1 py-1.5 px-2 bg-white/
                  >
                    <Download className="w-3.5 h-3.5" />
                    b¦Fc&JdB 'dFCd†/
                  </button>
                </div>
              ))}
            </div>
```

FILE (cont.): src/components/BulkGenerateModal.tsx

```
            </div>
          )}
        </div>

        {/* Footer */}
        <div className="flex items-center justify-end gap-3 px-6 py-4 border-t border-amber-500/20 bg-bla
          {!completed ? (
            <>
              <button
                type="button"
                onClick={reset}
                className="px-4 py-2.5 text-xs font-bold text-slate-400 hover:text-white rounded-xl trans
              >
                bVDc¦'b
              </button>
              <button
                type="button"
                onClick={handleGenerate}
                disabled={loading || !countInput || parsedCount < 1}
                className="flex items-center gap-2 px-6 py-3 bg-gradient-to-r from-amber-400 via-yellow-4
              >
                {loading ? (
                  <>
                    <Loader2 className="w-4 h-4 animate-spin text-black" />
                    <span>bÆ'c J bvDb¦HdFJbòââãÂ÷7  ãà
                  </>
                ) : (
                  <>
                    <Sparkles className="w-4 h-4 text-black" />
                    <span>b¦HdFJbò ·  '6VD6÷VçB ÇÂ rwÒ Cd†/ bvDb&F</span>
                  </>
                )}
              </button>
            </>
          ) : (
            <button
              type="button"
              onClick={reset}
              className="px-6 py-3 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 text-black
            >
              b¦E d†'dF9d†/b’ DdFHbÖ) bvDb¦-d6E
            </button>
          )}
        </div>
      </div>
    </div>
  );
}

```

FILE: src/components/DeveloperSettingsModal.tsx 252 lines | 11.1 KB

```tsx
import React, { useState, useEffect } from 'react';
import { X, Check, ExternalLink, Sparkles, Phone, MessageSquare, Link, Globe } from 'lucide-react';
import { PlatformSettings } from '../types/qr';

interface DeveloperSettingsModalProps {
  isOpen: boolean;
  onClose: () => void;
  settings: PlatformSettings;
  onSave: (updated: PlatformSettings) => Promise<void>;
}

export function DeveloperSettingsModal({
  isOpen,
  onClose,
  settings,
  onSave,
}: DeveloperSettingsModalProps) {
  const [phone, setPhone] = useState(settings.developer_whatsapp || '01550523365');
  const [contactUrl, setContactUrl] = useState(settings.developer_contact_url || 'https://wa.me/201550523
  const [title, setTitle] = useState(settings.developer_title || 'b¦Hbv5dB Ec’ 'dFEcvHc r“°
  const [message, setMessage] = useState(settings.support_message || 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvB
  const [publicDomain, setPublicDomain] = useState(settings.public_domain_url || 'https://smart-card-inky
  const [isSaving, setIsSaving] = useState(false);
  const [success, setSuccess] = useState(false);

  useEffect(() => {
    if (isOpen) {
      setPhone(settings.developer_whatsapp || '01550523365');
      setContactUrl(settings.developer_contact_url || 'https://wa.me/201550523365');
      setTitle(settings.developer_title || 'b¦Hbv5dB Ec’ 'dFEcvHc r“°
      setMessage(settings.support_message || 'dV1bÖ(bvK`Â #d†/ bvDb¦Hbv5dB (bæ5d†5 bvDb†7bvBb’ 'dF0d6Jb’r“°
      setPublicDomain(settings.public_domain_url || 'https://smart-card-inky.vercel.app');
      setSuccess(false);
    }
  }, [isOpen, settings]);

  if (!isOpen) return null;

  // Auto update direct contact URL when phone changes if using default wa.me scheme
  const handlePhoneChange = (val: string) => {
    setPhone(val);
    const clean = val.replace(/[^\d]/g, '');
    if (clean) {
      const num = clean.startsWith('01') ? '2' + clean : clean;
      setContactUrl(`https://wa.me/${num}`);
    }
  };

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setIsSaving(true);
    try {
      let finalUrl = contactUrl.trim();
      let cleanPhone = phone.trim();

      if (!finalUrl && cleanPhone) {
        let num = cleanPhone.replace(/[^\d]/g, '');
        if (num.startsWith('01')) num = '2' + num;
        finalUrl = `https://wa.me/${num}`;
      }

      let cleanDomain = publicDomain.trim();
      if (cleanDomain.endsWith('/')) {
        cleanDomain = cleanDomain.slice(0, -1);
      }

      await onSave({
        developer_whatsapp: cleanPhone || '01550523365',
```

FILE (cont.): src/components/DeveloperSettingsModal.tsx

```
        developer_contact_url: finalUrl || 'https://wa.me/201550523365',
        developer_title: title.trim() || 'b¦Hbv5dB Ec’ 'dFEcvHc rÀ
        support_message: message.trim(),
        public_domain_url: cleanDomain,
      });
      setSuccess(true);
      setTimeout(() => {
        setSuccess(false);
        onClose();
      }, 1400);
    } catch (err) {
      console.error(err);
    } finally {
      setIsSaving(false);
    }
  };

  const handleTestLink = () => {
    let url = contactUrl.trim();
    if (!url && phone.trim()) {
      let num = phone.replace(/[^\d]/g, '');
      if (num.startsWith('01')) num = '2' + num;
      url = `https://wa.me/${num}`;
    }
    if (!url) url = 'https://wa.me/201550523365';
    window.open(url, '_blank');
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/80 backdrop-blur-md
      <div className="w-full max-w-lg bg-[#0e0e12] border border-amber-500/30 rounded-3xl p-6 sm:p-8 shad
        {/* Ambient gold glow */}
        <div className="absolute -top-10 -right-10 w-28 h-28 bg-amber-500/10 rounded-full blur-2xl pointe
        <div className="absolute -bottom-10 -left-10 w-28 h-28 bg-yellow-500/10 rounded-full blur-2xl poi

        {/* Header */}
        <div className="flex items-start justify-between gap-3 border-b border-amber-500/20 pb-4">
          <div className="flex items-center gap-3">
            <div className="w-12 h-12 rounded-2xl bg-gradient-to-br from-amber-400/20 to-yellow-600/10 bo
              <MessageSquare className="w-6 h-6" />
            </div>
            <div>
              <div className="flex items-center gap-2">
                <h3 className="text-base sm:text-lg font-black text-transparent bg-clip-text bg-gradient-
                  bV9bö'bö'b¢ 'dF*d†'cVD dV9 bvDdV7d†1 d†'dF*bÖHd¦D
                </h3>
              </div>
              <p className="text-xs text-slate-400 mt-0.5">
                b¦9böJdB 1bv(cr Hc BdR 'dFHbv*c6'b, 'dF.bv5 b†'dF*bÖHd¦D c–Fbò -böHb² EcFCdF) b6H bÖ0d  'dF1dV2
              </p>
            </div>
          </div>
          <button
            type="button"
            onClick={onClose}
            className="p-1.5 text-slate-400 hover:text-white rounded-xl hover:bg-white/10 transition"
          >
            <X className="w-5 h-5" />
          </button>
        </div>

        {success && (
          <div className="p-3.5 bg-amber-500/20 border border-amber-400/40 rounded-2xl text-xs text-amber
            <Check className="w-4 h-4 text-amber-400 flex-shrink-0" />
            <span>b¦E bÖAc, %c–/bv/bv* bvDb¦Hbv5dB (df,bv-! b¦E bvDb¦-böJb² Ad¢ 'dF3d¦1d 1 d†'dF1d†'b†7 d Hc 'd²ãÂ÷7
          </div>
        )}

```

FILE (cont.): src/components/DeveloperSettingsModal.tsx

```
        {/* Form */}
        <form onSubmit={handleSubmit} className="space-y-4">
          {/* WhatsApp Phone */}
          <div className="space-y-1.5">
            <label className="block text-xs font-bold text-amber-200/90 flex items-center gap-1.5">
              <Phone className="w-3.5 h-3.5 text-amber-400" />
              <span>c BdR Hbv*c6'b, 'dFEcvHc  †'dF#böEdb“£Â÷7  ãà
            </label>
            <input
              type="text"
              value={phone}
              onChange={(e) => handlePhoneChange(e.target.value)}
              placeholder="01550523365"
              className="w-full px-4 py-2.5 bg-black/50 border border-amber-500/20 rounded-xl text-sm tex
              dir="ltr"
              required
            />
            <p className="text-[11px] text-slate-400">
              bvDc BdR 'dF-bvDd¢ 'dFEc–*dV/: <span className="font-mono text-amber-300 font-bold" dir="ltr">015505
            </p>
          </div>

          {/* Custom Link / URL */}
          <div className="space-y-1.5">
            <label className="block text-xs font-bold text-amber-200/90 flex items-center gap-1.5">
              <Link className="w-3.5 h-3.5 text-amber-400" />
              <span>bvDc 'b†7 bvDdV(bv4c  DdF*bÖHd¦D (URL):</span>
            </label>
            <input
              type="text"
              value={contactUrl}
              onChange={(e) => setContactUrl(e.target.value)}
              placeholder="https://wa.me/201550523365"
              className="w-full px-4 py-2.5 bg-black/50 border border-amber-500/20 rounded-xl text-sm tex
              dir="ltr"
              required
            />
            <p className="text-[11px] text-slate-400">
              d¦Ed6Fd2 Cb¦'b†) c 'b†7 d†'b¦3bv( dV(bv4c  #d, #d¢ 1bv(cr Ebæ5cR *d 6dFG dFDb¦-d†JdBà
            </p>
          </div>

          {/* Button Text */}
          <div className="space-y-1.5">
            <label className="block text-xs font-bold text-amber-200/90 flex items-center gap-1.5">
              <Sparkles className="w-3.5 h-3.5 text-amber-400" />
              <span>df5 c&1 bvDb¦Hbv5dB 'dF8bvGc  DdF9dVJdC£Â÷7  ãà
            </label>
            <input
              type="text"
              value={title}
              onChange={(e) => setTitle(e.target.value)}
              placeholder="b¦Hbv5dB Ec’ 'dFEcvHc
              className="w-full px-4 py-2.5 bg-black/50 border border-amber-500/20 rounded-xl text-sm tex
              required
            />
          </div>

          {/* Public Production Domain (For printing & live cards scanning) */}
          <div className="space-y-2 p-4 bg-gradient-to-br from-amber-500/10 via-yellow-500/5 to-transpare
            <div className="flex items-center justify-between">
              <label className="block text-xs font-bold text-amber-300 flex items-center gap-1.5">
                <Globe className="w-4 h-4 text-amber-400" />
                <span>c 'b†7 bvDböHdVJdb 'dF#d†FdF'd¦F dFDdVHd&9 (Public Production Domain):</span>
              </label>
              <span className="text-[10px] font-black text-amber-400 bg-amber-400/20 px-2 py-0.5 rounded-
                dVGdR DdF7b†'c–) d†Gd†'b¦A bvDc–EdF'b
              </span>
```

FILE (cont.): src/components/DeveloperSettingsModal.tsx

```
            </div>
            <input
              type="url"
              value={publicDomain}
              onChange={(e) => setPublicDomain(e.target.value)}
              placeholder="dV+bvD: https://cards.mybrand.com b6H c 'b†7 bvDc6Jc Ac  'dF#d†FdF'd¦F"
              className="w-full px-4 py-2.5 bg-black/70 border border-amber-500/30 rounded-xl text-sm tex
              dir="ltr"
            />
            <p className="text-[11px] text-slate-300 leading-relaxed">
              Ø=Ü¡ <strong>bÖD dV4d6Db’ 'dFEc6- dVF dv'b¦A b&.c £Â÷7G&öæsâ %c ' d&Eb¢ (b¦HdFJbò #d, 7b†'c–) bvDc Ec"
            </p>
          </div>

          {/* Action Buttons */}
          <div className="flex flex-col sm:flex-row items-center gap-2.5 pt-3 border-t border-amber-500/2
            <button
              type="button"
              onClick={handleTestLink}
              className="w-full sm:w-auto px-4 py-2.5 bg-white/5 hover:bg-white/10 text-amber-300 hover:t
            >
              <ExternalLink className="w-4 h-4" />
              bv.b¦(bv1 bvDc 'b†7 d Hc 'd°
            </button>

            <div className="flex items-center gap-2 w-full sm:w-auto sm:mr-auto justify-end">
              <button
                type="button"
                onClick={onClose}
                className="px-4 py-2.5 text-xs font-semibold text-slate-400 hover:text-white"
              >
                bVDc¦'b
              </button>
              <button
                type="submit"
                disabled={isSaving}
                className="px-6 py-2.5 bg-gradient-to-r from-amber-400 via-yellow-400 to-amber-500 hover:
              >
                {isSaving ? 'bÆ'c J bvDbÖAc,ãâår ¢ v-d 8 bvDbV9bö'bö'b¢wÐ
              </button>
            </div>
          </div>
        </form>
      </div>
    </div>
  );
}
```

FILE: src/components/EditQrModal.tsx 1005 lines | 43.6 KB

```tsx
import { useState, useEffect } from 'react';
import {
  Lock,
  Globe,
  ExternalLink,
  Check,
  Save,
  Download,
  QrCode as QrIcon,
  X,
  Smartphone,
  Eye,
  MessageSquare,
  Instagram,
  Facebook,
  CreditCard,
  Phone,
  Send,
  Video,
  Trash2,
  Building2,
  Wallet,
  Copy,
  Info,
  Sparkles,
  RotateCcw,
  Clock,
  Calendar
} from 'lucide-react';
import { adminUpdateQrCode, generateQrDataUrl, resetQrScanCount } from '../lib/qrService';
import {
  processSmartLink,
  encodeBankDetails,
  decodeBankDetails,
  detectWalletInfo,
  isQuickPayUrl,
  formatTikTokTargetUrl,
  formatInstagramTargetUrl,
  formatTelegramTargetUrl,
  formatSnapchatTargetUrl
} from '../lib/deepLinks';
import { AppType, QrCodeRecord, BankDetails } from '../types/qr';
import { PlatformBrandIcon, WalletProviderIcon } from './BrandIcons';

interface EditQrModalProps {
  isOpen: boolean;
  onClose: () => void;
  record: QrCodeRecord | null;
  domainUrl: string;
  onSaved: (updatedRecord: QrCodeRecord) => void;
  onDelete?: (id: string) => void;
}

const EGYPTIAN_BANKS = [
  'bvDb†Fd2 'dF#dvDd¢ 'dFEcV1d¢ „ä$R’rÀ
  'b†Fd2 EcV1 (Banque Misr)',
  'bvDb†Fd2 'dF*bÆ'c J bvDböHdFJ (CIB)',
  'b†Fd2 Bcv1 bvDd†7dfJ (QNB)',
  'b†Fd2 'dFBbvGc ) (Banque du Caire)',
  'b†Fd2 'dF%c6Cdf/c Jb’ „ ÆW„& æ²’rÀ
  'b†Fd2 Ad¦5dB 'dF%c6DbvEd¢rÀ
  'dV5c A b6(d†8b†J bvDbV3dF'dVJ (ADIB)',
  'b†Fd2 'dF(c Cb’ EcV1',
  'bvDb†Fd2 'dF9c (d¢ 'dF#d 1d¦Bd¢ 'dF/d†Dd¢ „  ”"’rÀ
  'b†Fd2 Cc JböJ b6,c Jd6HdB EcV1',
  'b†Fd2 …4$2 EcV1',
  'b†Fd2 "bæ1 / bÖ3bv( böHdFJ'
];
```

FILE (cont.): src/components/EditQrModal.tsx

```
69
70  export const PLATFORM_META: Record<AppType, { labelAr: string; labelEn: string; placeholder: string; hint
71    whatsapp: {
72      labelAr: 'd†'b¦3bv(',
73      labelEn: 'WhatsApp',
74      placeholder: '01012345678 b6H wa.me/2010...',
75      hint: 'b6/bæD c BdR 'dFEd†(bvJdB #d, 1bv(cr EbÖ'bö+b’ Hbv*c6'b,rÀ
76    },
77    instagram: {
78      labelAr: 'bVFc6*c¦1bvE',
79      labelEn: 'Instagram',
80      placeholder: '@username b6H c 'b†7 bvDbÖ3bv( instagram.com/...',
81      hint: 'b6/bæD d¦Hc&1 bvDbÖ3bv( b6H bvDc 'b†7 bvDd6'dVD',
82    },
83    facebook: {
84      labelAr: 'd Jc6(d†C',
85      labelEn: 'Facebook',
86      placeholder: 'facebook.com/yourpage b6H c 'b†7 bvDb†1d†AbvJdB #d, ”BrÀ
87      hint: 'b6/bæD c 'b†7 bvDcVAbÖ) b6H bvDbÖ3bv( c–Dd’ Ad¦3b†Hd2rÀ
88    },
89    telegram: {
90      labelAr: 'b¦JdFJbÆ1bvE',
91      labelEn: 'Telegram',
92      placeholder: 't.me/username b6H @channel',
93      hint: 'b6/bæD d¦Hc&1 bvDb¦Dd¦,c 'dR #d, 1bv(cr 'dFBdf'b’ö'dFEbÖ'bö+b’rÀ
94    },
95    tiktok: {
96      labelAr: 'b¦Jd2 *d†C',
97      labelEn: 'TikTok',
98      placeholder: 'tiktok.com/@username b6H @username',
99      hint: 'b6/bæD c 'b†7 b6H d¦Hc&1 bÖ3bv( b¦Jd2 *d†C',
100   },
101   phone: {
102     labelAr: 'bv*cV'dB Gbv*d J',
103     labelEn: 'Phone Call',
104     placeholder: '01012345678 b6H +2010...',
105     hint: 'b6/bæD c BdR 'dFGbv*d  DdF'b¦5bvD bvDdV(bv4c rÀ
106   },
107   website: {
108     labelAr: 'dVHd&9 d†Jb,rÀ
109     labelEn: 'Website',
110     placeholder: 'https://yourwebsite.com',
111     hint: 'b6/bæD c 'b†7 bvDdVHd&9 bvDbVDd6*c HdfJ bvDdV7dFHb, 'dF*d†,d¦G bVDd¦G',
112   },
113   instapay: {
114     labelAr: 'bVFc6*bv(bvJ',
115     labelEn: 'InstaPay',
116     placeholder: 'https://ipn.eg/S/... (c 'b†7 bvDböAc’ 'dF3c Jc’’rÀ
117     hint: 'bvDcVB c 'b†7 bvDböAc’ 'dF3c Jc’ 'dFEb†'cF1 dVF b¦7b†Jd" %df3b¦'b†'d¢rÀ
118   },
119   wallet: {
120     labelAr: 'dV-d 8b’ Cbv4',
121     labelEn: 'Cash Wallet',
122     placeholder: '010... b6H 012... b6H c 'b†7 böAc’rÀ
123     hint: 'c BdR EbÖAc†) d Hbö'd Hdbö'b¦5bvDbv*/b6Hc FbÂöHd¢ Cbv4',
124   },
125   bank: {
126     labelAr: 'bÖ3bv( b†Fd6J',
127     labelEn: 'Bank Account',
128     placeholder: 'b†JbvFbv* bvDbÖ3bv( bvDb†Fd6J',
129     hint: 'bV/bæ'dB (d¦'df'b¢ 'dF-c6'b, 'dF(dfCd¢ DdF*bÖHd¦D bvDd Hc J',
130   },
131   snapchat: {
132     labelAr: 'c6Fbv( cF'b¢rÀ
133     labelEn: 'Snapchat',
134     placeholder: 'snapchat.com/add/... b6H @username',
135     hint: 'b6/bæD c 'b†7 b6H d¦Hc&1 bÖ3bv( c6Fbv( cF'b¢rÀ
136   },
```

FILE (cont.): src/components/EditQrModal.tsx

```
  other: {
    labelAr: 'c 'b†7 dV.cV5',
    labelEn: 'Custom Link',
    placeholder: 'https://...',
    hint: 'b6/bæD b6J c 'b†7 d†Jb, Ebæ5cR #d, 5d -b’ .bv1bÆJb’rÀ
  },
};

export function EditQrModal({ isOpen, onClose, record, domainUrl, onSaved, onDelete }: EditQrModalProps)
  const [selectedType, setSelectedType] = useState<AppType>('website');
  const [targetUrl, setTargetUrl] = useState('');
  const [label, setLabel] = useState('');
  const [loading, setLoading] = useState(false);
  const [savedSuccess, setSavedSuccess] = useState(false);
  const [qrDataUrl, setQrDataUrl] = useState<string>('');

  // Subscription expiry state
  const [expiresAt, setExpiresAt] = useState<string | null>(null);

  // Bank Specific fields
  const [bankName, setBankName] = useState(EGYPTIAN_BANKS[0]);
  const [accountNumber, setAccountNumber] = useState('');
  const [accountName, setAccountName] = useState('');
  const [iban, setIban] = useState('');
  const [bankNotes, setBankNotes] = useState('');

  // Wallet specific
  const [walletPhone, setWalletPhone] = useState('');
  const [currentScans, setCurrentScans] = useState<number>(record?.total_scans || 0);

  useEffect(() => {
    if (record) {
      const type = record.app_type || 'website';
      setSelectedType(type);
      setLabel(record.label || '');
      setSavedSuccess(false);
      setCurrentScans(record.total_scans || 0);
      setExpiresAt(record.expires_at || null);

      const rawUrl = record.target_url || '';
      setTargetUrl(rawUrl);

      // If bank type, load details
      if (type === 'bank' || rawUrl.startsWith('bank://')) {
        const decoded = decodeBankDetails(rawUrl);
        if (decoded) {
          setBankName(decoded.bankName || EGYPTIAN_BANKS[0]);
          setAccountNumber(decoded.accountNumber || '');
          setAccountName(decoded.accountName || '');
          setIban(decoded.iban || '');
          setBankNotes(decoded.notes || '');
        } else {
          setAccountNumber(rawUrl.replace(/^https?:\/\//, ''));
        }
      } else if (type === 'wallet') {
        let clean = rawUrl;
        if (clean.startsWith('tel:*9*7*')) {
          clean = clean.replace('tel:*9*7*', '').replace('#', '').replace('%23', '');
        }
        setWalletPhone(clean);
      }

      const fullScanUrl = `${domainUrl}/q/${record.id}`;
      generateQrDataUrl(fullScanUrl, 400).then((url) => setQrDataUrl(url));
    }
  }, [record, domainUrl]);

  if (!isOpen || !record) return null;
```

FILE (cont.): src/components/EditQrModal.tsx

```
205
206   const handleResetScans = async () => {
207     if (!record) return;
208     const ok = await resetQrScanCount(record.id, 0);
209     if (ok) {
210       setCurrentScans(0);
211       record.total_scans = 0;
212       onSaved({ ...record, total_scans: 0 });
213     }
214   };
215
216   const handleExtendDays = (days: number) => {
217     const base = (expiresAt && new Date(expiresAt).getTime() > Date.now())
218       ? new Date(expiresAt).getTime()
219       : Date.now();
220     const nextDate = new Date(base + days * 24 * 60 * 60 * 1000).toISOString();
221     setExpiresAt(nextDate);
222   };
223
224   const handleSelectPlatform = (newType: AppType) => {
225     if (newType === selectedType) return;
226
227     setSelectedType(newType);
228
229     // If switching back to the card's originally saved platform, restore its saved values.
230     // If switching to a new/different platform, completely purge and clear all fields clean!
231     if (record && newType === (record.app_type || 'website')) {
232       const origUrl = record.target_url || '';
233       setTargetUrl(origUrl);
234       if (newType === 'bank' || origUrl.startsWith('bank://')) {
235         const decoded = decodeBankDetails(origUrl);
236         if (decoded) {
237           setBankName(decoded.bankName || EGYPTIAN_BANKS[0]);
238           setAccountNumber(decoded.accountNumber || '');
239           setAccountName(decoded.accountName || '');
240           setIban(decoded.iban || '');
241           setBankNotes(decoded.notes || '');
242         } else {
243           setAccountNumber(origUrl.replace(/^https?:\/\//, ''));
244         }
245       } else if (newType === 'wallet') {
246         let clean = origUrl;
247         if (clean.startsWith('tel:*9*7*')) {
248           clean = clean.replace('tel:*9*7*', '').replace('#', '').replace('%23', '');
249         }
250         setWalletPhone(clean);
251       }
252     } else {
253       // Switching to a new/different platform -> PURGE ALL OLD VALUES
254       setTargetUrl('');
255       setWalletPhone('');
256       setAccountNumber('');
257       setAccountName('');
258       setIban('');
259       setBankNotes('');
260     }
261   };
262
263   const handleSave = async (e: React.FormEvent) => {
264     e.preventDefault();
265     setLoading(true);
266     setSavedSuccess(false);
267
268     let finalRawInput = targetUrl.trim();
269
270     // Custom formatting based on selected platform
271     if (selectedType === 'bank') {
272       const bankDetails: BankDetails = {
```

FILE (cont.): src/components/EditQrModal.tsx

```
        bankName,
        accountNumber: accountNumber.trim(),
        accountName: accountName.trim(),
        iban: iban.trim(),
        notes: bankNotes.trim(),
      };
      finalRawInput = encodeBankDetails(bankDetails);
    } else if (selectedType === 'wallet') {
      const cleanInput = walletPhone.trim();
      if (!isQuickPayUrl(cleanInput)) {
        const detected = detectWalletInfo(cleanInput);
        finalRawInput = detected.cleanPhone;
      } else {
        finalRawInput = cleanInput;
      }
    } else if (selectedType === 'instapay') {
      let ipnLink = targetUrl.trim();
      const hasLink = ipnLink.includes('ipn.eg') || ipnLink.startsWith('http://') || ipnLink.startsWith('
      if (!hasLink) {
        alert('b¦7b†Jd" %df3b¦'b†'d¢ Jb¦7dF( d†6c’ 1bv(cr 'dF/d 9 bvDc61d¦9 bvDdV(bv4c  †Eb¶D: https://ipn.eg/S/...)
        setLoading(false);
        return;
      }
      if (ipnLink.startsWith('ipn.eg/')) {
        ipnLink = `https://${ipnLink}`;
      } else if (!ipnLink.startsWith('http://') && !ipnLink.startsWith('https://')) {
        ipnLink = `https://${ipnLink}`;
      }
    } else if (selectedType === 'tiktok') {
      finalRawInput = formatTikTokTargetUrl(targetUrl);
    } else if (selectedType === 'instagram') {
      finalRawInput = formatInstagramTargetUrl(targetUrl);
    } else if (selectedType === 'telegram') {
      finalRawInput = formatTelegramTargetUrl(targetUrl);
    } else if (selectedType === 'snapchat') {
      finalRawInput = formatSnapchatTargetUrl(targetUrl);
    }

    try {
      const result = await adminUpdateQrCode(
        record.id,
        finalRawInput,
        selectedType,
        label.trim(),
        expiresAt
      );
      if (result.success && result.record) {
        setSavedSuccess(true);
        onSaved(result.record);
        setTimeout(() => {
          setSavedSuccess(false);
          onClose();
        }, 1200);
      }
    } catch (err) {
      console.error('Failed to update QR code:', err);
    } finally {
      setLoading(false);
    }
  };

  const handleDownloadQr = () => {
    if (!qrDataUrl) return;
    const link = document.createElement('a');
    link.href = qrDataUrl;
    link.download = `QR_${record.id}.png`;
    link.click();
  };
```

FILE (cont.): src/components/EditQrModal.tsx

```
341
342   // Preview current computed URL
343   let currentPreviewInput = targetUrl.trim();
344   if (selectedType === 'bank') {
345     currentPreviewInput = encodeBankDetails({
346       bankName,
347       accountNumber: accountNumber.trim(),
348       accountName: accountName.trim(),
349       iban: iban.trim(),
350     });
351   } else if (selectedType === 'wallet') {
352     currentPreviewInput = walletPhone.trim();
353   }
354   const currentLinkInfo = processSmartLink(currentPreviewInput, selectedType);
355
356   // Platform Buttons: STRICT SINGLE SELECTION
357   const paymentPlatforms: Array<{ type: AppType; label: string; icon: any; hint: string }> = [
358     { type: 'bank', label: 'bÖ3bv( b†Fd6J c 3dVJ', icon: Building2, hint: 'c–1cb Cbv1b¢ -c6'b, Hb¦-d†JdB Ad†1d¢r ÒÀ
359     { type: 'instapay', label: 'bVFc6*bv(bvJ InstaPay', icon: CreditCard, hint: 'b¦-d†JdB Eb†'cF1 ipn.eg' },
360     { type: 'wallet', label: 'dV-d 8b’ Cbv4 (d Hbö'd Hdbö'b¦5bvDbv*)', icon: Wallet, hint: 'd6Hbò *bÖHd¦D d Hc J d†E
361   ];
362
363   const socialPlatforms: Array<{ type: AppType; label: string; icon: any }> = [
364     { type: 'whatsapp', label: 'd†'b¦3bv(', icon: MessageSquare },
365     { type: 'instagram', label: 'bVFc6*c¦1bvE', icon: Instagram },
366     { type: 'facebook', label: 'd Jc6(d†C', icon: Facebook },
367     { type: 'telegram', label: 'b¦JdFJbÆ1bvE', icon: Send },
368     { type: 'tiktok', label: 'b¦Jd2 *d†C', icon: Video },
369     { type: 'phone', label: 'bv*cV'dB Gbv*d J', icon: Phone },
370     { type: 'website', label: 'dVHd&9 d†Jb,rÂ –6öã¢ vÆö&R ÒÀ
371   ];
372
373   return (
374     <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-4 bg-black/85 backdrop-b
375       <div className="relative w-full max-w-2xl bg-[#0e0e12] rounded-3xl shadow-[0_0_50px_rgba(212,175,55
376         {/* Ambient Gold Glow */}
377         <div className="absolute -top-12 -right-12 w-32 h-32 bg-amber-500/10 rounded-full blur-2xl pointe
378         <div className="absolute -bottom-12 -left-12 w-32 h-32 bg-yellow-500/10 rounded-full blur-2xl poi
379
380         {/* Header */}
381         <div className="flex items-center justify-between px-6 py-4 border-b border-amber-500/20 bg-black
382           <div className="flex items-center gap-3">
383             <div className="w-10 h-10 rounded-2xl bg-gradient-to-tr from-amber-400 to-yellow-500 text-bla
384               <QrIcon className="w-5 h-5 text-black" />
385             </div>
386             <div>
387               <div className="flex items-center gap-2">
388                 <h2 className="text-base sm:text-lg font-black text-transparent bg-clip-text bg-gradient-
389                   b¦9böJdB 'dF1dV2 d†'dFEdf5b’ 'dFEc6*dv/d )
390                 </h2>
391                 <span className={`px-2 py-0.5 text-[10px] font-bold rounded-full ${
392                   record.is_active ? 'bg-emerald-500/20 text-emerald-300 border border-emerald-500/40' :
393                 }`}>
394                   {record.is_active ? 'dVAc–D df4crr ¢ vAd¢ 'df*c†'c  'dF*d 9d¦D'}
395                 </span>
396               </div>
397               <p className="text-xs text-slate-400">bv.b¦1 bvDdVFcV) b6H bvDb†Fd2 'dFEcvDd†( c (cvG b†Gc ' bvDd6Hbò
398             </div>
399           </div>
400           <button
401             onClick={onClose}
402             className="p-2 text-slate-400 hover:text-white hover:bg-white/10 rounded-xl transition"
403           >
404             <X className="w-5 h-5" />
405           </button>
406         </div>
407
408         {/* Form Body */}
```

FILE (cont.): src/components/EditQrModal.tsx

```
        <form onSubmit={handleSave} className="p-6 overflow-y-auto space-y-6">
          {/* Top Info: Immutable ID */}
          <div className="grid grid-cols-1 sm:grid-cols-3 gap-3">
            <div className="sm:col-span-2 space-y-1.5">
              <div className="flex items-center justify-between">
                <label className="text-xs font-bold text-amber-200/90 flex items-center gap-1.5">
                  <Lock className="w-3.5 h-3.5 text-amber-400" />
                  dV9c Qd  'dFCd†/ bvDd 1d¦/ (ID - Primary Key)
                </label>
                <span className="text-[10px] font-bold px-2 py-0.5 bg-amber-400/10 text-amber-300 rounded
                  b¶'b†* d†EbÖEd¢ †EdVFd†9 bvDb¦9böJdB•
                </span>
              </div>
              <div className="relative">
                <input
                  type="text"
                  value={record.id}
                  readOnly
                  disabled
                  className="w-full px-3.5 py-2.5 bg-black/60 border border-amber-500/20 rounded-xl font-
                  dir="ltr"
                />
                <Lock className="w-4 h-4 text-amber-400/50 absolute left-3 top-3" />
              </div>
            </div>

            <div className="space-y-1.5">
              <div className="flex items-center justify-between">
                <label className="text-xs font-bold text-amber-200/90">dV1bv* bvDdV3bÒ HbvDc&Jbv1bv*</label>
                {record.is_active && currentScans > 0 && (
                  <button
                    type="button"
                    onClick={handleResetScans}
                    className="text-[11px] text-amber-400 hover:text-amber-300 underline font-bold flex i
                    title="b¦5d Jc  'dF9bö'bò HbvDb†/b  Edb
                  >
                    <RotateCcw className="w-3 h-3 text-amber-400" />
                    <span>b¦5d Jc  'dF9bö'bóÂ÷7  ãà
                  </button>
                )}
              </div>
              <div className="px-3.5 py-2.5 bg-black/60 border border-amber-500/20 rounded-xl text-sm fon
                <span>{currentScans}</span>
                <span className="text-xs text-slate-400 font-normal">
                  {record.is_active ? 'c&Jbv1b’ -d&Jd&Jb’ (c–/ bvDb¦Ac–JdBr ¢ v'dF9bò Jb†/b2 (c–/ bvDb¦Ac–JdB Ad&7'}
                </span>
              </div>
            </div>
          </div>

          {/* Section 1: Bank & Financial Options (Single Select) */}
          <div className="space-y-2">
            <label className="text-xs font-bold text-amber-200/90 flex items-center justify-between">
              <span>Ø<ßæ bæJbv1bv* bvDb†Fd†C d†'dFEböAd†9bv* bvDbVDd6*c HdfJb“£Â÷7  ãà
              <span className="text-[11px] text-amber-400/80 font-normal">bv.b¦Jbv1 d†'bÕ/ d BcsÂ÷7  ãà
            </label>
            <div className="grid grid-cols-1 sm:grid-cols-3 gap-2">
              {paymentPlatforms.map((p) => {
                const isSelected = selectedType === p.type;
                return (
                  <button
                    key={p.type}
                    type="button"
                    onClick={() => handleSelectPlatform(p.type)}
                    className={`flex items-center gap-2.5 p-3 rounded-2xl border text-right transition cu
                      isSelected
                        ? 'bg-[#1e1c12] text-amber-300 border-amber-400 shadow-[0_0_20px_rgba(250,204,21,
                        : 'bg-black/40 text-slate-300 border-amber-500/20 hover:border-amber-400/40 hover
```

FILE (cont.): src/components/EditQrModal.tsx

```
                    }`}
                  >
                    <div className="w-8 h-8 rounded-xl flex items-center justify-center flex-shrink-0 bg-
                      <PlatformBrandIcon type={p.type} className="w-6 h-6" />
                    </div>
                    <div className="min-w-0">
                      <p className="text-xs font-bold truncate">{p.label}</p>
                      <p className={`text-[10px] truncate ${isSelected ? 'text-amber-200 font-bold' : 'te
                        {p.hint}
                      </p>
                    </div>
                  </button>
                );
              })}
            </div>
          </div>

          {/* Section 2: Social & Messaging Platforms (Single Select) */}
          <div className="space-y-2">
            <label className="text-xs font-bold text-amber-200/90 flex items-center justify-between">
              <span>Ø=Üñ dVFcV'b¢ 'dF*d†'cVD d†'dF*cv(d¦Bbv* bvDb6.c I:</span>
              <span className="text-[11px] text-amber-400/80 font-normal">bv.b¦Jbv1 d†'bÖ/ d BcsÂ÷7  ãà
            </label>
            <div className="grid grid-cols-3 sm:grid-cols-4 md:grid-cols-7 gap-2">
              {socialPlatforms.map((p) => {
                const isSelected = selectedType === p.type;
                return (
                  <button
                    key={p.type}
                    type="button"
                    onClick={() => handleSelectPlatform(p.type)}
                    className={`flex flex-col items-center justify-center p-2.5 rounded-2xl border text-x
                      isSelected
                        ? 'bg-[#1e1c12] text-amber-300 border-amber-400 shadow-[0_0_20px_rgba(250,204,21,
                        : 'bg-black/40 text-slate-300 border-amber-500/20 hover:border-amber-400/40 hover
                    }`}
                  >
                    <div className="w-7 h-7 flex items-center justify-center">
                      <PlatformBrandIcon type={p.type} className="w-6 h-6" />
                    </div>
                    <span className="text-[11px] truncate w-full text-center">{p.label}</span>
                  </button>
                );
              })}
            </div>
          </div>

          {/* Section 3: Dynamic Input fields based on selected platform */}

          {/* A. If BANK selected */}
          {selectedType === 'bank' && (
            <div className="p-4 bg-gradient-to-br from-amber-500/10 via-yellow-500/5 to-transparent borde
              <div className="flex items-center gap-2 text-amber-300 font-bold text-xs">
                <Building2 className="w-4 h-4 text-amber-400" />
                <span>bV/bæ'dB (d¦'df'b¢ 'dF-c6'b, 'dF(dfCd¢ †DdF*bÖHd¦D bvDd Hc J):</span>
              </div>

              <div className="grid grid-cols-1 sm:grid-cols-2 gap-3">
                {/* Bank Name Selector */}
                <div className="space-y-1">
                  <label className="text-xs font-bold text-amber-200/90">bv3dR 'dF(dfC:</label>
                  <select
                    value={bankName}
                    onChange={(e) => setBankName(e.target.value)}
                    className="w-full px-3 py-2 bg-black/60 border border-amber-500/30 rounded-xl text-xs
                  >
                    {EGYPTIAN_BANKS.map((b) => (
                      <option key={b} value={b} className="bg-[#121216] text-white">{b}</option>
```

FILE (cont.): src/components/EditQrModal.tsx

```
                    ))}
                  </select>
                </div>

                {/* Account Number */}
                <div className="space-y-1">
                  <label className="text-xs font-bold text-amber-200/90">c BdR 'dF-c6'b, 'dF(dfCd¢ †%dF2bvEd¢"£ÂöÆ
                  <input
                    type="text"
                    value={accountNumber}
                    onChange={(e) => setAccountNumber(e.target.value)}
                    placeholder="dV+bvD: 12345678901234"
                    className="w-full px-3 py-2 bg-black/60 border border-amber-500/30 rounded-xl text-xs
                    dir="ltr"
                    required
                  />
                </div>

                {/* Account Holder Name */}
                <div className="space-y-1">
                  <label className="text-xs font-bold text-amber-200/90">bv3dR 5bv-b, 'dF-c6'b, †'bæ*d¦'c J):</labe
                  <input
                    type="text"
                    value={accountName}
                    onChange={(e) => setAccountName(e.target.value)}
                    placeholder="dV+bvD: b6-dV/ dV-dV/ c–Dd¢
                    className="w-full px-3 py-2 bg-black/60 border border-amber-500/30 rounded-xl text-xs
                  />
                </div>

                {/* IBAN */}
                <div className="space-y-1">
                  <label className="text-xs font-bold text-amber-200/90">bvDb&Jb†'db 'dF/d†Dd¢ "$ â †'bæ*d¦'c J):</
                  <input
                    type="text"
                    value={iban}
                    onChange={(e) => setIban(e.target.value)}
                    placeholder="EG0000000000000000000000000"
                    className="w-full px-3 py-2 bg-black/60 border border-amber-500/30 rounded-xl text-xs
                    dir="ltr"
                  />
                </div>
              </div>

              <div className="p-3 bg-black/40 rounded-xl border border-amber-500/20 flex items-start gap-
                <Info className="w-4 h-4 text-amber-400 flex-shrink-0 mt-0.5" />
                <span>
                  c–Fbò Ec6- dv0br 'dF1dV2`Â 3b¦8dv1 dFDc–Ed¦D b†7bvBb' (dfCd¦) b6Hb†3d¦/d¦'db Hc Gb, Abv.c ) b¦9c 6
                </span>
              </div>
            </div>
          )}

          {/* B. If WALLET selected */}
          {selectedType === 'wallet' && (
            <div className="p-4 bg-gradient-to-br from-amber-500/10 via-yellow-500/5 to-transparent borde
              <div className="flex items-center justify-between">
                <div className="flex items-center gap-2 text-amber-300 font-bold text-xs">
                  <Wallet className="w-4 h-4 text-amber-400" />
                  <span>c BdR 'dFEbÖAc†) b6H c 'b†7 bvDböAc' 'dF3c Jc' †Ad†/bvAd†F d6'cB ò 'b¦5bvDbv* / b6Hc FbÂ ò H
                </div>
                {walletPhone && (
                  <button
                    type="button"
                    onClick={() => setWalletPhone('')}
                    className="text-[11px] text-rose-400 hover:text-rose-300 font-bold flex items-center
                  >
                    <X className="w-3.5 h-3.5" />
```

FILE (cont.): src/components/EditQrModal.tsx

```
                    <span>dV3bÓÂ÷7  ãà
                  </button>
                )}
              </div>
              <div className="relative">
                <input
                  type="text"
                  value={walletPhone}
                  onChange={(e) => setWalletPhone(e.target.value)}
                  placeholder="010... b6H 012... b6H c 'b†7 bvDböAc’ ‡GG 3¢òòâââ
                  className="w-full pr-3.5 pl-10 py-2.5 bg-black/60 border border-amber-500/30 rounded-xl
                  dir="ltr"
                  required
                  autoFocus
                />
                {walletPhone && (
                  <button
                    type="button"
                    onClick={() => setWalletPhone('')}
                    className="absolute left-3 top-3 text-slate-400 hover:text-amber-300 transition curso
                    title="b¦Ac Jc¢ 'dF-d&D"
                  >
                    <X className="w-4 h-4" />
                  </button>
                )}
              </div>

              {/* Real-time detection badge */}
              {walletPhone.trim() ? (
                isQuickPayUrl(walletPhone) ? (
                  <div className="p-3 bg-amber-500/15 border border-amber-500/30 rounded-xl flex items-ce
                    <Sparkles className="w-5 h-5 text-amber-400 flex-shrink-0" />
                    <div className="text-xs text-right">
                      <p className="font-bold text-amber-300">c 'b†7 böAc’ 3c Jc’ DdFEbÖAc†) &¡</p>
                      <p className="text-[11px] text-slate-300">c6Jb¦E b¦-d†JdB 'dF9dVJdB *dFBbv&d¦'d² %dFI dv0br 'd
                    </div>
                  </div>
                ) : (() => {
                  const detected = detectWalletInfo(walletPhone);
                  return (
                    <div className="p-3 bg-black/70 border border-white/10 rounded-xl flex items-center g
                      <div className="w-18 h-12 rounded-xl bg-black/60 border border-white/10 p-1 flex it
                        <WalletProviderIcon provider={detected.provider} size={48} className="w-full h-fu
                      </div>
                      <div className="text-xs text-right">
                        <p className="font-bold text-amber-300 flex items-center gap-1.5">
                          <span>{detected.nameAr}</span>
                          <span className="text-[10px] text-slate-400">({detected.nameEn})</span>
                        </p>
                        <p className="text-[11px] text-slate-400">
                          {detected.companyNameAr} • d¦9c 6 b†7bvBb’ Abv.c ) b†'dFDd†,d, Hc BdR ‡¶FWFV7FVBæf÷&Ö GFVE
                        </p>
                      </div>
                    </div>
                  );
                })()
              ) : (
                <p className="text-[11px] text-amber-200/70">
                  Ø=Ü¡ d¦/c–E c Hbv(cr 'dF/d 9 bvDc61d¦9 (d¦*dR 'dF*d†,d¦G bvDd Hc J dFGbr’ #d, 1d&E bvDdVHb†'d¦D (d
                </p>
              )}
            </div>
          )}

          {/* C. If INSTAPAY selected */}
          {selectedType === 'instapay' && (
            <div className="p-4 bg-gradient-to-br from-amber-500/10 via-yellow-500/5 to-transparent borde
              <div className="flex items-center justify-between">
```

FILE (cont.): src/components/EditQrModal.tsx

```
                <div className="flex items-center gap-2 text-amber-300 font-bold text-xs">
                  <CreditCard className="w-4 h-4 text-amber-400" />
                  <span>c 'b†7 bvDböAc’ 'dF3c Jc’ Edb %df3b¦'b†'d¢ –ç7F   ’ †%dF2bvEd¢“£Â÷7  ãà
                </div>
                {targetUrl && (
                  <button
                    type="button"
                    onClick={() => setTargetUrl('')}
                    className="text-[11px] text-rose-400 hover:text-rose-300 font-bold flex items-center
                  >
                    <X className="w-3.5 h-3.5" />
                    <span>dV3bÓÂ÷7  ãà
                  </button>
                )}
              </div>
              <div className="relative">
                <input
                  type="text"
                  value={targetUrl}
                  onChange={(e) => setTargetUrl(e.target.value)}
                  placeholder="https://ipn.eg/S/... (c 'b†7 bvDböAc’ 'dF3c Jc’ Ad&7)"
                  className="w-full pr-3.5 pl-10 py-2.5 bg-black/60 border border-amber-500/30 rounded-xl
                  dir="ltr"
                  required
                  autoFocus
                />
                {targetUrl && (
                  <button
                    type="button"
                    onClick={() => setTargetUrl('')}
                    className="absolute left-3 top-3 text-slate-400 hover:text-amber-300 transition curso
                    title="b¦Ac Jc¢ 'dF-d&D"
                  >
                    <X className="w-4 h-4" />
                  </button>
                )}
              </div>
              <p className="text-[11px] text-amber-200/80 leading-relaxed">
                Ø=Ü¡ <strong>cv1d¦Bb’ 'dF-cVHdB 9dFI bvDc 'b†7:</strong> bvAb¦- b¦7b†Jd" %df3b¦'b†'d¢ fwC² 'cf:cr g
              </p>
            </div>
          )}

          {/* D. Standard Target URL for other platforms */}
          {selectedType !== 'bank' && selectedType !== 'wallet' && selectedType !== 'instapay' && (() =>
            const currentMeta = PLATFORM_META[selectedType] || PLATFORM_META.website;
            return (
              <div className="space-y-2 animate-in fade-in">
                <div className="flex items-center justify-between">
                  <label className="text-xs font-bold text-amber-200/90 flex items-center gap-1.5">
                    <span>bvDc 'b†7 bvDdV3b¦GböA b6H bvDbÖ3bv(</span>
                    <span className="text-amber-400 font-black">({currentMeta.labelAr} - {currentMeta.lab
                  </label>
                  {targetUrl && (
                    <button
                      type="button"
                      onClick={() => setTargetUrl('')}
                      className="text-[11px] text-rose-400 hover:text-rose-300 font-bold flex items-cente
                      title="dV3bÒ Hb¦Ac Jc¢ 'dF-d&D"
                    >
                      <X className="w-3.5 h-3.5" />
                      <span>dV3bÒ 'dF1bv(cr 'dFBböJdSÂ÷7  ãà
                    </button>
                  )}
                </div>
                <div className="relative">
                  <input
                    type="text"
```

FILE (cont.): src/components/EditQrModal.tsx

```
                    value={targetUrl}
                    onChange={(e) => setTargetUrl(e.target.value)}
                    placeholder={currentMeta.placeholder}
                    autoCapitalize="none"
                    autoCorrect="off"
                    spellCheck={false}
                    className="w-full pr-4 pl-10 py-3 bg-black/60 border border-amber-500/30 rounded-xl t
                    dir="ltr"
                    required
                    autoFocus
                  />
                  {targetUrl && (
                    <button
                      type="button"
                      onClick={() => setTargetUrl('')}
                      className="absolute left-3 top-3.5 text-slate-400 hover:text-amber-300 transition c
                      title="b¦Ac Jc¢ 'dF-d&D"
                    >
                      <X className="w-4 h-4" />
                    </button>
                  )}
                </div>
                <p className="text-[11px] text-slate-400">
                  {currentMeta.hint}
                </p>
              </div>
            );
          })()}

          {/* Label / Description */}
          <div className="space-y-1.5">
            <label className="text-xs font-bold text-amber-200/90">
              b¦3dVJb’ 'dFCbv1b¢ ò HcVA bö'bæDd¢ DdF#böEdb †'bæ*d¦'c J):
            </label>
            <input
              type="text"
              value={label}
              onChange={(e) => setLabel(e.target.value)}
              placeholder="dV+bvD: d6'c * b¦-d†JdB (dfCd¢ DdFEb¦,c  Ò 'dF-c6'b, 'dF1bfJc6J"
              className="w-full px-3.5 py-2.5 bg-black/60 border border-amber-500/20 rounded-xl text-xs t
            />
          </div>

          {/* Subscription Expiry & Duration Management */}
          <div className="p-4 bg-gradient-to-br from-amber-500/10 via-black/60 to-[#121216] border border
            <div className="flex items-center justify-between">
              <span className="text-xs font-bold text-amber-300 flex items-center gap-1.5">
                <Clock className="w-4 h-4 text-amber-400" />
                <span>bV/bv1b’ Ebö) bvDb¦Ac–JdB HbvDbv4b¦1bvC bvDcFGc J:</span>
              </span>
              {expiresAt ? (
                new Date(expiresAt).getTime() < Date.now() ? (
                  <span className="px-2.5 py-0.5 rounded-full text-[10px] font-black bg-rose-500/20 text-
                    dVFb¦Gd¢ 'dF5dF'bÖJb’ j àð
                  </span>
                ) : (
                  <span className="px-2.5 py-0.5 rounded-full text-[10px] font-black bg-emerald-500/20 te
                    df4cr †(bvBd¢ ´Ö F,æÖ ,ƒ Â Ö F,æ6V–Â,†æWr F FR†W‡ —&W4 B’ævWEF–ÖR,’ Ò F FRææ÷r,’’ ò ƒ
                  </span>
                )
              ) : (
                <span className="px-2.5 py-0.5 rounded-full text-[10px] font-black bg-cyan-500/20 text-cy
                  bö'bfE / c¦Jc  EbÖ/d†/ '&
                </span>
              )}
            </div>

            {/* Current Expiry Date Display & Date Input */}
```

FILE (cont.): src/components/EditQrModal.tsx

```
817             <div className="grid grid-cols-1 sm:grid-cols-2 gap-3 items-center">
818               <div className="space-y-1">
819                 <label className="text-[11px] text-slate-300 font-semibold block">
820                   b¦'c Jbâ 'df*dv'b  'dF'cF*c 'd3
821                 </label>
822                 <div className="relative">
823                   <input
824                     type="date"
825                     value={expiresAt ? expiresAt.split('T')[0] : ''}
826                     onChange={(e) => {
827                       if (e.target.value) {
828                         setExpiresAt(new Date(e.target.value + 'T23:59:59.000Z').toISOString());
829                       } else {
830                         setExpiresAt(null);
831                       }
832                     }}
833                     className="w-full px-3 py-2 bg-black/70 border border-amber-500/30 rounded-xl text-xs
834                   />
835                 </div>
836               </div>
837
838               {/* Fast Extend Buttons */}
839               <div className="space-y-1">
840                 <label className="text-[11px] text-slate-300 font-semibold block">
841                   b¦EböJbò 3c Jc’ DdF'cF*c 'd3
842                 </label>
843                 <div className="flex items-center gap-1.5 flex-wrap">
844                   <button
845                     type="button"
846                     onClick={() => handleExtendDays(30)}
847                     className="flex-1 py-1.5 px-2 bg-amber-400/15 hover:bg-amber-400 hover:text-black tex
848                   >
849                     <span>+1 cFGc Â÷7  ãà
850                   </button>
851                   <button
852                     type="button"
853                     onClick={() => handleExtendDays(90)}
854                     className="flex-1 py-1.5 px-2 bg-amber-400/15 hover:bg-amber-400 hover:text-black tex
855                   >
856                     <span>+3 cFGd†1</span>
857                   </button>
858                   <button
859                     type="button"
860                     onClick={() => handleExtendDays(180)}
861                     className="flex-1 py-1.5 px-2 bg-amber-400/15 hover:bg-amber-400 hover:text-black tex
862                   >
863                     <span>+6 cFGd†1</span>
864                   </button>
865                   <button
866                     type="button"
867                     onClick={() => setExpiresAt(null)}
868                     className={`py-1.5 px-2.5 rounded-xl text-xs font-bold transition border ${
869                       expiresAt === null
870                         ? 'bg-cyan-500/30 text-cyan-200 border-cyan-400'
871                         : 'bg-black/40 text-slate-400 border-white/10 hover:text-white'
872                     }`}
873                   >
874                     <span>bö'bfE</span>
875                   </button>
876                 </div>
877               </div>
878             </div>
879
880             <p className="text-[11px] text-slate-400 leading-normal">
881               * c–Fbò 'df*dv'b  Ebö) bvDb¦Ac–JdF  c6*b¦Hd&A bV9bv/b’ 'dF*d†,d¦G d†3d¦8dv1 dFDc–Ed¦D cVAbÖ) d 'bæ1b’
882             </p>
883           </div>
884
```

FILE (cont.): src/components/EditQrModal.tsx

```
          {/* Live Preview Card */}
          <div className="p-4 bg-black/60 border border-amber-500/20 rounded-2xl space-y-2.5">
            <div className="flex items-center justify-between">
              <span className="text-xs font-bold text-amber-300 flex items-center gap-1.5">
                <Smartphone className="w-4 h-4 text-amber-400" />
                dV9bvJdf) df*d¦,b’ 'dFEc6- bvDdV(bv4c
              </span>
              <span className="text-[10px] px-2 py-0.5 bg-amber-400/15 border border-amber-400/30 text-am
                bÆ'dv2 dFDc–EdB (df3b†) 100%
              </span>
            </div>

            {selectedType === 'bank' ? (
              <div className="p-3 bg-[#141418] rounded-xl border border-amber-500/30 space-y-1.5 text-xs"
                <p className="font-bold text-amber-300 flex items-center gap-1.5">
                  <Building2 className="w-4 h-4 text-amber-400" />
                  {bankName}
                </p>
                <div className="flex items-center justify-between bg-black/50 p-2 rounded-lg font-mono" d
                  <span className="text-amber-200 font-bold">{accountNumber || 'c BdR 'dF-c6'b,wÓÂ÷7  ãà
                  <span className="text-[11px] text-slate-400">Account #</span>
                </div>
                {accountName && <p className="text-slate-300 text-[11px]">bvDbv3dS¢ ¶ 66÷VçDæ ÖWÓÂ÷ çÐ
                {iban && <p className="text-amber-200/60 text-[10px] font-mono" dir="ltr">IBAN: {iban}</p
              </div>
            ) : (
              <div className="space-y-1 text-xs">
                <div className="flex items-center gap-2">
                  <span className="text-slate-400 font-mono text-[11px] w-24">bvDc 'b†7 bvDdV(bv4c £Â÷7  ãà
                  <code className="text-amber-300 bg-black/80 px-2 py-1 rounded border border-amber-500/2
                    {currentLinkInfo.schemeUrl || '—'}
                  </code>
                </div>
              </div>
            )}

            <div className="flex items-center justify-end gap-2 pt-1">
              <a
                href={`${domainUrl}/q/${record.id}`}
                target="_blank"
                rel="noopener noreferrer"
                className="inline-flex items-center gap-1 text-xs font-bold text-amber-400 hover:text-amb
              >
                <Eye className="w-3.5 h-3.5" />
                b¦,c (b’ Ec6- bvDd6Hbò HdV-bvCbv) bvDb¦HbÆJdr Ad¢ *b†Hd¦( bÆ/d¦/
              </a>
            </div>
          </div>

          {/* QR Image Box */}
          <div className="p-4 bg-[#141418] rounded-2xl border border-amber-500/20 flex flex-col sm:flex-r
            <div className="flex items-center gap-4">
              {qrDataUrl && (
                <div className="p-1.5 bg-white border border-amber-500/30 rounded-xl shadow-md">
                  <img src={qrDataUrl} alt="QR Code" className="w-16 h-16 object-contain" />
                </div>
              )}
              <div>
                <p className="text-xs font-bold text-amber-200">c Ec" 'dF@ QR bvDd6Dbv3d¦Cd¢ 9bvDd¢ 'dF/d&)</p>
                <p className="text-[11px] text-amber-400/80 font-mono" dir="ltr">{domainUrl}/q/{record.id
              </div>
            </div>

            <button
              type="button"
              onClick={handleDownloadQr}
              className="flex items-center gap-1.5 px-3 py-2 bg-white/5 hover:bg-white/10 text-amber-300
            >
```

FILE (cont.): src/components/EditQrModal.tsx

```
              <Download className="w-3.5 h-3.5 text-amber-400" />
              b¦Fc&JdB 'dF5d†1b’ … är•
            </button>
          </div>

          {/* Success Banner */}
          {savedSuccess && (
            <div className="p-3 bg-amber-400/20 border border-amber-400/30 rounded-2xl text-xs text-amber
              <Check className="w-4 h-4 text-amber-400 flex-shrink-0" />
              b¦E bÖAc, 'dF*c–/d¦Dbv* d†*bÖ/d¦+ bvDdVFcV) d†'dF1bv(cr (df,bv-!
            </div>
          )}

          {/* Footer Actions */}
          <div className="flex flex-wrap items-center justify-between gap-3 pt-3 border-t border-amber-50
            {onDelete ? (
              <button
                type="button"
                onClick={() => {
                  onDelete(record.id);
                  onClose();
                }}
                className="flex items-center gap-1.5 px-3.5 py-2.5 text-rose-300 hover:text-white hover:b
              >
                <Trash2 className="w-3.5 h-3.5" />
                bÖ0d  'dFCd†/ dfGbv&d¦'d°
              </button>
            ) : <div />}

            <div className="flex items-center gap-2">
              <button
                type="button"
                onClick={onClose}
                className="px-4 py-2.5 text-xs font-bold text-slate-400 hover:text-white rounded-xl trans
              >
                bVDc¦'b
              </button>
              <button
                type="submit"
                disabled={loading}
                className="flex items-center gap-2 px-6 py-2.5 bg-gradient-to-r from-amber-400 via-yellow
              >
                <Save className="w-4 h-4 text-black" />
                {loading ? 'bÆ'c J bvDbÖAc,ãâår ¢ v-d 8 bvDb¦9böJdF'b¢wÐ
              </button>
            </div>
          </div>
        </form>
      </div>
    </div>
  );
}

```

FILE: src/components/PrintSheetModal.tsx 194 lines | 8.3 KB

```tsx
import { useState, useEffect } from 'react';
import { Printer, X, Download, Sliders, Sparkles, Filter } from 'lucide-react';
import { generateQrDataUrl } from '../lib/qrService';
import { QrCodeRecord } from '../types/qr';

interface PrintSheetModalProps {
  isOpen: boolean;
  onClose: () => void;
  records: QrCodeRecord[];
  domainUrl: string;
}

export function PrintSheetModal({ isOpen, onClose, records, domainUrl }: PrintSheetModalProps) {
  const [qrMap, setQrMap] = useState<Record<string, string>>({});
  const [columns, setColumns] = useState<number>(3);
  const [filterType, setFilterType] = useState<'all' | 'inactive' | 'active'>('all');

  const filtered = records.filter((r) => {
    if (!r || !r.id) return false;
    if (filterType === 'inactive') return !r.is_active;
    if (filterType === 'active') return r.is_active;
    return true;
  });

  useEffect(() => {
    if (!isOpen) return;

    let isMounted = true;
    const generateAll = async () => {
      const map: Record<string, string> = {};
      for (const record of filtered) {
        const fullScanUrl = `${domainUrl}/q/${record.id}`;
        map[record.id] = await generateQrDataUrl(fullScanUrl, 400);
      }
      if (isMounted) setQrMap(map);
    };

    generateAll();
    return () => {
      isMounted = false;
    };
  }, [isOpen, filterType, filtered.length, domainUrl]);

  if (!isOpen) return null;

  const handlePrint = () => {
    window.print();
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/85 backdrop-blur-md
      <div className="relative w-full max-w-4xl bg-[#0e0e12] rounded-3xl shadow-[0_0_50px_rgba(212,175,55
        {/* Ambient Gold Glow */}
        <div className="absolute -top-12 -right-12 w-32 h-32 bg-amber-500/10 rounded-full blur-2xl pointe
        <div className="absolute -bottom-12 -left-12 w-32 h-32 bg-yellow-500/10 rounded-full blur-2xl poi

        {/* Header - Not printed */}
        <div className="no-print flex items-center justify-between px-6 py-4 border-b border-amber-500/20
          <div className="flex items-center gap-3">
            <div className="w-10 h-10 rounded-2xl bg-gradient-to-tr from-amber-400 to-yellow-500 text-bla
              <Printer className="w-5 h-5 text-black" />
            </div>
            <div>
              <h2 className="text-lg font-black text-transparent bg-clip-text bg-gradient-to-r from-amber
                b¦,dvJc" Hcv(bv9b’ 1dVHc" 'dF@ QR dFDb†7bvBbv* d†'dFEdF5d&'b
              </h2>
              <p className="text-xs text-slate-400">dV.c ,bv* dV,dv2b’ Dd†1d" 'dF7b†'c–) A4 b†/d&) c–'dFJb’ Hb¦Fc6Jd
            </div>
```

FILE (cont.): src/components/PrintSheetModal.tsx

```
          </div>
          <button
            onClick={onClose}
            className="p-2 text-slate-400 hover:text-white hover:bg-white/10 rounded-xl transition"
          >
            <X className="w-5 h-5" />
          </button>
        </div>

        {/* Toolbar - Not printed */}
        <div className="no-print px-6 py-3 bg-[#121216] border-b border-amber-500/20 flex flex-wrap items
          <div className="flex items-center gap-4 flex-wrap">
            <div className="flex items-center gap-2">
              <span className="font-bold text-amber-200/90">b¦5d Jb“£Â÷7  ãà
              <select
                value={filterType}
                onChange={(e) => setFilterType(e.target.value as any)}
                className="bg-black/60 border border-amber-500/30 rounded-xl px-3 py-1.5 text-amber-300 f
              >
                <option value="all">bÆEd¦9 bvDb6Cd†'bò ‡·&V6÷&G2æÆVæwF‡Ò“Âö÷ F–öãà
                <option value="inactive">c¦Jc  'dFEd 9dF) d Bcr †,bvGc&) dFDc–EdF'b “Âö÷ F–öãà
                <option value="active">bvDdVAc–Db’ Ad&7</option>
              </select>
            </div>

            <div className="flex items-center gap-2">
              <span className="font-bold text-amber-200/90">b69dV/b’ 'dFHc Bb“£Â÷7  ãà
              <button
                type="button"
                onClick={() => setColumns(2)}
                className={`px-3 py-1.5 rounded-xl border text-xs font-bold transition ${
                  columns === 2
                    ? 'bg-amber-400 text-black border-amber-300 font-black shadow-md'
                    : 'bg-black/40 text-slate-300 border-amber-500/20 hover:border-amber-400/40'
                }`}
              >
                c–Ed†/d¦F (d61d†* d6(d¦1b’•
              </button>
              <button
                type="button"
                onClick={() => setColumns(3)}
                className={`px-3 py-1.5 rounded-xl border text-xs font-bold transition ${
                  columns === 3
                    ? 'bg-amber-400 text-black border-amber-300 font-black shadow-md'
                    : 'bg-black/40 text-slate-300 border-amber-500/20 hover:border-amber-400/40'
                }`}
              >
                3 b69dV/b’ †Ed&'c2 Bd¦'c6J)
              </button>
            </div>
          </div>

          <button
            onClick={handlePrint}
            className="flex items-center gap-2 px-5 py-2.5 bg-gradient-to-r from-amber-400 via-yellow-400
          >
            <Printer className="w-4 h-4 text-black" />
            cv(bv9b’ 'dFHc Bb’ … &–çB  B•
          </button>
        </div>

        {/* Printable Sheet Area */}
        <div className="p-6 overflow-y-auto bg-black/40 flex-1">
          <div className="bg-white p-8 rounded-2xl shadow-xl min-h-[600px] border border-amber-500/20 tex
            {filtered.length === 0 ? (
              <div className="text-center py-16 text-slate-400 font-bold">
                dF' b¦Hbƒ/ b6Cd†'bò Ecv'b†Bb’ DdF*cVAd¦) bvDdV-bö/b’à
              </div>
```

FILE (cont.): src/components/PrintSheetModal.tsx

```
            ) : (
              <div
                className={`grid gap-4 print-grid ${
                  columns === 2 ? 'grid-cols-2' : 'grid-cols-3'
                }`}
              >
                {filtered.map((r, i) => (
                  <div
                    key={r.id}
                    className="print-card p-4 rounded-xl border-2 border-dashed border-slate-300 bg-white
                  >
                    {/* Header of sticker */}
                    <div className="w-full flex items-center justify-between text-[10px] text-slate-500 f
                      <span className="flex items-center gap-1 text-black font-black font-mono">
                        <span>'&</span>
                        <span>Smart Card</span>
                      </span>
                      <span>#{i + 1}</span>
                    </div>

                    {/* Classic crisp black & white QR */}
                    <div className="my-3 p-1 bg-white">
                      {qrMap[r.id] ? (
                        <img
                          src={qrMap[r.id]}
                          alt={`QR ${r.id}`}
                          className="w-32 h-32 object-contain"
                        />
                      ) : (
                        <div className="w-32 h-32 bg-slate-100 animate-pulse rounded" />
                      )}
                    </div>

                    {/* Instructions and ID */}
                    <div className="w-full space-y-1">
                      <p className="text-[11px] font-black text-slate-900">
                        bvEc6- bvDd6Hbò (d6'dVJc ' dv'b¦Ad0
                      </p>
                      <p className="text-[10px] text-slate-600 font-semibold">
                        {r.is_active ? 'd *bÒ 'dF1bv(cr 'dFEb†'cF1' : 'b¦Ac–JdB 'dFCbv1b¢ 'dF0d6J'}
                      </p>
                      <div className="pt-2">
                        <span className="font-mono text-xs font-bold bg-slate-100 text-slate-900 px-2.5 p
                          {r.id}
                        </span>
                      </div>
                    </div>
                  </div>
                ))}
              </div>
            )}
          </div>
        </div>
      </div>
    );
}
```

FILE: src/components/QrScannerModal.tsx 168 lines | 6.0 KB

```tsx
import { useState, useRef, useEffect } from 'react';
import { Camera, X, RefreshCw, AlertCircle, Sparkles } from 'lucide-react';
import jsQR from 'jsqr';
import { extractQrIdFromUrl } from '../lib/qrService';

interface QrScannerModalProps {
  isOpen: boolean;
  onClose: () => void;
  onScannedId: (id: string) => void;
}

export function QrScannerModal({ isOpen, onClose, onScannedId }: QrScannerModalProps) {
  const [errorMsg, setErrorMsg] = useState<string | null>(null);
  const [isScanning, setIsScanning] = useState(false);
  const videoRef = useRef<HTMLVideoElement>(null);
  const streamRef = useRef<MediaStream | null>(null);
  const animFrameRef = useRef<number | null>(null);

  useEffect(() => {
    if (!isOpen) {
      stopCamera();
      return;
    }

    startCamera();

    return () => {
      stopCamera();
    };
  }, [isOpen]);

  const startCamera = async () => {
    setErrorMsg(null);
    setIsScanning(true);

    try {
      const stream = await navigator.mediaDevices.getUserMedia({
        video: { facingMode: 'environment' },
      });
      streamRef.current = stream;

      if (videoRef.current) {
        videoRef.current.srcObject = stream;
        videoRef.current.setAttribute('playsinline', 'true');
        videoRef.current.play();
        scanVideoFrame();
      }
    } catch (err) {
      console.warn('Camera access error:', err);
      setErrorMsg('b¦9c 1 bvDd†5d†D bVDd’ 'dFCbvEd¦1brâ Jc ,d’ 'dF*bÖBd" Edb 'dF#c Hdf'b¢ #d, 'c6*bæ/bvE d -cR 'dF5d
      setIsScanning(false);
    }
  };

  const stopCamera = () => {
    if (animFrameRef.current) {
      cancelAnimationFrame(animFrameRef.current);
      animFrameRef.current = null;
    }
    if (streamRef.current) {
      streamRef.current.getTracks().forEach((track) => track.stop());
      streamRef.current = null;
    }
    setIsScanning(false);
  };

  const scanVideoFrame = () => {
    const video = videoRef.current;
```

FILE (cont.): src/components/QrScannerModal.tsx

```
    if (!video || video.readyState !== video.HAVE_ENOUGH_DATA) {
      animFrameRef.current = requestAnimationFrame(scanVideoFrame);
      return;
    }

    const canvas = document.createElement('canvas');
    canvas.width = video.videoWidth;
    canvas.height = video.videoHeight;
    const ctx = canvas.getContext('2d');

    if (ctx) {
      ctx.drawImage(video, 0, 0, canvas.width, canvas.height);
      const imageData = ctx.getImageData(0, 0, canvas.width, canvas.height);
      const code = jsQR(imageData.data, imageData.width, imageData.height, {
        inversionAttempts: 'dontInvert',
      });

      if (code && code.data) {
        const id = extractQrIdFromUrl(code.data);
        if (id) {
          stopCamera();
          onScannedId(id);
          onClose();
          return;
        }
      }
    }

    animFrameRef.current = requestAnimationFrame(scanVideoFrame);
  };

  if (!isOpen) return null;

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/80 backdrop-blur-md
      <div className="relative w-full max-w-md bg-[#0e0e12] rounded-3xl shadow-[0_0_50px_rgba(212,175,55,
        {/* Header */}
        <div className="flex items-center justify-between px-6 py-4 border-b border-white/5 bg-black/50">
          <div className="flex items-center gap-3">
            <div className="w-10 h-10 rounded-2xl bg-gradient-to-tr from-amber-400 to-yellow-500 text-bla
              <Camera className="w-5 h-5 text-black" />
            </div>
            <div>
              <h2 className="text-lg font-black text-transparent bg-clip-text bg-gradient-to-r from-amber
                d6'dVJc ' dV3bÒ 'dF@ QR (Live Scanner)
              </h2>
              <p className="text-xs text-slate-400">d†,e G bvDd6'dVJc ' df-d, Cd†/ bvDd   " DdF*c–1d  'dF*dFBbv&d£Â÷
            </div>
          </div>
          <button
            onClick={() => {
              stopCamera();
              onClose();
            }}
            className="p-2 text-slate-400 hover:text-white hover:bg-white/10 rounded-xl transition"
          >
            <X className="w-5 h-5" />
          </button>
        </div>

        {/* Video Viewer */}
        <div className="p-6 flex flex-col items-center">
          <div className="relative w-full aspect-square max-w-[320px] bg-black rounded-2xl overflow-hidde
            <video
              ref={videoRef}
              className="w-full h-full object-cover"
              muted
              playsInline
```

FILE (cont.): src/components/QrScannerModal.tsx

```
            />

            {/* Scanning Laser Line */}
            {isScanning && (
              <div className="absolute inset-0 pointer-events-none flex flex-col items-center justify-cen
                <div className="w-56 h-56 border-2 border-amber-400/80 rounded-2xl relative">
                  <div className="absolute top-0 left-0 w-4 h-4 border-t-4 border-l-4 border-amber-400" /
                  <div className="absolute top-0 right-0 w-4 h-4 border-t-4 border-r-4 border-amber-400"
                  <div className="absolute bottom-0 left-0 w-4 h-4 border-b-4 border-l-4 border-amber-400
                  <div className="absolute bottom-0 right-0 w-4 h-4 border-b-4 border-r-4 border-amber-40
                  <div className="w-full h-0.5 bg-amber-400 shadow-[0_0_15px_#f59e0b] animate-bounce mt-2
                </div>
              </div>
            )}
          </div>

          {errorMsg && (
            <div className="mt-4 p-3 bg-amber-500/15 border border-amber-400/30 rounded-xl text-xs text-a
              <AlertCircle className="w-4 h-4 text-amber-400 flex-shrink-0 mt-0.5" />
              <span>{errorMsg}</span>
            </div>
          )}

          <p className="text-xs text-slate-400 mt-4 text-center">
            d¦*dR AbÖ5 bvDd6Hbò *dFBbv&d¦'d² Ad¢ #bÆ2bv! dVF bvDb¶'dfJb’ (dV,c / c†Gd†1 bvDc Ec" Ad¢ 'dFEc (c•
          </p>
        </div>
      </div>
    </div>
  );
}

```

FILE: src/components/UploadQrModal.tsx 320 lines | 12.6 KB

```tsx
import { useState, useRef, DragEvent } from 'react';
import { Upload, Search, AlertCircle, Loader2, X, Image as ImageIcon, Sparkles, PlusCircle } from 'lucide
import { decodeQrFromImageFile, extractQrIdFromUrl, lookupExistingQrCode, getQrCode } from '../lib/qrServ
import { QrCodeRecord } from '../types/qr';

interface UploadQrModalProps {
  isOpen: boolean;
  onClose: () => void;
  onCodeFound: (record: QrCodeRecord) => void;
}

export function UploadQrModal({ isOpen, onClose, onCodeFound }: UploadQrModalProps) {
  const [isDragging, setIsDragging] = useState(false);
  const [loading, setLoading] = useState(false);
  const [errorMsg, setErrorMsg] = useState<string | null>(null);
  const [notFoundId, setNotFoundId] = useState<string | null>(null);
  const [manualId, setManualId] = useState('');
  const [imagePreview, setImagePreview] = useState<string | null>(null);
  const fileInputRef = useRef<HTMLInputElement>(null);

  if (!isOpen) return null;

  // Process uploaded image file
  const handleProcessFile = async (file: File) => {
    if (!file.type.startsWith('image/')) {
      setErrorMsg('d¦1bÆI bv.b¦Jbv1 dVDd  5d†1b’ 5bvDbÒ … ärÂ ¥ rÂ tT% ’r“°
      return;
    }

    setLoading(true);
    setErrorMsg(null);
    setNotFoundId(null);

    const previewUrl = URL.createObjectURL(file);
    setImagePreview(previewUrl);

    try {
      const decodedText = await decodeQrFromImageFile(file);
      if (!decodedText) {
        setErrorMsg('b¦9c 1 d&1bv!b’ 1dV2 QR dVF bvDcVHc ) bvDdV1d Hc–). b¦#d6/ dVF d†6d†- bvDcVHc ) d†*d†3cr 'dF1dV
        setLoading(false);
        return;
      }

      const extractedId = extractQrIdFromUrl(decodedText);
      const cleanId = extractedId || decodedText.trim();

      // Query database
      const record = await lookupExistingQrCode(cleanId);
      if (!record) {
        setNotFoundId(cleanId);
        setErrorMsg(`b¦E bv3b¦.c 'bÂ 'dFEc–1e A [${cleanId}] d†Dd6F bvDd6Hbò :d¦1 dV3bÆD b†Bbv9bö) bvDb†JbvFbv*.`);
        setLoading(false);
        return;
      }

      // Found! Pass record to parent
      setLoading(false);
      onCodeFound(record);
      onClose();
    } catch (err) {
      console.error('Scan error:', err);
      setErrorMsg('bÖ/b² .cv# b6+df'b  Ec–'dF,b’ 'dF5d†1b’âr“°
      setLoading(false);
    }
  };

  const handleDragOver = (e: DragEvent) => {
```

FILE (cont.): src/components/UploadQrModal.tsx

```
    e.preventDefault();
    setIsDragging(true);
  };

  const handleDragLeave = () => {
    setIsDragging(false);
  };

  const handleDrop = (e: DragEvent) => {
    e.preventDefault();
    setIsDragging(false);
    if (e.dataTransfer.files && e.dataTransfer.files[0]) {
      handleProcessFile(e.dataTransfer.files[0]);
    }
  };

  // Search by manual ID
  const handleManualSearch = async (e: React.FormEvent) => {
    e.preventDefault();
    let raw = manualId.trim();
    if (!raw) return;

    // Handle full URL pasted
    const extracted = extractQrIdFromUrl(raw);
    const cleanId = extracted || raw;

    setLoading(true);
    setErrorMsg(null);
    setNotFoundId(null);

    try {
      const record = await lookupExistingQrCode(cleanId);
      if (!record) {
        setNotFoundId(cleanId);
        setErrorMsg(`dFE d¦*dR 'dF9b¶Hc  9dFI b6J d6Hbò (bvDdV9c Qd  "G¶6ÆV ä–GÒ"æ “°
        setLoading(false);
        return;
      }
      setLoading(false);
      onCodeFound(record);
      onClose();
    } catch (err) {
      console.error('Search error:', err);
      // Fallback
      try {
        const fallbackRecord = await getQrCode(cleanId);
        if (fallbackRecord) {
          setLoading(false);
          onCodeFound(fallbackRecord);
          onClose();
          return;
        }
      } catch {}
      setErrorMsg('b¦9c 1 bvDb†-b² 9db 'dFCd†/`Â Jc ,d’ 'dFEbÖ'd†Db’ Ec ) b6.c I.');
      setLoading(false);
    }
  };

  // Create & Edit new card on the fly if not found
  const handleCreateAndEdit = () => {
    if (!notFoundId) return;
    const newRecord: QrCodeRecord = {
      id: notFoundId,
      is_active: false,
      target_url: null,
      created_at: new Date().toISOString(),
      total_scans: 0,
      subscription_months: 1,
```

FILE (cont.): src/components/UploadQrModal.tsx

```
      expires_at: new Date(Date.now() + 30 * 24 * 60 * 60 * 1000).toISOString(),
    };
    onCodeFound(newRecord);
    onClose();
  };

  const handleReset = () => {
    setImagePreview(null);
    setErrorMsg(null);
    setNotFoundId(null);
    setManualId('');
    onClose();
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/85 backdrop-blur-md
      <div className="relative w-full max-w-lg bg-[#0e0e12] rounded-3xl shadow-[0_0_50px_rgba(212,175,55,

        {/* Ambient gold glow */}
        <div className="absolute -top-12 -right-12 w-32 h-32 bg-amber-500/10 rounded-full blur-2xl pointe
        <div className="absolute -bottom-12 -left-12 w-32 h-32 bg-yellow-500/10 rounded-full blur-2xl poi

        {/* Header */}
        <div className="flex items-center justify-between px-6 py-4 border-b border-amber-500/20 bg-black
          <div className="flex items-center gap-3">
            <div className="w-10 h-10 rounded-2xl bg-gradient-to-tr from-amber-400 to-yellow-500 text-bla
              <Upload className="w-5 h-5 text-black" />
            </div>
            <div>
              <h2 className="text-base sm:text-lg font-black text-transparent bg-clip-text bg-gradient-to
                d -cR Hb¦9böJdB 1dV2 bvDd   " †1d 9 cVHc ) b6H b†-b² (c BdR 'dFCbv1b¢•
              </h2>
              <p className="text-xs text-slate-400">bv(bÖ+ b†1d&E bvDd6'c * b6H bv1d 9 bvDcVHc ) dF,dF( bvDd6'c * d†
            </div>
          </div>
          <button
            onClick={handleReset}
            className="p-2 text-slate-400 hover:text-white hover:bg-white/10 rounded-xl transition cursor
          >
            <X className="w-5 h-5" />
          </button>
        </div>

        {/* Content */}
        <div className="p-6 space-y-6 relative z-10">

          {/* Section 1: Drag & Drop Photo Area */}
          <div>
            <input
              type="file"
              ref={fileInputRef}
              accept="image/*"
              className="hidden"
              onChange={(e) => {
                if (e.target.files && e.target.files[0]) {
                  handleProcessFile(e.target.files[0]);
                }
              }}
            />

            <div
              onDragOver={handleDragOver}
              onDragLeave={handleDragLeave}
              onDrop={handleDrop}
              onClick={() => fileInputRef.current?.click()}
              className={`relative border-2 border-dashed rounded-2xl p-6 sm:p-8 text-center cursor-point
                isDragging
                  ? 'border-amber-400 bg-amber-400/10 scale-[0.99]'
```

FILE (cont.): src/components/UploadQrModal.tsx

```
                  : 'border-amber-500/30 hover:border-amber-400/70 bg-black/50 hover:bg-[#15151c]'
              }`}
            >
              {loading ? (
                <div className="flex flex-col items-center gap-3 text-amber-400">
                  <Loader2 className="w-8 h-8 animate-spin" />
                  <p className="text-sm font-bold text-amber-200">bÆ'c J d&1bv!b’ Hd C b¦4d Jc  'dF@ QR Code...</p>
                  <p className="text-xs text-slate-400">b¦-dFJdB EcVAd†Ab’ 'dF1dV2 d†'c6*bæ1bv, c BdR 'dFCbv1b£Â÷ à
                </div>
              ) : imagePreview ? (
                <div className="flex flex-col items-center gap-2">
                  <img
                    src={imagePreview}
                    alt="Preview"
                    className="w-24 h-24 object-contain rounded-xl border border-amber-500/30 bg-white p-
                  />
                  <span className="text-xs text-amber-300 font-bold underline">bvFd&1 dF'bæ*d¦'c  5d†1b’ #bæ1d“Â÷7
                </div>
              ) : (
                <>
                  <div className="w-12 h-12 rounded-2xl bg-amber-400/15 border border-amber-400/30 text-a
                    <ImageIcon className="w-6 h-6" />
                  </div>
                  <p className="text-sm font-black text-slate-100">bv3bÖ( d†#d Db¢ 5d†1b’ 'dF@ QR dvFbsÂ÷ à
                  <p className="text-xs text-slate-400 mt-1">b6H bvFd&1 dF*cVAbÒ Hbv.b¦Jbv1 cVHc ) dVF bÆGbv2d2 … är
                  <span className="mt-3 inline-flex items-center gap-1.5 px-3 py-1 bg-amber-400/10 border
                    <Sparkles className="w-3 h-3 text-amber-400" />
                    <span>d C b¦4d Jc  Ad†1d¢ Hbv3b¦/c–'b  'dFCbv1b£Â÷7  ãà
                  </span>
                </>
              )}
            </div>
          </div>

          {/* Error Message */}
          {errorMsg && (
            <div className="flex flex-col sm:flex-row items-start sm:items-center justify-between gap-3 p
              <div className="flex items-center gap-2.5">
                <AlertCircle className="w-4 h-4 text-rose-400 flex-shrink-0" />
                <span className="font-semibold">{errorMsg}</span>
              </div>
              {notFoundId && (
                <button
                  type="button"
                  onClick={handleCreateAndEdit}
                  className="px-3 py-1.5 bg-gradient-to-r from-amber-400 to-yellow-500 text-black font-bl
                >
                  <PlusCircle className="w-3.5 h-3.5" />
                  <span>b¦3bÆJdB Gc ' bvDd6Hbò Hb¦9böJdFG bvDb&F</span>
                </button>
              )}
            </div>
          )}

          {/* Divider with High-Contrast Label */}
          <div className="relative flex items-center justify-center py-1">
            <div className="absolute inset-0 flex items-center">
              <div className="w-full border-t border-amber-500/25" />
            </div>
            <span className="relative bg-[#0e0e12] px-4 text-xs font-black text-amber-400 tracking-wide">
              b6H bvCb¦( c BdR 'dFCbv1b¢ Eb†'cF1b’ „”B•
            </span>
          </div>

          {/* Section 2: Manual ID Input with Pristine High-Contrast Colors */}
          <form onSubmit={handleManualSearch} className="space-y-2.5">
            <div className="flex items-center justify-between">
              <label className="block text-xs font-bold text-amber-200/90">
```

FILE (cont.): src/components/UploadQrModal.tsx

```
                b6/bæD dV9c Qd  #d, 1d&E bvDd6'c * (ID):
              </label>
              <span className="text-[11px] text-slate-400 font-mono">
                dV+bvD: I9pFBZwn8Y
              </span>
            </div>

            <div className="flex flex-col sm:flex-row gap-2.5">
              <div className="relative flex-1">
                <input
                  type="text"
                  placeholder="bvCb¦( c BdR 'dFCbv1b¢ Gdf'... dV+dB “— d%§vã…’
                  value={manualId}
                  onChange={(e) => {
                    setManualId(e.target.value);
                    setErrorMsg(null);
                    setNotFoundId(null);
                  }}
                  className="w-full px-4 py-3 bg-black/80 border-2 border-amber-500/40 rounded-2xl text-a
                  dir="ltr"
                  autoFocus
                />
              </div>

              <button
                type="submit"
                disabled={loading || !manualId.trim()}
                className="flex items-center justify-center gap-2 px-6 py-3 bg-gradient-to-r from-amber-4
              >
                {loading ? (
                  <Loader2 className="w-4 h-4 animate-spin text-black" />
                ) : (
                  <Search className="w-4 h-4 text-black" />
                )}
                <span>b†-b² HbÆDb, 'dFCbv1b£Â÷7  ãà
              </button>
            </div>
            <p className="text-[11px] text-slate-400 text-right">
              b†EbÆ1bò 'dFFd&1 c–Dd’ &(bÖ+ d†,dF( bvDd6'c *" c6Jb¦E d *bÒ FbvAc ) bvDb¦9böJdB Eb†'cF1b’ Db¦,böJbò 'd
            </p>
          </form>

        </div>
      </div>
    </div>
  );
}
```