

Oracle for Developers (PL/SQL)

Introduction to Cursors



To understand the following topics:

- Introduction to Cursors
- Implicit Cursors
- Explicit Cursors
- Cursor attributes
- Processing Implicit Cursors and Explicit Cursors
- Cursor with Parameters
- Use of Cursor Variables
- Difference between Cursors and Cursor Variables





A cursor is a “handle” or “name” for a private SQL area

- An SQL area (context area) is an area in the memory in which a parsed statement and other information for processing the statement are kept
- PL/SQL implicitly declares a cursor for all SQL data manipulation statements, including queries that return “only one row”
- For queries that return “more than one row”, you must declare an explicit cursor
- Thus the two types of cursors are:
 - implicit
 - explicit



Implicit Cursor:

- The PL/SQL engine takes care of automatic processing
- PL/SQL implicitly declares cursors for all DML statements
- They are simple SELECT statements and are written in the BEGIN block (executable section) of the PL/SQL
- They are easy to code, and they retrieve exactly one row



Processing Implicit Cursors:

- Oracle implicitly opens a cursor to process each SQL statement that is not associated with an explicitly declared cursor
- This implicit cursor is known as **SQL** cursor
 - Program cannot use the OPEN, FETCH, and CLOSE statements to control the SQL cursor. PL/SQL implicitly does those operations
 - You can use cursor attributes to get information about the most recently executed SQL statement
 - Implicit Cursor is used to process INSERT, UPDATE, DELETE, MERGE and single row SELECT INTO statements



```
BEGIN
```

```
    UPDATE dept SET dname = 'Production' WHERE deptno= 50;
```

```
    IF SQL%NOTFOUND THEN
```

```
        INSERT into department_master VALUES ( 50, 'Production');
```

```
    END IF;
```

```
END;
```

```
BEGIN
```

```
    UPDATE dept SET dname = 'Production' WHERE deptno = 50;
```

```
    IF SQL%ROWCOUNT = 0 THEN
```

```
        INSERT into department_master VALUES ( 50, 'Production');
```

```
    END IF;
```

```
END;
```



Explicit Cursor:

- The set of rows returned by a query can consist of zero, one, or multiple rows, depending on how many rows meet your search criteria
- When a query returns multiple rows, you can explicitly declare a cursor to process the rows
- You can declare a cursor in the declarative part of any PL/SQL block, subprogram, or package
- Processing has to be done by the user



While processing Explicit Cursors you have to perform the following four steps:

- Declare the cursor
- Open the cursor for a query
- Fetch the results into PL/SQL variables
- Close the cursor



Declaring a Cursor:

- Syntax:

```
CURSOR Cursor_Name IS Select_Statement;
```

- Any SELECT statements are legal including JOINS, UNION, and MINUS clauses.
 - SELECT statement should not have an INTO clause.
- Cursor declaration can reference PL/SQL variables in the WHERE clause.
 - The variables (bind variables) used in the WHERE clause must be visible at the point of the cursor.



Opening a Cursor

- Syntax:

```
OPEN Cursor_Name;
```

- When a cursor is opened, the following events occur:
 - Cursor SQL statement executed.
 - The active result set is determined.
 - The active result set pointer is set to the first row.



Fetching from a Cursor

- Syntax:

```
FETCH Cursor_Name INTO List_Of_Variables;  
FETCH Cursor_Name INTO PL/SQL_Record;
```

- The “list of variables” in the INTO clause should match the “column names list” in the SELECT clause of the CURSOR declaration, both in terms of count as well as in datatype.
- After each FETCH, the active set pointer is increased to point to the next row.
 - The end of the active set can be found out by using %NOTFOUND attribute of the cursor.



Closing a Cursor

- Syntax

```
CLOSE Cursor_Name;
```

- Closing a Cursor frees the resources associated with the Cursor.
 - You cannot FETCH from a closed Cursor.
 - You cannot close an already closed Cursor.



Cursor Attributes:

- Explicit cursor attributes return information about the execution of a multi-row query.
- When an “Explicit cursor” or a “cursor variable” is opened, the rows that satisfy the associated query are identified and form the result set.
- Rows are fetched from the result set.
- Examples: %ISOPEN, %FOUND, %NOTFOUND, %ROWCOUNT, etc.



The different types of cursor attributes are described in brief, as follows:

- %ISOPEN
 - %ISOPEN returns TRUE if its cursor or cursor variable is open. Otherwise it returns FALSE.
 - Syntax:

Cur_Name%ISOPEN



Example:

```
DECLARE
    cursor c1 is
        select_statement ;
BEGIN
    IF c1%ISOPEN THEN
        pl/sql_statements ;
    END IF;
END ;
```



%FOUND

- %FOUND yields NULL after a cursor or cursor variable is opened but before the first fetch.
- Thereafter, it yields:
 - TRUE if the last fetch has returned a row, or
 - FALSE if the last fetch has failed to return a row
- Syntax:

```
cur_Name%FOUND
```




Example:

```
DECLARE section;  
  open c1 ;  
  fetch c1 into var_list ;  
IF c1%FOUND THEN  
  pl/sql_statements ;  
END IF ;
```



%NOTFOUND

- %NOTFOUND is the logical opposite of %FOUND.
- %NOTFOUND yields:
 - FALSE if the last fetch has returned a row, or
 - TRUE if the last fetch has failed to return a row
- It is mostly used as an exit condition.
- Syntax:

```
cur_Name%NOTFOUND
```



%ROWCOUNT

- %ROWCOUNT returns number of rows fetched from the cursor area using FETCH command
- %ROWCOUNT is zeroed when its cursor or cursor variable is opened.
 - Before the first fetch, %ROWCOUNT yields 0
 - Thereafter, it yields the number of rows fetched at that point of time
- The number is incremented if the last FETCH has returned a row
- Syntax:

```
cur_Name%ROWCOUNT
```



- They are examples of simple loop statements
- The FETCH statement should be followed by the EXIT condition to avoid infinite looping
- Condition to be checked is `cursor%NOTFOUND`

Examples: LOOP .. END LOOP, WHILE LOOP, etc



```
DECLARE
    cursor c1 is .....
BEGIN
    open cursor c1; /* open the cursor and identify the active result set.*/
LOOP
    fetch c1 into variable_list ;
    -- exit out of the loop when there are no more rows.
    /* exit is done before processing to prevent handling of null rows.*/
    EXIT WHEN C1%NOTFOUND ;
    /* Process the fetched rows using variables and PL/SQLstatements */
END LOOP;
    -- Free resources used by the cursor
    close c1;
    -- commit
    commit;
END;
```



➤ Cursor FOR Loop

```
FOR i IN 1..15                -- Normal for loop
  LOOP
    Process the variables
  END LOOP

FOR i IN Cursor_Name          -- Cursor for loop
  LOOP
    Process the variables
  END LOOP;
```

➤ You can pass parameters to the cursor in a CURSOR FOR loop.

```
FOR Variable in Cursor_Name ( PARAM1 , PARAM 2 ....)
  LOOP
    Process the variables
  END LOOP;
```



SELECT ... FOR UPDATE cursor:

- The method of locking records which are selected for modification, consists of two parts:
 - The FOR UPDATE clause in CURSOR declaration.
 - The WHERE CURRENT OF clause in an UPDATE or DELETE statement.
 - Syntax: FOR UPDATE

CURSOR Cursor_Name IS SELECT FROM ... WHERE .. ORDER BY
FOR UPDATE [OF column names][NOWAIT]

- when

against which the query is fired. The column names are optional.



- If the cursor is declared with a FOR UPDATE clause, the WHERE CURRENT OF clause can be used in an UPDATE or DELETE statement.
 - Syntax: WHERE CURRENT OF

WHERE CURRENT OF Cursor_Name

- The WHERE CURRENT OF clause is used to lock rows in a table.
- When querying multiple tables rows in a table are locked only if the FOR UPDATE OF clause refers to a column in that table.

contd.



For example: Following query locks the staff_master table but not the department_master table.

```
CURSOR C1 is SELECT staff_code, job, dname from emp, dept WHERE  
emp.deptno=dept.deptno FOR UPDATE OF sal;
```

- Using



- To promote professors who earn more than 20000

```
DECLARE
CURSOR c_staff is SELECT staff_code, staff_master.design_code
FROM staff_master, designation_master
WHERE design_name = 'Professor' and staff_sal > 20000
and staff_master.design_code = designation_master.design_code
FOR UPDATE OF staff_master.design_code NOWAIT;
d_code designation_master.design_code%type;
BEGIN
    SELECT design_code into d_code FROM designation_master
    WHERE design_name='Director';
    FOR v_rec in c_staff
    LOOP
        UPDATE staff_master SET design_code = d_code
        WHERE current of c_staff;
    END LOOP;
END;
```



You must use the OPEN statement to pass parameters to a cursor.

- Unless you want to accept default values, each “formal parameter” in the Cursor declaration must have a corresponding “actual parameter” in the OPEN statement.
- The scope of parameters is local to the cursor.
- Syntax:

```
OPEN Cursor-name(param1, param2.....)
```



Parameters are passed to a parametric cursor using the syntax OPEN (param1, param2 ...) as shown in the following example:

```
OPEN C_Select_staff( 800,5000);  
Query → SELECT * from staff_master  
WHERE staff_sal BETWEEN 800 AND 5000;
```



Like a Cursor, a Cursor Variable points to the current row in the result set of a multi-row query

- A Cursor is static whereas a Cursor Variable is dynamic because it is not tied to a specific query
- You can open a Cursor Variable for any type-compatible query
 - This offers more flexibility
- You can assign new values to a Cursor Variable and pass it as a parameter to subprograms, including those in database
 - This offers an easy way to centralize data retrieval



Cursor variables are available to every PL/SQL client.

- You can declare a cursor variable in a PL/SQL host environment, and then pass it as a bind variable to PL/SQL
- Oracle Forms and Oracle Reports, which have a PL/SQL engine, can use cursor variables entirely on the client side



To access the processing information stored in an unnamed work area, you can use:

- an Explicit Cursor, which names the SQL work area or
- a Cursor Variable, which points to any SQL work area

However, Cursors and Cursor Variables are not interoperable.

- a Cursor always refers to the “same query work area”
- a Cursor Variable can refer to “different work areas”



Defining REF CURSOR types:

- Syntax:

```
TYPE ref_type_name IS REF CURSOR RETURN return_type;  
TYPE ref_type_dname IS REF CURSOR;
```

```
DECLARE  
    TYPE DeptCurTyp IS REF CURSOR RETURN  
department_master%ROWTYPE;
```

- where:
 - ref_type_name is a type specifier used in subsequent declarations of cursor variables
 - Return_type must represent a record or a row in a database table.



- REF CURSOR types are strong (restrictive), or weak (non-restrictive)

```
DECLARE
  TYPE staffCurTyp IS REF CURSOR
  RETURN staff_master%ROWTYPE; -- Strong types

  TYPE GenericCurTyp IS REF CURSOR; -- Weak types
```



Declaring Cursor Variables: Example 1:

```
DECLARE  
TYPE DeptCurTyp IS REF CURSOR RETURN  
department_master%ROWTYPE;  
dept_cv DeptCurTyp; -- Declare cursor variable
```

```
TYPE TmpCurTyp IS REF CURSOR RETURN staff_master%ROWTYPE;  
tmp_cv TmpCurTyp; -- Declare cursor variable
```




```
DECLARE
  TYPE staffcurtyp is REF CURSOR RETURN
    staff_master%rowtype;
  staff_cv  staffcurtyp; -- declare cursor variable
  staff_cur  staff_master%rowtype;
BEGIN
  open staff_cv for select * from staff_master;
  LOOP
    EXIT WHEN staff_cv%notfound;
    FETCH staff_cv into staff_cur;
    INSERT into temp_table VALUES (staff_cur.staff_code,
      staff_cur.staff_name,staff_cur.staff_sal);
  END LOOP;
  CLOSE staff_cv;
END;
```



In this lesson, you have learnt:

- Cursor is a “handle” or “name” for a private SQL area
- Implicit cursors are declared for queries that return only one row
- Explicit cursors are declared for queries that return more than one row
- Like a Cursor, a Cursor Variable points to the current row in the result set of a multi-row query
- However, Cursors and Cursor Variables are not interoperable






Question 1: A “Cursor” is static whereas a “Cursor Variable” is dynamic because it is not tied to a specific query.

- True / False

Question 2: %COUNT returns number of rows fetched from the cursor area by using FETCH command.

- True / False





Question 3: Implicit SQL cursor is opened or closed by the program.

- True / False

Question 4: A ____ specifies a Return Type.

Question 5: PL/SQL provides a shortcut via a ____ Loop, which implicitly handles the cursor processing.

