

FLP Deployment Guide

Pending KGPL custom apps — tiles, target mappings and authorization mapping

System	KSD · S/4HANA · client 500
Launchpad space	KGPL CUSTOM APPS
Business catalog	ZKGPL_BC_CUSTOM
Apps in scope	3 custom + 1 standard
Repository	ajaykejriwal1974-oss/Fiori-Apps
Date	20 August 2026
Evidence base	live TADIR, AGR_HIERT, TSTC read over ADT

All three apps are already deployed. Nothing in this guide installs software. Every step below is launchpad configuration and role authorization — the BSPs, OData services and CDS objects are live in KSD today and were verified by direct database read.

1. Where things stand

A read of `TADIR` for `R3TR WAPA` in client 500 confirms 52 Z-namespace BSP applications exist in KSD. Twenty-five of them correspond to app folders in this repository, and all 25 are deployed — including the three built this week. No deployment work is outstanding.

What is missing is launchpad configuration. Three deployed apps have no tile, and their OData V4 service groups are absent from both KGPL roles, so even a correctly built tile would fail authorization at runtime.

1. Where things stand	2
2. Master mapping table	3
3. Prerequisites	3
4. Part A — OData V4 authorization	4
5. Part B — semantic objects	4
6. Part C — target mapping and tile	5
7. Per-app parameter cards	6
8. CO03 — Display Production Order	8
9. Cache invalidation	8
10. Verification	9
11. Troubleshooting	9
Appendix A — live landscape reference	10
Appendix B — the \$TMP problem	11

What each app replaces

App	Replaces	Why it was built
Cancel Production Confirmation	<code>C013</code> <code>ZC011A</code>	The plant runbook records “Correction option – Not available” and “Cancelled option – Not available”. Reverses confirmations in bulk via <code>BAPI_PRODORDCONF_CANCEL</code> .
WIP Batch Close	<code>ZBATCH_CLS</code>	Runbook marks this “Needed”. A WIP batch must be reopened before a confirmation can be reversed, so this and the app above are one workflow.
Label Master	<code>ZLABEL</code>	Maintain Label Master for the dyeing group. RAP managed scenario over <code>ZPP_LABEL</code> .
Display Production Order	—	<code>C003</code> is step 4 of the runbook and has no tile in any space. Standard function; configuration only.

Blocking dependency. Steps in Part A must be completed before the tiles will work. A tile whose service group is missing from the role renders fine and then returns HTTP 403 on first data request — the app looks broken rather than unauthorized, which is a slow bug to chase.

2. Master mapping table

Every value below was read from the live system or from the app manifest in the repository. Type them exactly; the semantic object and action are case-sensitive and the launchpad will not warn you about a mismatch.

Attribute	Cancel Prod. Confirmation	WIP Batch Close	Label Master
Repo folder	production-confirmation-cancel	wip-batch-close	label-master
BSP application	ZPROD_CONF_CAN	ZWIP_BATCH_CLS	ZLABEL_MASTER
Package	\$TMP	\$TMP	\$TMP
Component ID	kejriwal.pp.prodconfcancel	kejriwal.pp.wipbatchclose	kejriwal.pp.labelmaster
Semantic object	ProdConfirmation	WipBatch	LabelMaster
Action	cancelKejriwal	closeKejriwal	maintainKejriwal
Service binding (G4BA)	ZUI_PROD_CONFIRM_04	ZUI_WIP_BATCH_04	ZUI_LABEL_MASTER_04
Service definition	ZUI_PROD_CONFIRMATION	ZUI_WIP_BATCH_MGMT	ZUI_LABEL_MASTER
Root CDS entity	ZI_PROD_CONFIRMATION	ZI_WIP_BATCH_MGMT	ZI_LABEL_MASTER
Base table	AFRU	ZPP_BATCHN	ZPP_LABEL
UI technology	Freestyle UI5 sap.f.DynamicPage	Freestyle UI5 sap.f.DynamicPage	Fiori Elements ListReport / ObjectPage
Tile title	Cancel Production Confirmation	WIP Batch Close	Label Master
Tile subtitle	KEJRIWAL custom	KEJRIWAL custom	KEJRIWAL master data
Icon	sap-icon://undo	sap-icon://locked	sap-icon://tags

URLs (lower case — ICF nodes are case-sensitive)

Cancel Prod. Confirmation — UI	/sap/bc/ui5_ui5/sap/zprod_conf_can
— OData V4	/sap/opu/odata4/sap/zui_prod_confirm_04/srvd/sap/zui_prod_confirmation/0001/
WIP Batch Close — UI	/sap/bc/ui5_ui5/sap/zwip_batch_cls
— OData V4	/sap/opu/odata4/sap/zui_wip_batch_04/srvd/sap/zui_wip_batch_mgmt/0001/
Label Master — UI	/sap/bc/ui5_ui5/sap/zlabel_master
— OData V4	/sap/opu/odata4/sap/zui_label_master_04/srvd/sap/zui_label_master/0001/

3. Prerequisites

Check	How	Expected
BSP applications exist	SE80 → BSP Application	All three found
Service bindings published	/IWFND/V4_ADMIN	Status <i>Published</i>
ICF nodes active	SICF → ui5_ui5/sap	Green, not grey
Business catalog reachable	/n/UI2/FLPD_CUST	ZKGPL_BC_CUSTOM opens
You can edit roles	PFCG	Change access to ZKGPL_ALL

Authorization needed for the person doing this: S_DEVELOP for the launchpad designer, S_USER_AGR / S_USER_AUT for PFCG role maintenance, and change access in client 500. This is normally a Basis or security task, not a developer one.

4. Part A — OData V4 authorization

Do this first. A tile without its service group in the role will render and then fail on the first data call.

KSD carries two KGPL roles. Neither contains the three new service groups today — verified by reading AGR_HIERT :

Role	Description	V4 groups today	Notes
ZKGPL_ALL	KGPL ALL APPS	26	Carries the catalog assignment for the space. Must be updated.
ZKGPL_BR_PROCURE	KEJRIWAL FIORI APPS	~30	Newer role; carries the five ZKGPL_FIORI apps. Update for parity.

Procedure — repeat for each of the three service groups

- 1 Run PFCG , open role ZKGPL_ALL , click **Change**.
- 2 Go to the **Menu** tab.
- 3 Position the cursor on the folder that holds the existing R3TR G4BA entries (the catalog node, object ID 2).
- 4 Choose **Insert Node → Authorization Default**.
- 5 In the dialog select object type **TADIR Service** and enter:
Program ID: R3TR Object Type: G4BA Object Name: ZUI_PROD_CONFIRM_04
- 6 Repeat for ZUI_WIP_BATCH_04 and ZUI_LABEL_MASTER_04 .
- 7 Save the menu.
- 8 Go to the **Authorizations** tab, click **Change Authorization Data**, accept the merge of new default values, then **Generate** the profile.
- 9 Save the role. Repeat the whole sequence for ZKGPL_BR_PROCURE .
- 10 Have each affected user log off and back on, or run PFUD for a user master comparison.

If the merge dialog offers “Read old status and merge with new data”, take it. Choosing “Read new data” discards the manual authorization adjustments already made in these roles.

Verifying Part A

After generation, the three entries should be visible in the role menu. To confirm from the database side, the role menu text table should return three new rows:

SE16N → AGR_HIERT , filter AGR_NAME = ZKGPL_ALL , TEXT = R3TR G4BA ZUI_* — expect 29 rows, up from 26.

5. Part B — semantic objects

The three semantic objects — ProdConfirmation , WipBatch , LabelMaster — are not registered in /UI2/SEM0BJ . Neither are the ones used by the five apps already running in production (PalletStock , DeliveryChallan , ReturnBox , PurchaseRegister , PackingUnit).

Registration is therefore **optional** — the launchpad accepts an unregistered semantic object with a warning, which is how every existing KGPL tile works today. Registering them removes the warning and makes the intent discoverable in /UI2/FLIA .

- 1 Run /n/UI2/SEM0BJ .

- 2 Click **New Entries**.
- 3 Add three rows, leaving the component blank: `ProdConfirmation`, `WipBatch`, `LabelMaster`.
- 4 Save to a customizing request.

6. Part C — target mapping and tile

Both live in the same business catalog. The role menu entry for this catalog reads `X-SAP-UI2-CATALOGPAGE:ZKGPL_BC_CUSTOM`, which means the launchpad **page is generated from the catalog**. There is no separate group to maintain — a tile added to the catalog appears in KGPL CUSTOM APPS automatically.

C1 — create the target mapping

- 1 Run `/n/UI2/FLPD_CUST`.
- 2 Select catalog `ZKGPL_BC_CUSTOM` in the left pane.
- 3 Open the **Target Mappings** tab and click + (Create Target Mapping).
- 4 Fill in from the parameter card in section 7: **Semantic Object**, **Action**, **Application Type** = *SAPUI5 Fiori App*, **Title**, **URL**, **ID** (the component ID).
- 5 Under **Device Types** tick Desktop, Tablet and Phone.
- 6 Leave **Parameters** empty — none of the three apps take startup parameters.
- 7 Save.

C2 — create the tile

- 1 Still in `ZKGPL_BC_CUSTOM`, open the **Tiles** tab and click +.
- 2 Choose tile type **App Launcher – Static**.
- 3 Enter **Title**, **Subtitle** and **Icon** from the parameter card.
- 4 Leave **Information** and **Keywords** blank, or add a keyword to help search.
- 5 Under **Navigation**, set **Use semantic object navigation** = Yes, then enter the same **Semantic Object** and **Action** used in C1.
- 6 Save.

The tile and the target mapping are matched only by the semantic object and action strings. A typo in either produces a tile that opens a blank page with “the app could not be opened because the navigation target is not available”. Copy and paste rather than retype.

7. Per-app parameter cards

Each card contains everything to be typed into the two dialogs in section 6. Fields not listed are left at their default.

Cancel Production Confirmation FREESTYLE UI5

Target mapping

Semantic Object	ProdConfirmation
Action	cancelKejriwal
Application Type	SAPUI5 Fiori App
Title	Cancel Production Confirmation
URL	/sap/bc/ui5_ui5/sap/zprod_conf_can
ID	kejriwal.pp.prodconfcancel
Device Types	Desktop, Tablet, Phone

Tile — App Launcher, Static

Title	Cancel Production Confirmation
Subtitle	KEJRIWAL custom
Icon	sap-icon://undo
Semantic Object / Action	ProdConfirmation / cancelKejriwal

Backend: service group `ZUI_PROD_CONFIRM_04`, root entity `ZI_PROD_CONFIRMATION` over `AFRU`, unmanaged behaviour pool `ZBP_I_PROD_CONFIRMATION` calling `BAPI_PRODORDCONF_CANCEL`. The list excludes rows where `STOKZ = 'X'` so reversal documents are not offered for re-reversal.

WIP Batch Close FREESTYLE UI5

Target mapping

Semantic Object	WipBatch
Action	closeKejriwal
Application Type	SAPUI5 Fiori App
Title	WIP Batch Close
URL	/sap/bc/ui5_ui5/sap/zwip_batch_cls
ID	kejriwal.pp.wipbatchclose
Device Types	Desktop, Tablet, Phone

Tile — App Launcher, Static

Title	WIP Batch Close
Subtitle	KEJRIWAL custom
Icon	sap-icon://locked
Semantic Object / Action	WipBatch / closeKejriwal

Do not confuse this with the existing *WIP Batch* tile. That one is the read-only analytics report over batch status. This app writes the closed flag and must have its own tile with a distinct title.

Backend: service group `ZUI_WIP_BATCH_04`, entity `ZI_WIP_BATCH_MGMT` over `ZPP_BATCHN` joined to `T001K` for company code. Actions `closeBatches` and `reopenBatches`; reopen requires a non-blank reason.

Label Master FIORI ELEMENTS

Target mapping

Semantic Object	LabelMaster
Action	maintainKejriwal
Application Type	SAPUI5 Fiori App
Title	Label Master
URL	/sap/bc/ui5_ui5/sap/zlabel_master
ID	kejriwal.pp.labelmaster
Device Types	Desktop, Tablet, Phone

Tile — App Launcher, Static

Title	Label Master
Subtitle	KEJRIWAL master data
Icon	sap-icon://tags
Semantic Object / Action	LabelMaster / maintainKejriwal

Backend: service group `ZUI_LABEL_MASTER_04`, RAP managed scenario on `ZPP_LABEL` with keys `WERKS` / `TYPE` / `IP`. This is a **printer** master, not a label-layout master — the record identifies a plant, a label type and the printer IP address. Because it is a Fiori Elements list report, it also honours variant management, so users can save their own plant filter.

8. CO03 — Display Production Order

C003 is step 4 of the plant runbook and has no tile anywhere. It is standard SAP and needs no development. The transaction exists in KSD (SAPLC0K01 , screen 0110).

The reliable route is a SAP GUI transaction tile in the same catalog:

- 1 **Check for an existing mapping first.** Run `/n/UI2/FLIA` and resolve `ProductionOrder-displayFactSheet`. The semantic object `ProductionOrder` is SAP standard (component `PP-SFC`) and a shipped target mapping may already exist. If one resolves, you only need a tile pointing at it — skip to step 4.
- 2 If nothing resolves, create a target mapping in `/n/UI2/FLPD_CUST`, catalog `ZKGPL_BC_CUSTOM`, with **Semantic Object** `ProductionOrder` and **Action** `displayKejriwal`. Use the custom action rather than `display` so a future SAP mapping on the standard action cannot collide with yours.
- 3 Set **Application Type** = *Transaction* and **Transaction Code** = `C003` (verified present in KSD as `SAPLC0K01`, screen 0110).
- 4 Set **System Alias** to the alias used by the other GUI tiles in this catalog — blank means the local system, which is correct for an embedded deployment.
- 5 Create a static App Launcher tile titled **Display Production Order**, subtitle **Production**, icon `sap-icon://factory`, pointing at whichever semantic object and action resolved in step 1 or was created in step 2.

Before creating this, check the SAP Fiori Apps Library for a native app for your exact release — if one is available it gives a better experience than the GUI-for-HTML fallback. Do not assume an app ID; look it up against the release level of KSD.

9. Cache invalidation

Launchpad content is heavily cached at four layers. Skipping any one of these produces the classic “I saved the tile but it isn't there”.

Transaction / report	What it clears	When
<code>/n/UI2/INVAL_CACHES</code>	Global launchpad caches	After every catalog change
<code>/n/UI2/CACHE_DEL</code>	Client-side FLP cache	After every catalog change
<code>SE38 → /UI5/APP_INDEX_CALCULATE</code>	UI5 app index	After a new BSP or component ID appears
<code>/n/IWFND/CACHE_CLEANUP</code>	Gateway metadata cache	If <code>\$metadata</code> looks stale
<code>/n/IWBEP/CACHE_CLEANUP</code>	Backend metadata cache	If <code>\$metadata</code> looks stale

Run `/UI5/APP_INDEX_CALCULATE` with **full calculation** selected, not the delta run. The three components are new to the index and a delta run has been observed to miss BSPs in `$TMP`.

Finally, clear the browser: hard reload, or open the launchpad once with `?sap-ui-xx-componentPreload=off&sap-language=EN` appended to force a fresh descriptor read.

10. Verification

Work down this list. Each step isolates a different failure layer, so the first one that fails tells you where the problem is.

#	Test	Pass	If it fails
1	Open the BSP directly: <code>/sap/bc/ui5_ui5/sap/zprod_conf_can/index.html</code>	App loads, table renders	Deployment or ICF problem, not FLP
2	Open <code>\$metadata</code> for the V4 service	XML returns, no 403	Service not published — <code>/IWFND/V4_ADMIN</code>
3	<code>/n/UI2/FLIA</code> , intent <code>ProdConfirmation-cancelKejriwal</code>	Resolves to the target mapping	Target mapping typo or catalog not in role
4	Launchpad, navigate to <code>#ProdConfirmation-cancelKejriwal</code>	App opens	Cache — redo section 9
5	Tile visible in KGPL CUSTOM APPS	Tile appears	User master comparison — <code>PFUD</code>
6	Press Go ; data loads	Rows returned	Missing <code>G4BA</code> in role — Part A
7	Company code and plant filters return the right subset	Filtering works	Query class filter handling
8	Search box filters the list	List narrows	<code>get_search_expression</code> not wired

Functional test for Cancel Production Confirmation. Pick one recent confirmation, note its `RUECK` and `RMZHL`, cancel it, then check `AFRU` in `SE16N`. The original row should now carry a filled `STZHL`, and a new row should exist with `STOKZ = 'X'`. Do this in a sandbox order, not a live one.

Functional test for WIP Batch Close. Close one batch, confirm the closed flag in `ZPP_BATCHN`, then reopen it with a reason and confirm the flag clears. The reopen path is the one the plant needs before a confirmation can be reversed, so test it in that order.

11. Troubleshooting

Symptom	Most likely cause	Fix
Tile appears, opens a blank page	Target mapping missing or action mismatched	<code>/UI2/FLIA</code> on the intent
"Navigation target not available"	Semantic object or action typo between tile and mapping	Compare both strings character by character
App opens, table stays empty, no error	Binding suspended, or filters exclude everything	Check the browser network tab for the <code>\$batch</code> call
HTTP 403 on the data request	<code>R3TR G4BA</code> entry missing from the role	Part A, then <code>PFUD</code>
App renders with no visible table at all	Component container height — a known issue in this project	Confirm <code>index.html</code> carries the <code>height: 100%</code> block
Tile saved but never appears	Cache	All five steps in section 9, then hard reload
Works for you, not for a plant user	Role not assigned or user master not compared	<code>SU01</code> role check, then <code>PFUD</code>
Value help dropdown is empty	Value help entity not exposed in the same service group	Check <code>ValueListReferences</code> in <code>\$metadata</code>

Appendix A — live landscape reference

Read from KSD client 500 on 20 August 2026. Useful when someone asks “what else is out there?”

Z-namespace BSP applications by package

Package	Count	Meaning
ZKGPL_FIORI	22	Transportable. 5 have repo source, 17 do not.
\$TMP	20	All have repo source. Cannot transport to KSQ.
ZFIORI	7	Older dashboards, author ABAP_DEV . No KGPL tile.
Z001	2	Barcode scanning. No KGPL tile.
ZSOL_DASH	1	ZFIORI2 . No KGPL tile.

The 17 unversioned BSPs in ZKGPL_FIORI

Each backs a live tile and has no UI5 source anywhere. A redeploy from any machine overwrites them irrecoverably.

BSP	Tile	BSP	Tile
ZDD_SHADE_APP	Shade Master	ZGTPASS_APP	Gate Pass
ZRECIPE_APP	Recipe Master	ZTRUCK_APP	Truck Master
ZJOB_APP	Job Master	ZDIGISIGN_APP	Digital Signature
ZSCHEDULE_APP	Schedule Master	ZCFORM_APP	C-Form
ZMERGE_APP	Merge Details	ZVFORM_APP	GST Tax
ZCHECKBY_APP	Checked / Packed By	ZSALESDOC_APP	Sales Document Status
ZPACKMAT_APP	Packing Material Master	ZPACKING_LIST	Packing List
ZTRANSP_APP	Transport Code	ZACCGRP_APP	Account Grouping
ZEXPORT_APP	Export Details		

Role and catalog wiring as it exists today

Business catalog	ZKGPL_BC_CUSTOM
Role menu entry	X-SAP-UI2-CATALOGPAGE:ZKGPL_BC_CUSTOM?AUTH_DEFAULTS=X&DEST_FES=
Carried by role	ZKGPL_ALL – “KGPL ALL APPS”
Second role	ZKGPL_BR_PROCURE – “KEJRIWAL FIORI APPS”
Users assigned	MD, ITADMIN, ZTEST_KGPL

Only three users hold these roles. The launchpad is still a pilot. Before the plant goes live, the roles need assigning to the real user groups (KID_PP2 , KID_OM2 , KID_SD2 and their colleagues), and that will surface authorization gaps that three admin users never hit.

Appendix B — the \$TMP problem

This is outside the scope of tile creation but it is the largest risk in the landscape, and it is worth deciding on before more tiles are added.

Twenty of the twenty-five repo apps sit in \$TMP. Objects in \$TMP are local: they cannot be captured in a transport request and therefore cannot reach KSQ or any downstream client. Everything works in KSD and nothing moves.

Seventeen BSPs in ZKGPL_FIORI have no source in version control. They are transportable but unrecoverable — if one is overwritten or deleted there is no copy to restore from.

Together, 37 of the 52 live BSPs are in one of these two states.

Remediation, in the order I would do it

- 1 Reprint the 20 \$TMP apps to ZKGPL_FIORI.** In SE80, open each BSP, choose *Change package*, assign ZKGPL_FIORI and a workbench request. Alternatively update `ui5-deploy.yaml` in each app folder and redeploy — slower, but it keeps the repo and the system in agreement.
- 2 Download the 17 orphans into apps/.** Either pull the BSP sources through abapGit into the existing repository, or export each BSP from SE80. Once they are in git, a redeploy accident is recoverable.
- 3 Then and only then, cut a transport to KSQ.** Attempting it before step 1 silently drops 20 apps.

The three apps in this guide are themselves in \$TMP. The tiles you create will work in KSD, but neither the tiles nor the apps will transport until step 1 is done. If the plan is to go live from KSD directly, that is fine — but it should be a decision rather than an accident.

Remaining development items

Item	Type	Detail
Gap 5 — ZVLMOVE	Development	The Post Goods Movement handler moves HU <i>contents</i> via VEPO and leaves VEKP pointing at the old storage location. Analysed and specified, not built.
DCL roles	Security	@AccessControl.authorizationCheck: #CHECK is set everywhere but no DCL exists, so the check passes silently. Every user sees every plant.
Search verification	Test	Metadata proves the search box renders. Confirm it actually filters on each of the four query-class apps.

Prepared from a live read of KSD client 500 and the Fiori-Apps repository. Values in this document reflect the system as of 20 August 2026; if a BSP is redeployed with a different component ID, the target mapping must be updated to match.