

QC Apps Deployment Guide

Raw Material / Post-Dyeing / Post-Winding QC
BSP deploy, PFCG check, launchpad tiles

System	KSD · S/4HANA · client 500
Launchpad space	KGPL CUSTOM APPS
Business catalog	ZKGPL_BC_CUSTOM
Service binding	ZUI_QC_INSPECTION_04 (published)
Repository	ajaykejriwal1974-oss/Fiori-Apps
Date	21 August 2026

Backend is done. The RAP objects, service definition and service binding are active and published, verified by direct read of KSD (TADIR SRVB + G4BA entries for `ZUI_QC_INSPECTION_04`). This guide covers only what is left: the three UI5 apps and their launchpad tiles.

1. Where things stand

None of the three BSP applications exist in KSD yet — a live search of `ZQC_*` against the repository information system returned zero results. This is genuinely new deployment work, unlike the earlier three apps (Cancel Production Confirmation, WIP Batch Close, Label Master) which were already live when their FLP guide was written.

Three code-level gaps were found and fixed in this pass, before writing this guide, so the apps are ready to deploy rather than deployed-then-patched:

- **Plant value help.** `onPlantHelp` in all three worklist controllers was a stub (`MessageToast.show("Plant value help")`), not wired to any control. Replaced with a working `SelectDialog` over `/PlantVH ( ZI_VH_PLANT )`, the same pattern already used in the `batch-status` app. The Plant input now carries `showValueHelp="true"` `valueHelpRequest=".onPlantVH"`.
- **Hard-coded operation number.** `onRecord` in all three detail controllers sent a literal `"00000010"` regardless of what operation the lot's characteristics actually belong to. It now reads `OperationNumber` off the first bound characteristic row in the lot's own unfiltered characteristics list, which is correct because each of these three apps is scoped to one inspection stage and therefore one operation per lot.
- **Missing UD_SELECTED_SET.** `BAPI_INSPLOT_SETUSAGEDECISION` needs `UD_SELECTED_SET` in addition to code group and code — the code group alone does not identify a code, because the same group can appear in more than one selected set. This field was added to `ZD_QC_USAGE_DECISION` earlier, but the UI never actually sent it. It now sends the constant `UD_SELECTED_SET = "ZQC_UD"`. This value has **not** been confirmed against `QS51` customizing — if Usage Decision posting fails with a selected-set error, this is the one constant to correct (see section 9).

1. Where things stand	1
2. Master mapping table	2
3. Prerequisites	2
4. Part A — deploy the three BSPs	3
5. Part B — confirm authorization	3
6. Part C — target mapping and tile	4
7. Per-app parameter cards	4
8. Cache invalidation	6
9. Verification and known open items	6
10. Troubleshooting	7

2. Master mapping table

Every value below comes from the app manifests and `ui5-deploy.yaml` files already committed in the repository — nothing here needs to be invented at deployment time except the transport request number.

Attribute	Raw Material QC	Post-Dyeing QC	Post-Winding QC
Repo folder	qc-raw-material	qc-post-dyeing	qc-post-winding
BSP application	ZQC_RAW_DYE	ZQC_POST_DYE	ZQC_POST_WIND
Package	ZKGPL_FIORI	ZKGPL_FIORI	ZKGPL_FIORI
Component ID	kejriwal.qm.qcrawmaterial	kejriwal.qm.qcpostdyeing	kejriwal.qm.qcpostwinding
Semantic object	QcRawMaterial	QcPostDyeing	QcPostWinding
Action	inspectKejriwal (same action on all three — the semantic object is what distinguishes them)		
Fixed InspectionType	Stage 1 (raw material)	Stage 2 (post-dyeing)	Stage 3 (post-winding)

Backend is shared: all three point at service binding `ZUI_QC_INSPECTION_04` / service definition `ZUI_QC_INSPECTION` / root entity `ZI_QC_INSP_LOT`. One service, three stage-specific UIs — each app filters `InspectionType` to its own stage in `_buildFilters()`.

URLs (lower case — ICF nodes are case-sensitive)

Raw Material QC — UI	/sap/bc/ui5_ui5/sap/zqc_raw_dye
Post-Dyeing QC — UI	/sap/bc/ui5_ui5/sap/zqc_post_dye
Post-Winding QC — UI	/sap/bc/ui5_ui5/sap/zqc_post_wind
OData V4 (all three)	/sap/opu/odata4/sap/zui_qc_inspection_04/srvc/sap/zui_qc_inspection/0001/

3. Prerequisites

Check	How	Expected
Service binding published	/IWFND/V4_ADMIN	ZUI_QC_INSPECTION_04 , status <i>Published</i>
Transport request available	SE09 / SE01	An open workbench request in your name, target ZKGPL_FIORI package
Network reachability	—	Deploy must run from a machine that can reach 192.168.0.19:8000 — the cloud session cannot
ICF nodes active	SICF → ui5_ui5/sap	Green, not grey
Business catalog reachable	/n/UI2/FLPD_CUST	ZKGPL_BC_CUSTOM opens

Transport, not \$TMP. Unlike the three earlier apps (which sit in `$TMP` and can never transport to KSQ), these three are already configured in `ui5-deploy.yaml` to target `ZKGPL_FIORI`, a transportable package. That means each deploy needs a real transport request number in place of the `<TRANSPORT>` placeholder currently in all three `ui5-deploy.yaml` files — create one in `SE09` first if you do not already have one open for this work.

4. Part A — deploy the three BSPs

Two ways to do this; use whichever has worked before in this project. Repeat once per app.

Option 1 — command line (`fiori deploy`)

- 1 On a machine with network access to `192.168.0.19:8000` (VPN connected), open a terminal in `apps/<app-folder>`.
- 2 Edit `ui5-deploy.yaml` and replace `<TRANSPORT>` with the real transport request number.
- 3 Run `npm install` once per app folder if `node_modules` is not already present.
- 4 Run `npm run deploy`. This runs `fiori deploy --config ui5-deploy.yaml`, which builds the app and uploads it as BSP application `ZQC_RAW_DYE` / `ZQC_POST_DYE` / `ZQC_POST_WIND` in package `ZKGPL_FIORI`.
- 5 Confirm in `SE80` → BSP Application that the app now exists and contains the expected files.

Option 2 — Eclipse (ADT “Deploy to SAPUI5 ABAP Repository”)

- 1 In Eclipse, right-click the app's `webapp` folder (needs the SAPUI5 Team Provider set up against the ABAP project already used for the RAP work this session).
- 2 **Team** → **SAPUI5** → **Deploy to SAPUI5 ABAP Repository**.
- 3 Enter Name `ZQC_RAW_DYE` (or the matching name per app), Package `ZKGPL_FIORI`, and the transport request.
- 4 Finish, and watch the Console view for a successful upload.

Whichever option is used, keep it the same for all three apps and for any future redeploy — mixing command-line and Eclipse deploys against the same BSP has not caused a problem in this project so far, but there is no reason to test that.

5. Part B — confirm authorization

This part is already done. `ZUI_QC_INSPECTION_04`'s `G4BA` service group was inserted into role `ZKGPL_BR_PROCURE` (the role used for all Fiori apps in this project) via **PFCG** → **Menu** → **Insert Node** → **Authorization Default** → **TADIR Service**, the profile was regenerated, and the user confirmed completion before this UI work began.

Sanity check only, no action expected: `SE16N` → `AGR_HIERT`, filter `AGR_NAME = ZKGPL_BR_PROCURE`, `TEXT = R3TR G4BA ZUI_QC_INSPECTION_04` — should return one row.

6. Part C — target mapping and tile

Same catalog as every other KGPL app — `ZKGPL_BC_CUSTOM`, generated as a page automatically, no separate group to maintain.

C1 — create the target mapping (repeat three times)

- 1 Run `/n/UI2/FLPD_CUST`.
- 2 Select catalog `ZKGPL_BC_CUSTOM` in the left pane.
- 3 Open the **Target Mappings** tab and click +.
- 4 Fill in from the parameter card in section 7: **Semantic Object**, **Action** = `inspectKejriwal`, **Application Type** = *SAPUI5 Fiori App*, **Title**, **URL**, **ID** (component ID).
- 5 Under **Device Types** tick Desktop and Tablet only — the three manifests declare `"phone": false`, matching how narrow the characteristics lists are to read on a phone screen.
- 6 Leave **Parameters** empty.
- 7 Save.

C2 — create the tile (repeat three times)

- 1 Still in `ZKGPL_BC_CUSTOM`, open the **Tiles** tab and click +.
- 2 Choose tile type **App Launcher – Static**.
- 3 Enter **Title**, **Subtitle** and **Icon** from the parameter card.
- 4 Under **Navigation**, set **Use semantic object navigation** = Yes, then enter the same **Semantic Object** and **Action** used in C1.
- 5 Save.

The tile and the target mapping are matched only by the semantic object and action strings. Copy and paste rather than retype — a typo produces a tile that opens to “the app could not be opened because the navigation target is not available”.

7. Per-app parameter cards

Raw Material QC FREESTYLE UI5

Target mapping

Semantic Object	QcRawMaterial
Action	inspectKejriwal
Application Type	SAPUI5 Fiori App
Title	Raw Material QC
URL	/sap/bc/ui5_ui5/sap/zqc_raw_dye
ID	kejriwal.qm.qcrawmaterial
Device Types	Desktop, Tablet

Tile — App Launcher, Static

Title	Raw Material QC
Subtitle	Incoming greige yarn inspection
Icon	sap-icon://inspect
Semantic Object / Action	QcRawMaterial / inspectKejriwal

Records: boiling water shrinkage (5-package spread, substitute for the cut dye-uniformity test) plus the standard characteristic list. Grade is a 3-way segmented button (AA/A/B) rather than a dropdown.

Post-Dyeing QC FREESTYLE UI5

Target mapping

Semantic Object	QcPostDyeing
Action	inspectKejriwal
Application Type	SAPUI5 Fiori App
Title	Post-Dyeing QC
URL	/sap/bc/ui5_ui5/sap/zqc_post_dye
ID	kejriwal.qm.qcpostdyeing
Device Types	Desktop, Tablet

Tile — App Launcher, Static

Title	Post-Dyeing QC
Subtitle	Shade and fastness inspection
Icon	sap-icon://palette
Semantic Object / Action	QcPostDyeing / inspectKejriwal

Records: delta E vs approved standard, shade variation by carrier position (not just package count), and a fastness battery panel that only opens for the qualifying batch of a recipe (currently always defaulted to “first of recipe = true” until the recipe link is confirmed — open item, see section 9).

Post-Winding QC

FREESTYLE UI5

Target mapping

Semantic Object	QcPostWinding
Action	inspectKejriwal
Application Type	SAPUI5 Fiori App
Title	Post-Winding QC
URL	/sap/bc/ui5_ui5/sap/zqc_post_wind
ID	kejriwal.qm.qcpostwinding
Device Types	Desktop, Tablet

Tile — App Launcher, Static

Title	Post-Winding QC
Subtitle	Wound cone release inspection
Icon	sap-icon://cargo-train
Semantic Object / Action	QcPostWinding / inspectKejriwal

Records: denier / elongation / broken filaments compared against the incoming (stage 1) figures for the same greige lot — the delta is what winding did, not the absolute value. Currently the incoming figures never load (`_loadIncoming` is a stub returning `null`) until the batch-to-greige-lot link is confirmed — open item, see section 9.

8. Cache invalidation

Transaction / report	What it clears	When
/n/UI2/INVAL_CACHES	Global launchpad caches	After every catalog change
/n/UI2/CACHE_DEL	Client-side FLP cache	After every catalog change
SE38 → /UI5/APP_INDEX_CALCULATE	UI5 app index	After each new BSP appears — use full calculation, not delta
/n/IWFND/CACHE_CLEANUP	Gateway metadata cache	If <code>\$metadata</code> looks stale

9. Verification and known open items

#	Test	Pass	If it fails
1	Open each BSP directly, e.g. <code>/sap/bc/ui5_ui5/sap/zqc_raw_dye/index.html</code>	App loads, worklist appears after Go	Deployment or ICF problem
2	Plant field — press the value help icon	Dialog opens, lists plants, picks one into the field	Check <code>PlantVH</code> is really exposed in <code>\$metadata</code>
3	Open a lot, change a result, Save	<code>recordSingleResult</code> succeeds, list refreshes	Check the action namespace still matches <code>\$metadata</code>
4	Press Record Results on a lot with characteristics loaded	Succeeds against the lot's real operation, not a hard-coded one	Confirm the unfiltered list id used per app (<code>lstChars</code> / <code>lst0ther</code> / <code>lstGeometry</code>) still exists in the view
5	Press Usage Decision, pick a code	<code>setUsageDecision</code> succeeds	If it fails naming the selected set, correct <code>UD_SELECTED_SET</code> in the controller (see below)
6	Tile visible in KGPL CUSTOM APPS, opens each app	Tile appears, app opens	Cache — redo section 8

Confirm `UD_SELECTED_SET` against `QS51`. All three apps currently send the constant `"ZQC_UD"`, matching the existing `ZQC_UD` code group by name. This is a reasonable default, not a verified one — the BAPI will reject it cleanly with an error message if it is wrong, it will not silently misfile a usage decision. The constant lives at the top of each `Detail.controller.js`, one line to fix in all three files.

Still open from the QM master-data workbook (item 8, unchanged by this pass): the grade code list and the coning-oil target block in `QS21`. Neither blocks deploying or opening the apps — the worklists and characteristic lists render regardless — but the grade segmented button and some target/tolerance readouts will show as “not maintained” until that customizing is done.

Post-Dyeing recipe qualification and Post-Winding incoming figures both depend on a batch-to-recipe / batch-to-grey-lot link that is not yet confirmed in the data model (also part of item 8). Post-Dyeing defaults to “first of recipe” = true (over-testing, the safe direction). Post-Winding's incoming-figure deltas simply do not render until this is resolved — the absolute values still record correctly.

10. Troubleshooting

Symptom	Most likely cause	Fix
Tile appears, opens a blank page	Target mapping missing or action mismatched	<code>/UI2/FLIA</code> on the intent
HTTP 403 on the data request	<code>R3TR G4BA</code> entry missing from the role	Re-check section 5, then <code>PFUD</code>
Value help icon does nothing	<code>PlantVH</code> not in the same service group, or a stale UI5 cache	Check <code>ValueListReferences</code> in <code>\$metadata</code> ; hard-reload the browser
Record Results always uses the wrong operation	The lot has characteristics across more than one operation, which the current single-operation assumption does not handle	Confirm this against a real multi-operation lot; if it happens, the fix needs to group by operation rather than take the first row
Usage Decision fails with a selected-set error	<code>UD_SELECTED_SET = "ZQC_UD"</code> is wrong for this landscape	Look up the real value in <code>QS51</code> and correct the one constant
Tile saved but never appears	Cache	All steps in section 8, then hard reload

Prepared from a live read of KSD client 500 and the `Fiori-Apps` repository, 21 August 2026. If a BSP is redeployed with a different component ID, the target mapping in section 6 must be updated to match.