

KEJRIWAL Fiori — ADT Activation Checklist

The four system-side follow-ups + development-server runbook

Clean-core extension package · KSQ/KHQ · client 500

Generated 26 June 2026 · companion to KEJRIWAL_Fiori_Module_Plan.pdf

Repository: [ajaykejriwal1974-oss/fiori-apps](https://github.com/ajaykejriwal1974-oss/fiori-apps) (merged to main) · source: docs/ADT-ACTIVATION-CHECKLIST.md

How the four follow-ups interleave

They are not four independent passes — FU#3 happens *inside* FU#2, and FU#1 depends on FU#2 finishing. Inventory to activate: **123** CDS views, **52** behavior definitions, **28** behavior pools, **26** service definitions (13 managed masters + 13 unmanaged transactional), 0 metadata extensions, 0 DCL.

```
FU#2  Activate CDS -> BDEF -> behavior pool -> SRVD
      +- FU#3  Confirm VERIFY markers (surface as activation errors on the unmanaged pools)
FU#1  Create + activate service bindings, fill manifest + SERVICE_NS
FU#4  ATC clean run, then publish tiles / assign roles
```

FU#2 — Activate the CDS / behavior / service objects (first)

Activate bottom-up the first time so errors stay local:

1. Interface CDS views ZI_* (over the legacy Z-tables + released I_* views).
2. Projection CDS views ZC_* — depend on the interface views.
3. Interface behavior definitions ZI_*.bdef.
4. Behavior pool classes ZBP_I_* — the 13 managed masters activate cleanly; the 13 unmanaged pools must syntax-check against the release DDIC structures (this is where FU#3 bites).
5. Projection behavior definitions ZC_*.bdef.
6. Service definitions ZUI_*.srvd (26).

FU#3 — Confirm the VERIFY markers (inside FU#2)

Release-specific BAPI/DDIC details CI cannot check (it validates block balance, not type names). Each is a VERIFY comment in the source; wrong names fail activation on that pool.

Behavior pool	Confirm
goods-movement-hu-rap / zbp_i_hu_item	gm_code ('04' transfer / '01' GR) + move type for the box scenario
post-packing-gr-rap / zbp_i_post_packing_gr	GR gm_code '01' / movement type for the post-packing GR
mtos-process-rap / zbp_i_mtos_process	BAPI_MATPHYSINV_CREATE_MULT head/item/docs structure names + head ↔ item linkage
batch-status-rap / zbp_i_batch_status	ZPP_BATCHN key (BATCHNO ± GJAHR); BAPI_BATCH_CHANGE MATERIAL vs MATERIAL_LONG width
palletization-rap / zbp_i_palletization	BAPI_HU_CREATE / BAPI_HU_PACK parameter names
packing-detail-rap / zbp_i_packing_detail	BAPI_HU_CREATE / BAPI_HU_PACK + BAPI_HU_REPACK_ITM interface
hu-inbound-rap / zbp_i_hu_inbound	BAPI_INB_DELIVERY_CONFIRM_DEC bapiibdlvhdrcon / bapiibdlvhdrctrlcon fields
sales-doc-status-rap / zbp_i_sales_doc_status	contract path (BAPI_CUSTOMERCONTRACT_CHANGE alt), 'fully delivered' test, PR00 condition type
packing-hu-rap / zbp_i_packing_unit	BAPI_HU_CREATE / BAPI_HU_PACK parameter names
hu-unpack-rap / zbp_i_hu_unpack	BAPI_HU_UNPACK parameter names + target storage location

qm-mass-results-rap / zbp_i_qm_inspectionchar	bapi2045d4 result-structure field names
dispatch-correction-rap / zbp_i_dispatch_box	guard: reverse goods movement only if the box is not already invoiced/posted

FU#1 — Create + activate the OData V4 service bindings

One service binding (OData V4 — UI) per service definition; activate to publish the service group. Then set the manifest `dataSources.mainService.uri` token and, for bound-action apps, the controller `SERVICE_NS` = the activated service definition name.

Service definition	manifest token	SERVICE_NS?	App(s)
ZUI_HU_GOODS_MOVEMENT	REPLACE_WITH_HU_GM_SERVICE	yes	post-goods-movement-hu
ZUI_PACKING	REPLACE_WITH_PACKING_SERVICE	yes	dyeing-packing
ZUI_CONTRACT_BATCH	REPLACE_WITH_CONTRACT_BATCH_SERVICE	yes	contract-batch-update
ZUI_PALLETIZATION	REPLACE_WITH_PALLETIZATION_SERVICE	yes	palletization
ZUI_DISPATCH_CORRECTION	REPLACE_WITH_DISPATCH_CORRECTION_SERVICE	yes	dispatch-correction
ZUI_HU_INBOUND	REPLACE_WITH_HU_INBOUND_SERVICE	yes	inbound-delivery-hus
ZUI_PACKING_DETAIL	REPLACE_WITH_PACKING_DETAIL_SERVICE	yes	manage-packing-details
ZUI_MTOS_PROCESS	REPLACE_WITH_MTOS_PROCESS_SERVICE	yes	mtos-process
ZUI_HU_UNPACK	REPLACE_WITH_HU_UNPACK_SERVICE	yes	hu-unpack
ZUI_POST_PACK_GR	REPLACE_WITH_POST_PACK_GR_SERVICE	yes	post-packing-gr
ZUI_BATCH_STATUS	REPLACE_WITH_BATCH_STATUS_SERVICE	yes	batch-status
ZUI_QM_INSPECTIONCHAR	REPLACE_WITH_QM_MASS_SERVICE	no (mass saver)	record-inspection-results-mass
ZUI_SALESDOC_STATUS	REPLACE_WITH_SALESDOC_STATUS_SERVICE ×2	n/a (adaptation)	manage-sales-contracts/-orders-ext
13 master services (ZUI_DD_SHADE, ZUI_RECIPE, ...)	per-app token	no (list/object only)	13 managed-master apps

Done when `grep -rn "REPLACE_WITH" apps` returns nothing (11 freestyle controllers + 2 sales-doc SERVICE_URLs).

FU#4 — ATC clean run + Fiori tile publishing

- **ATC** — run the clean-core / SAP-Cloud-Ready variant over the Z packages. Target zero P1/P2. We only consume released `I_*` CDS + released BAPIs, so released-API findings should be none — confirm.
- **DCL gap** — no access controls were authored (views are `@AccessControl.authorizationCheck:#CHECK, 0 .dcls`). Author a DCL per business object, or set `#NOT_REQUIRED` with sign-off; ATC flags `#CHECK` without a matching DCL.

- **Fiori tiles** — per app, create the target mapping + tile in a business catalog and assign to the business role in PFCG (see PUBLISHING.md / ACTIVATION.md role map).
- **Adaptation projects** (manage-sales-contracts-ext / -orders-ext / -deliveries-ext / confirm-production-operation-ext) — fill the base-app component id / extension-point ids in the BAS Adaptation Editor against the live base apps, then deploy.
- **Smoke test** each tile end-to-end in the FLP (/sap/bc/ui2/flp?sap-client=500).

Development-server runbook (condensed)

The activation sequence on DEV, end to end. The full per-step plan with all modules is in KEJRIWAL_Fiori_Module_Plan.pdf (Part C); this is the activation-focused short form.

1 Baseline & import

Confirm ADT access to the DEV system feeding KSQ/KHQ (client 500), the embedded FES is active, and the standard base apps are activated via Basis Rapid Activation. Import the repo package into a transport request.

Reference: ACTIVATION.md, TRANSPORT-PLAN.md

2 Activate objects (FU#2)

Activate in dependency order: 123 ZI_*/ZC_* views → 52 behavior definitions → 28 behavior pools → 26 service definitions. Do the 13 managed masters first (no BAPI code).

Reference: backend/*

3 Confirm VERIFY markers (FU#3)

As the 13 unmanaged pools activate, confirm each release-specific BAPI/DDIC name in the table below; wrong names = activation error. Smoke-test one action per BAPI family.

Reference: WIRING-CHECKLIST.md §3

4 Service bindings (FU#1)

Create + activate one OData V4 binding per service definition (convention ZUI_*_O4); publish in /IWFND/V4_ADMIN. Fill the REPLACE_WITH_*_SERVICE manifest tokens and the 11 controller SERVICE_NS + 2 sales-doc SERVICE_URLs.

Reference: WIRING-CHECKLIST.md §1, §4

5 ATC, DCL, tiles, go-live (FU#4)

Run ATC clean; record the DCL decision; publish tiles + assign roles; deploy the 4 adaptation projects; transport DEV → KSQ → PROD.

Reference: GO-LIVE-CHECKLIST.md, STD-RETIREMENT.md