

Calibration baths

Compact calibration baths			
Model	Range	Stability	Depth
6330	35 °C to 300 °C (95 °F to 572 °F)	± 0.005 °C at 100 °C ± 0.015 °C at 300 °C	234 mm (9.25 in)
7320	–20 °C to 150 °C (–4 °F to 302 °F)	± 0.005 °C at –20 °C ± 0.005 °C at 25 °C	234 mm (9.25 in)
7340	–40 °C to 150 °C (–40 °F to 302 °F)	± 0.005 °C at –40 °C ± 0.005 °C at 25 °C	234 mm (9.25 in)
7380	–80 °C to 100 °C (–112 °F to 212 °F)	± 0.006 °C at –80 °C ± 0.010 °C at 0 °C	178 mm (7 in)
6331	35 °C to 300 °C (95 °F to 572 °F)	± 0.015 °C at 300 °C ± 0.005 °C at –20 °C	457 mm (18 in)
7321	–20 °C to 150 °C (–4 °F to 302 °F)	± 0.005 °C at 25 °C ± 0.005 °C at –40 °C	457 mm (18 in)
7341	–45 °C to 150 °C (–49 °F to 302 °F)	± 0.005 °C at –40 °C ± 0.005 °C at 25 °C	457 mm (18 in)
7381	–80 °C to 110 °C (–112 °F to 230 °F)	± 0.006 °C at –80 °C ± 0.005 °C at 0 °C	457 mm (18 in)
Standard size calibration baths			
7080	–80 °C to 110 °C (–112 °F to 230 °F)	± 0.0025 °C at –80 °C ± 0.0015 °C at 25 °C	305 mm (12 in)
7008	–5 °C to 110 °C (23 °F to 230 °F)	± 0.0007 °C at 25 °C ± 0.0008 °C at 0 °C	331 mm (13 in)
7011	–10 °C to 110 °C (14 °F to 230 °F)	± 0.0008 °C at 25 °C ± 0.0008 °C at 0 °C	305 mm (12 in)
7040	–40 °C to 110 °C (–40 °F to 230 °F)	± 0.0015 °C at 25 °C ± 0.001 °C at 40 °C	305 mm (12 in)
6020	40 °C to 300 °C (104 °F to 572 °F)	± 0.005 °C at 300 °C ± 0.001 °C at 40 °C	305 mm (12 in)
6022	40 °C to 300 °C (104 °F to 572 °F)	± 0.005 °C at 300 °C ± 0.001 °C at 40 °C	464 mm (18.25 in)
6024	40 °C to 300 °C (104 °F to 572 °F)	± 0.005 °C at 300 °C ± 0.002 °C at 200 °C	337 mm (13.25 in)
6050H	180 °C to 550 °C (356 °F to 1022 °F)	± 0.007 °C at 500 °C ± 0.006 °C at –80 °C	305 mm (12 in)
Other			
Item	Description		
Bath accessories	Stands, rods, and clamps to suspend and support your probes and thermometers.		
Bath fluids	Silicone oils, salt, and cold fluids in convenient, small quantities.		
Rosemount bath controllers	Model 7900 controller designed by Hart integrates the features of Hart's 2100 controller and can be used in place of the Rosemount 915 controller with Rosemount-designed baths.		
Fluke Calibration bath controllers	Model 2100 and 2200 controllers can be integrated with homemade baths or other heat sources to achieve performance levels approaching Fluke Calibration baths.		