

# CCC '20 J4 - Cyclic Shifts

---

**Time Limit:** 1.0s    **Memory Limit:** 512M

---

## Canadian Computing Competition: 2020 Stage 1, Junior #4

Thuc likes finding cyclic shifts of strings. A *cyclic shift* of a string is obtained by moving characters from the beginning of the string to the end of the string. We also consider a string to be a cyclic shift of itself. For example, the cyclic shifts of `ABCDE` are:

`ABCDE`, `BCDEA`, `CDEAB`, `DEABC`, and `EABCD`.

Given some text,  $T$ , and a string,  $S$ , determine if  $T$  contains a cyclic shift of  $S$ .

## Input Specification

---

The input will consist of exactly two lines containing only uppercase letters. The first line will be the text  $T$ , and the second line will be the string  $S$ . Each line will contain at most 1000 characters.

For 6 of the 15 available marks,  $S$  will be exactly 3 characters in length.

## Output Specification

---

Output `yes` if the text,  $T$ , contains a cyclic shift of the string,  $S$ . Otherwise, output `no`.

## Sample Input 1

---

```
ABCCDEABAA
ABCDE
```

## Output for Sample Input 1

---

```
yes
```

## Explanation of Output for Sample Input 1

---

`CDEAB` is a cyclic shift of `ABCDE` and is contained in the text `ABC` `CDEAB` `AA`.

## Sample Input 2

---

ABCDDEBCAB

ABA

## Output for Sample Input 2

---

no

## Explanation of Output for Sample Input 2

---

The cyclic shifts of `ABA` are `ABA`, `BAA`, and `AAB`. None of these shifts are contained in the text `ABCDDEBCAB`.