

Day 2 KPI Definitions

BlueMart retail analysis | Source: bm_*.csv

Revenue	SUM(bm_sales.total_value), grouped as requested. Currency is preserved as supplied.
Region	bm_stores.city, because the source store table has city but no separate region field.
Store type	bm_stores.store_type, such as Mall, Community, and High Street.
Top categories	Product categories ranked by total revenue after joining sales to bm_skus.
Spend tier	Customer lifetime spend split into thirds with NTILE(3): bottom = Low, middle = Medium, top = High.
Promotion effect	Comparison of lines, units, revenue, and average line value when discount_pct > 0 versus 0. This is association, not causal.
Above-average customer	A customer whose total spend exceeds the mean total spend across customers with a non-null customer_id.
Falling product sales	A product whose latest available month has fewer units than its immediately previous available month.
Store rank	DENSE_RANK by revenue within each region; rank 1 is the highest-revenue store.
Data quality	Counts nulls, invalid numeric ranges, duplicate customer IDs, and missing store/SKU references.
Repeat purchase rate	Customers with purchases on at least two distinct dates divided by all customers with a non-null purchase.
Category mix	Category revenue divided by total revenue in the same region, expressed as a percentage.

Interpret results with the source-data limitations above, especially missing customer IDs and the promotion proxy.