

# ELECTRICAL INSTALLATION CONDITION REPORT

Issued in accordance with British Standard 7671 - Requirements for Electrical Installations by an Approved Contractor or Conforming Body enrolled with NICEIC, Warwick House, Houghton Hall Park, Houghton Regis, Dunstable LU5 5ZX

Original (To the person ordering the work)

## A. DETAILS OF THE CLIENT

Client: Britannia Student Services

Address: 1 Rathbone Place  
London

Postcode: W1T 1HH

## B. PURPOSE OF THE REPORT

*This report must be used only for reporting on the condition of an existing installation.*

Purpose for which this report is required: Land lord test

Date(s) on which inspection and testing were carried out:

## C. DETAILS OF THE INSTALLATION

Occupier: Britannia Student Services

Address: 1 Rathbone Place  
London

Postcode: W1T 1HH

Estimated age of the electrical installation: 15 years

Description of premises: domestic, commercial, industrial, other (Please state)

Commercial

Evidence of alterations or additions



If yes, estimated age 5 years

Date of previous inspection:

Electrical Installation Certificate No or previous Periodic Inspection or Condition Report No:

Records of installation available:

No

Records held by:

## D. EXTENT OF THE INSTALLATION AND LIMITATIONS ON THE INSPECTION AND TESTING

Extent of the electrical installation covered by this report:

Office area & student rooms - but limited access to some areas

Agreed limitations (including the reasons), if any, on the inspection and testing:

No removal of panels or boards  
Insulation test Ph/N - Earth only  
No test on lighting over 2.4m  
20% sample test  
No EM testing (only power off test- if visible)

Agreed with: KL

Operational limitations including the reasons (see page No. )

The inspection has been carried out in accordance with BS 7671, as amended. Cables concealed within trunking and conduits, or cables and conduits concealed under floors, in inaccessible roof spaces and generally within the fabric of the building or underground, have not been visually inspected.

## E. SUMMARY OF THE CONDITION OF THE INSTALLATION

General condition of the installation (in terms of electrical safety):

The installation is TP&N supply with no.8 single phase distribution boards throughout the building.  
All distribution boards are plastic construction with rcd's & mcb's.  
Some fittings show signs of age

Summary of the condition of the installation continued on additional pages?

No



Yes

Specify page No(s):

Overall assessment of the installation:

**SATISFACTORY** UNSATISFACTORY

(Delete as appropriate)

An 'Unsatisfactory' assessment indicates that dangerous and/or potentially dangerous conditions have been identified



# ELECTRICAL INSTALLATION CONDITION REPORT

## H. SCHEDULES AND ADDITIONAL PAGES

Inspection Schedule: Page(s) No 4,5,6

Additional pages, including additional source(s) data sheets:

Page No(s)

Schedule of Circuit Details for the Installation: Page No(s)

Odd, 7 - 21

Schedule of Test Results for the Installation:

Page No(s)

Even, 8 - 22

The pages identified are an essential part of this report. The report is valid only if accompanied by all the schedules and additional pages identified above.

## I. NEXT INSPECTION

I/We recommend that this installation is further inspected and tested after an interval of not more than 3 months

(Enter interval in terms of years, months or weeks, as appropriate)

provided that any items at F which have been attributed a Classification code C1 (danger present) are remedied immediately and that any items which have been attributed a code C2 (potentially dangerous) or require further investigation are remedied or investigated respectively as a matter of urgency. Items which have been attributed a Classification code C3 should be improved as soon as practicable (see F).

## J. DETAILS OF NICEIC APPROVED CONTRACTOR

Trading Title: londonsparks.com

Address:

Airport House  
Purley Way  
Croydon  
Surrey

Postcode:CR0 0XZ

Telephone number: +447850 557684

Email Address: kevin@londonsparks.com



Enrolment number:  
(Essential information) D035258

Branch number:  
(if applicable)

## K. SUPPLY CHARACTERISTICS AND EARTHING ARRANGEMENTS

System Type(s)		Number and Type of Live Conductors						Nature of Supply Parameters						Overcurrent Protective Device(s)		
TN-S	✓	a.c.	✓			d.c.	N/A	Nominal Voltage(s): $U^{(1)}$	400	V	$U_0^{(1)}$	230	V	BS(EN)	Lim	
TN-C-S	N/A	1-phase (2 wire)	N/A	1-phase (3 wire)	N/A	2 pole	N/A	Nominal frequency, $f^{(1)}$	50	Hz	Notes: (1) by enquiry			Type	Lim	
TN-C	N/A	2-phase (3 wire)	N/A			3 pole	N/A	Prospective fault current, $I_{pf}^{(2)(3)}$		kA	(2) by enquiry or by measurement			Rated current		A
TT	N/A	3-phase (3 wire)	N/A	3-phase (4 wire)	✓	other		External earth fault loop impedance, $Z_e^{(3)(4)}$		Ω	(3) where more than one supply, record the higher or highest values			Short-circuit capacity		kA
IT	N/A	Other						Number of sources			(4) by measurement			Confirmation of supply polarity	×	(✓)

## L. PARTICULARS OF INSTALLATION AT THE ORIGIN

Means of Earthing		Details of Installation Earth Electrode (where applicable)			
Distributor's facility:	<input checked="" type="checkbox"/>	Type: (eg rod(s), tape(s))		Location:	
Installation earth electrode:	N/A	Electrode resistance, $R_A$ :		Method of measurement:	

  

Main Switch/Switch-Fuse/Circuit-Breaker/RCD				Earthing and protective bonding conductors			
Type: BS(EN)	BS EN 60947-	Voltage rating	230	V	Conductor material	Copper	
No of Poles	2	Rated current, $I_n$		A	Conductor csa	16/10	mm <sup>2</sup>
Primary supply conductors material	Copper	RCD operating current, $I_{\Delta n}^*$		mA	Connection/continuity verified	<input checked="" type="checkbox"/>	(✓)
Primary supply conductors csa	Var	Rated time delay*		ms			
		RCD operating time (at $I_{\Delta n}^*$ )		ms			

  

Main protective bonding conductors				Bonding of extraneous-conductive parts (✓)			
Conductor material	Copper			Water service	<input checked="" type="checkbox"/>	Gas Service	<input checked="" type="checkbox"/>
Conductor csa	10	mm <sup>2</sup>		Oil service	N/A	Structural steel	N/A
Connection/continuity verified	<input checked="" type="checkbox"/>	(✓)		Lightning protection	N/A	Other incoming service(s)	N/A
				Specify			

\* (applicable only where an RCD is suitable and is used as a main circuit-breaker)

# ELECTRICAL INSTALLATION CONDITION REPORT

## INSPECTION SCHEDULE FOR DISTRIBUTION BOARDS AND CIRCUITS

Item	Description	Outcome *	Location reference
<b>1.0 Condition/adequacy of distributor's/supply intake equipment</b>			
1.1	Service cable	LIM	
1.2	Service cut-out/fuse(s)	LIM	
1.3	Meter tails - distributor	LIM	
1.4	Meter tails - consumer	LIM	
1.5	Metering equipment	LIM	
1.6	Means of main isolation (where present)	N/A	
2.0	Presence of adequate arrangements for parallel or switched alternative sources	N/A	
<b>3.0 Automatic disconnection of supply</b>			
<b>3.1 Main earthing and bonding arrangements</b>			
	* Presence and condition of distributor's earthing arrangement	✓	
	* Presence and condition of earth electrode arrangement		
	* Adequacy of earthing conductor size	✓	
	* Adequacy of earthing conductor connections	✓	
	* Accessibility of earthing conductor connections	✓	
	* Adequacy of main protective bonding conductor size(s)	✓	
	* Adequacy of main protective bonding conductor connections		
	* Accessibility of main protective bonding connections		
	* Provision of earthing/bonding labels at all appropriate locations		
<b>3.2 FELV</b>			
	* Source providing at least simple separation		
	* Plugs, socket-outlets and the like not interchangeable with those of other systems within the premises		
<b>3.3 Reduced low voltage</b>			
	* Adequacy of source		
	* Plugs, socket-outlets and the like not interchangeable with those of other systems within the premises		
<b>4.0 Other methods of protection (where the methods of protection listed below are employed, details should be provided on separate sheets)</b>			
4.1	Double insulation	✓	
4.2	Reinforced insulation	✓	
4.3	Use of obstacles	✓	
4.4	Placing out of reach	✓	
4.5	Non-conducting location		
4.6	Earth-free local equipotential bonding		
4.7	Electrical separation for more than one item of equipment		
<b>5.0 Distribution equipment</b>			
5.1	Adequacy of working space/accessibility of equipment	C3	
5.2	Security of fixing	✓	
5.3	Condition of insulation of live parts	✓	
5.4	Adequacy/security of barriers	✓	
5.5	Condition of enclosure(s) in terms of IP rating	C3	
5.6	Condition of enclosure(s) in terms of fire rating	C2	
5.7	Enclosure not damaged/deteriorated so as to impair safety	✓	
5.8	Presence of main switch(es), linked where required	✓	
5.9	Operation of main switch(es) (functional check)	✓	
5.10	Correct identification of circuit protective devices	✓	
5.11	Adequacy of protective devices for prospective fault current	✓	
5.12	RCD(s) provided for fault protection - includes RCBOs	C2	

\* All Boxes must be completed  
 ✓ indicates **Acceptable condition**  
 'LIM' indicates a **limitation**  
 'N/A' indicates **Not applicable**

**Unacceptable condition state C1 or C2**  
**Improvement recommended state C3**  
**Further investigation required state F/I**  
*(to determine whether danger or potential danger exists)*

**Outcome**  
 Provide additional comment where appropriate on attached numbered sheets. C1, C2 and C3 coded items to be recorded in section F of the report.

# ELECTRICAL INSTALLATION CONDITION REPORT

## INSPECTION SCHEDULE FOR DISTRIBUTION BOARDS AND CIRCUITS

Item	Description	Outcome *	Location reference
5.13	RCD(s) provided for additional protection - includes RCBOs	C2	
5.14	RCD(s) provided for protection against fire - includes RCBOs		
5.15	Manual operation of circuit-breakers and RCDs to prove disconnection	✓	
5.16	Presence of RCD retest notice at or near equipment where required	C3	
5.17	Presence of diagrams, charts or schedules at or near equipment where required	C3	
5.18	Presence of non-standard (mixed) cable colour warning notice at or near equipment where required	LIM	
5.19	Presence of alternative supply arrangement warning notice(s) at or near equipment where required	N/A	
5.20	Presence of replacement next inspection recommendation label	C3	
5.21	Presence of other required labelling (specify)	C3	
5.22	Examination of protective device(s) and base(s); correct type and rating (no signs of unacceptable thermal damage, arcing or overheating)	C3	
5.23	Protection against mechanical damage where cables enter equipment		
5.24	Protection against electromagnetic effects where cables enter metallic enclosures		
<b>6.0 Distribution/final circuits</b>			
6.1	Identification of conductors	C3	
6.2	Cables correctly supported throughout their length	LIM	
6.3	Condition of insulation of live parts	✓	
6.4	Non-sheathed cables protected by enclosure in conduit, duct or trunking	LIM	
6.5	Suitability of containment systems for continued use (including flexible conduit)	LIM	
6.6	Cables correctly terminated in enclosures (indicate extent of sampling in Section D of report)		
6.7	Examination of cables for signs of unacceptable thermal and mechanical damage/deterioration		
6.8	Adequacy of cables for current-carrying capacity with regard to the type and nature of installation		
6.9	Adequacy of protective devices; type and rated current for fault protection		
6.10	Presence and adequacy of circuit protective conductors		
6.11	Co-ordination between conductors and overload protective devices	✓	
6.12	Cable installation methods/practices appropriate to the type and nature of installation and external influences		
6.13	Cables where exposed to direct sunlight, of a suitable type		
6.14	Concealed cables installed in prescribed zones (see extent and limitations)		
6.15	Concealed cables incorporating earthed armour or sheath, or run within earthed wiring system, or otherwise protected against mechanical damage caused by nails, screws and the like where not in prescribed zones or not protected by 30 mA RCD (see extent and limitations)		
6.16	Provision of additional protection by 30 mA RCD for cables concealed in walls or partitions		
6.17	Provision of additional protection by 30 mA RCD		
	* Where reasonably likely to be used to supply mobile equipment for use outdoors		
	* For all socket-outlets of rating 20 A or less provided for use by ordinary persons		
6.18	Provision of fire barriers, sealing arrangements and protection against thermal effects		
6.19	Band II cables segregated/separated from Band I cables		
6.20	Cables segregated/separated from non-electrical services		
6.21	Termination of cables at enclosures (identify numbers and locations of items inspected in Section D)		
	* Connections under no undue strain	LIM	
	* No basic insulation of a conductor visible outside an enclosure	✓	
	* Connections of live conductors adequately enclosed		
	* Adequacy of connection at point of entry to enclosure (gland, bush or similar)		
6.22	General condition of wiring systems	✓	
6.23	Temperature rating of cable insulation	✓	
6.24	Condition of accessories including socket-outlets, switches and joint boxes	C3	
6.25	Suitability of accessories for external influences	C3	

\* All Boxes must be completed

✓ indicates Acceptable condition  
'LIM' indicates a limitation  
'N/A' indicates Not applicable

Unacceptable condition state C1 or C2

Improvement recommended state C3  
Further investigation required state F/I  
(to determine whether danger or potential  
danger exists)

Outcome

Provide additional comment where appropriate on  
attached numbered sheets. C1, C2 and C3 coded items  
to be recorded in section F of the report.

# ELECTRICAL INSTALLATION CONDITION REPORT

## INSPECTION SCHEDULE FOR DISTRIBUTION BOARDS AND CIRCUITS

Item	Description	Outcome *	Location reference
<b>7.0 Isolation and switching</b>			
<b>7.1 Isolators</b>			
	* presence and condition of appropriate devices		
	* acceptable location		
	* capable of being secured in the OFF position		
	* correct operation verified		
	* clearly identified by position and/or durable marking(s)		
	* Warning label posted in situations where live parts cannot be isolated by the operation of a single device		
<b>7.2 Switching off for mechanical maintenance</b>			
	* presence and condition of appropriate devices		
	* acceptable location		
	* capable of being secured in the OFF position		
	* correct operation verified		
	* clearly identified by position and/or durable marking(s)		
<b>7.3 Emergency switching/stopping</b>			
	* presence and condition of appropriate devices		
	* readily accessible for operation where danger might occur		
	* correct operation verified		
	* clearly identified by position and/or durable marking(s)		
<b>7.4 Functional switching</b>			
	* presence and condition of appropriate devices	✓	
	* correct operation verified	✓	
<b>8.0 Current-using equipment (permanently connected)</b>			
8.1	Condition of equipment in terms of IP rating	C3	
8.2	Equipment does not constitute a fire hazard	C3	
8.3	Enclosure not damaged/deteriorated so as to impair safety		
8.4	Suitability for the environment and external influences		
8.5	Security of fixing	C3	
8.6	Cable entry holes in ceiling above luminaires, sized or sealed so as to restrict the spread of fire (indicate extent of sampling in Section D of report)		
<b>8.7 Recessed luminaires (e.g. downlighters)</b>			
	* correct type of lamps fitted		
	* installed to minimise build-up of heat by use of fire rated fittings, insulation displacement box or similar		
	* no signs of overheating to surrounding building fabric		
	* no signs of overheating to conductors/terminations		
<b>9.0 Location(s) containing a bath or shower</b>			
9.1	Additional protection for all low voltage (LV) circuits by RCD not exceeding 30 mA	✓	
9.2	Where used as a protective measure, requirements for SELV or PELV are met	LIM	
9.3	Shaver sockets comply with BS EN 61558-2-5 or BS 3535		
9.4	Presence of supplementary bonding conductors unless not required by BS 7671: 2008		
9.5	Low voltage (e.g. 230 volts) socket-outlets sited at least 3 m from zone 1		
9.6	Suitability of equipment for external influences for installed location in terms of IP rating		
9.7	Suitability of equipment for installation in a particular zone		
9.8	Suitability of current-using equipment for a particular position within the location		
<b>10.0 Other special installations or locations</b>			
	List special locations present, if any. List the results of particular inspections applied.- a separate page is required for each location		

**\* All Boxes must be completed**

✓ indicates **Acceptable condition**  
 'LIM' indicates **alimitation**  
 'N/A' indicates **Not applicable**

**Unacceptable condition state C1 or C2**

**Improvement recommended state C3**  
**Further investigation required state F/I**  
*(to determine whether danger or potential danger exists)*

**Outcome**

Provide additional comment where appropriate on attached numbered sheets. C1, C2 and C3 coded items to be recorded in section F of the report.

## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*							
Location of distribution board:	1st Floor landing	Supply to distribution board is from:		No of phases:	1	Nominal voltage:	240	V	
Distribution board designation:	DB6 LL	Overcurrent protective device for the distribution circuit:		Associated RCD (if any):					
		Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:				
Characteristics at this distribution board						Earth fault loop impedance	16103359		RCD	
Confirmation of supply polarity										
* See note below										
Z <sub>S</sub>	0.07	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>			ms	Insulation resistance		Multi function
I <sub>pf</sub>	3.23	kA		At 5I <sub>Δn</sub>		ms	Continuity		Other	

[illegible]

\* *Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.*

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	07/06/2017



## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*							
Location of distribution board:	Ground Floor high level	Supply to distribution board is from:		No of phases:		Nominal voltage:		V	
Distribution board designation:	Rye field	Overcurrent protective device for the distribution circuit:		Associated RCD (if any):					
		Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:				
Characteristics at this distribution board						Earth fault loop impedance	16103359		RCD	
Confirmation of supply polarity										
* See note below										
Z <sub>S</sub>	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>		ms		Insulation resistance		Multi function	
I <sub>pf</sub>	kA		At 5I <sub>Δn</sub>		ms	Continuity		Other		

[illegible]

\* Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	

## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*							
Location of distribution board:	Flat 1 high level cupboard	Supply to distribution board is from:		No of phases:		Nominal voltage:		V	
Distribution board designation:	DB4	Overcurrent protective device for the distribution circuit:		Associated RCD (if any):					
		Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>

**Original** (To the person ordering the work)

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:				
Characteristics at this distribution board						Earth fault loop impedance	16103359		RCD	
Confirmation of supply polarity										
* See note below										
Z <sub>S</sub>	0.05	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>			ms	Insulation resistance		Multi function
I <sub>pr</sub>	4.29	kA		At 5I <sub>Δn</sub>		ms	Continuity		Other	

[illegible]

\* Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	07/06/2017

## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*							
Location of distribution board:	Flat 2 2nd Floor high level	Supply to distribution board is from:		No of phases:		Nominal voltage:		V	
Distribution board designation:	DB5	Overcurrent protective device for the distribution circuit:		Associated RCD (if any):					
		Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:			
Characteristics at this distribution board						Earth fault loop impedance	16103359	RCD	
Confirmation of supply polarity									
* See note below									
Z <sub>S</sub>	0.30	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>					
I <sub>pf</sub>	0.765	kA		At 5I <sub>Δn</sub>		ms	Insulation resistance	Multi function	
						Continuity			

[illegible]

\* Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	07/06/2017

## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

**Original** (To the person ordering the work)

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*										
Location of distribution board:	Flat 3 2nd floor high level	Supply to distribution board is from:				No of phases:		Nominal voltage:		V		
		Overcurrent protective device for the distribution circuit:					Associated RCD (if any):	BS(EN)				
Distribution board designation:	DB2	Type: BS(EN)			Rating:		A	RCD No of poles:		IΔn		mA

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:				
Characteristics at this distribution board						Earth fault loop impedance	16103359		RCD	
Confirmation of supply polarity										
* See note below										
Z <sub>S</sub>	0.14	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>			ms	Insulation resistance		Multi function
I <sub>pr</sub>	1.65	kA		At 5I <sub>Δn</sub>		ms	Continuity		Other	

[illegible]

\* Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	07/06/2017



## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*							
Location of distribution board:	Flat 4 3rd Floor	Supply to distribution board is from:		No of phases:		Nominal voltage:		V	
Distribution board designation:	DB3	Overcurrent protective device for the distribution circuit:		Associated RCD (if any):					
		Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>

**Original** (To the person ordering the work)

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:					
Characteristics at this distribution board						Earth fault loop impedance			RCD		
Confirmation of supply polarity											
* See note below											
Z <sub>S</sub> 0.10 Ω      Operating times of associated RCD (if any)      At I <sub>Δn</sub> ms											
I <sub>pf</sub> 2.99 kA      At 5I <sub>Δn</sub> ms						Insulation resistance			Multi function		
						Continuity			Other		

[illegible]

\* Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	07/06/2017

## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*							
Location of distribution board:	Flat 5 3rd floor high level	Supply to distribution board is from:		No of phases:		Nominal voltage:		V	
Distribution board designation:	DB1	Overcurrent protective device for the distribution circuit:		Associated RCD (if any):					
		Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	O (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/SWA cables	Thermosetting/SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:				
Characteristics at this distribution board						Earth fault loop impedance	16103359		RCD	
Confirmation of supply polarity										
* See note below										
Z <sub>S</sub>	0.06	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>			ms	Insulation resistance		Multi function
I <sub>pr</sub>	3.7	kA		At 5I <sub>Δn</sub>		ms	Continuity		Other	

[illegible]

\* *Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.*

<b>TESTED BY</b>			
<b>Signature:</b>		<b>Position:</b>	
<b>Name: (CAPITALS)</b>		<b>Date of testing:</b>	07/06/2017

## SCHEDULE OF CIRCUIT DETAILS FOR THE PRIMARY DISTRIBUTION BOARD

**Original** (To the person ordering the work)

## CIRCUIT DETAILS

TO BE COMPLETED IN EVERY CASE		TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION*									
Location of distribution board:	Office	Supply to distribution board is from:			No of phases:		Nominal voltage:		V		
		Overcurrent protective device for the distribution circuit:			Associated RCD (if any):	BS(EN)					
Distribution board designation:	DB7	Type: BS(EN)		Rating:		A	RCD No of poles:		I <sub>Δn</sub>		mA

[illegible]

\* In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

↑ See Table 4A2 of Appendix 4 of BS 7671

CODES FOR TYPE OF WIRING								
A	B	C	D	E	F	G	H	0 (Other - please state)
Thermoplastic insulated/sheathed cables	Thermoplastic cables in non metallic conduit	Thermoplastic cables in non metallic conduit	Thermoplastic cables in non metallic trunking	Thermoplastic cables in non metallic trunking	Thermoplastic/ SWA cables	Thermosetting/ SWA cables	Mineral-insulated cables	

## SCHEDULE OF TEST RESULTS FOR THE PRIMARY DISTRIBUTION BOARD

## TEST RESULTS

TO BE COMPLETED ONLY IF THE DISTRIBUTION BOARD IS NOT CONNECTED DIRECTLY TO THE ORIGIN OF THE INSTALLATION						Test instruments (serial numbers) used:			
Characteristics at this distribution board						Earth fault loop impedance	16103359	RCD	
Confirmation of supply polarity									
* See note below									
Z <sub>S</sub>	Ω	Operating times of associated RCD (if any)	At I <sub>Δn</sub>		ms	Insulation resistance		Multi function	
I <sub>pf</sub>	kA		At 5I <sub>Δn</sub>		ms				
Continuity									

[illegible]

\* Note: Where the installation can be supplied by more than one source, such as a primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

TESTED BY			
Signature:		Position:	
Name: (CAPITALS)		Date of testing:	