



AJAY PRASATH P 2024-CSE ▾

A2**Started on** Sunday, 24 August 2025, 1:12 AM**State** Finished**Completed on** Sunday, 24 August 2025, 1:13 AM**Time taken** 1 min 23 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int n;
5      scanf("%d", &n);
6      int a[n], b[n];
7      for (int i = 0; i < n; i++) scanf("%d", &a[i]);
8      for (int i = 0; i < n; i++) scanf("%d", &b[i]);
9      for (int i = 0; i < n - 1; i++) {
10         for (int j = i + 1; j < n; j++) {
11             if (a[i] > a[j]) {
12                 int temp = a[i]; a[i] = a[j]; a[j] = temp;
13             }
14         }
15     }
16     for (int i = 0; i < n - 1; i++) {
17         for (int j = i + 1; j < n; j++) {
18             if (b[i] < b[j]) {
19                 int temp = b[i]; b[i] = b[j]; b[j] = temp;
20             }
21         }
22     }
23     long long sum = 0;
24     for (int i = 0; i < n; i++) {
25         sum += (long long)a[i] * b[i];
26     }
27     printf("%lld\n", sum);
28     return 0;
29 }
30

```

	Input	Expected	Got	
✓	3	28	28	✓
	1			
	2			
	3			
	4			
	5			
	6			

	Input	Expected	Got	
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)