Rajalakshmi Engineering College

Name: AJAY PRASATH

Email: 240701023@rajalakshmi.edu.in

Roll no: 240701023 Phone: 8778228414

Branch: REC

Department: I CSE AG

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

01023

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

- 1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
- 2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

- 1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
- 2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

- 1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
- 2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

24010102

```
Output: 10 is inserted in the queue.
    Elements in the queue are: 10
    Invalid option.
    Answer
    #include <stdio.h>
    #include <stdlib.h>
    #define max 5
    int queue[max];
   int insertq(int *data) {

if (rear == max - 1)

return
      if (front == -1)
         front = 0;
      queue[++rear] = *data;
      return 1;
    }
    void delq() {
      if (front == -1 || front > rear) {3
       printf("Queue is empty.\n");
         return;
      printf("Deleted number is: %d\n", queue[front++]);
      if (front > rear)
         front = rear = -1;
    }
    void display() {
      if (front == -1 || front > rear) {
         printf("Queue is empty.\n");
         return;
      printf("Elements in the queue are:");
      for (int i = front; i <= rear; i++)
```

```
printf(" %d", queue[i]);
printf("\n");
}
```

240707023

240/0/023

```
int main()
        int data, reply, option;
        while (1)
        {
          if (scanf("%d", &option) != 1)
             break;
          switch (option)
                                                         240707023
             case 1:
               if (scanf("%d", &data) != 1)
                 break;
               reply = insertq(&data);
               if (reply == 0)
                 printf("Queue is full.\n");
               else
                 printf("%d is inserted in the queue.\n", data);
               break;
             case 2:
               delq(); //
                           Called without arguments
break case 3: disr'
               break:
               display();
               break;
```

040707023

240101023

240 ¹⁰ } return (printf("Invalid option.\n"); break; 0;	240701023	240707023
Status : 0	Correct		Marks : 10/10
240701023	240101023	240701023	240701023
240701023	240707023	240701023	240701023