

EXPERIMENT - 05

Student Name: Ajay Pratap Devra	UID: 24BAI70645
Branch: CSE - AIML	Section/Group: 24AIT_KRG-1_B
Semester: 5	Date of Performance: 10/08/2026
Subject Name: ADBMS	Subject Code: 24CSP-310

(A) A website maintains records of users who have registered on the platform and the status of confirmation requests sent to them. A confirmation request can either be successfully completed or may expire without completion.
 For each registered user, calculate the confirmation rate, which is defined as:

$$\text{Confirmation Rate} = \frac{\text{Number of Successful Confirmations}}{\text{Total Confirmation Requests}}$$

If a user has never received any confirmation request, their confirmation rate should be considered **0**.

Display the user ID along with the confirmation rate rounded to **2 decimal places**. The result can be returned in any order.

Example

Suppose a user has the following confirmation records:

Action

confirmed
 confirmed
 timeout

Then:

Successful Confirmations = 2
 Total Requests = 3

Confirmation Rate = $2 / 3 = 0.67$

```

SELECT
S.user_id,
ROUND(avg(
case
    when c.action = 'confirmed' THEN 1
    else 0
end
),2) AS confirmation_rate
from
Signups AS s
LEFT JOIN
Confirmations AS c
ON
s.user_id = c.user_id
GROUP BY
S.user_id;

```

(B) Problem Statement

A ride-booking company maintains information about trip requests and the users involved in those trips. Some users may be restricted from using the platform, while others are active participants. Each trip can either be completed successfully or cancelled by one of the participants.

For each day between **2013-10-01** and **2013-10-03**, determine the proportion of canceled trips among all valid trips. A trip should be considered valid only when both the customer and the driver associated with that trip are active users. The final result should display the date and the calculated cancellation rate rounded to two decimal places.

We need to calculate:	But only consider trips where:	Date between
Cancellation Rate	Client is NOT banned	2013-10-01
=	AND	And
	Driver is NOT	2013-10-03
	banned	
Cancelled Trips		

Total Valid Trips		

```
SELECT
    t.request_at AS day,
    ROUND(
        AVG(
            CASE
                WHEN t.status IN ('cancelled_by_client',
                                   'cancelled_by_driver')
                THEN 1.0
                ELSE 0.0
            END
        ), 2
    ) AS cancellation_rate
FROM Trips AS t
JOIN Users AS client
    ON t.client_id = client.users_id
JOIN Users AS driver
    ON t.driver_id = driver.users_id
WHERE client.banned = 'No'
    AND driver.banned = 'No'
GROUP BY t.request_at
ORDER BY t.request_at;
```