

body { font-family: Arial, sans-serif; line-height: 1.4; } /* Table styling */ table { font-size: 11px; width: 80%; border-collapse: collapse; margin-bottom: 10px; } /* Cell spacing */ th, td { padding: 4px 6px; text-align: left; } /* Prevent table centering */ table { margin-left: 0; margin-right: auto; } /* Reduce heading spacing */ h2, h3 { margin-top: 10px; margin-bottom: 5px; }

Cybersecurity Analysis Report

Report Information

Project Name: VibeSecSys

Report Version: 2.0

Analyst (K ID): K2509118

Generated By: AI-assisted system

Reviewer: Human validation required

Date: 2026-05-16

Report Type: Vulnerability Assessment Report

NOTE:

This report has been generated using an AI-assisted system based on automated scan analysis.

Human validation is required before applying remediation actions.

1. Executive Summary

The assessment identified an elevated overall risk posture across three systems, with the greatest concern concentrated on 192.168.56.20 due to multiple critical and high-risk exposures involving legacy services, remote access pathways, database access, file-sharing services, and shell-like access. The environment also includes a smaller web-facing system at 192.168.56.30 with moderate exposure and a Windows-oriented host at 192.168.56.50 with high-risk RPC and SMB-related exposure. Priority remediation should focus on reducing unnecessary services, removing critical remote access risks, restricting exposed services to trusted networks, and hardening authentication and monitoring controls.

2. System Overview

2.1 Target Systems

Asset ID	IP Address	Hostname	System Type	Description
ASSET-001	192.168.56.20	filesrv01	Multi-service server	Broad service profile including remote access, file-sharing, database, web, naming, and administrative services
ASSET-002	192.168.56.30	web-prod	Web-facing system	Focused service profile offering SSH and HTTP services
ASSET-003	192.168.56.50	N/A	Windows-oriented host	Microsoft RPC, NetBIOS, and Microsoft-DS services exposed

2.2 Scan Source

Tool	Version	Data Format	Scan Type
Nmap	7.92	XML	Service/version detection and default script scanning

3. Vulnerability Classification

Vulnerability Classification Table

Asset ID	System	Vulnerability	Classification	Evidence-Based Impact
ASSET-001	192.168.56.20	Exposed vsftpd 2.3.4 FTP Service	OWASP A06 Vulnerable and Outdated Components	FTP service on port 21 exposes vsftpd 2.3.4, creating risk of remote compromise and credential exposure
ASSET-001	192.168.56.20	Exposed Telnet Service	OWASP A02 Cryptographic Failures	Telnet service on port 23 may transmit credentials in cleartext

ASSET-001	192.168.56.20	Outdated OpenSSH Service	OWASP A06 Vulnerable and Outdated Components	OpenSSH 4.7p1 on port 22 indicates outdated remote administration exposure
ASSET-001	192.168.56.20	Exposed Web and AJP Services	OWASP A05 Security Misconfiguration	Apache 2.2.8 on port 80, AJP13 on port 8009, and Tomcat/Coyote on port 8180 expose web and middleware attack surface
ASSET-001	192.168.56.20	Exposed Samba NetBIOS Services	Service Misconfiguration	Samba services on ports 139 and 445 may enable enumeration, file-share abuse, and lateral movement
ASSET-001	192.168.56.20	Exposed r-services	Service Misconfiguration	exec and login services on ports 512 and 513 expose insecure remote command and login pathways
ASSET-001	192.168.56.20	Exposed Bindshell Service	Service Misconfiguration	Bash bindshell on port 1524 may allow direct shell access and full host compromise
ASSET-001	192.168.56.20	Exposed NFS and rpcbind Services	Service Misconfiguration	rpcbind on port 111 and NFS on port 2049 may expose file shares and support lateral movement
ASSET-001	192.168.56.20	Exposed Database Services	Service Misconfiguration	MySQL 5.0.51a on port 3306 and PostgreSQL 8.3.x on port 5432 expose database access to the network

ASSET-001	192.168.56.20	Exposed VNC and X11 Services	Service Misconfiguration	VNC on port 5900 and X11 on port 6000 expose remote graphical access surfaces
ASSET-001	192.168.56.20	Exposed Java RMI and IRC Services	OWASP A05 Security Misconfiguration	Java RMI on port 1099 and UnrealIRCd on port 6667 expose remote service interfaces that may be abused
ASSET-002	192.168.56.30	Exposed SSH and HTTP Services	Service Misconfiguration	OpenSSH 9.6p1 on port 22 and Apache 2.4.58 on port 80 expose management and web services requiring hardening
ASSET-003	192.168.56.50	Exposed Windows RPC and SMB Services	Service Misconfiguration	MSRPC on port 135, NetBIOS on port 139, and Microsoft-DS on port 445 expose Windows file-sharing and remote procedure services

4. Severity Assessment

Vulnerability Severity and Impact Assessment

VULN ID	Asset ID	Target System	Vulnerability	Severity	Potential Impact	Mitigation ID
---------	----------	---------------	---------------	----------	------------------	---------------

VULN-001	ASSET-001	192.168.56.20	Exposed vsftpd 2.3.4 FTP Service	Critical	Remote compromise risk and credential exposure from vulnerable FTP service	MIT-001
VULN-002	ASSET-001	192.168.56.20	Exposed Telnet Service	High	Credential interception and unauthorized remote access	MIT-002
VULN-003	ASSET-001	192.168.56.20	Outdated OpenSSH Service	Medium	Remote administration exposure with outdated service version	MIT-003
VULN-004	ASSET-001	192.168.56.20	Exposed Web and AJP Services	High	Web application compromise, middleware abuse, and backend exposure	MIT-004
VULN-005	ASSET-001	192.168.56.20	Exposed Samba NetBIOS Services	High	File-share enumeration, unauthorized access, and lateral movement	MIT-005

VULN-006	ASSET-001	192.168.56.20	Exposed r-services	Critical	Unauthorized remote command execution and insecure login access	MIT-006
VULN-007	ASSET-001	192.168.56.20	Exposed Bindshell Service	Critical	Direct shell access, full host compromise, and privilege escalation	MIT-007
VULN-008	ASSET-001	192.168.56.20	Exposed NFS and rpcbind Services	High	Unauthorized file access and lateral movement through exposed file-sharing services	MIT-008
VULN-009	ASSET-001	192.168.56.20	Exposed Database Services	High	Unauthorized database access and data exfiltration	MIT-009
VULN-010	ASSET-001	192.168.56.20	Exposed VNC and X11 Services	High	Remote session compromise and unauthorized system interaction	MIT-010

VULN-011	ASSET-001	192.168.56.20	Exposed Java RMI and IRC Services	High	Remote service abuse and potential exploitation of exposed interfaces	MIT-011
VULN-012	ASSET-002	192.168.56.30	Exposed SSH and HTTP Services	Medium	Brute-force attempts, web exposure, and service-specific exploitation	MIT-012
VULN-013	ASSET-003	192.168.56.50	Exposed Windows RPC and SMB Services	High	SMB enumeration, credential relay, lateral movement, and unauthorized file-sharing access	MIT-013

5. Risk Assessment (OCTAVE / STRIDE)

Asset	Threat	Impact	Likelihood	Risk Level
ASSET-001	Legacy and vulnerable service exposure	Credential theft, unauthorized remote access, lateral movement, and host compromise	High	Critical
ASSET-001	Exposed database services	Unauthorized database access, data exfiltration, and integrity compromise	High	High

ASSET-001	Exposed file-sharing and remote administration services	Unauthorized file access, remote command execution, and privilege escalation	High	Critical
ASSET-001	Exposed web and middleware services	Web application compromise, backend service abuse, and remote exploitation	Medium	High
ASSET-002	Exposed SSH and HTTP services	Brute-force attempts, web service exploitation, and unauthorized access	Medium	Medium
ASSET-003	Exposed Windows RPC and SMB services	SMB enumeration, credential relay, unauthorized file-sharing access, and lateral movement	High	High

6. Mitigation Recommendations

Mitigation Recommendations

MIT ID	Vulnerability	Recommended Mitigation
MIT-001	Exposed vsftpd 2.3.4 FTP Service	Disable vulnerable FTP service or replace it with SFTP/FTPS and upgrade to a supported secure version
MIT-002	Exposed Telnet Service	Disable Telnet and use SSH with strong authentication and restricted network access
MIT-003	Outdated OpenSSH Service	Upgrade OpenSSH, disable weak algorithms, enforce key-based authentication, and restrict administrative access
MIT-004	Exposed Web and AJP Services	Patch Apache and Tomcat components, restrict AJP to trusted internal hosts, and disable unused web services
MIT-005	Exposed Samba NetBIOS Services	Restrict SMB and NetBIOS to trusted networks, disable anonymous access, and harden share permissions

MIT-006	Exposed r-services	Disable exec and login services and replace them with hardened SSH-based administration
MIT-007	Exposed Bindshell Service	Remove the bindshell immediately, isolate the host, and investigate for compromise
MIT-008	Exposed NFS and rpcbind Services	Restrict NFS and rpcbind to approved hosts, enforce least-privilege exports, and block unnecessary access
MIT-009	Exposed Database Services	Bind databases to trusted interfaces only, enforce strong authentication, patch database versions, and apply least privilege
MIT-010	Exposed VNC and X11 Services	Restrict VNC and X11 to trusted networks or encrypted tunnels and enforce strong authentication
MIT-011	Exposed Java RMI and IRC Services	Restrict Java RMI and IRC services, patch or remove unused components, and monitor for abuse
MIT-012	Exposed SSH and HTTP Services	Harden SSH and HTTP services with patching, secure configuration, access control, and monitoring
MIT-013	Exposed Windows RPC and SMB Services	Restrict RPC and SMB to trusted networks, enable SMB signing, patch Windows services, and disable unnecessary file-sharing exposure

7. Conclusion

The assessed environment demonstrates a security posture that requires prioritised remediation, particularly around the concentration of critical and high-risk exposures on 192.168.56.20. The presence of legacy protocols, exposed administrative services, database access, file-sharing services, and shell-like access pathways substantially increases the likelihood of unauthorised access, credential compromise, lateral movement, and service abuse. Remediation should therefore focus first on removing unnecessary and high-risk services, restricting access to trusted networks, strengthening authentication, patching outdated components, and improving monitoring. Addressing these areas will reduce the attack surface and improve the resilience of the assessed environment.