RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:12 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:13 PM
Time taken	1 min 45 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int count = 0; // Step counter

    int i = 1;
    count++; // Execution for: int i = 1;

    int s = 1;
    count++; // Execution for: int s = 1;

    // Loop runs as long as s <= n
    while (s <= n) {
        count++; // For the while condition test (true branch)

        i++;
        count++; // Execution for: i++;

        s += i;
        count++; // Execution for: s += i;
    }
    count++; // For the final while condition test (false branch)

    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔

	Input	Expected	Got	
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:13 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:29 PM
Time taken	15 mins 17 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int count = 0;

    if (n == 1) {
        count++;          // if (n == 1) condition
        count++;          // printf("*")
    } else {
        count++;          // if (n == 1) condition (false)

        for (int i = 1; i <= n; i++) {
            count++;      // inner condition j <= n (true)
            count++;      // printf("*") 1
            count++;      // printf("*") 2
            count++;      // break
        }

        count += n + 1;   // outer condition i <= n checked n+1 times
    }

    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:16 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:23 PM
Time taken	7 mins 10 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main() {
    int num, i;
    int count = 0;

    scanf("%d", &num);   // not counted (as per note)

    // Count for-loop condition evaluations: (num + 1) times
    // Count if-condition evaluations: num times
    // Count printf executions inside if: d(num) times
    for (i = 1; i <= num; ++i) {
        count++;                // if-condition checked
        if (num % i == 0) {
            // printf("%d ", i); // we do NOT print the divisor
            count++;            // but we count the printf statement
        }
    }
    count += (num + 1);         // for-loop condition evaluations

    printf("%d\n", count);      // output only the counter
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:24 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:26 PM
Time taken	2 mins 55 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int count = 0;
    int c = 0;

    // Initialization of the outermost loop
    count++;          // i = n/2

    int i = n / 2;
    while (i < n) {
        count++;      // i < n condition (true)

        int j = 1;
        while (j < n) {
            count++;  // j < n condition (true)

            int k = 1;
            while (k < n) {
                count++;   // k < n condition (true)
                c++;
                count++;   // c++ execution
                k = k * 2;
            }
            count++;      // k < n condition (false)
            j = 2 * j;
        }
        count++;          // j < n condition (false)
        i++;
    }
    count++;              // i < n condition (false)

    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:27 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:28 PM
Time taken	1 min 17 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int count = 0;
    int rev = 0, remainder;
    count++;                // initialization: rev = 0

    while (n != 0) {
        count++;            // while condition check (true)
        remainder = n % 10;
        count++;            // remainder = n % 10
        rev = rev * 10 + remainder;
        count++;            // rev = rev * 10 + remainder
        n /= 10;
        count++;            // n /= 10
    }
    count++;                // while condition check (false)

    count++;                // print(rev) statement

    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:29 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:30 PM
Time taken	35 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int V;
    scanf("%d", &V);

    int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
    int n = 9;
    int count = 0;

    for (int i = 0; i < n; i++) {
        if (V >= denominations[i]) {
            count += V / denominations[i];
            V = V % denominations[i];
        }
        if (V == 0)
            break;
    }

    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:30 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:31 PM
Time taken	24 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparator for sorting in ascending order
int compare(const void *a, const void *b) {
    int x = *(int *)a;
    int y = *(int *)b;
    if (x < y) return -1;
    if (x > y) return 1;
    return 0;
}

int main() {
    int n, m;

    // Read number of children
    scanf("%d", &n);
    int *g = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &g[i]);
    }

    // Read number of cookies
    scanf("%d", &m);
    int *s = (int *)malloc(m * sizeof(int));
    for (int i = 0; i < m; i++) {
        scanf("%d", &s[i]);
    }

    // Sort both arrays
    qsort(g, n, sizeof(int), compare);
    qsort(s, m, sizeof(int), compare);

    // Greedy assignment: try to satisfy the least greedy child first
    int child = 0;
    int cookie = 0;

    while (child < n && cookie < m) {
```

```
    while (child < n && cookie < m) {
        if (s[cookie] >= g[child]) {
            // Cookie satisfies this child
            child++;
        }
        cookie++;
    }

    printf("%d\n", child);

    free(g);
    free(s);
    return 0;
}
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:31 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:56 AM
Time taken	10 days 16 hours
Marks	0.00/1.00
Grade	**0.00** out of 10.00 (**0**%)

Question 1 | Incorrect Mark 0.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3 burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparator for sorting in DESCENDING order
int compare(const void *a, const void *b) {
    long long x = *(long long *)a;
    long long y = *(long long *)b;
    if (x > y) return -1;
    if (x < y) return 1;
    return 0;
}

int main() {
    int n;
    // Read until EOF to handle single or multiple test cases
    while (scanf("%d", &n) == 1) {
        if (n <= 0) {
            printf("0\n");
            continue;
        }

        long long *cal = (long long *)malloc(n * sizeof(long long));
        for (int i = 0; i < n; i++) {
            scanf("%lld", &cal[i]);
        }

        // Greedy: sort calories in descending order
        qsort(cal, n, sizeof(long long), compare);
```

```
29
30          unsigned long long total = 0;
31          unsigned long long power = 1;   // 3^0 = 1
32
33          for (int i = 0; i < n; i++) {
34              total += power * (unsigned long long)cal[i];
35              if (i < n - 1) {
36                  power *= 3;             // next multiplier: 3^(i+1)
37              }
38          }
39
40          printf("%llu\n", total);
41          free(cal);
42      }
43      return 0;
44  }
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Your code failed one or more hidden tests.

Your code must pass all tests to earn any marks. Try again.

Incorrect

Marks for this submission: 0.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:43 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:44 PM
Time taken	57 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparator for ascending order
int compare(const void *a, const void *b) {
    long long x = *(long long *)a;
    long long y = *(long long *)b;
    if (x < y) return -1;
    if (x > y) return 1;
    return 0;
}

int main() {
    int n;
    scanf("%d", &n);

    long long *arr = (long long *)malloc(n * sizeof(long long));
    for (int i = 0; i < n; i++) {
        scanf("%lld", &arr[i]);
    }

    // Greedy: sort in ascending order
    qsort(arr, n, sizeof(long long), compare);

    long long sum = 0;
    for (int i = 0; i < n; i++) {
        sum += arr[i] * i;
    }

    printf("%lld\n", sum);

    free(arr);
    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:44 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:45 PM
Time taken	50 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparator for ascending order
int cmpAsc(const void *a, const void *b) {
    long long x = *(long long *)a;
    long long y = *(long long *)b;
    return (x > y) - (x < y);
}

// Comparator for descending order
int cmpDesc(const void *a, const void *b) {
    long long x = *(long long *)a;
    long long y = *(long long *)b;
    return (x < y) - (x > y);
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    long long *A = (long long *)malloc(n * sizeof(long long));
    long long *B = (long long *)malloc(n * sizeof(long long));

    for (int i = 0; i < n; i++) {
        scanf("%lld", &A[i]);
    }
    for (int i = 0; i < n; i++) {
        scanf("%lld", &B[i]);
    }

    // Greedy: sort one ascending, the other descending
    qsort(A, n, sizeof(long long), cmpAsc);
    qsort(B, n, sizeof(long long), cmpDesc);

    long long sum = 0;
    for (int i = 0; i < n; i++) {
        sum += A[i] * B[i];
    }

    printf("%lld\n", sum);

    free(A);
    free(B);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:45 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:45 PM
Time taken	31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

// Recursive divide-and-conquer function to count zeroes
int countZeroes(int arr[], int low, int high) {
    // Base case: empty range
    if (low > high)
        return 0;

    // If the first element is 0, all remaining elements are 0
    if (arr[low] == 0)
        return high - low + 1;

    // If the last element is 1, there are no zeroes in this range
    if (arr[high] == 1)
        return 0;

    int mid = low + (high - low) / 2;

    if (arr[mid] == 0) {
        // mid is a zero; count from mid to high, and search left part
        return (high - mid + 1) + countZeroes(arr, low, mid - 1);
    } else {
        // arr[mid] == 1; zeroes can only be in the right part
        return countZeroes(arr, mid + 1, high);
    }
}

int main() {
    int m;
    scanf("%d", &m);

    if (m <= 0) {
        printf("0\n");
        return 0;
    }

    int arr[m];
    for (int i = 0; i < m; i++) {
        scanf("%d", &arr[i]);
    }

    int zeroCount = countZeroes(arr, 0, m - 1);
    printf("%d\n", zeroCount);

    return 0;
}
```

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔
✔	10 1 1 1 1 1 1 1 1 1 1	0	0	✔
✔	8 0 0 0 0 0 0 0 0	8	8	✔
✔	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:45 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:46 PM
Time taken	25 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    long long candidate = 0;
    int count = 0;

    for (int i = 0; i < n; i++) {
        long long x;
        scanf("%lld", &x);

        if (count == 0) {
            candidate = x;
            count = 1;
        } else if (x == candidate) {
            count++;
        } else {
            count--;
        }
    }

    // The majority element always exists, so candidate is the answer
    printf("%lld\n", candidate);
    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:46 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:46 PM
Time taken	23 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int floorSearch(int arr[], int low, int high, int x) {
    if (low > high) return -1;
    if (x >= arr[high]) return arr[high];
    if (x < arr[low]) return -1;

    int mid = low + (high - low) / 2;
    if (arr[mid] == x) return arr[mid];
    if (arr[mid] < x) {
        int right = floorSearch(arr, mid + 1, high, x);
        if (right != -1) return right;
        return arr[mid];
    } else {
        return floorSearch(arr, low, mid - 1, x);
    }
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++) scanf("%d", &arr[i]);
    int x;
    scanf("%d", &x);

    int result = floorSearch(arr, 0, n - 1, x);
    printf("%d\n", result);
    return 0;
}
```

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔

	Input	Expected	Got	
✔	5 10 22 85 108 129 100	85	85	✔
✔	7 3 5 7 9 11 13 15 10	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:47 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:47 PM
Time taken	26 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int found = 0;
int res1, res2;

void findPair(int arr[], int low, int high, int x) {
    if (found || low >= high) return;

    int mid = low + (high - low) / 2;

    // Check cross pairs between left half [low..mid] and right half [mid+1..high]
    int i = low, j = high;
    while (i <= mid && j > mid) {
        int sum = arr[i] + arr[j];
        if (sum == x) {
            found = 1;
            res1 = arr[i];
            res2 = arr[j];
            return;
        } else if (sum < x) {
            i++;
        } else {
            j--;
        }
    }

    // Recurse on left and right halves
    findPair(arr, low, mid, x);
    if (found) return;
    findPair(arr, mid + 1, high, x);
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }
    int x;
    scanf("%d", &x);

    findPair(arr, 0, n - 1, x);

    if (found) {
        printf("%d\n%d\n", res1, res2);
    } else {
        printf("No\n");
    }
    return 0;
}
```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Saturday, 19 September 2026, 7:47 PM
State	Finished
Completed on	Saturday, 19 September 2026, 7:48 PM
Time taken	30 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```c
#include <stdio.h>

// Partition function using Lomuto partition scheme
int partition(int arr[], int low, int high) {
    int pivot = arr[high];   // choose last element as pivot
    int i = low - 1;

    for (int j = low; j < high; j++) {
        if (arr[j] <= pivot) {
            i++;
            int temp = arr[i];
            arr[i] = arr[j];
            arr[j] = temp;
        }
    }

    // Place pivot in its correct position
    int temp = arr[i + 1];
    arr[i + 1] = arr[high];
    arr[high] = temp;

    return i + 1;
}

// Recursive Quick Sort
void quickSort(int arr[], int low, int high) {
    if (low < high) {
        int pi = partition(arr, low, high);
        quickSort(arr, low, pi - 1);
        quickSort(arr, pi + 1, high);
    }
}

int main() {
    int n;
    scanf("%d", &n);

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    quickSort(arr, 0, n - 1);

    for (int i = 0; i < n; i++) {
        printf("%d", arr[i]);
        if (i != n - 1)
            printf(" ");
    }
    printf("\n");

    return 0;
```

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:28 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:35 PM
Time taken	7 mins 41 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*
Output:*6*
Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1
3+3
1+1+1+3
1+1+3+1
1+3+1+1
3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"

long long count_ways(int n) {
    if (n < 0) return 0;
    if (n == 0 || n == 1 || n == 2) return 1;

    long long w0 = 1;
    long long w1 = 1;
    long long w2 = 1;
    long long current = 0;

    for (int i = 3; i <= n; i++) {
        current = w2 + w0;
        w0 = w1;
        w1 = w2;
        w2 = current;
    }

    return w2;
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        printf("%lld\n", count_ways(n));
    }
    return 0;
}
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:36 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:37 PM
Time taken	45 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    // Allocate memory for grid and dp tables
    int **grid = (int **)malloc(n * sizeof(int *));
    int **dp = (int **)malloc(n * sizeof(int *));
    for (int i = 0; i < n; i++) {
        grid[i] = (int *)malloc(n * sizeof(int));
        dp[i] = (int *)malloc(n * sizeof(int));
    }

    // Read chessboard values
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &grid[i][j]);
        }
    }

    // Base case
    dp[0][0] = grid[0][0];

    // Initialize first row
    for (int j = 1; j < n; j++) {
        dp[0][j] = dp[0][j - 1] + grid[0][j];
    }

    // Initialize first column
    for (int i = 1; i < n; i++) {
        dp[i][0] = dp[i - 1][0] + grid[i][0];
    }

    // Fill the rest of the DP table
    for (int i = 1; i < n; i++) {
        for (int j = 1; j < n; j++) {
            int max_prev = (dp[i - 1][j] > dp[i][j - 1]) ? dp[i - 1][j] : dp[i][j - 1];
            dp[i][j] = grid[i][j] + max_prev;
        }
    }

```

```
    // Output the maximum path value at the bottom-right cell
    printf("%d\n", dp[n - 1][n - 1]);

    // Free allocated memory
    for (int i = 0; i < n; i++) {
        free(grid[i]);
        free(dp[i]);
    }
    free(grid);
```

	Input	Expected	Got	
✔	3 1 2 4 2 3 4 8 7 1	19	19	✔
✔	3 1 3 1 1 5 1 4 2 1	12	12	✔
✔	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:39 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:39 PM
Time taken	32 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1		a	g	**g**	**t**	**a**	**b**
s2	**g**	x	**t**	**x**	**a**	**y**	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "string.h"
#include "stdlib.h"

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    char s1[1005], s2[1005];

    // Read the two input strings
    if (scanf("%s %s", s1, s2) != 2) return 0;

    int m = strlen(s1);
    int n = strlen(s2);

    // Allocate DP table of size (m + 1) x (n + 1)
    int **dp = (int **)malloc((m + 1) * sizeof(int *));
    for (int i = 0; i <= m; i++) {
        dp[i] = (int *)malloc((n + 1) * sizeof(int));
    }

    // Build the DP table
    for (int i = 0; i <= m; i++) {
        for (int j = 0; j <= n; j++) {
            if (i == 0 || j == 0) {
                dp[i][j] = 0;
            } else if (s1[i - 1] == s2[j - 1]) {
                dp[i][j] = dp[i - 1][j - 1] + 1;
            } else {
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
            }
        }
    }

    // The bottom-right cell contains the length of the LCS
    printf("%d\n", dp[m][n]);

    // Free allocated memory
    for (int i = 0; i <= m; i++) {
        free(dp[i]);
    }
```

```
    free(dp);

    return 0;
}
```

	Input	Expected	Got	
✔	aab azb	2	2	✔
✔	ABCD ABCD	4	4	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:39 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:41 PM
Time taken	1 min 10 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int *dp = (int *)malloc(n * sizeof(int));
    int max_len = 0;

    for (int i = 0; i < n; i++) {
        dp[i] = 1; // Minimum length is 1
        for (int j = 0; j < i; j++) {
            if (arr[j] <= arr[i]) {
                if (dp[j] + 1 > dp[i]) {
                    dp[i] = dp[j] + 1;
                }
            }
        }
        if (dp[i] > max_len) {
            max_len = dp[i];
        }
    }

    printf("%d\n", max_len);

    free(arr);
    free(dp);

    return 0;
}
```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:41 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:41 PM
Time taken	38 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Allocate a frequency/visited array initialized to 0
    int *freq = (int *)calloc(n + 1, sizeof(int));
    int duplicate = -1;

    for (int i = 0; i < n; i++) {
        if (freq[arr[i]] == 1) {
            duplicate = arr[i];
            break;
        }
        freq[arr[i]] = 1;
    }

    printf("%d\n", duplicate);

    // Free allocated memory
    free(arr);
    free(freq);

    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:41 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:42 PM
Time taken	28 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Allocate a frequency/visited array initialized to 0
    int *freq = (int *)calloc(n + 1, sizeof(int));
    int duplicate = -1;

    for (int i = 0; i < n; i++) {
        if (freq[arr[i]] == 1) {
            duplicate = arr[i];
            break;
        }
        freq[arr[i]] = 1;
    }

    printf("%d\n", duplicate);

    // Free allocated memory
    free(arr);
    free(freq);

    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:42 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:45 PM
Time taken	3 mins 8 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int T;
    // Read the number of test cases
    if (scanf("%d", &T) != 1) return 0;

    while (T--) {
        int n1;
        if (scanf("%d", &n1) != 1) break;

        int *a = (int *)malloc(n1 * sizeof(int));
        for (int i = 0; i < n1; i++) {
            scanf("%d", &a[i]);
        }

        int n2;
        if (scanf("%d", &n2) != 1) {
            free(a);
            break;
        }

        int *b = (int *)malloc(n2 * sizeof(int));
        for (int j = 0; j < n2; j++) {
            scanf("%d", &b[j]);
        }

        int i = 0, j = 0;
```

```
        int first_output = 1;

        // Two-pointer approach for sorted arrays
        while (i < n1 && j < n2) {
            if (a[i] < b[j]) {
                i++;
            } else if (a[i] > b[j]) {
                j++;
            } else {
                if (!first_output) {
                    printf(" ");
                }
                printf("%d", a[i]);
                first_output = 0;

                // Skip duplicates to handle intersection properly
                int current = a[i];
                while (i < n1 && a[i] == current) i++;
                while (j < n2 && b[j] == current) j++;
            }
        }
        printf("\n");
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:46 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:50 PM
Time taken	4 mins 13 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array

2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

void solve() {
    int n1;
    if (scanf("%d", &n1) != 1) return;

    int *a = (int *)malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; i++) {
        scanf("%d", &a[i]);
    }

    int n2;
    if (scanf("%d", &n2) != 1) {
        free(a);
        return;
    }

    int *b = (int *)malloc(n2 * sizeof(int));
    for (int j = 0; j < n2; j++) {
        scanf("%d", &b[j]);
    }

    int i = 0, j = 0;
    int first_output = 1;

    // Two-pointer approach for sorted arrays
    while (i < n1 && j < n2) {
        if (a[i] < b[j]) {
```

```
            i++;
        } else if (a[i] > b[j]) {
            j++;
        } else {
            if (!first_output) {
                printf(" ");
            }
            printf("%d", a[i]);
            first_output = 0;

            // Skip duplicates in both arrays to output unique intersections
            int current = a[i];
            while (i < n1 && a[i] == current) i++;
            while (j < n2 && b[j] == current) j++;
        }
    }
    printf("\n");

    free(a);
    free(b);
}

int main() {
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:50 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:53 PM
Time taken	2 mins 16 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int *A = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &A[i]);
    }

    int k;
    if (scanf("%d", &k) != 1) {
        free(A);
        return 0;
    }

    // If fewer than 2 elements, no pair can exist
    if (n < 2) {
        printf("0\n");
        free(A);
        return 0;
    }

    int i = 0, j = 1;
    int found = 0;

    while (i < n && j < n) {
        if (i == j) {
            j++;
            continue;
        }

        int diff = A[j] - A[i];

        if (diff == k) {
            found = 1;
            break;
```

```
40          } else if (diff < K) {
41              j++;
42          } else {
43              i++;
44          }
45      }
46
47      printf("%d\n", found);
48
49      free(A);
50      return 0;
51  }
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Ajay Surya A 250701030-2025-CSE

A2

Started on	Thursday, 24 September 2026, 1:50 PM
State	Finished
Completed on	Thursday, 24 September 2026, 1:50 PM
Time taken	32 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include "stdio.h"
#include "stdlib.h"

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int *A = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &A[i]);
    }

    int k;
    if (scanf("%d", &k) != 1) {
        free(A);
        return 0;
    }

    // If fewer than 2 elements, no pair can exist
    if (n < 2) {
        printf("0\n");
        free(A);
        return 0;
    }

    int i = 0, j = 1;
    int found = 0;

    while (i < n && j < n) {
        if (i == j) {
            j++;
            continue;
        }

        int diff = A[j] - A[i];

        if (diff == k) {
            found = 1;
            break;
```

```
40          } else if (diff < K) {
41              j++;
42          } else {
43              i++;
44          }
45      }
46
47      printf("%d\n", found);
48
49      free(A);
50      return 0;
51  }
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course