

# Detecting Meteors Within Spectrographs With Machine Learning

Kirin Patel



# What do I Propose to do?

- My project proposes to introduce a machine learning model to identify and mark meteors within spectrographs that can be continuously trained with new data so that accuracy can be continually improved.

# Why am I Proposing this?

- There is no accurate automated method for detecting meteors within spectrographs that are generated by BRAMS (Belgian RAdio Meteor Stations).
  - There is an OpenCV implementation that was created but it has not been maintained for over 2 years and its accuracy and effectiveness are unknown (it is also not well known).
- Large amounts of data are collected by BRAMS daily, roughly one spectrograph per minute per location, with roughly 30 locations within Belgium.
  - This data needs to be processed so that analysis can be conducted. By decreasing data processing times, more analysis can be done.

# What has Already Been Done?

- This problem has already been solved! (Calders, 2019)
  - A feature detection algorithm has already been made, this can help guide my machine learning model implementation.
- Color salience has been shown to improve accuracy or feature detection. (Weijer & Bagdanov, 2006)
  - By attributing weight values to different colors, specifically those representing activity within spectrographs, meteors can be more accurately detected.
- Extensive research has been conducted on low end hardware efficiency for running real-time image processing. (Rosten & Drummond, 2006; Khan, Bennamoun, Sohel & Togneri, 2014)
  - This research can help propel a machine learning model's efficiency when run on cost effective hardware.

# What do I Already Have?

- Machines for development and model training
- Access to a Kubernetes Cluster to run Kubeflow Pipelines
- Access to the Kubeflow Pipelines team for assistance with Kubeflow Pipelines
- Access to resources to learn Keras/Tensorflow and to create a machine learning model

# What do I Need?

- Access to a large data set
  - Ideally this data set will already have meteors identified for each spectrograph
- Knowledge on how to use Keras/Tensorflow to create a machine learning model

# What are Some Expected Roadblocks?

- Lack of data
- Data format
- Time
- Lack of knowledge regarding Keras/Tensorflow
- Motivation

# Alternative Solutions

- Another solution would be to implement an OpenCV based feature detection algorithm
  - This would not provide a new medium for detecting meteors within spectrographs
  - Large improvements in efficiency can be made over the current implementation that was created by Stijn Calders (Calders, 2019)



# Detecting Meteors Within Spectrographs With Machine Learning

Kirin Patel

- [kirinpatel@gmail.com](mailto:kirinpatel@gmail.com)
- [@kirinpatel](https://twitter.com/kirinpatel)

# References

- Calders, S. (2019, January 29). calders/RadioMeteorZoo. Retrieved from <https://github.com/calders/RadioMeteorZoo>.
- Khan, S. H., Bennamoun, M., Soheli, F., & Togneri, R. (2014). Automatic Feature Learning for Robust Shadow Detection. 2014 IEEE Conference on Computer Vision and Pattern Recognition. doi: 10.1109/cvpr.2014.249
- Kubat, M., Holte, R. C., & Matwin, S. (1998). Machine Learning for the Detection of Oil Spills in Satellite Radar Images. Machine Learning, 30(2/3), 195–215. doi: 10.1023/a:1007452223027
- Rosten, E., & Drummond, T. (2006). Machine Learning for High-Speed Corner Detection. Computer Vision – ECCV 2006 Lecture Notes in Computer Science, 430–443. doi: 10.1007/11744023\_34
- Weijer, J. V. D., Gevers, T., & Bagdanov, A. (2006). Boosting color saliency in image feature detection. IEEE Transactions on Pattern Analysis and Machine Intelligence, 28(1), 150–156. doi: 10.1109/tpami.2006.3