SELF-ASSEMBLY AND DYNAMICS OF ANISOTROPIC COLLOIDS

Draft of September 2, 2010 at 21:08

BY

ADAM DECONINCK

THESIS

Submitted in partial fulfillment of the requirements for the degree of Master of Science in Materials Science and Engineering in the Graduate College of the University of Illinois at Urbana-Champaign, 2010

Urbana, Illinois

Master's Committee:

Abstract

This work details the development of techniques to fabricate and study structured colloidal particles...

To Leigh.

Acknowledgements

Table of Contents

Chapte	er 1 Introduction		 1
-			
Chapte			
2.1	Anisotropic and Patchy Colloids		
2.2	Fabrication of Janus Colloids		
2.3	Flow Lithography		
2.4	Particle Tracking		 2
Chapte	er 3 Computerized Tracking of Anisotropic Colloids		 3
3.1	Introduction		
3.2	Algorithms		
3.3	Implementation		
3.4	Assessment		
Chapte	ser 4 Assembly and Dynamics of Rod-Shaped Colloids		5
4.1	Introduction		
4.2	Experimental Procedure		
4.2	4.2.1 Stop-Flow Lithography		
	4.2.2 Mask Design		
	4.2.2 Mask Besign		
	4.2.4 Diffusion Measurements		
4.3	Results and Discussion		
4.5			
	4.3.2 Translational and Rotational Diffusion		
	4.3.3 Self-Assembly of Janus Rods	•	 6
Chapte	er 5 Assembly and Dynamics of Exotic Colloids		8
5.1	Introduction		 8
5.2	Experimental Procedure		 8
	5.2.1 Device Design		 8
	5.2.2 SFL with Multiple Co-Flowing Streams		 8
	5.2.3 Mask Design		
	5.2.4 Particle Collection		
5.3	Results and Discussion		
0.0	5.3.1 Diffusion Measurements		
	5.3.2 Self-Assembly		
Chant	er 6 Conclusions		9
-	Future work		

Draft of September 2, 2010 at 21:08

Appen	$\mathbf{dix} \; \mathbf{A}$	Microfluidic Devices for Studying Self-Assembly	LO
A.1	Introd	uction	10
A.2	Experi	mental Procedure	10
	A.2.1	Device Design and Fabrication	10
	A.2.2	Proposed Protocol	10
A.3	Result	s and Discussion	10
	A.3.1	Fabrication	10
	A.3.2	Particle collection	10
	A.3.3	Solvent exchange	10
	A.3.4	Challenges	10
Appen	dix B	Grayscale Stop-Flow Lithography	11
B.1	Introd	uction	11
B.2	Experi	mental Procedure	11
	B.2.1	Design of Grayscale Filters	11
	B.2.2	Grayscale Stop-Flow Lithography	11
B.3	Result	s and Discussion	11
	B.3.1	Intensity Reduction	11
	B.3.2	Particle Size Reduction	11
	B.3.3	Particle Swelling Issues	11

List of Figures

Introduction

• Motivation

- Colloidal materials are important because of x, y, and z.
- Limited assembly mechanisms available for conventional spherical particles. (Figure: crystal, gel, glass graphics)
- Desirable to produce self-assembled structures which have different types of order.
- One way to do this: fabricate anisotropic colloids which naturally assemble in a different fashion.

• Broad Description

- Fabricated polymer colloids with shape and chemical anisotropy.
- Specifically: rods with various aspect ratios, and Janus rods.
- Also fabricated two-patch rods and more complex geometries.
- Wrote tracking software for rods
- Wrote tracking software for complex geometries (drop this if needed)
- Measurement of two-dimensional dynamical behavior by time-series fluorescence/confocal microscopy.
- Particle tracking to measure translational and rotational diffusion of particles.
- Also fabricated microfluidic devices to study confined particles (appendix)
- Also developed grayscale techniques to produce particles with controllable height (appendix)

Literature Review

- 2.1 Anisotropic and Patchy Colloids
- 2.2 Fabrication of Janus Colloids
- 2.3 Flow Lithography
- 2.4 Particle Tracking

Computerized Tracking of Anisotropic Colloids

3.1 Introduction

- Desirable to locate anisotropic particles in microscopy images to study dynamics and assembly.
- Previous work in this area: Crocker and Grier, Solomon
- Can't use Solomon method: fluorescence is too flat for SFL particles. 2D-extruded objects. (Figure to illustrate.)
- Must develop new algorithms which can work on these particles.

3.2 Algorithms

- Tracking algorithm for rods
 - Image cleanup using erosion, opening
 - Particle segmentation using watershed transform
 - Particle skeleton (backbone) using distance transform plus rank-order filter
 - Calculation of center-of-mass, oritentation according to Solomon
 - Time-series tracking according to Blair and Dufrense
 - Difference between 2D and 3D version of algorithm
- Tracking algorithm for arbitrary shapes
 - Initial steps same as for rods: cleanup, segmentation
 - "Skeletonization" as above, but producing a more complex skeleton than for rods
 - Calculate center-of-mass as with rods
 - Choose a sample skeleton as the "canonical" particle skeleton

- Isolate particles into individual windows
- To measure orientation: rotate canonical skeleton image in small increments. For each one, AND together the rotated skeleton and the sample skeleton. Maximize pixel sum of ANDed image.
- Faster in 2D than in 3D
- Implementation not finished!

3.3 Implementation

- Rod tracking implemented in 2D in Matlab.
- Go over the details of the matlab implementation
- Rod tracking implemented in 3D in Matlab, but with major bugs.
- Arbitrary tracker not yet fully implemented, using Matlab.

3.4 Assessment

- Identify issues caused by morphological image processing for these algorithms.
- Estimate errors in particle segmentation
- Estimate error of rod COM and orientation calculations.
- Estimate error of skeleton-based orientation calculations.

Assembly and Dynamics of Rod-Shaped Colloids

4.1 Introduction

- Natural rod systems
- Systems studied by Solomon
- Janus colloids: Granick
- Interest in Janus rods

4.2 Experimental Procedure

4.2.1 Stop-Flow Lithography

- Microscope setup
- Pressure system–Rob
- LabView controller for SFL
- Design of microfluidic devices for up to 3-stream SFL
- Fabrication of microfluidic devices

4.2.2 Mask Design

- Demagnification using 60X objective
- Design parameters
- Rod aspect ratios used

4.2.3 Particle Collection

- Considerations for collection
- Solvents used
- Pipettes
- Fluorosilane coatings

4.2.4 Diffusion Measurements

- Confocal microscopy setup
- Space and time resolution requirements
- Fluorescence requirements

4.3 Results and Discussion

4.3.1 Resolution

- Limiting factors for SFL resolution: mask design, optics, flow effects
- Resolution limits constrained by 60X lens-need to redo this (1 hour work)
- Resolution limits for Janus rods–interface effects

4.3.2 Translational and Rotational Diffusion

- Particle collection—PEGDA vs TMPTA
- Compare particle/solvent/surface effects
- 2D diffusion size series: TMPTA in toluene (additional experiments may be required)
- Analyze diffusion data for rods (partially done).

4.3.3 Self-Assembly of Janus Rods

- Fabrication of Janus rods: various sizes (figure)
- Comparison of self-assembly in various solvents (figure)

Draft of September 2, 2010 at 21:08

- Small clusters vs large structures
- Alignment of assembled rods
- Image segmentation for analyzing structures
- Some more images may be required

Assembly and Dynamics of Exotic Colloids

- 5.1 Introduction
- 5.2 Experimental Procedure
- 5.2.1 Device Design
- 5.2.2 SFL with Multiple Co-Flowing Streams
- 5.2.3 Mask Design
- 5.2.4 Particle Collection
- 5.3 Results and Discussion
- 5.3.1 Diffusion Measurements
- 5.3.2 Self-Assembly

Conclusions

6.1 Future work

Appendix A

Microfluidic Devices for Studying Self-Assembly

- A.1 Introduction
- A.2 Experimental Procedure
- A.2.1 Device Design and Fabrication
- A.2.2 Proposed Protocol
- A.3 Results and Discussion
- A.3.1 Fabrication
- A.3.2 Particle collection
- A.3.3 Solvent exchange
- A.3.4 Challenges

Appendix B

Grayscale Stop-Flow Lithography

- **B.1** Introduction
- **B.2** Experimental Procedure
- **B.2.1** Design of Grayscale Filters
- B.2.2 Grayscale Stop-Flow Lithography
- **B.3** Results and Discussion
- **B.3.1** Intensity Reduction
- **B.3.2** Particle Size Reduction
- **B.3.3** Particle Swelling Issues