NPTEL Course: Programming, Data Structures and Algorithms in Python (*by* Prof. Madhvan Mukund)

Tutorial (Week 4)

Presented by: Jivesh Dixit

Problem 1: Convert all the digits of a number to respective word

Idea here is to convert the digits of a number to word, for example, 1234 will be read as 'One Two Three Four'.

Approach:

- > First of all, we shall check for the validity of the user input.
- > For a valid user input, we shall start with a base case, where 0 will return 'Zero'
- ➤ Now we shall *recursively* assign the word for respective digit.
- However, we need to be careful while printing our output as printing before recursion call can produce a reversed output (see example in the <u>notebook</u> used).

Problem 2: Converting a dictionary with values as a list to flat dictionary.

In real life problems the memory required to store the data could be quite large. In practice it is handy to wisely store the data in a variable in such a manner that it takes minimum possible memory.

For example, a dictionary {'seq_in_year' : [1, 2, 3, 4], 'month' : ['JAN', 'FEB', 'MARCH',]} can be rewritten as: {1: 'JAN', 2: 'FEB', 3: 'MAR'}, this will not only save some memory stored in the variable, but will also simplify the iterations when required for calculations.

Approach:

- ➤ Using *inbuilt* functions like zip() and dict() we can easily simplify our dictionary.
- Example for the same and importance is discussed in the <u>notebook</u> discussed during tutorial.

Problem 3: Standard deviation of the numeric values in a tuple of the form (('str1',num1),('str2',num2)..so on)

Standard deviation** is the statistical measure of the spread about the mean in a dataset.

$$mean\left(\overline{x}
ight) \ = \ rac{1}{N} \sum_{i=1}^{N} x_i$$

standard deviation
$$(\sigma) = \sqrt{\frac{1}{N-1} \sum_{i=1}^{N} (x_i - \bar{x})^2}$$

Approach:

- As the standard deviation is meaningful only for numeric value, hence second element of the nested tuple is of importance.
- We need to carefully iterate over the numeric element of the nested tuple to compute the mean and then standard deviation.
- ➤ However, there are numerous standard libraries in python to compute the statistical parameters.