

Database Schema

1. Orders

Column Name	Data Type	Description
order_id	INT (PK)	Unique order identifier
customer_id	INT	Customer identifier
store_id	INT (FK)	Dark store identifier
rider_id	INT (FK)	Assigned rider
order_time	DATETIME	Time when order was placed
dispatch_time	DATETIME	Time when order left the store
delivery_time	DATETIME	Time when order was delivered
order_status	VARCHAR	Delivered / Cancelled / Returned
payment_mode	VARCHAR	UPI / Card / COD / Wallet
total_amount	DECIMAL	Total order value (₹)
sla_target_minutes	INT	Promised delivery time
actual_delivery_minutes	INT	Actual delivery time

2. Order_Items

Column Name	Data Type	Description
order_item_id	INT (PK)	Unique order item ID
order_id	INT (FK)	Links to Orders table
sku_id	INT (FK)	Product ID
quantity	INT	Quantity ordered
unit_price	DECIMAL	Price per unit (₹)
discount	DECIMAL	Discount applied (₹)
final_price	DECIMAL	Final amount after discount (₹)

3. Products

Column Name	Data Type	Description
sku_id	INT (PK)	Unique product ID
product_name	VARCHAR	Product name
category	VARCHAR	Grocery, Dairy, Snacks, Beverages, Personal Care
brand	VARCHAR	Brand name
mrp	DECIMAL	Maximum Retail Price (₹)
selling_price	DECIMAL	Selling Price (₹)
weight	VARCHAR	500g, 1L, 250ml etc.
shelf_life_days	INT	Product shelf life
reorder_level	INT	Minimum stock before replenishment
is_active	BOOLEAN	Active / Discontinued

4. Inventory

Column Name	Data Type	Description
inventory_id	INT (PK)	Unique inventory record ID
store_id	INT (FK)	Dark store ID
sku_id	INT (FK)	Product ID
system_stock	INT	Stock available in the system
physical_stock	INT	Physically counted stock
damaged_stock	INT	Damaged/expired stock
reserved_stock	INT	Stock reserved for pending orders
reorder_level	INT	Minimum stock threshold
last_restock_date	DATE	Last replenishment date
inventory_check_date	DATE	Date of stock audit

5. Stores

Column Name	Data Type	Description
store_id	INT (PK)	Unique dark store ID
store_name	VARCHAR	Store name
city	VARCHAR	City
locality	VARCHAR	Area/Locality
manager_name	VARCHAR	Store manager
opening_date	DATE	Store opening date
operating_hours	VARCHAR	Example: 6 AM – 12 AM
store_capacity	INT	Maximum inventory capacity
latitude	DECIMAL	Store latitude
longitude	DECIMAL	Store longitude

6. Riders

Column Name	Data Type	Description
rider_id	INT (PK)	Unique rider ID
rider_name	VARCHAR	Rider name
store_id	INT (FK)	Assigned dark store
shift	VARCHAR	Morning / Afternoon / Evening / Night
experience_months	INT	Experience in months
vehicle_type	VARCHAR	Bike / Cycle / EV
employment_type	VARCHAR	Full-Time / Part-Time
status	VARCHAR	Active / Inactive