

# Joint Track Machine Learning

---

Andrew Jensen

March 9, 2023

# Outline

## Aims

Aim 1 - Joint Track Machine Learning

Aim 2 - Overcoming Single-Plane Limitations

Aim 3 - Pilot Human Study

Aim 4 - Standardized Kinematics Exam

Aim 5 - Joint Track Auto Toolkit

## References

## Acknowledgments

I would like to thank the McJunkin Family Charitable Foundation for their generous grant that supports this work.


# The Problem

- By 2030, roughly 3.5 million Total Knee Arthroplasty (TKA) will be performed in the US [15].
- 20% of patients receiving TKA are dissatisfied.
  - Instability, pain, unnatural [14, 17, 18].
- No reliable method of clinically assessing and quantifying joint dynamics.
  - Human supervision
  - Time consuming
  - Specialized equipment



# Our Proposition

Orthopaedic surgeons and clinicians would readily adopt a **practical** and **inexpensive** technology that allows them to **measure** a patient's knee kinematics during **activities of daily living**.




# Constraints

- It must fit within a **standard clinical workflow**
- The technology must utilize equipment **commonly found in hospitals**
- There must not be significant **human supervision** nor interaction to generate an examination report.




## Background - Projective Geometry



## Background - Model-Image Registration


If we know the projective parameters of the fluoroscopy machine, can we tinker with  $T_{implant}^{cam}$  so that our virtual projection matches the fluoroscopic image?



From [11]

## Background - Model-Image Registration

If we know the projective parameters of the fluoroscopy machine, can we tinker with  $T_{implant}^{cam}$  so that our virtual projection matches the fluoroscopic image?



From [11]

## Historical Overview

Many different approaches have attempted to solve the model-image registration problem.

- Pre-computed projections
- Skin-mounted motion Capture
- Biplane Imaging
- Iterative Projections
- Roentgen Stereophotogrammetry

# Pre-Computed Projections

- Saving space and memory by pre-computing as much as possible.
- Pre-computed distance maps [34, 6].
- Pre-computed shape libraries [7]





Fig. 2. Projection line to surface distance computation.

From [6]



# Limitations of Pre-Computed Projections

- Requires an accurate contour from the input image in order to perform calculations.
  - Human supervision for isolated contour
  - Inaccuracy with naive edge detection






Fig. 2. Projection line to surface distance computation.

From [6]



# Motion Capture (MoCap)




From [16]

- Can measure motion of MoCap beads very accurately.
- Skin-mounted [16, 19, 21].
- Bone pins [5].



# Limitations of Motion Capture



From [16]



## Skin Mounted


- Doesn't accurately describe underlying skeletal motion with clinical accuracy [16, 19, 21].

## Bone Pins


- Any volunteers?

# Biplane Imaging

- Utilizes multiple cameras to resolve 3D position and orientation[20, 29].
  - Highly accurate.
  - Gold Standard.




Both from [20]




# Limitations of Biplane Imaging

- Not many hospitals have biplane fluoroscopy setups.
- Clinically impractical




Both from [20]



# Iterative Projections

- Take advantage of modern computational graphics pipelines to quickly perform projection matching.
  - Image/Intensity similarity metrics [11]
  - Feature/Contour similarity metrics [24]




From [11]



From [24]

# Limitations of (historic) Iterative Projection Methods

- Requires human supervision for:
  - Pose initialization
  - Escaping local minima
  - Implant detection
- Chaotic and Noisy objective function




From [11]



From [24]

# Roentgen Stereophotogrammetry (RSA)


- Uses implanted tantalum beads for motion tracking [10, 4]
- Extremely accurate [12, 13]
- Gold standard Measurement [33]



From [10]

# Limitations of RSA

- Involves additional surgical procedures for inserting tantalum beads.
- Human supervision
- Bi-plane imaging



From [10]

## Aims

---

# Aims

## Aims 1/2

Joint Track Machine

Learning and Overcoming

Single-Plane Limitations

## Aim 3/4

Pilot Trials and

Standardized Kinematics

Exam

## Aim 5

Joint Track Auto Toolkit

## Aims

Aim 1 - Joint Track Machine Learning

Aim 2 - Overcoming Single-Plane Limitations

Aim 3 - Pilot Human Study

Aim 4 - Standardized Kinematics Exam

Aim 5 - Joint Track Auto Toolkit


## References

# Goal

Demonstrate the feasibility of a fully autonomous, model-image registration pipeline.


# Method

- Three-tiered approach
  - Convolutional Neural networks (CNN) for autonomous implant detection
  - Normalized Fourier Descriptor shape libraries
  - Robust contour-based global optimization scheme




# Autonomous Implant Detection Using Convolutional Neural Networks

- 2 CNNs
  - Femoral and Tibial implants
- High Resolution Network [27]




# Neural Network Data

- ~8000 images
  - 7 TKA kinematics studies
    - 71 subjects
    - 7 implant manufacturers
    - 36 distinct implants
    - Squat, lunge, kneel, stair ascent




# Neural Network Robustness

- Additional augmentations introduced during training [25].



# Normalized Fourier Descriptor Shape Libraries

- Pose initialization using segmentation output.
- $\pm 30^\circ$  library span at  $3^\circ$  increments.



# Pose Refinement Using Global Optimization

- Two main features
  - Objective function
  - Optimization routine


$$\underset{x}{\operatorname{argmin}} \{f(x) : x \in \Omega\}$$

## Contour-based Objective Function

- With accurate projection, contours provide a strong heuristic for orientation.
- Overlapping pixels between CNN segmentation and projected implant.
  - $L_1$  norm has quick parallel computation.

$$J = \sum_{i \in H} \sum_{j \in W} |I_{ij} - P_{ij}| = L_1(I, P)$$

- Sensitive to minor perturbations



## Improving Robustness

- Dilation decreases sensitivity to perturbations.
- Multi-stage optimization can reduce dilation back to original edges.




## Optimization Routine

- No analytic form of the objective function exists, it **must** be sampled at points of interest.
  - Black Box Optimization [22, 28]

# Lipschitzian Optimization

- Robust, global, black-box optimization routine if Lipschitz constant ( $K$ ) is known [2].
- Lipschitz constant bounds the rate of change of a function.
- What if you don't know the Lipschitz constant?




# Lipschitzian Optimization without the Lipschitz Constant

## Lipschitzian Optimization Without the Lipschitz Constant

D. R. JONES,<sup>1</sup> C. D. PERTTUNEN,<sup>2</sup> AND B. E. STUCKMAN<sup>3</sup>

- Sample end-points instead of intersecting lines.
- Potentially optimal regions based on value at center and total size.
  - Trisect potentially optimal regions and re-sample centers



# Trisecting Region


$$\begin{bmatrix} f(x = c_1) & d(c_1) \\ f(x = c_2) & d(c_2) \\ \vdots & \vdots \\ f(x = c_N) & d(c_N) \end{bmatrix}$$

Where

$f(x = c_i) \equiv$  Sampled function value

$d(c_i) \equiv$  Sub-domain size

for  $i \in [1, N]$



## Another Iteration


$$\begin{bmatrix} f(x = c_1) & d(c_1) \\ f(x = c_2) & d(c_2) \\ \vdots & \vdots \\ f(x = c_N) & d(c_N) \end{bmatrix}$$

Where

$f(x = c_i) \equiv$  Sampled function value


$d(c_i) \equiv$  Sub-domain size

for  $i \in [1, N]$



# Determining Potentially Optimal Regions

- Convex hull [1, 3, 9, 8] of region size vs. center value




# DiRECT for Joint Track Machine Learning

- Search region is along all 6 degrees of freedom.
  - Normalize to [0, 1].
- Three stages, each with decreasing levels of dilation.
  - Iteration budget for each stage.

Stage	Budget [Iterations]	Search Range [mm,deg]	Dilation (pixels)
“Tree”	~20,000	±45	5
“Branch”	~20,000	±25	3
“Leaf”	~10,000	±100 ( $z_{trans}$ ) / ±3 ( <i>else</i> )	1


# Testing Performance

Now that we have our refined poses, how well does our system perform?



# Validation

- Independent research group using Model-Based RSA.
- Determine the level of concordance between the two measurement systems
  - Bland-Altman Plots
- Achieved clinically acceptable accuracy [33, 32].
- Highly repeatable



## Awards

The work presented in this aim won the HAP Paul Award for Best Paper from the International Society for Technology in Arthroplasty's 2022 Annual Meeting.



## Aims

Aim 1 - Joint Track Machine Learning

Aim 2 - Overcoming Single-Plane Limitations

Aim 3 - Pilot Human Study

Aim 4 - Standardized Kinematics Exam

Aim 5 - Joint Track Auto Toolkit

## References

## Goal

- The goal of this aim is to validate and test methods that can overcome single-plane limitations for model-image registration.
  - Out-of-plane (OOP) Translation
  - Symmetry Traps

## Translation

- Depth perception is lost when using a single camera.
- Utilize a virtual “spring” to constrain relative OOP translation between implant components.

$$J = \alpha L_1(I, P) + \beta ML(Fem, Tib)$$


Where

$ML \equiv$  Relative mediolateral translation

## Symmetry Traps

With a symmetric tibial implant, the contour is not always a perfect heuristic for true pose. Human operators typically utilize relative varus-valgus to determine correct pose.


Found “ambiguous zone” within  $3^\circ$  of pure lateral pose with high propensity for symmetry traps [32].



## Solving the Symmetric Pose

Algorithm devised to “flip” pose into symmetric counterpart.

1. Determine viewing ray from camera to implant centroid, denote  $\vec{v}$ , normalize.
2. Denote symmetric-plane normal vector  $\vec{s}$ , normalize.
3. Measure relative “off-lateral” orientation of implant,  
$$\cos(\theta) = \frac{\vec{v} \cdot \vec{s}}{||\vec{v}|| ||\vec{s}||}$$
4. Apply body-centered rotation to implant about  $\vec{m} = \vec{s} \times \vec{v}$  by  $\psi = 2\theta$ .



## Four Approaches

- Virtual ligaments
- Binary selection between two poses
- Bland-Altman Calibration Constant
- Fully Connected Network

## Virtual Ligaments

$$J = \alpha L_1(I, P) + \beta ML(Fem, Tib) + \gamma VV(Fem, Tib)$$

Where

$VV \equiv$  Relative Varus-Valgus rotation


## Binary Selection

1. Determine optimized pose using  $L_1 + ML$
2. Calculate symmetric pose.
3. Pick pose with lower relative VV

This method can simplify the selection criteria (one fewer hyperparameter).


# Bland-Altman Calibration Constant

- Utilizing Bland-Altmann plots from gold-standard kinematics, create a “correction constant” for relative varus/valgus (ad/abduction) angles.
- Notice linear trend in BA plots.



# Fully Connected Network

- Encode symmetric pose calculation into FCN.
- Feed femoral and tibial **pose** into network.
  - “Keep” or “Switch”
- Could incorporate categorical features as well
  - Weightbearing vs non-weightbearing
  - Activity (walking, stair, lunge, etc)



## Timeline

- All kinematics data has already been collected.
- Completed Methods
  - Virtual Ligaments
- In Progress
  - Binary Selection
- Pending Methods
  - Bland-Altman Calibration
  - Fully Connected Network

Journal paper will be ready for submission by June.

## Aims

Aim 1 - Joint Track Machine Learning

Aim 2 - Overcoming Single-Plane Limitations

**Aim 3 - Pilot Human Study**

Aim 4 - Standardized Kinematics Exam

Aim 5 - Joint Track Auto Toolkit

## References

# Goal

No kinematics studies have exclusively utilized Joint Track Machine Learning; let's be the first.

What are we measuring?

- Kinematics
- Time to full examination report
  - Time/frame
  - Usage hiccups
  - Symmetry traps

## Methods

- 20-30 patients
- ~Dozen activities with fluoroscopic machine
  - Weightbearing and Non-weightbearing
  - Static and Dynamic

IRB approval ~4 months out.

## Aims

Aim 1 - Joint Track Machine Learning

Aim 2 - Overcoming Single-Plane Limitations

Aim 3 - Pilot Human Study

**Aim 4 - Standardized Kinematics Exam**

Aim 5 - Joint Track Auto Toolkit

## References

## Goal

Establish a “standard kinematics exam” by determining the most statistically and anatomically relevant fluoroscopic image(s) to capture during a clinical visit.

## Motivation

- We have standardized pain/outcome scores
  - KOOS, KSS, FJS, etc..
- No standardized kinematics examination
  - Per-study differences
  - No reason to standardize

Autonomous kinematics measurements allow researchers to spend more time asking and answering questions rather than fiddling with annoying software.

## Method

- Use images and kinematics from Aim 3.
- Utilize statistical methods to determine covariance and causal/corollary relationships.
  - Clustering
  - Transformers [26, 23, 31, 30] (“translating” movements into outcomes and other movements)

## Aims

Aim 1 - Joint Track Machine Learning

Aim 2 - Overcoming Single-Plane Limitations

Aim 3 - Pilot Human Study

Aim 4 - Standardized Kinematics Exam

Aim 5 - Joint Track Auto Toolkit

## References

## Joint Track Auto Toolkit (JTAT)

Create a freely available Python library that allows other researchers to utilize JTML's model-image registration framework. Extra emphasis will be placed on extensibility to allow other researchers to compose their own registration pipelines.

## Presentations

---

- [1] Scott Banks, Andrew James Jensen, and Paris Flood. *In Regione Caecorum Rex Est Lucus - Towards Routine Clinical Examinations of Joint Kinematics.* Oslo, Norway, 2019.
- [2] Paris Flood, Andrew Jensen, and Scott Banks. *Towards Practical Clinical Examination of 3D Joint Kinematics Using Machine Learning.* Podium. Toronto, Ontario, 2019.
- [3] Andrew Jensen, Yifei Dai, and Andrea Gardner. *Impact of Sagittal Resection Variability on Implant Fit during Partial Knee Arthroplasty.* Podium. Phoenix, AZ, Feb. 2020.

## Presentations ii

- [4] Andrew Jensen et al. *Comparison of Clinical and Computational Implant Fit Analysis in Partial Knee Arthroplasty*. Podium. Phoenix, AZ, Feb. 2020.
- [5] Andrew Jensen et al. *Towards Routine Clinical Examination of 3D Joint Kinematics*. Korea, 2020.
- [6] Yifei Dai et al. *Comparative Analysis of Fixation Structure Design on the Primary Stability of Cementless TKA during Walking*. Podium. Online, Feb. 2021.
- [7] Yifei Dai et al. *Impact of Fixation Components on Primary Stability of Cementless TKA during Walking*. Podium. Online, Feb. 2021.
- [8] Andrew Jensen et al. *Accuracy of an Autonomous Method for Extracting Joint Kinematics from Single-Plane Fluoroscopy*. Oslo, Norway, 2021.

- [9] Andrew James Jensen et al. *An Autonomous Method for Extracting 3D Knee Replacement Kinematics from Dynamic Single Plane Fluoroscopic Images.* Online, 2021.
- [10] Jacob Griffith et al. *Automated Segmentation and Grading of Rodent Knee OA Histology Using Convolutional Neural Networks.* Poster. Tampa, FL, Feb. 2022.
- [11] Andrew Jensen, Lindsey Palm, and Scott Banks. *Autonomous Measurement of 3D TKA Kinematics from Dynamic Single-Plane Fluoroscopic Images.* Podium. Tampa, FL, Feb. 2022.
- [12] Andrew Jensen. *Deep Learning for Image Processing in Orthopaedics.* Virtual Scientific Session. Online, Jan. 2023.

## Publications

---

- [1] William Burton et al. “**Automatic Tracking of Healthy Joint Kinematics from Stereo-Radiography Sequences.**”. In: *Computers in Biology and Medicine* (2021). DOI: 10.1016/j.combiomed.2021.104945.
- [2] Andrew Jensen et al. “**Joint Track Machine Learning: An Autonomous Method for Measuring 6DOF TKA Kinematics from Single-Plane x-Ray Images**”. In: *arXiv:2205.00057 [q-bio]* (Apr. 2022). arXiv: 2205.00057 [q-bio]. (Visited on 05/03/2022).

## Publications ii

- [3] Jordan S. Broberg et al. “**Validation of a Machine Learning Technique for Segmentation and Pose Estimation in Single Plane Fluoroscopy**”. In: *Journal of Orthopaedic Research* (Feb. 2023). ISSN: 0736-0266, 1554-527X. DOI: 10.1002/jor.25518. (Visited on 02/13/2023).

## Timeline

Date(s)	Event
2015-2019	Mech. Eng. B.S, Magna Cum Laude, UF
April 2019 - April 2020	Internship at Exactech
April 2020	Started in Miller Lab
August 2020	Officially Started PhD at UF
November 2021	Best Presentation Award at ISTA: Emerging Technologies
April 2022	Submitted JTML for HAP Paul Award
September 2022	HAP Paul Award at ISTA 2022
June 2023	Single-plane limitations paper submitted
July 2023	Est. IRB Approval
August 2023	v1.0 JTAT
December 2023 ~ May 2024	Patient Data Fully Collected (Aims 3/4)
August 2024	Papers for Aims 3/4 Submitted
December 2024 - April 2025	Est. Graduation

Thank you!

Thanks for listening!!

## References

---

## References

---

- [1] R.L. Graham. “**An Efficient Algorithm for Determining the Convex Hull of a Finite Planar Set**”. In: *Information Processing Letters* 1.4 (June 1972), pp. 132–133. ISSN: 00200190. DOI: 10.1016/0020-0190(72)90045-2. (Visited on 02/20/2023).
- [2] Bruno O. Shubert. “**A Sequential Method Seeking the Global Maximum of a Function**”. In: *SIAM Journal on Numerical Analysis* 9.3 (1972), pp. 379–388. DOI: 10.1137/0709036. eprint: <https://doi.org/10.1137/0709036>.
- [3] R A Jarvis. “**On the Identification of the Convex Hull of a Finite Set of Points in the Plane**”. In: (1973).
- [4] Göran Selvik. “**Roentgen Stereophotogrammetry: A Method for the Study of the Kinematics of the Skeletal System**”. In: *Acta Orthopaedica Scandinavica* 60.sup232 (Jan. 1989), pp. 1–51. ISSN: 0001-6470. DOI: 10.3109/17453678909154184. (Visited on 02/14/2023).

## References ii

- [5] Mario A. Lafortune et al. “**Three-Dimensional Kinematics of the Human Knee during Walking.**”. In: *Journal of Biomechanics* (1992). DOI: 10.1016/0021-9290(92)90254-x.
- [6] S. Lavallee and R. Szeliski. “**Recovering the Position and Orientation of Free-Form Objects from Image Contours Using 3D Distance Maps**”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 17.4 (Apr. 1995), pp. 378–390. ISSN: 01628828. DOI: 10.1109/34.385980. (Visited on 05/12/2021).
- [7] S.A. Banks and W.A. Hodge. “**Accurate Measurement of Three-Dimensional Knee Replacement Kinematics Using Single-Plane Fluoroscopy**”. In: *IEEE Transactions on Biomedical Engineering* 43.6 (June 1996), pp. 638–649. ISSN: 00189294. DOI: 10.1109/10.495283. (Visited on 03/22/2021).
- [8] C. Bradford Barber, David P. Dobkin, and Hannu Huhdanpaa. “**The Quickhull Algorithm for Convex Hulls**”. In: *ACM Transactions on Mathematical Software* 22.4 (Dec. 1996), pp. 469–483. ISSN: 0098-3500, 1557-7295. DOI: 10.1145/235815.235821. (Visited on 02/20/2023).

## References iii

- [9] T. M. Chan. “Optimal Output-Sensitive Convex Hull Algorithms in Two and Three Dimensions”. In: *Discrete & Computational Geometry* 16.4 (Apr. 1996), pp. 361–368. ISSN: 0179-5376, 1432-0444. DOI: 10.1007/BF02712873. (Visited on 02/20/2023).
- [10] Henri A Vrooman et al. “Fast and Accurate Automated Measurements in Digitized Stereophotogrammetric Radiographs”. In: *Journal of Biomechanics* 31.5 (May 1998), pp. 491–498. ISSN: 00219290. DOI: 10.1016/S0021-9290(98)00025-6. (Visited on 09/09/2021).
- [11] M.R. Mahfouz et al. “A Robust Method for Registration of Three-Dimensional Knee Implant Models to Two-Dimensional Fluoroscopy Images”. In: *IEEE Transactions on Medical Imaging* 22.12 (Dec. 2003), pp. 1561–1574. ISSN: 0278-0062. DOI: 10.1109/TMI.2003.820027. (Visited on 03/22/2021).
- [12] B L Kaptein et al. “Evaluation of Three Pose Estimation Algorithms for Model-Based Roentgen Stereophotogrammetric Analysis”. In: *Proceedings of the Institution of Mechanical Engineers, Part H: Journal of Engineering in Medicine* 218.4 (Apr. 2004), pp. 231–238. ISSN: 0954-4119, 2041-3033. DOI: 10.1243/0954411041561036. (Visited on 12/19/2022).

- [13] Tuuli Saari et al. “Knee Kinematics in Medial Arthroscopy. Dynamic Radiostereometry during Active Extension and Weight-Bearing”. In: *Journal of Biomechanics* 38.2 (Feb. 2005), pp. 285–292. ISSN: 00219290. DOI: 10.1016/j.jbiomech.2004.02.009. (Visited on 09/09/2021).
- [14] P. N. Baker et al. “The Role of Pain and Function in Determining Patient Satisfaction After Total Knee Replacement: Data From the National Joint Registry for England and Wales”. In: *The Journal of Bone and Joint Surgery. British volume* 89-B.7 (July 2007), pp. 893–900. ISSN: 0301-620X, 2044-5377. DOI: 10.1302/0301-620X.89B7.19091. (Visited on 03/22/2021).
- [15] Steven Kurtz et al. “Projections of Primary and Revision Hip and Knee Arthroplasty in the United States from 2005 to 2030:” in: *The Journal of Bone & Joint Surgery* 89.4 (Apr. 2007), pp. 780–785. ISSN: 0021-9355. DOI: 10.2106/JBJS.F.00222. (Visited on 01/20/2021).
- [16] Bo Gao and Naiquan (Nigel) Zheng. “Investigation of Soft Tissue Movement during Level Walking: Translations and Rotations of Skin Markers”. In: *Journal of Biomechanics* 41.15 (Nov. 2008), pp. 3189–3195. ISSN: 00219290. DOI: 10.1016/j.jbiomech.2008.08.028. (Visited on 03/31/2022).

- [17] Robert B. Bourne et al. “**Patient Satisfaction after Total Knee Arthroplasty: Who Is Satisfied and Who Is Not?**” In: *Clinical Orthopaedics & Related Research* 468.1 (Jan. 2010), pp. 57–63. ISSN: 0009-921X. DOI: 10.1007/s11999-009-1119-9. (Visited on 03/22/2021).
- [18] C. E. H. Scott et al. “**Predicting Dissatisfaction Following Total Knee Replacement: A Prospective Study of 1217 Patients**”. In: *The Journal of Bone and Joint Surgery. British volume* 92-B.9 (Sept. 2010), pp. 1253–1258. ISSN: 0301-620X, 2044-5377. DOI: 10.1302/0301-620X.92B9.24394. (Visited on 03/22/2021).
- [19] Mei-Ying Kuo et al. “**Influence of Soft Tissue Artifacts on the Calculated Kinematics and Kinetics of Total Knee Replacements during Sit-to-Stand**”. In: *Gait & Posture* 33.3 (Mar. 2011), pp. 379–384. ISSN: 09666362. DOI: 10.1016/j.gaitpost.2010.12.007. (Visited on 09/09/2021).
- [20] John C. Ivester et al. “**A Reconfigurable High-Speed Stereo-Radiography System for Sub-Millimeter Measurement of In Vivo Joint Kinematics**”. In: *Journal of Medical Devices* 9.4 (Dec. 2015), p. 041009. ISSN: 1932-6181, 1932-619X. DOI: 10.1115/1.4030778. (Visited on 10/18/2022).

- [21] Cheng-Chung Lin et al. “**Effects of Soft Tissue Artifacts on Differentiating Kinematic Differences between Natural and Replaced Knee Joints during Functional Activity**”. In: *Gait & Posture* 46 (May 2016), pp. 154–160. ISSN: 09666362. DOI: 10.1016/j.gaitpost.2016.03.006. (Visited on 09/09/2021).
- [22] Charles Audet and Warren Hare. ***Derivative-Free and Blackbox Optimization***. Springer Series in Operations Research and Financial Engineering. Cham: Springer International Publishing, 2017. ISBN: 978-3-319-68912-8 978-3-319-68913-5. DOI: 10.1007/978-3-319-68913-5. (Visited on 01/27/2023).
- [23] Ashish Vaswani et al. ***Attention Is All You Need***. Dec. 2017. arXiv: 1706.03762 [cs]. (Visited on 12/23/2022).
- [24] P. D. L. Flood and Scott A. Banks. “**Automated Registration of 3-D Knee Implant Models to Fluoroscopic Images Using Lipschitzian Optimization**”. In: *IEEE Transactions on Medical Imaging* 37.1 (2018), pp. 326–335. DOI: 10.1109/tmi.2017.2773398.
- [25] Alexander Buslaev et al. “**Albumentations: Fast and Flexible Image Augmentations**”. In: *Information* 11.2 (Feb. 2020), p. 125. ISSN: 2078-2489. DOI: 10.3390/info11020125. (Visited on 10/24/2020).

- [26] Nicolas Carion et al. “**End-to-End Object Detection with Transformers**”. In: (2020), pp. 213–229. DOI: 10.1007/978-3-030-58452-8\_13.
- [27] Jingdong Wang et al. “**Deep High-Resolution Representation Learning for Visual Recognition**”. In: *arXiv:1908.07919 [cs]* (Mar. 2020). arXiv: 1908.07919 [cs]. (Visited on 09/29/2020).
- [28] Ishan Bajaj, Akhil Arora, and M. M. Faruque Hasan. “**Black-Box Optimization: Methods and Applications**”. In: (Jan. 2021), pp. 35–65. DOI: 10.1007/978-3-030-66515-9\_2.
- [29] William Burton et al. “**Automatic Tracking of Healthy Joint Kinematics from Stereo-Radiography Sequences.**”. In: *Computers in Biology and Medicine* (2021). DOI: 10.1016/j.combiomed.2021.104945.
- [30] Alexey Dosovitskiy et al. *An Image Is Worth 16x16 Words: Transformers for Image Recognition at Scale*. June 2021. arXiv: 2010.11929 [cs]. (Visited on 02/14/2023).
- [31] Meng-Hao Guo et al. “**Attention Mechanisms in Computer Vision: A Survey**”. In: *arXiv: Computer Vision and Pattern Recognition* (Nov. 2021).

- [32] Andrew Jensen et al. “**Joint Track Machine Learning: An Autonomous Method for Measuring 6DOF TKA Kinematics from Single-Plane x-Ray Images**”. In: *arXiv:2205.00057 [q-bio]* (Apr. 2022). arXiv: 2205.00057 [q-bio]. (Visited on 05/03/2022).
- [33] Jordan S. Broberg et al. “**Validation of a Machine Learning Technique for Segmentation and Pose Estimation in Single Plane Fluoroscopy**”. In: *Journal of Orthopaedic Research* (Feb. 2023). ISSN: 0736-0266, 1554-527X. DOI: 10.1002/jor.25518. (Visited on 02/13/2023).
- [34] S. Zuffi et al. “**A Model-Based Method for the Reconstruction of Total Knee Replacement Kinematics**”. In: *IEEE Transactions on Medical Imaging* 18.10 (Oct./1999), pp. 981–991. ISSN: 02780062. DOI: 10.1109/42.811310. (Visited on 09/01/2020).