

Submission for Problem Set 5 (due Monday, November 5, 11:59 PM)

Name: Deepanshu Parihar

Problem 1. (5 points) Three-character Huffman codes

Consider the problem of Huffman codes where we use three characters from $\{0, 1, 2\}$ in our code, as opposed to the bits 0 and 1. Modify the Huffman encoding algorithm to determine a minimum-length compression of any sequence of characters from an alphabet A of size n , with the i th letter of the alphabet having frequency $f[i]$. Your algorithm should encode each character with a variable-length codeword over the values $\{0, 1, 2\}$ such that no codeword is a prefix of another codeword and so as to obtain the maximum possible compression. Prove that your algorithm is correct. Analyze the worst-case running time of your algorithm.

Answer: There are two possible cases, one when n is odd and one when n is even
 A is a set of n characters. So,

if(n is odd)

```
1 Initialize Min-priority Queue  $Q = A$ 
2  $n = \text{size of } (A)$ 
3 for  $i = 1$  to  $n - 1$ 
4   allocate a new node  $z$ 
5    $z.\text{left} = p = \text{EXTRACT-MIN}(Q)$ 
6    $z.\text{right} = q = \text{EXTRACT-MIN}(Q)$ 
7    $z.\text{center} = r = \text{EXTRACT-MIN}(Q)$ 
7    $z.\text{freq} = p.\text{freq} + q.\text{freq} + r.\text{freq}$ 
8    $\text{INSERT}(Q, z)$ 
9 return  $\text{EXTRACT-MIN}(Q)$ 
```

10 else if(n is even)

```
11 Initialize Min-priority Queue  $Q = A$ 
12  $n = \text{size of } (A)$ 
13 allocate a new node  $z$ 
14  $z.\text{left} = p = \text{EXTRACT-MIN}(Q)$ 
15  $z.\text{right} = q = \text{EXTRACT-MIN}(Q)$ 
16  $z.\text{freq} = p.\text{freq} + q.\text{freq}$ 
17  $\text{INSERT}(Q, z)$  (now the size is odd, so we can do the same procedure again)
18 for  $i = 1$  to  $n - 2$  (as now the length of the queue has been reduced by one)
.   Using Min-priority queue  $Q$ 
19   allocate a new node  $m$ 
20    $m.\text{left} = p = \text{EXTRACT-MIN}(Q)$ 
21    $m.\text{right} = q = \text{EXTRACT-MIN}(Q)$ 
```

```

22  m.center= r =EXTRACT-MIN(Q)
23  m.freq = p.freq + q.freq +r.freq
24  INSERT(Q,m)
25 return EXTRACT-MIN(Q)

```

Proof-

Extending the proof that was used for 2 bit encoding in class.

here we replace the frequency of three least frequency characters with one and calculate the cost of the new tree say A'. The difference of cost is either less than or greater to zero. Thus proving this to be a even more optimal solution.

Hence Proved

Running Time- All the extract and insert operations for a priority queue take $O(\log n)$ time individually. We do it here for n iterations. So the net complexity is $O(n \log(n))$

Problem 2. (5 points) Matching Widgets and Gadgets

You are given a set W of n widgets and a set G of n gadgets. Each widget w has a weight $W(w)$ and each gadget g has a weight $W(g)$. You would like to match each widget w in W to a unique gadget g in G so as to minimize the sum of the absolute values of the weight differences of the matched pairs. That is, you would like to find a perfect matching M between W and G that minimizes

$$\sum_{(w,g) \in M} |W(w) - W(g)|.$$

Design an efficient greedy algorithm to solve the given problem. Prove that your algorithm is correct. Analyze the worst-case running time of your algorithm.

Answer:

Algorithm-

Matching()

1. Sort set W of widgets in increasing order.
2. Sort set G of gadgets in increasing order.
3. n = number of widgets
4. Initialize a list L
5. for($i=0$ to n)
6. Add($Widget(i), gadget(i)$) to L
7. Return L

Running Time-

Since sorting is the dominant function here the running time is $O(n \log n)$.

Proof-

Suppose the pair were returned in a different order , then the net difference would be greater as

here after sorting the weights of the two. The net difference is being balanced out. If any other pair was taken in some other order then the aggregation of the difference of the weight between the pair would be minimized.

Problem 3. (3 + 2 = 5 points) Uniqueness of MSTs when all weights are distinct

- (a) Suppose T_1 and T_2 are distinct minimum spanning trees for graph G . Let (u, v) be the lightest edge (smallest weight edge) among all edges that are in T_1 and but not in T_2 . Let (x, y) be any edge that is in T_2 and not in T_1 . Show that $w(x, y) \geq w(u, v)$.

Answer:

Assume that there exists an edge e' in T_2 such that the $w(e')$ is less than the minimum edge in T_1 i.e. $w(u, v)$.

If this were true, then both T_1 and T_2 are MST of same graph G and this edge would be part of T_1 as well. So adding it to T_1 , we form a cycle. So we remove another edge whose weight is greater than e' . But now both T_1 and T_2 have a common edge e' which is not possible as we are considering all edges that are not common. Hence no such edge e' existed to begin with. Hence no such edge exists. Proved by contradiction.

- (b) Using part (a), prove that if the weights on the edges of a connected, undirected graph are distinct, then there is a unique minimum spanning tree.

Answer:

Suppose more than one MST exist for a connected, undirected graph whose edges are distinct. So considering two distinct MST T_1 and T_2 of same weight.

Then based on (a) $w(x, y)$ for T_2 is greater than equal to $w(u, v)$ i.e. minimum weight edge in T_1 .

Now, here every edge is distinct. So we get $w(x, y)$ for T_2 is greater than $w(u, v)$ i.e. minimum weight edge in T_1 for all the edges that are not common for T_1 and T_2 .

As this is true for two distinct MST for a graph G . The weight of the two trees cannot be the same as weight of each edge in T_2 is greater than the minimum edge in T_1 . So these trees cannot co exist. This is a contradiction to our assumption. Hence, Proved by contradiction.

Problem 4. (5 points) Leaf-Constrained Spanning Tree

Design an algorithm, which takes as input a connected undirected graph $G = (V, E)$, a weight function $w : E \rightarrow \mathbb{Z}^+$, and a subset U of V , and returns minimum-weight spanning tree of G satisfying the property that every vertex in U is a leaf in T . If no such spanning tree exists, then your algorithm must indicate so. Analyze the worst-case running time of your algorithm.

(Note: The desired spanning tree may not be a minimum spanning tree of G . The spanning tree your algorithm returns must satisfy the desired property and have the minimum weight among all spanning trees satisfying the desired property.)

Answer:

So here I form a MST by using vertices that are a part of set $V - U$ as subset U of vertices V are to be used as node and hence wont be connectors in MST.

If I dont get an MST then no spanning tree can be formed.

Else for vertices in U I find edges of minimum weight such that the edge links a vertex in U to a vertex of MST and if such edges cant be formed for all the vertices in U then also no spanning tree is formed. Else I return a spanning tree with connected leaves.

Algorithm-

1. Form a new graph G' formed by removing vertices that are present in set U and all its related edges.
2. Using Kruskal to find the MST.
3. If no MST exists, then no Spanning tree of desired property exists.
4. if (MST exists)
5. for (every vertex in U)
6. Find and connect minimum weighted edge e such that e connects a vertex in U to a vertex in MST.
7. if (no such edge exists)
8. no Spanning tree of desired property exists
9. Return MST.

Running Time-

Both Kruskal and find steps used in steps 2 and 6 respectively use $O(m \log(n))$ time i.e. $O(v \log(e))$. So worst case time is $O(v \log(e))$.