

# Quantum Algorithms & Qiskit

Alexander J. Heilman

August 18, 2021

# The Quantum Fourier Transform

The quantum Fourier transform (QFT) is a quantum implementation of the discrete Fourier transform

# The Quantum Fourier Transform

The quantum Fourier transform (QFT) is a quantum implementation of the discrete Fourier transform

This means if you give the QFT some state  $\sum_n |nk + l\rangle$ , the QFT will give back  $|k\rangle$ .

# The Quantum Fourier Transform

The quantum Fourier transform (QFT) is a quantum implementation of the discrete Fourier transform

This means if you give the QFT some state  $\sum_n |nk + l\rangle$ , the QFT will give back  $|k\rangle$ .

But what does that look like?

## QFT: The gory details

The explicit action of the n-qubit QFT on some given basis vector is

$$|j_1, \dots, j_n\rangle \longrightarrow \frac{(|0\rangle + e^{2\pi i 0.j_n} |1\rangle) \otimes (|0\rangle + e^{2\pi i 0.j_{n-1}j_n} |1\rangle) \otimes \dots \otimes (|0\rangle + e^{2\pi i 0.j_1 \dots j_n} |1\rangle)}{2^{n/2}}$$

.

## QFT: The gory details

The explicit action of the n-qubit QFT on some given basis vector is

$$\frac{|j_1, \dots, j_n\rangle \longrightarrow (|0\rangle + e^{2\pi i 0 \cdot j_n} |1\rangle) \otimes (|0\rangle + e^{2\pi i 0 \cdot j_{n-1} j_n} |1\rangle) \otimes \dots \otimes (|0\rangle + e^{2\pi i 0 \cdot j_1 \dots j_n} |1\rangle)}{2^{n/2}}$$

. Show circuit here

Sorry for asking?

## QFT: The gory details

The explicit action of the n-qubit QFT on some given basis vector is

$$\frac{|j_1, \dots, j_n\rangle \longrightarrow (|0\rangle + e^{2\pi i 0 \cdot j_n} |1\rangle) \otimes (|0\rangle + e^{2\pi i 0 \cdot j_{n-1} j_n} |1\rangle) \otimes \dots \otimes (|0\rangle + e^{2\pi i 0 \cdot j_1 \dots j_n} |1\rangle)}{2^{n/2}}$$

. Show circuit here

Sorry for asking? Don't be it's easier to see in matrix form

## QFT: The gory details II

For example with  $n = 3$  the QFT is

$$\frac{1}{2\sqrt{2}} \begin{bmatrix} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & \omega & \omega^2 & \omega^3 & \omega^4 & \omega^5 & \omega^6 & \omega^7 \\ 1 & \omega^2 & \omega^4 & \omega^6 & 1 & \omega^2 & \omega^4 & \omega^6 \\ 1 & \omega^3 & \omega^6 & \omega & \omega^4 & \omega^7 & \omega^2 & \omega^5 \\ 1 & \omega^4 & 1 & \omega^4 & 1 & \omega^4 & 1 & \omega^4 \\ 1 & \omega^5 & \omega^2 & \omega^7 & \omega^4 & \omega & \omega^6 & \omega^3 \\ 1 & \omega^6 & \omega^4 & \omega^2 & 1 & \omega^6 & \omega^4 & \omega^2 \\ 1 & \omega^7 & \omega^6 & \omega^5 & \omega^4 & \omega^3 & \omega^2 & \omega \end{bmatrix}$$



## QFT: The gory details II

For example with  $n = 3$  the QFT is

$$\frac{1}{2\sqrt{2}} \begin{bmatrix} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & \omega & \omega^2 & \omega^3 & \omega^4 & \omega^5 & \omega^6 & \omega^7 \\ 1 & \omega^2 & \omega^4 & \omega^6 & 1 & \omega^2 & \omega^4 & \omega^6 \\ 1 & \omega^3 & \omega^6 & \omega & \omega^4 & \omega^7 & \omega^2 & \omega^5 \\ 1 & \omega^4 & 1 & \omega^4 & 1 & \omega^4 & 1 & \omega^4 \\ 1 & \omega^5 & \omega^2 & \omega^7 & \omega^4 & \omega & \omega^6 & \omega^3 \\ 1 & \omega^6 & \omega^4 & \omega^2 & 1 & \omega^6 & \omega^4 & \omega^2 \\ 1 & \omega^7 & \omega^6 & \omega^5 & \omega^4 & \omega^3 & \omega^2 & \omega \end{bmatrix}$$

Not so interesting yet, but it's usefulness will soon be found in phase estimation

# Phase Estimation

Phase Estimation takes some given unitary operator and an associated eigenvector and returns the corresponding eigenvalue.

# Phase Estimation

Phase Estimation takes some given unitary operator and an associated eigenvector and returns the corresponding eigenvalue.

Phase estimation really returns  $|k\rangle$ , where the eigenvalue is  $\lambda = e^{i\theta}$  with  $\theta = k\frac{2\pi}{2^n}$ .

# Phase Estimation

Phase Estimation takes some given unitary operator and an associated eigenvector and returns the corresponding eigenvalue.

Phase estimation really returns  $|k\rangle$ , where the eigenvalue is  $\lambda = e^{i\theta}$  with  $\theta = k\frac{2\pi}{2^n}$ .

So how do we do this?

# Phase Estimation

Phase Estimation takes some given unitary operator and an associated eigenvector and returns the corresponding eigenvalue.

Phase estimation really returns  $|k\rangle$ , where the eigenvalue is  $\lambda = e^{i\theta}$  with  $\theta = k\frac{2\pi}{2^n}$ .

So how do we do this? Easy!

## Phase Estimation: Not so bad!

show circuit here with annotated state vector evolution, compare resulting statevector to QFT output

# Amplitude Estimation

Amplitude estimation takes some superposition of states partitioned into a good and a bad subspace, and returns a statevector nudged towards the good subspace.

# Amplitude Estimation

Amplitude estimation takes some superposition of states partitioned into a good and a bad subspace, and returns a statevector nudged towards the good subspace.

This is accomplished with consecutive applications of a special operator Show diagram here



# Amplitude Estimation: Working principles

The initial statevector can be decomposed as  
 $|\psi\rangle = \sin(\theta)|\mathcal{G}\rangle + \cos(\theta)|\mathcal{B}\rangle.$

# Amplitude Estimation: Working principles

The initial statevector can be decomposed as

$$|\psi\rangle = \sin(\theta)|\mathcal{G}\rangle + \cos(\theta)|\mathcal{B}\rangle.$$

We then construct the operator:  $\mathcal{S} = \mathbb{I} - 2|\mathcal{B}\rangle\langle\mathcal{B}|$

Qiskit is a software development kit with a python front-end partially developed by IBM.

Qiskit is a software development kit with a python front-end partially developed by IBM.

## Features

1. Simulate + visualize quantum circuits you create yourself

Qiskit is a software development kit with a python front-end partially developed by IBM.

## Features

1. Simulate + visualize quantum circuits you create yourself
2. Compatible with IBM's current quantum computers

Qiskit is a software development kit with a python front-end partially developed by IBM.

## Features

1. Simulate + visualize quantum circuits you create yourself
2. Compatible with IBM's current quantum computers
3. Vibrant and active online community

# Running the QFT

Let's run the 3-qubit QFT on some states

# Running the QFT

Let's run the 3-qubit QFT on some states



# Running the QFT

Let's run the 3-qubit QFT on some states

# Running the QFT

Let's run the 3-qubit QFT on some states

Put bloch spheres of QFT inputs + outputs here

# Finding Phases

Let's run the 3-qubit phase estimation algorithm on some gates

# Finding Phases

Let's run the 3-qubit phase estimation algorithm on some gates

If we use controlled phase gates, we already know that  $|0\rangle$  is an eigenvector. Put counts screenshots here

# Finding Phases

Let's run the 3-qubit phase estimation algorithm on some gates

# Finding Phases

Let's run the 3-qubit phase estimation algorithm on some gates

If we use controlled phase gates, we already know that  $|0\rangle$  is an eigenvector. Put counts screenshots here

# References I

Thanks