IBM z/OS Connect EE V3.0

zCEE Security and CICS Hands-on Lab



IBM Z
Wildfire Team –
Washington System Center

Lab Version Date: February 22, 2020

Table of Contents

Overview	4
Enabling Identity Propagation to CICS	
Test with identity propagation not enabled	
Summary	
Enabling CICS SSL security to a zCEE Server	10
Review the Loan Application	
Creating CICS SAF resources	
Enabling CICS SSL support	
Test the SSL connection from CICS to the zCEE server	22
Summary	24

Important: On the desktop there is a file named *Basic Configuration CopyPaste.txt*. This file contains commands and other text used in this workshop. Locate that file and open it. Use the copy-and-paste function (**Ctrl-C** and **Ctrl-V**) to enter commands or text. It will save time and help avoid typo errors. As a reminder text that appears in this file will be highlighted in yellow.

General Exercise Information and Guidelines

- ✓ This exercise requires the completion of the *zCEE Basic Configuration* and *zCEE Basic Security Configurations* exercises before it can be performed.
- ✓ This exercise requires using z/OS user identities *FRED* and *USER1*. The password for these users will be provided by the lab instructions.
- ✓ The acronyms RACF (resource access control facility) and SAF (*system authorization facility*) are used in this exercise. RACF is the IBM security manager product whereas SAF is a generic term for any security manager product, e.g. ACF2 or Top Secret or RACF. An attempt has been to use SAF when referring to information appropriate for any SAF product and to use RACF when referring to specific RACF commands or examples.
- ✓ Any time you have any questions about the use of IBM z/OS Explorer, 3270 screens, features or tools do not hesitate to ask the instructor for assistance.
- ✓ Text in **bold** and highlighted in **yellow** in this document should be available for copying and pasting in a file named *Basic Configuration CopyPaste* file on the desktop.
- ✓ Please note that there may be minor differences between the screen shots in this exercise versus what you see when performing this exercise. These differences should not impact the completion of this exercise.

Overview

This exercise demonstrates using examples the steps required to enable security between a CICS region and a z/OS Connect EE (zCEE) server.

In part one of the exercise identity propagation between a z/OS Connect EE (zCEE) server and CICS region be enabled and tested. Identity propagation in this context means that the identity authenticated by the zCEE server will be sent to the CICS region for subsequent CICS authorization checks. and in the second part SSL security between a CICS region and a z/OS Connect (zCEE) server will be demonstrated.

In part two of the exercise, SSL support will be added to a CICS region and the steps required to enable the exchange of certificates for mutual authentication between the CICS region and the zCEE server will be demonstrated. Finally, and SSL security and mutual authentication from a zCEE server to outbound API provider will be demonstrated.

Enabling Identity Propagation to CICS

When identity propagation is not required the only CICS connectivity related resource required is a TCPIPService resource, see an example below:

```
₩G31
File Edit Settings View Communication Actions Window Help
  OVERTYPE TO MODIFY
                                                                                    CICS RELEASE = 0710
     EDA ALter TCpipservice(
TCpipservice : IPIC
GROup : SYSPGRP
                    TCpipservice( IPIC
     DEScription ==>
                       ==> DFHISAIP
     Urm ==> DFHIS
POrtnumber => 01491
STatus ==> Open
PROtocol ==> IPic
                                                      Open | Closed
Http | Eci | User | IPic
     TRansaction ==> CISS
Backlog ==> 0000
                       ==> 00000
                                                        0-32767
      TSqprefix
     Host ==>
(Mixed Case) ==>
                       ==> ANY
      Ipaddress
                       ==> ANY
     SPeciftcps
                                                        No | 0-240000 (HHMMSS)
No | 0-65535
     SOcketclose ==> No
     MAXPersist ==> No
MAXDatalen ==> 000032
                                                        3-524288
                                                                           SYSID=CICS APPLID=CICS53Z
                                                 6 CRSR 7 SBH 8 SFH 9 MSG 10 SB 11 SF 12 CNCL
    1 HELP 2 COM 3 END
Connected to remote server/host wg31 using lu/pool TCP00112 and port 23
```

When the above resource definition is installed in a CICS region the CICS region will listen for inbound IPIC request on port 1491. When a request arrives, the CICS transaction CISS will be started and process the inbound IPIC request. The CICS authorization under which the CICS transaction will execute depends on the security configuration of the TCPIPService.

Now let's enable identity propagation between the zCEE server and a CICS region.

Test with identity propagation not enabled

But first let's explore the CICS application involved and observe the behavior when identity propagation is not enabled.

The CICS application that will be executed uses the command below to save the CICS transaction identity in a response container and will return it to the client.

```
* Save current CICS userid
EXEC CICS ASSIGN USERID(USERID of Response-Container)
END-EXEC.
```

_1. Edit the *server.xml* configuration file for the *myServer* server, e.g. /var/zosconnect/servers/myServer/server.xml and add an include for *shared.xml*, see below:

```
<include location=''/wasetc/zc3lab/shared.xml'' optional=''true''/>
```

This will install some predefined services and APIs in the server.

____2. Stop and restart the server with MVS commands *PBAQSTRT* and *SBAQSTRT*.

Tech-Tip: MVS and JES2 commands can be entered from SDSF by enter a / (slash) on the command line followed by the command itself (e.g. /D T). The command results can be found in the system log. If a command is especially long, then simply enter a / (slash) to display *a SDSF* – *System Command Extension* panel where a command can span multiple lines. When an MVS command must be entered, the instructions in these exercises will indicate that the command is a MVS command and you may enter the command at the prompt by using the / (slash) prefix or using the *SDSF* – *System Command Extension* panel.

- ____3. Open a DOS command prompt and go to directory c:/z/admin.
- 4. Enter the cURL command below:

```
curl -X get --cacert certauth.pem --cert fred.p12:secret --cert-type P12 https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
```

Invoking this API will cause the CICS program to be executed and return the identity under which the CICS program executed in the JSON response property USERID, see below:

```
c:\z\admin>curl -X get --cacert certauth.pem --cert fred.p12:secret --cert-type P12
https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
{"cscvincServiceOperationResponse":{"Container1":{"RESPONSE_CONTAINER":{"CEIBRESP2":0,
"FILEA_AREA":{"STAT":"","ADDRX":"SURREY, ENGLAND","AMOUNT":"$0100.11",
"PHONE":"32156778","DATEX":"26 11 81","NUMB":"000100","COMMENT":"**********,
"NAME":"S. D. BORMAN"},"ACTION":"S","USERID":"CICSUSER","CEIBRESP":0}}}}
```

In this case identity propagation was not enable and no other identity was provided so the transaction executed under the CICS default user identity *CICSUSER*.

5. Enter the cURL command below:

```
curl -X GET --cacert certauth.pem --cert user1.p12:secret --cert-type P12 https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
```

The CICS program will be executed and return the CICS transaction identity in the JSON response property USERID, see below:

```
c:\z\admin>curl -X get --cacert certauth.pem --cert user1.p12:secret --cert-type P12
https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
{"cscvincServiceOperationResponse":{"Container1":{"RESPONSE_CONTAINER":{"CEIBRESP2":0,
"FILEA_AREA":{"STAT":"","ADDRX":"SURREY, ENGLAND","AMOUNT":"$0100.11",
"PHONE":"32156778","DATEX":"26 11 81","NUMB":"000100","COMMENT":"***********,
"NAME":"S. D. BORMAN"},"ACTION":"S","USERID":"CICSUSER","CEIBRESP":0}}}}
```

Although a different client certificate was provided, identity propagation was not enabled so again the CICS transaction executed under the CICS default user identity.

Test with identity propagation enabled

When no action is taken, CICS will auto installed an IPCONN resource when a TCPIPService is started. The template used to auto install an IPCONN resource does not enable identity propagation. Enabling identity propagation from a zCEE server to a CICS region requires overriding the default auto installed CICS IPCONN resource with an explicit IPCONN resource with identity propagation enabled for each TCPIPService.

__1. The IPCONN resource below specifies *CSCVINC* for both the *APplid* and *Networkid* attributes. The values specified here must match corresponding values in a *zosconnect_cicsIpicConnection* configuration element, see below. The value for *Tcpipservice* must match the name of the associated TCPIPService resource.

```
₩ WG31
File Edit Settings View Communication Actions Window
  OVERTYPE TO MODIFY
                                                                      CICS RELEASE = 0710
   CEDA ALter Ipconn( CSCVINC )
                     : CSCVINC
    Ipconn
                      : SYSPGRP
    Group
    DEScription ==>
   IPIC CONNECTION IDENTIFIERS
                ==> CSCVINC
==> CSCVINC
    APplid
    Networkid
                   ==>
    (Mixed Case) ==>
                                              No | 1-65535
    Port
                   ==> No
    Tcpipservice ==> CSCVINC
    HA
                   ==> No
                                              No | Yes
   IPIC CONNECTION PROPERTIES
                                              1-999
    Receivecount ==> 001
    SENdcount |
                   ==> 000
                                              0 - 999
                                              No 0-9999
No 0-9999
    Queuelimit
                   ==> No
    MAxatime
                   ==> Nn
 + OPERATIONAL PROPERTIES
                                                               SYSID=CICS APPLID=CICS53Z
PF 1 HELP 2 COM 3 END
                                        6 CRSR 7 SBH 8 SFH 9 MSG 10 SB 11 SF 12 CNCL
M<u>A</u>
Connected to remote server/host wg31 using lu/pool TCP00103 and port 23
```

_____2. Identity propagation attributes are specified in the *Security* section of the IPCONN resource. In this case the *Linkauth* attribute was set to *Secuser*, Userauth attribute was set to *Identify* and the *IDprop* attribute was set to *Required* in advance.

```
₩G31
File Edit Settings View Communication Actions Window Help
                                                                  CICS RELEASE = 0710
  OVERTYPE TO MODIFY OR PRESS ENTER TO EXECUTE
  CEDA ALter Ipconn( CSCVINC )
    AUtoconnect ==> No
INservice ==> Yes
                                            No Yes
                                            Yes | No
   SECURITY
    SSI
                  ==> No
                                            No | Yes
    CErtificate ==>
                                                                           (Mixed Case)
    CIphers
                  ==>
    (Mixed Case)
    Linkauth
                 ==> Secuser
                                           Secuser | Certuser
    SECurityname ==>
                                            Local | Identify | Verify | Defaultuser
    Userauth
                 ==> Identifu
                                            Notallowed | Optional | Required
    IDoroo
                  ==> Required
   RECOVERY
                                            Keep | Force
    Xlnaction
                  ==> Keen
  MIRROR TASK PROPERTIES
    MIrrorlife
                                            Request | Task | Uow
                  ==> Request
   DEFINITION SIGNATURE
                   : 02/16/20 13:04:07
   DEFinetime
                                                           SYSID=CICS APPLID=CICS53Z
                                                                                        f 24
                                      6 CRSR 7 SBH 8 SFH 9 MSG 10 SB 11 SF 12 CNCL
PF 1 HELP 2 COM 3 END
                                                                                 04/022
   A
Connected to remote server/host wg31 using lu/pool TCP00103 and port 23
```

Tech Tip: There will be at least one security check performed when CICS starts the mirror transaction. The security check will be for *READ* access to either transaction code *CSMI* (the CICS default mirror transaction) or the value of the transaction code specified in service's configuration for the *Transaction ID* attribute when the *Transaction ID Usage* attribute is set to *EIB_AND_MIRROR*

One check will be performed with the identity propagated from z/OS Connect. But first another check may be performed using a *link identity*. The *link identity* is determined as follows. For an SSL connection, e.g. *LINKAUTH(CERTUSER)*, the *link identity* will be the local SAF identity mapped to the client certificate. For a non-SSL connection, e.g. *LINKAUTH(SECUSER)*, the *link identity* will be the value provided the *SECURITYNAME* IPCONN attribute. If no value is provided in this attribute, the CICS default user identity will be used for the *link identity*.

If the *link identity* matches the SAF identity under which the CICS region is running, only the propagated identity is used for a SAF check for access to the mirror transaction. If the *link identity* does not match the SAF identity of the CICS region then a SAF check is also performed for the *link identity's* access to the mirror transaction.

Setting the *Userauth* attribute to *Identify* requires the client to provide the identity authenticated by the client.

Review the CICS documentation regarding the *IDprop* attribute. Behavior of this attributes depends on whether the zCEE server and the CICS region are in the same Sysplex or not.

_3. Edit the server.xml file again and replace the include for ipic.xml with an include for ipicIDprop.xml

```
<include location="/wasetc/zc3lab/saf.xml" optional="true"/>
<include location="/wasetc/zc3lab/mutual.xml" optional="true"/>
<include location="/wasetc/zc3lab/group.xml" optional="true"/>
<include location="/wasetc/zc3lab/ipicIDProp.xml" optional="true"/>
<include location="/wasetc/zc3lab/shared.xml" optional="true"/>
```

Below is the updated *zosconnect_cicsIpicConnection* configuration element in the *ipicIDProp.xml* file for the connection reference used by the API services in this API.

```
<zosconnect_cicsIpicConnection id="cscvinc"
host="wg31.washington.ibm.com"
zosConnectNetworkid="CSCVINC"
zosConnectApplid="CSCVINC"
port="1453"/>
```

Again, note the values for *zosConnectNetworkid* and *zosConnectApplid* must match the *Networkid* and *APplid* defined in the CICS IPCONN resource definition.

____4. Stop and restart the server with MVS commands *P BAQSTRT* and *S BAQSTRT*.

Tech Tip: A restart is required other than refresh because the state of the connection between the zCEE server and CICS is being changed. A refresh would not work in this circumstance.

- 5. At a DOS command prompt and go to directory *c:/z/admin*.
- ____6. Enter the cURL command below:

```
curl -X get --cacert certauth.pem --cert fred.p12:secret --cert-type P12 https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
```

The CICS program will be executed and return the transaction identity under which the CICS program executed in the JSON response property USERID, see below:

```
c:\z\admin>curl -X get --cacert certauth.pem --cert fred.p12:secret --cert-type P12
https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
{"cscvincServiceOperationResponse":{"Container1":{"RESPONSE_CONTAINER":{"CEIBRESP2":0,
"FILEA_AREA":{"STAT":"","ADDRX":"SURREY, ENGLAND","AMOUNT":"$0100.11",
"PHONE":"32156778","DATEX":"26 11 81","NUMB":"000100","COMMENT":"**********",
"NAME":"S. D. BORMAN"},"ACTION":"S","USERID":"FRED","CEIBRESP":0}}}
```

In this case the identity (FRED) associated with the client certificate provided by the cURL command in file *fred.p12* is propagated to CICS.

7. Enter the cURL command below:

```
curl -X GET --cacert certauth.pem --cert user1.p12:secret --cert-type P12 https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
```

The CICS program will be executed and return the CICS transaction identity in the JSON response property USERID, see below:

```
c:\z\admin>curl -X get --cacert certauth.pem --cert fred.p12:secret --cert-type P12
https://wg31.washington.ibm.com:9443/cscvinc/employee/000100
{"cscvincServiceOperationResponse":{"Container1":{"RESPONSE_CONTAINER":{"CEIBRESP2":0,
"FILEA_AREA":{"STAT":"","ADDRX":"SURREY, ENGLAND","AMOUNT":"$0100.11",
"PHONE":"32156778","DATEX":"26 11 81","NUMB":"000100","COMMENT":"*********","NAME":"S.
D. BORMAN"},"ACTION":"S","USERID":"USER1","CEIBRESP":0}}}
```

In this the case the identity (USER1) associated with the client certificate provided by the cURL command in file *user1.p12* is propagated to CICS.

Summary


In this section a simple REST client has been used to invoke and API which accesses a CICS region to execute an application. The application returns the identity under which the task is executing to the client. Initially the REST client accesses the CICS program without propagating the identity authenticated by the zCEE server. Changes were made in CICS and the server.xml so that the identity associated with the client certificate (fred.p12 and user1.p12) provided by the cURL command were propagated to CICS.

Enabling CICS SSL security to a zCEE Server

Adding SSL support to a CICS regions requires the creation of a key ring belonging to the identity under which the CICS region is executing (look for message IEF695I in the CICS regions JES messages). This key ring contains the personal and all the certificate authority certificates that will be used during SSL handshakes. The creation of the key ring and the connection of certificates to the key ring are done using the RACDCERT RACF command. Enabling SSL support in the CICS region itself will be done by adding a few SIT overrides. This will require a restart of the CICS region.

Review the Loan Application

The *CICS Miniloan Application* is a CICS application that uses BMS to display screens in a 3270-terminal session. The application is started by entering CICS transaction **APIR** in a CICS terminal session. This will display the screen displayed below.




The application use rules for determining whether a loan request is approved or rejected based on the information entered using the above screen.

The rules for rejecting a loan can be for any one of the following:

- If the credit score of the borrower is less than 300.
- If the yearly repayment amount is more than 30% of the borrower's income.
- If the income of the borrower is less than \$24,000.
- If the age of the borrower is more than 65 years.
- The loan amount is more than \$1,000,000.


N.B., Most of the 3270 screen shots in the remainder of this exercise are shown in reverse video simply for printing purposes.

Below is an example of a display when all the rules are used to reject a loan request.



The source for this application can be found in member LOANAPIR in data set USER1.ZCEE.SOURCE.

The host, port and protocol (Scheme) CICS will use to communicate with the z/OS Connect server is configured in a *BAQURIMAP* CICS URIMAP resource.



If interested use CEDF to trace through the flow of this program and eventually you will see a screen like the below.

```
₩G31
File Edit Settings View Communication Actions Window Help
TRANSACTION: APIR PROGRAM: LOANAPIR TASK: 0000284 APPLID: CICS53Z
                                                                          DISPLAY:
 STATUS: ABOUT TO EXECUTE COMMAND
 EXEC CICS WEB WRITE
  HTTPHEADER ('zCEE-ApiRequester-Metadata')
  NAMELENGTH (26)
  VALUE ('zCEE-ApiRequester-Path=%2Fminiloancics%2Floan&zCEE-ApiRequester'...)
  VALUELENGTH (113)
  SESSTOKEN ('....')
  NOHANDI F
                           LINE: 00090500
                                                      EIBFN=X'380E'
ENTER: CONTINUE
PF1 : UNDEFINED
                             PF2: SWITCH HEX/CHAR
                                                         PF3 : UNDEFINED
PF4 : SUPPRESS DISPLAYS
                             PF5 : WORKING STORAGE
                                                         PF6 : USER DISPLAY
                                                         PF9 : STOP CONDITIONS
PF7 : SCROLL BACK
                             PF8 : SCROLL FORWARD
PF10: PREVIOUS DISPLAY
                                                         PF12: ABEND USER TASK
                             PF11: EIB DISPLAY
                                                                                 017001
Connected to remote server/host wg31 using lu/pool TCP00115 and port 23
```

You can use EDF features to review the details of the request (see an example below)

```
File Edit Settings View
             Communication Actions Window Help
TRANSACTION: APIR PROGRAM: LOANAPIR TASK: 0000284 APPLID: CICS53Z
                                                                      DISPLAY:
 ADDRESS: <u>1</u>570CB10
                     A9C3C5C5 60C19789 D98598A4 85A2A385
1570CB10
           000000
                                                             zCEE-ApiRequeste
1570CB20
           000010
                     9960D781 A3887E6C F2C69489 95899396
                                                             r-Path=%2Fminilo
1570CB30
           000020
                     81958389 83A26CF2 C6939681 9550A9C3
                                                             ancics%2Floan&zC
1570CB40
           000030
                     C5C560C1 9789D985 98A485A2 A3859960
                                                             EE-ApiRequester-
                     D485A388 96847ED7 D6E2E350 A9C3C5C5
1570CB50
           000040
                                                             Method=POST&zCEE
1570CB60
           000050
                     60C19789 D98598A4 85A2A385 9960C1A2
                                                             -ApiRequester-As
1570CB70
           000060
                     A28599A3 8584C984 7EC3C9C3 E2E4E2C5
                                                             sertedId=CICSUSE
1570CB80
                     D9000000 00000000 00000000 00000000
           000070
                                                             R......
1570CB90
           000080
                     0000000 00000000 0000000 00000000
1570CBA0
           000090
                     00000000 1570D1B0 1570D1ED 1570D22A
                                                             .....J...J...K.
1570CBB0
           0000A0
                     1570D267 1570D2A4 1570D2E1 1570D31E
                                                             ..K...Ku..K...L.
1570CBC0
            0000B0
                     1570D35B 00000000 00000000 00000000
                                                             ..L$........
1570CBD0
           0000C0
                     00000000 00000000 00000000 00000000
                     00000000 1570CBF8 000001E8 0000003D
           000000
                                                              .....8...Y....
1570CBE0
                     1570C5E0 00000828 00000000 00000000
1570CBF0
           DODDED
                                                              ..E\.....
1570CC00
           0000F0
                     00000000 00000000 00000000 00000000
        CURRENT DISPLAY
ENTER:
PF1 : UNDEFINED
                           PF2: BROWSE TEMP STORAGE PF3:
                                                             UNDEFINED
PF4 : EIB DISPLAY
                           PF5 : INVOKE CECI
                                                       PF6 :
                                                             USER DISPLAY
PF7: SCROLL BACK HALF
                           PF8 : SCROLL FORWARD HALF PF9 :
                                                             UNDEFINED
                                                             REMEMBER DISPLAY
PF10: SCROLL BACK FULL
                           PF11: SCROLL FORWARD FULL PF12:
    D
                                                                             02/012
Connected to remote server/host wg31 using lu/pool TCP00115 and port 23
```

```
₩ WG31
                                                                                                       File Edit Settings View Communication Actions Window Help
TRANSACTION: APIR PROGRAM: LOANAPIR TASK: 0000323 APPLID: CICS53Z DISPLAY: 00
  STATUS: ABOUT TO EXECUTE COMMAND EXEC CICS WEB CONVERSE
   SESSTOKEN ('.¬....')
    PATH ('/zosConnect/apiRequesters/miniloancics_1.0.0')
    PATHLENGTH (44)
   METHOD (749)
   FROM ('.....JOHN
                                                                                      100.....
   FROMLENGTH (142)
    MEDIATYPE ('application/octet-stream.....')
    SET (X'168D90B0')
                                                                                             AT X'1570A73C'
    TOLENGTH (6338)
    STATUSCODE (0)
    \mathsf{STATUSTEXT} \left( {}', \ldots, \mathsf{v} \{ ..., \mathsf{y}, \mathsf{n}, \ldots, \mathsf{y}, \ldots, \mathsf{j}, \ldots, \mathsf{v} \mathsf{H}, \mathsf{t}, \ldots, \mathsf{t}, \mathsf{nzT} \& \mathsf{n}, \ldots, \mathsf{n}, \ldots, \mathsf{v}, \ldots \right)
    STATUSLEN (256)
    NOHANDLE
                                                                     EIBFN=X'381C'
                                 LINE:00037100
 ENTER: CONTINUE
PF1: UNDEFINED PF2: SWITCH HEX/CHAR PF3: UNDEFINED PF4: SUPPRESS DISPLAYS PF5: WORKING STORAGE PF6: USER DISPLAY PF7: SCROLL BACK PF8: SCROLL FORWARD PF9: STOP CONDITION PF10: PREVIOUS DISPLAY PF11: EIB DISPLAY PF12: ABEND USER TO
                                                                           PF9: STOP CONDITIONS
                                                                            PF12: ABEND USER TASK
ΜА
                                                                                                          01/001
Connected to remote server/host wg31 using lu/pool TCP00111 and port 23
```


Tech-Tip: The EXEC CICS WEB CONVERSE command is the point where the request flows from CICS to the zCEE server.

This exercise will begin going through the steps to enable SSL communications between CICS and the z/OS Connect server.


Creating CICS SAF resources

In this scenario the certificate authority used by organization has provided two certificates in advance. Both certificates currently reside in MVS data sets. One certificate is a personal certificate that will be used by CICS. This certificate was exported with a private key and will be used as a server certificate when CICS is acting a server endpoint or as a client or personal certificate when CICS is the client endpoint. The other certificate is the public certificate authority certificate that was used the sign the certificate assigned to CICS (this certificate only contains the public key).

____1. Browse data set *USER1.CERTAUTH.PEM* and you should see the provided certificate authority exported certificate



2. Browse data set *USER1.CICS.P12* and you should see the CA provided certificate for use as CICS personal certificate. Since it contains a private key it is password protected.



- 3. Browse data set *USER1.ZCEE30.CNTL*. You should see the members in that data set.
- __4. Next browse member **CICSRCF1**, you should see the RACF commands below. Submit the job for execution.

```
racdcert CERTAUTH withlabel('CICS-CA') -
   add('USER1.CICSCA.PEM')

racdcert id(START1) withlabel('CICS-Client-Cert') -
   add('USER1.CICS.P12') password('secret')

setropts raclist(digtcert) refresh

racdcert certauth list(label('CICS-CA'))

racdcert id(START1) list(label('CICS-Client-Cert')
```

Tech-Tip: In summary, these commands add the certificates that were provided by a certificate authority (currently stored in MVS in data sets) and installs them in RACF.


The certificate authority certificate contains the public key of the CA and is used to verify personal certificates. This certificate only contains the public key.

The personal certificate is associated with RACF identity START1. This certificate is mapped to identity START and contains a private key and therefore a password must be provided in order to access the private key when the certificate is added to RACF

The in-storage profile for digital certificates resources are refreshed and the just added certificates are displayed.

__5. Next browse member **CICSRCF2**, you should see the RACF commands below. Submit the job for execution.

Below is visual representation of the key ring just created



Tech-Tip: These commands are creating a key ring belonging to the identity under which the CICS region is executing. Then the personal certificate and CA certificate used to sign the CICS personal certificate are connected to this key ring. Finally, the certificate authority certificate used to sign the server certificate that will be sent from the zCEE server during a handshake is connected to the key ring. The latter is done in order to verify the server certificate sent form the zCEE server

The in-storage profile for digital certificates resources is refreshed and the just added certificates are displayed.

The identity mapped to this client certificate needs access to the zCEE server (via group ZCEEUSRS) and access for invoking an APIs and API requesters (via group GMINVOKE).

Enabling CICS SSL support


The next step is to update the CICS's regions initialization parameters to add support for SSL. This involves adding system initialization table (SIT) parameters.

- 1. Edit member CICSZ in data set CICSTS.CICSZ.SYSIN.
- __2. Add the following system initialization overrides anywhere before the .END line.

```
KEYRING=CICS.KeyRing,
ENCRYPTION=STRONG,
MAXSSLTCBS=8,
SSLDELAY=600,
```

____3. Use the CEDA transaction to change the *SCheme* and *POrt* of the *BAQURIMP* Urimap resource from *HTTP* to *HTTPS* and from *9080* to *9443*, see below.

CEDA EX G(SYSPGRP) URIMAP(BAQURIMP)



- ____4. Shutdown CICS with a *CEMT PE SHUTDOWN* command, using either an MVS modify command or in a CICS terminal session.
- 5. When CICS is no longer active restart the region with MVS command S CICSZ

____6. The next step is to connect the CICS certificate authority to the key ring used for inbound SSL connection to the zCEE server. Browse member CICSRCF3, you should see the RACF commands below. Submit the job for execution.

Tech-Tip: These commands are connecting the certificate authority certificate to the zCEE server key ring used for inbound SSL handshakes. If this certificate was non connected to this keyring the personal certificate sent by CICS during mutual authentication would be rejected.

_____7. Edit the *apiRequestersSSL.xml* file in /wasetc/zc3lab and change the requireSecure and requireAuth attributes from false to *true*.

```
<zosconnect_apiRequesters location="/var/zcee/shared/apiRequesters"
idAssertion="ASSERT_ONLY">
  <apiRequester name="miniloancics_1.0.0"
    requireSecure="true" requireAuth="true" />
  </zosconnect_apiRequesters>
```

____8. Enter MVS commands *P BAQSRT and S BASSTRT* to refresh the zCEE server's runtime configuration.

Tech-Tip: If we had not change the apiRequesters *requireSecure* and <u>requireAuth</u> attributes in the above step, the updated key ring could have been activated by entering MVS command:

F BAOSTRT, REFRESH, KEYSTORE


This would have dynamically made the information about CICS CA certificate available in the zCEE runtime

__9. Next browse member **CICSRCF4**, you should see the RACF commands below. Submit the job for execution.

```
/* Create personal certficate for zCEE outbound client request */
racdcert id(libserv) gencert subjectsdn(cn('zCEE Client Cert') +
ou('ATS') o('IBM')) withlabel('zCEE Client Cert') signwith(certauth
label('zCEE CA')) notafter(date(2021/12/31)
 /* Create zCEE outbound key ring and connect certificates */
racdcert id(libserv) addring(zCEE.KeyRing)
racdcert id(libserv) connect(ring(zCEE.KeyRing) +
          label('zCEE CA') certauth usage(certauth))
racdcert id(libserv) connect(ring(zCEE.KeyRing) +
          label('LibertyCA.LIBERTY') certauth usage(certauth))
 /* Connect CA certificate to Liberty inbound key ring */
racdcert id(libserv) connect(ring(Keyring.LIBERTY) +
          label('zCEE CA') certauth usage(certauth))
 /* Connect default personal certificiate */
racdcert id(libserv) connect(ring(zCEE.KeyRing) +
          label('zCEE Client Cert') default)
setr raclist(digtcert digtring) refresh
connnect libserv group(zceeusers)
connnect libserv group(gminvoke)
```

Tech-Tip: These commands create the key ring used for outbound SSL request. The personal certificate used for SSL handshakes is connect to this key ring as well the CA certificate for validating the server certificate sent by the API provider and the CA certificate used to sign the zCEE server personal certificate to this key ring. Since in this case the API provider is a zCEE server the identity mapped to this server's personal certificate needs access to the zCEE server (via group ZCEEUSRS) and access for invoking an APIs and API requesters (via group GMINVOKE).

Below is visual representation of the key ring just created



- ____8. Submit the job for executions by entering ISPF command *SUBMIT* on the command line. The job should complete with a return code of zero. Review the output is desired.
- ____9. Edit the *server.xml* configuration file for the *myServer* server, e.g. /var/zosconnect/servers/myServer/server.xml and change the include for file *mutual.xml* to an include of file *mutualOutBound.xml*, see below:

<include location=''/wasetc/zc3lab/mutualOutBound.xml'' optional=''true''/>

and refresh the server with MVS command

F BAQSTRT,ZCON,REFRESH

```
<!-- Enable features -->
<featureManager>
     <feature>transportSecurity-1.0</feature>
</featureManager>
<sslDefault sslRef="DefaultSSLSettings"</pre>
  outboundSSLRef="OutboundSSLSettings" />
<ssl id="DefaultSSLSettings"</pre>
  keyStoreRef="CellDefaultKeyStore"
   trustStoreRef="CellDefaultKeyStore"
   clientAuthenticationSupported="true"
   clientAuthentication="true"/>
<keyStore id="CellDefaultKeyStore"</pre>
   location="safkeyring://Keyring.LIBERTY"
   password="password" type="JCERACFKS"
   fileBased="false" readOnly="true" />
<ssl id="OutboundSSLSettings"</pre>
   keyStoreRef="OutboundKeyStore"
   trustStoreRef="OutboundKeyStore"/>
<keyStore id="OutboundKeyStore"</pre>
   location="safkeyring://zCEE.KeyRing"
   password="password" type="JCERACFKS"
   fileBased="false" readOnly="true" />
```

Test the SSL connection from CICS to the zCEE server

____1. In a CICS terminal session start the *APIR* transaction and enter the information for a loan request. When you press enter the request will flow to CICS asserting the CICS default identity. This identity does not the authority to invoke the API requester and the message show in the screen below should appear.


₩ WG31	×
File Edit Settings View Communication Actions Window Help	
CICS Minil Borrower Information Name <u>JOHN</u> Age 100 Credit Score 100	Loan Application Loan Information Loan Amount
000000403 {"errorMessage":"BAQR7115E: The not authorized to invoke the AF Connect/apiRequesters/miniloanci	PI requester on resource /zos
F3=Exit	
MB B Gonnected to remote server/host wg31 using lu/pool TCP00117 and port 23	<u>^</u> 05/014

___2. Use the CICS *CESN* transaction to authenticate to CICS as *FRED* and retry the *LOAN* transaction. This time identity FRED is flowed to the zCEE server. This identity has authority to invoke the API requester.

₩ WG31			-		×
File Edit	Settings View Communication Actions Window Help				
File Edit	Borrower Information Name JOHN Age100 Credit Score100		1000	<u>00</u>	
		_			
F3=E	si†				
MA L	В	^		19/	043
	cted to remote server/host wg31 using lu/pool TCP00117 and port 23	111111111111111111111111111111111111111			

The results raise a question. Why is the CICS identity LIBSERV and not FRED? For an explanation see below.

The diagram below shows the identity that flows the CICS API requester. Since the connection between CICS and the zCEE server is protected by SSL the identity under which the CICS task is running can be asserted from CICS to the zCEE server for an authorization check for executing the API requester. This identity is not flowed to the API provider. Since it is an SSL connection and mutual authentication is enabled between the zCEE server and the API Provider the RACF identity mapped to the zCEE server client certificate is used authorization checks and, in this case, propagated to the CICS application.



Summary

The loan application was used to test accessing a z/OS Connect server using SSL and asserting the CICS identity to the zCEE server for further authorization.