Design and Simulation of an Event-Driven Smart Home Environment using Cisco Packet Tracer

Ajitesh Rastogi
Department of Information Technology
Indian Institute of Information Technology, Vadodara
202352304@iiitvadodara.ac.in

***Abstract*—The proliferation of the Internet of Things (IoT) has enabled the creation of highly responsive residential environments where device interoperability improves security and energy efficiency. This laboratory experiment details the construction of a smart home network comprising ten distinct IoT end devices connected via a central Home Gateway. Using Cisco Packet Tracer, we simulated a realistic automation framework governed by fifteen specific conditional rules. The system integrates diverse hardware, including multimedia devices (Bluetooth Speakers, Portable Music Players), security mechanisms (Webcams, Garage Doors), and environmental controls. This report analyzes the logical "If-Then" structures implemented to handle complex scenarios such as "Night Security Mode," "Garage Entry," and "Smoke Alarm Triggers," demonstrating the efficacy of centralized IoT orchestration.**

***Index Terms*—Home Automation, Packet Tracer, IoT Logic, Smart Gateway, Network Simulation, Event-Driven Architecture**

I. Introduction

Smart home technology has evolved from simple remote control applications to complex, autonomous ecosystems capable of decision-making. The fundamental requirement for such systems is a robust communication protocol that allows sensors (input devices) to dictate the state of actuators (output devices).

In this study, we model a home environment that goes beyond basic connectivity. We employ a star topology centered around a DLC100 Home Gateway to manage ten wireless devices. The core contribution of this lab is the implementation of fifteen granular automation rules. These rules are designed to handle specific lifestyle and safety events, such as the automatic securing of the perimeter when a camera is active, or the calibration of environmental systems (Fan, AC) based on the state of windows and doors.

II. System Architecture

A. Network Topology

The network is architected as a single-SSID wireless LAN. The centralized Home Gateway (Device ID: `Home Gateway0`) acts as the DHCP server and IoT Registration Server. All end devices communicate over the 2.4 GHz wireless channel using WPA2-PSK security.

B. Device Inventory

The ecosystem is comprised of ten IoT nodes, identified by their unique naming convention in the simulation:

1) Multimedia: Portable Music Player (`MP`), Bluetooth Speaker (`Speaker`).
2) Security & Access: Smoke Detector (`SD`), Webcam (`Cam`), Smart Door (`Door`), Garage Door (`Garage`).
3) Environmental: Air Conditioner (`AC`), Ceiling Fan (`Fan`), Window (`Window`), Smart Light (`Lamp`).

An administrative Tablet PC (`Tablet PC0`) is connected to the gateway to provide the user interface for rule programming and status monitoring.



Fig. 1. Network Topology displaying the central Home Gateway connected to 10 IoT endpoints including multimedia and security devices.



Fig. 2. Registered device list on the IoT Server showing successful connectivity.

III. Automation Logic and Implementation

The intelligence of the system is defined by fifteen programmed conditions. These rules monitor state changes

(True/False, On/Off) and execute complex multi-device responses.

A. Safety and Security Protocols

These rules prioritize physical security and hazard response.

- SMOKE ALARM TRIGGERED: If `SD Alarm` is True → The system maximizes visibility and escape routes by turning on the Lamp, opening the Window, unlocking the Door, opening the Garage, and activating the Webcam.
- SMOKE ALARM CLEARED: If `SD Alarm` is False → The system resets: Lamp Off, Window Closed, Door Locked, Garage Closed, Webcam Off.
- NIGHT SECURITY MODE: If `Cam On` is True → The house enters lockdown: Lamp Off, Door Locked, Garage Closed, MP Off, Window Closed.
- MOTION DETECTED ALERT: A secondary security rule where `Cam On` triggers the Door Lock, Lamp On, MP On, and AC On to deter intruders.

B. Entry and Exit Automation

Rules designed to seamlessly handle user transitions into and out of the home.

- WELCOME MODE: If `Door Open` is True → The home prepares for arrival: Lamp On, Fan High, MP On, AC On, Door Unlocked.
- LEAVE HOME MODE: If `Door Open` is False → Energy saving protocol: Lamp Off, Fan Off, AC Off, MP Off, Door Locked.
- GARAGE ENTRY MODE: If `Garage On` is True → Pathway lighting and comfort: Lamp On, AC On, Fan Low, MP On, Door Unlocked.
- GARAGE LIGHT ON TRIGGER: A variation of entry mode that sets Fan to High for rapid ventilation.

C. Environmental and Lifestyle Control

Rules that adjust the home environment based on comfort needs.

- FRESH AIR MODE: If `Window On` is True → AC turns Off (to save energy), Fan High, MP On, Lamp On.
- WINDOW OPEN AC LOCK: A constraint rule ensuring AC is Off if the Window is Open, while securing the Door.
- COOLING COMFORT MODE: If `AC On` is True → Fan High, Lamp On, MP On, Window Closed, Door Unlocked.
- RELAX MODE: If `Window On` is False → Creates a cozy environment: MP On, Lamp On, Fan Low, AC On.
- PARTY MODE OFF: If `Speaker Playing` is False → Shutdown sequence: Lamp Off, MP Off, Fan Off, AC Off, Door Locked.

IV. Observations and Results

The simulation confirmed the functionality of all fifteen rules. Specifically:



Fig. 3. Automation Rules (Part 1): Showing Smoke Alarm, Garage, and Door triggers.



Fig. 4. Automation Rules (Part 2): Showing Security, Party, and Comfort modes.

1) Conflict Handling: We observed that the "SMOKE ALARM TRIGGERED" rule (which opens the window) effectively overrides the "LEAVE HOME MODE" (which usually locks down the house), ensuring safety prioritization.
2) Garage Integration: The `Garage` device successfully acted as a primary trigger for the home's HVAC and lighting systems, demonstrating how external entry points can control internal environments.
3) Energy Logic: The "WINDOW OPEN AC LOCK" rule successfully prevented the AC from running while the window was open, validating the energy-efficiency logic of the design.

V. Conclusion

This experiment successfully demonstrated the implementation of a complex, event-driven IoT smart home. By utilizing 10 devices and 15 distinct automation conditions, we created a system that is not only responsive to user commands but also

autonomous in safety and energy management. The use of the `Garage` and `Speaker` as triggers added a layer of realism to the simulation, proving that Packet Tracer is an effective tool for prototyping sophisticated IoT behaviors.

REFERENCES

[1] Cisco Networking Academy, "IoT Fundamentals: Connecting Things," 2023.

[2] IEEE Standards Association, "IEEE 802.11 Wireless LAN Standards," 2022.

[3] A. Al-Fuqaha et al., "Internet of Things: A Survey on Enabling Technologies," IEEE Comm. Surveys, 2015.