

Developer Mock Test Results

Student: Shiva kasula

Name:	Shiva kasula	Student ID:	112
Date:	2026-03-07 15:04:38	Performance:	■■ Needs Improvement
Overall Score:	5.9/25 (23.6%)	Test ID:	1a3b2ce1-22de-4bd7...
Warnings:	0/3	Status:	Completed ■

Section-wise Performance

Section	Score	Percentage	Status
■ Aptitude	2/10	20.0%	■■ Needs Work
■ MCQ/Theory	0/10	0.0%	■■ Needs Work
■ Coding	3.9/5	78.0%	■ Pass

Detailed Question Review

■ APTITUDE SECTION (2/10 - 20.0%)

■ Q1. If "HOUSE" is coded as "URHVL", what is the code for "CHAIR"? Select the correct answer from the options below.

Your Answer: FDJUL

■ Well done!

■ Q2. A can do a job in 5 hours. B can do the same job in 10 hours. How long will it take for A and B to do the job together? Select the correct answer from...

Your Answer: 3 hours

■ Correct! Well done.

■ Q3. A is the brother of B. C is the sister of B. What is the relationship between A and C? Select the correct answer from the options below.

Your Answer: Brother and brother

Correct Answer: Brother and sister

■ The correct answer is "Brother and sister" because A is the brother of B, and C is the sister of B, making A and C siblings. The user's answer, "Brother and brother", is incorrect because it doesn't account for C being a sister. The user likely mistakenly assumed that since A is a brother, C must also be a brother, ignoring the information that C is B's sister.

■ Q4. If today is Wednesday, what day of the week will it be 100 days from now? Select the correct answer from the options below.

Your Answer: Saturday

Correct Answer: Sunday

■ To find the day of the week 100 days from now, we need to calculate the remainder when 100 is divided by 7, since there are 7 days in a week. The key calculation step is: $100 \div 7 = 14$ remainder 2. This means that 100 days from now is equivalent to 2 days after Wednesday, which would be Friday, but since 14 weeks (98 days) would bring us back to Wednesday, adding the remaining 2 days would make it Friday, however, considering the actual calculation: Wednesday + 2 days = Friday, but since we are looking for the day after 14 weeks (which is Wednesday), we add the 2 remaining days to Wednesday, making the correct calculation: Wednesday (today) + 14 weeks (98 days, multiple of 7) = Wednesday, then Wednesday + 2 days = Friday. However, my calculation indicates Friday, but considering the days of the week and the provided correct

■ Q5. What is the next number: 3, 6, 9, 12, 15, ?

Your Answer: 22

Correct Answer: 18

■ The correct answer is 18 because the pattern of the sequence is adding 3 to the previous number. The key calculation step is: 15 (previous number) + $3 = 18$. The user's likely mistake was not recognizing the consistent addition of 3 in the sequence, instead possibly adding a larger or incorrect number to arrive at 22.

■ Q6. If a number is decreased by 20% and then increased by 20%, what is the overall percentage change?

Your Answer: 10%

Correct Answer: -4%

■ To find the overall percentage change, let's consider the key calculation step: if a number is decreased by 20% and then increased by 20%, we can calculate this as $0.8x \times 1.2 = 0.96x$, where x is the original number. This shows that the final result is 96% of the original, meaning there's a 4% decrease, so the correct answer is -4%. The user likely made a mistake by not considering the compounding effect of the percentage changes, which results in a loss rather than no change or a gain.

■ Q7. A pipe can fill a tank in 6 hours. Another pipe can empty the tank in 8 hours. How long will it take to fill the tank if both pipes are open? Select t...

Your Answer: 12 hours

Correct Answer: 16 hours

■ To find the time it takes to fill the tank with both pipes open, we calculate the net rate of filling the tank. The first pipe fills the tank at a rate of $\frac{1}{6}$ tank per hour, while the second pipe empties it at a rate of $\frac{1}{8}$ tank per hour. The key calculation step is: $\frac{1}{6} - \frac{1}{8} = \frac{4}{24} - \frac{3}{24} = \frac{1}{24}$, but since the question asks for the time to fill the tank and the net rate is filling, the calculation should consider the combined work rate which actually results in $\frac{1}{\frac{1}{6} - (-\frac{1}{8})} = \frac{1}{\frac{1}{6} + \frac{1}{8}} = \frac{1}{\frac{4+3}{24}} = \frac{1}{\frac{7}{24}} = \frac{24}{7}$ hours, which is approximately $3.43 \times 4 =$

■ Q8. What is the HCF of 12, 18, and 24? Select the correct answer from the options below.

Your Answer: 12

Correct Answer: 6

■ To find the highest common factor (HCF) of 12, 18, and 24, we need to identify the largest number that divides all three numbers without leaving a remainder. The key calculation step involves listing the factors of each number: factors of 12 are 1, 2, 3, 4, 6, 12; factors of 18 are 1, 2, 3, 6, 9, 18; and factors of 24 are 1, 2, 3, 4, 6, 8, 12, 24. The largest common factor among these is 6. The user's answer, 12, is incorrect because 12 is not a factor of 18. The user likely made a mistake by not considering all the factors of each number or by assuming that the largest number in the list (12) would automatically be the HCF, which is not the case if it doesn't

■ Q9. The series is: 2, 6, 12, 20, 30, ? What is the next number in the series? Select the correct answer from the options below.

Your Answer: 36

Correct Answer: 42

■ The correct answer is 42. The series appears to be formed by adding 4, 6, 8, 10, 12, ... to the previous term, which suggests a pattern of increasing differences. The key calculation step is: $30 + 12 = 42$, which confirms that the next number in the series is indeed 42, not 36, likely due to the user underestimating the increase in the difference between terms.

■ Q10. Ramesh is 5 years older than his brother, and their average age is 25. What are their current ages? Select the correct answer from the options below.

Your Answer: Ramesh: 30, Brother: 20

Correct Answer: Ramesh: 28, Brother: 22

■ Let's denote Ramesh's age as R and his brother's age as B . We know that $R = B + 5$ and $(R + B) / 2 = 25$. The key calculation step is to substitute R with $B + 5$ in the second equation: $((B + 5) + B) / 2 = 25$, which simplifies to $(2B + 5) / 2 = 25$, then $2B + 5 = 50$, and $2B = 45$, so $B = 22.5$. Since B must be a whole number, we likely made a calculation mistake. Let's retry: $(R + B) / 2 = 25$, so $R + B = 50$, and since $R = B + 5$, we have $B + 5 + B = 50$, which gives $2B + 5 = 50$, then $2B = 45$. This

■ MCQ SECTION (0/10 - 0.0%)

■ Q1. What is abstraction in Java?

Your Answer: The concept of hiding all internal details and showing no information

Correct Answer: The concept of showing only necessary information and hiding internal details

■ The correct answer is A) The concept of showing only necessary information and hiding internal details, because abstraction in Java refers to the practice of exposing only the necessary features of an object or system while concealing its internal implementation details. This allows for more flexibility, modularity, and ease of maintenance in programming. The user's answer, C) The concept of hiding all internal details and showing no information, is incorrect because abstraction is about showing some information, not none, and is intended to simplify interactions with complex systems, not completely obscure them.

■ Q2. How can a Java program be compiled and run, as mentioned in the course content? Choose the correct answer from the options below.

Your Answer: Using an IDE

Correct Answer: Both A and B

■ The correct answer is "Both A and B" because a Java program can be compiled and run using either a terminal or command prompt by manually invoking the Java compiler and runtime environment, or using an Integrated Development Environment (IDE) such as Eclipse or IntelliJ, which provides a graphical interface for these tasks. The user's answer, "Using an IDE", is incorrect because it only accounts for one of the possible methods. The user likely missed the fact that Java programs can also be compiled and run from the command line, making "Both A and B" the most comprehensive and correct answer.

■ Q3. What type of control structure is used to repeat a block of code in Java, as mentioned in the course content? Choose the correct answer from the options below.

Your Answer:

while loop

Correct Answer:

for loop

■ The correct answer is indeed B) for loop, as it is a type of control structure used to repeat a block of code in Java. The user's answer, C) while loop, is also a loop structure, but the question seems to be pointing towards a more specific type of loop, which is the for loop. The user's mistake was likely due to not carefully reading the question, as both for and while loops can be used to repeat code, but the course content specifically mentioned the for loop.

■ Q4. What are packages in Java, according to the course content? Choose the correct answer from the options below.

Your Answer: Collections of related variables

Correct Answer: Collections of related classes

■ The correct answer is A) Collections of related classes because in Java, packages are used to organize and group related classes, interfaces, and other types to avoid naming conflicts and make the code more manageable. The user's answer, C) Collections of related variables, is incorrect because packages are not primarily used to group variables, but rather to group classes and other types that are related in functionality or purpose. The user's mistake likely stems from a misunderstanding of the purpose and definition of packages in Java.

■ Q5. What type of mobile apps can be built using Java, according to the course content? Choose the correct answer from the options below.

Your Answer: iOS apps

Correct Answer: Android apps

■ The correct answer is Android apps because Java is widely used for developing Android applications due to the Android SDK's support for Java. The user's answer, iOS apps, is incorrect because iOS apps are typically built using Swift or Objective-C, not Java. The user's mistake likely stems from a lack of knowledge about the programming languages used for different mobile platforms.

■ **Q6. What is method overriding in Java?**

Your Answer:

A subclass provides the same implementation of a method

Correct Answer:

A subclass provides a different implementation of a method

■ The correct answer is A) A subclass provides a different implementation of a method, because method overriding in Java allows a subclass to provide a specific implementation of a method that is already defined in its superclass. This enables the subclass to specialize the behavior of the method to suit its own needs. The user's answer, B) A subclass provides the same implementation of a method, is likely incorrect because the purpose of method overriding is to provide a different implementation, not to duplicate the same one.

■ **Q7. What is used for error handling in Java, as mentioned in the course content? Choose the correct answer from the options below.**

Your Answer:

for loops

Correct Answer:

try-catch blocks

■ The correct answer is try-catch blocks because they are specifically designed for error handling in Java, allowing developers to enclose code that might throw an exception and handle it in a separate block. The user's answer, for loops, is incorrect because for loops are used for repetitive execution of a block of code, not for error handling. The user's likely mistake is confusing the purpose of different control structures in Java, failing to recognize that try-catch blocks are the standard mechanism for handling exceptions and errors.

■ **Q8. What type of desktop applications can be built using Java, according to the course content? Choose the correct answer from the options below.**

Your Answer: Productivity software

Correct Answer: All of the above

■ The correct answer is "All of the above" because Java is a versatile programming language that can be used to build a wide range of desktop applications, including games, productivity software, and graphics editors. The user's answer, "Productivity software", is incorrect because it only represents one type of application that can be built with Java, whereas the language's capabilities extend far beyond that. The user likely underestimated the breadth of Java's applications, failing to consider its use in game development and graphics editing.

■ **Q9. How should code be organized in Java, according to the course content? Choose the correct answer from the options below.**

Your Answer: Using arrays and collections

Correct Answer: Using classes and packages

■ The correct answer is "Using classes and packages" because in Java, code organization is primarily achieved through the use of classes, which encapsulate related data and methods, and packages, which group related classes together. This structure helps to promote modularity, reusability, and maintainability of the code. The user's answer, "Using arrays and collections", is incorrect because while these data structures are important in Java, they are not the primary means of organizing code.

■ **Q10. What happens when a Java file is compiled?**

Your Answer:

It is converted to a .exe file

Correct Answer:

It is converted to a .class file

■ When a Java file is compiled, it is converted to a .class file, which contains the bytecode that can be executed by the Java Virtual Machine (JVM). This is because Java is a compiled language that requires a compilation step to translate the source code into an intermediate form that can be run on any platform with a JVM. The user's mistake likely stems from confusing Java with a native executable format, such as .exe files, which are specific to certain operating systems and are not the direct result of compiling Java code.

■ CODING SECTION (3.9/5 - 78.0%)

■ **Q1. Write a Java program that reads an array of integers from stdin and finds the minimum element along with its index. **Input Format:** - Line 1: The n...**

Your Answer:

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt(); // number of elements
        int[] arr = new int[n];

        // Read array elements
        for (int i = 0; i < n; i++) {
            arr[i] = sc.nextInt();
        }

        int min = arr[0];
        int index = 0;

        // Find minimum element and its index
        for (int i = 1; i < n; i++) {
            if (arr[i] < min) {
                min = arr[i];
                index = i;
            }
        }

        // Print result
        System.out.println(min + " " + index);

        sc.close();
    }
}
```

■ Huge congratulations are in order - your code has passed all 2 test cases with flying colors! You should be incredibly proud of yourself, as this is a fantastic achievement, and I'm thrilled to see your hard work paying off! ■ Score: 1.0 / 1

■ **Q2. Write a Java program that reads a list of student grades from stdin and calculates the average grade. **Input Format:** - Line 1: The number of stude...**

Your Answer:

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt(); // number of students
        double sum = 0;
```

```

        // Read grades and calculate sum
        for (int i = 0; i < n; i++) {
            sum += sc.nextInt();
        }

        double average = sum / n;

        // Print average grade
        System.out.println(average);

        sc.close();
    }
}

```

■ Huge congratulations are in order - your code passed all 2 test cases with flying colors, which is a fantastic achievement! You should be incredibly proud of yourself for writing such effective and accurate code, keep up the amazing work! ■ Score: 1.0 / 1

■ **Q3. Write a Java program that reads the details of a shopping cart from stdin and calculates the total cost. ***Input Format:*** - Line 1: The number of it...**

Your Answer:

```

import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt(); // number of items
        int totalCost = 0;

        for (int i = 0; i < n; i++) {
            String itemName = sc.next(); // read item name
            int price = sc.nextInt();    // read item price
            totalCost += price;
        }

        System.out.println(totalCost);

        sc.close();
    }
}

```

■ Huge congratulations are in order - your code has passed all 2 test cases with flying colors, which is a fantastic achievement! You should be incredibly proud of yourself for writing such effective and efficient code, keep up the amazing work! ■ Score: 1.0 / 1

■ **Q4. Write a Java program that reads a graph from stdin and finds the strongly connected components. ***Input Format:*** - Line 1: The number of nodes - Lin...**

Your Answer:

```

import java.util.*;

public class Main {

    static void dfs(int v, boolean[] visited, Stack<Integer> stack, List<List<Integer>>> adj) {
        visited[v] = true;
        for (int n : adj.get(v)) {
            if (!visited[n]) {
                dfs(n, visited, stack, adj);
            }
        }
    }
}

```

```

    }
    stack.push(v);
}

static void dfsTranspose(int v, boolean[] visited, List<List<Integer>> transpose, List<Integer>
component) {
    visited[v] = true;
    component.add(v);

    for (int n : transpose.get(v)) {
        if (!visited[n]) {
            dfsTranspose(n, visited, transpose, component);
        }
    }
}

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);

    int nodes = sc.nextInt();
    int edges = sc.nextInt();

    List<List<Integer>> adj = new ArrayList<>();
    for (int i = 0; i < nodes; i++) {
        adj.add(new ArrayList<>());
    }

    // Read edges
    for (int i = 0; i < edges; i++) {
        int u = sc.nextInt();
        int v = sc.nextInt();
        adj.get(u).add(v);
    }

    Stack<Integer> stack = new Stack<>();
    boolean[] visited = new boolean[nodes];

    // Step 1: Fill stack with finishing times
    for (int i = 0; i < nodes; i++) {
        if (!visited[i]) {
            dfs(i, visited, stack, adj);
        }
    }

    // Step 2: Create transpose graph
    List<List<Integer>> transpose = new ArrayList<>();
    for (int i = 0; i < nodes; i++) {
        transpose.add(new ArrayList<>());
    }

    for (int i = 0; i < nodes; i++) {
        for (int j : adj.get(i)) {
            transpose.get(j).add(i);
        }
    }

    // Step 3: Process stack and find SCCs
    Arrays.fill(visited, false);
    List<List<Integer>> result = new ArrayList<>();

    while (!stack.isEmpty()) {
        int v = stack.pop();

```

```

        if (!visited[v]) {
            List<Integer> component = new ArrayList<>();
            dfsTranspose(v, visited, transpose, component);
            result.add(component);
        }
    }

    System.out.println(result);

    sc.close();
}
}

```

Correct Answer:

```

import java.util.*;

public class Main {
    static class Graph {
        private final int numNodes;
        private final List<List<Integer>> adjacencyList;
        private final boolean[] visited;
        private final Stack<Integer> stack;
        private final List<List<Integer>> stronglyConnectedComponents;

        public Graph(int numNodes) {
            this.numNodes = numNodes;
            this.adjacencyList = new ArrayList<>();
            this.visited = new boolean[numNodes];
            this.stack = new Stack<>();
            this.stronglyConnectedComponents = new ArrayList<>();

            for (int i = 0; i < numNodes; i++) {
                adjacencyList.add(new ArrayList<>());
            }
        }

        public void addEdge(int source, int destination) {
            adjacencyList.get(source).add(destination);
        }

        public void fillStack(int node) {
            visited[node] = true;
            for (int neighbor : adjacencyList.get(node)) {
                if (!visited[neighbor]) {
                    fillStack(neighbor);
                }
            }
            stack.push(node);
        }

        public void transposeGraph() {
            Graph transpose = new Graph(numNodes);
            for (int i = 0; i < numNodes; i++) {
                for (int neighbor : adjacencyList.get(i)) {
                    transpose.addEdge(neighbor, i);
                }
            }
            return transpose;
        }

        public void findStronglyConnectedComponents() {
            for (int i = 0; i < numNodes; i++) {

```



```

        if (!visited[i]) {
            fillStack(i);
        }
    }

    Graph transpose = transposeGraph();
    boolean[] visitedTranspose = new boolean[numNodes];
    while (!stack.isEmpty()) {
        int node = stack.pop();
        if (!visitedTranspose[node]) {
            List<Integer> component = new ArrayList<>();
            dfs(node, visitedTranspose, transpose, component);
            stronglyConnectedComponents.add(component);
        }
    }
}

private void dfs(int node, boolean[] visitedTranspose, Graph transpose, List<Integer>
component) {
    visitedTranspose[node] = true;
    component.add(node);
    for (int neighbor : transpose.adjacencyList.get(node)) {
        if (!visitedTranspose[neighbor]) {
            dfs(neighbor, visitedTranspose, transpose, component);
        }
    }
}

public List<List<Integer>> getStronglyConnectedComponents() {
    return stronglyConnectedComponents;
}

}

public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);
    int numNodes = scanner.nextInt();
    int numEdges = scanner.nextInt();
    scanner.nextLine(); // Consume newline left-over

    Graph graph = new Graph(numNodes);
    for (int i = 0; i < numEdges; i++) {
        String[] edge = scanner.nextLine().split(" ");
        int source = Integer.parseInt(edge[0]);
        int destination = Integer.parseInt(edge[1]);
        graph.addEdge(source, destination);
    }

    graph.findStronglyConnectedComponents();
    List<List<Integer>> stronglyConnectedComponents = graph.getStronglyConnectedComponents();
    for (List<Integer> component : stronglyConnectedComponents) {
        System.out.println(component);
    }

    scanner.close();
}
}

```

■ You're on the right track! I can see that you've attempted to implement a depth-first search (DFS) approach to find strongly connected components, which is a great start. The key issue seems to be with the order of visiting nodes in the transpose graph, consider re-examining the `dfsTranspose` method to ensure it's correctly adding nodes to the component list. Don't give up, you are closer than you think! ■ Score: 0.4 / 1

■ Q5. Write a Java program that reads an array of integers from stdin and finds the minimum and maximum values along with their indices. ****Input Format:**** ...

Your Answer:

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        int[] arr = new int[n];

        for (int i = 0; i < n; i++) {
            arr[i] = sc.nextInt();
        }

        int min = arr[0], max = arr[0];
        int minIndex = 0, maxIndex = 0;

        for (int i = 1; i < n; i++) {
            if (arr[i] < min) {
                min = arr[i];
                minIndex = i;
            }
            if (arr[i] > max) {
                max = arr[i];
                maxIndex = i;
            }
        }

        System.out.println(min + " " + minIndex + " " + max + " " + maxIndex);

        sc.close();
    }
}
```

Correct Answer:

```
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = scanner.nextInt();
        int[] array = new int[n];
        for (int i = 0; i < n; i++) {
            array[i] = scanner.nextInt();
        }
        int minIndex = 0;
        int maxIndex = 0;
        int min = array[0];
        int max = array[0];
        for (int i = 1; i < n; i++) {
            if (array[i] < min) {
                min = array[i];
                minIndex = i;
            }
            if (array[i] > max) {
                max = array[i];
                maxIndex = i;
            }
        }
        System.out.println(min + " " + minIndex + " " + max + " " + maxIndex);
    }
}
```

```
        scanner.close();
    }
}
```

■ You're almost there! I can see that you've made great progress, passing 1 out of 2 test cases, which is definitely something to be proud of. To get the remaining test case to pass, it looks like you just need to update the `minIndex` when a new minimum value is found, and also consider the original index of the minimum and maximum values in the output, as the current output '1 3 9 4' should be '1 0 9 4' to match the expected output. You are very close to full marks, keep it up! ■
Score: 0.5 / 1

■ Recommendations

Areas that need improvement:

- **Aptitude:** Practice more logical reasoning, quantitative aptitude, and problem-solving questions.
- **MCQ/Theory:** Review programming concepts, data structures, and algorithms theory.