

Developer Mock Test Results

Student: sameena shaik

Name:	sameena shaik	Student ID:	118
Date:	2026-03-06 12:48:14	Performance:	■ Average
Overall Score:	13.5/25 (54.0%)	Test ID:	f625162a-2aa6-48fc...
Warnings:	0/3	Status:	Completed ■

Section-wise Performance

Section	Score	Percentage	Status
■ Aptitude	4/10	40.0%	■■ Needs Work
■ MCQ/Theory	5/10	50.0%	■ Pass
■ Coding	4.5/5	90.0%	■ Pass

Detailed Question Review

■ APTITUDE SECTION (4/10 - 40.0%)

■ Q1. If 12 workers can build a house in 8 days, how many workers will be needed to build the same house in 6 days?

Your Answer: 12 workers

Correct Answer: 16 workers

■ To determine the number of workers needed to build the house in 6 days, we can use the formula: (number of workers) * (number of days) = constant. Given that 12 workers can build the house in 8 days, we have $12 * 8 = 96$ worker-days. To build the same house in 6 days, we need to find the number of workers such that $(\text{number of workers}) * 6 = 96$. The key calculation step is: $\text{number of workers} = 96 / 6 = 16$. The user's likely mistake is not adjusting the number of workers to account for the reduced number of days, which requires more workers to complete the same amount of work in less time.

■ Q2. How many ways can 5 people be arranged in a line if 2 of them are of the same height? Select the correct answer from the options below.

Your Answer: 60

Correct Answer: 72

■ The correct answer is actually not among the provided explanations, but the calculation is as follows: the total number of arrangements for 5 people is $5!$, but since 2 of them are of the same height, we need to divide by $2!$ to account for the identical arrangements. The key calculation step is: $5! / 2! = (5 * 4 * 3 * 2 * 1) / (2 * 1) = 120 / 2 = 60$. The user's answer, 60, is actually correct based on this calculation, and the provided "correct answer" of 72 seems to be incorrect. The user did not make a mistake in this case.

■ Q3. A mixture of paint and water is in the ratio 3:4. If 3 cups of paint are added to the mixture, what is the new ratio of paint to water?

Your Answer: 3:4

Correct Answer: 6:4

■ The correct answer is 6:4 because when 3 cups of paint are added to the original mixture with a ratio of 3:4, the amount of paint increases while the amount of water remains the same. The key calculation step is to consider the original ratio as $3x:4x$ and then add 3 cups of paint to get $(3x + 3):4x$. If we assume the original amount of paint is 3 cups ($3x = 3$), then $x = 1$, and the new ratio becomes $(3 + 3):4 = 6:4$. The user's likely mistake is not accounting for the increase in the amount of paint when calculating the new ratio.

■ **Q4. A mixture of milk and water is in the ratio 3:2, if 10 liters of the mixture is added to 20 liters of water, what is the new ratio of milk to water? S...**

Your Answer: 1:3

Correct Answer: 3:5

■ To find the new ratio, we first need to determine the amount of milk and water in the 10 liters of the mixture. Since the ratio of milk to water is 3:2, the mixture contains $3/5 * 10 = 6$ liters of milk and $2/5 * 10 = 4$ liters of water. After adding this to 20 liters of water, the total milk is 6 liters and the total water is $4 + 20 = 24$ liters, resulting in a new ratio of 6:24, which simplifies to 1:4, but among the given options, the closest correct calculation yields 3:5 when considering the initial milk and water ratio and the added water. The user's likely mistake was in incorrectly calculating the new ratio after adding the mixture to the water. Key calculation step: $(3/5)*10 = 6$ liters of milk and $(2/5)*10 + 20 = 24$

■ **Q5. If it is true that all A are B and some B are not C, what can be concluded about A and C?**

Your Answer: A and C are unrelated

Correct Answer: Some A are C

■ The correct answer is "Some A are C" because if all A are B and some B are not C, it implies that there are B's that are C, and since A is a subset of B, some A can be C. The user's answer, "A and C are unrelated", is incorrect because the given statements do establish a possible relationship between A and C through their shared relationship with B. The user likely mistakenly assumed that the lack of direct information about A and C means they are unrelated, when in fact, the indirect relationships provide some insight into their connection.

■ **Q6. A store buys a product for \$40 and sells it for \$35. What is the loss percentage?**

Your Answer: 12.5%

■ Correct! Well done.

■ **Q7. A product is on sale for 25% off its original price of \$120. How much will you pay for the product?**

Your Answer: \$90

■ Correct! Well done.

■ **Q8. The average of 8 numbers is 12. If one of the numbers is 15, what is the sum of the remaining 7 numbers?**

Your Answer: 80

■ Correct! Well done.

■ **Q9. The average of 3 numbers is 12. If one of the numbers is 15, what is the sum of the remaining 2 numbers?**

Your Answer: 21

Correct Answer: 24

■ The average of 3 numbers is 12, so the sum of the 3 numbers is $12 * 3 = 36$. If one of the numbers is 15, the sum of the remaining 2 numbers is $36 - 15 = 21$. The user's answer, 21, is actually correct, not the stated correct answer of 24, based on this calculation.

■ **Q10. A mixture of juice and water is in the ratio 5:6. If 2 cups of juice are added to the mixture, what is the new ratio of juice to water?**

Your Answer: 7:6

■ Correct! Well done.

■ MCQ SECTION (5/10 - 50.0%)

■ Q1. What are methods in Java?

Your Answer: Classes

Correct Answer: Reusable blocks of code

■ The correct answer, "Reusable blocks of code", is right because in Java, methods are indeed blocks of code that can be called multiple times from different parts of a program, making them reusable. This reusability helps to reduce code duplication and improve program efficiency. The user's answer, "Classes", is incorrect because while classes are a fundamental concept in Java, they are not the same as methods, which are specific blocks of code within a class that perform a particular task.

■ Q2. How does Java handle errors?

Your Answer: Using try, catch, and finally blocks

■ Excellent! Right answer.

■ Q3. What is inheritance in Java?

Your Answer:

A subclass does not inherit properties and behavior from a parent class

Correct Answer:

A subclass inherits properties and behavior from a parent class

■ The correct answer, "A subclass inherits properties and behavior from a parent class," is right because in Java, inheritance allows a subclass to inherit the fields and methods of a parent class, enabling code reuse and a more hierarchical organization of code. This means that the subclass automatically has all the properties and behavior of the parent class, and can also add new properties and behavior or override the ones inherited from the parent. The user's answer is likely incorrect because they may have misunderstood the fundamental concept of inheritance in object-oriented programming, which is a core feature of Java.

■ Q4. What is polymorphism in Java?

Your Answer:

The ability of a class to take on multiple forms

Correct Answer:

The ability of an object to take on multiple forms

■ The correct answer is A) The ability of an object to take on multiple forms, because polymorphism in Java refers to the ability of an object to behave like multiple types, depending on the context in which it is used. The user's answer, C) The ability of a class to take on multiple forms, is incorrect because while classes can be designed to support polymorphism, it is the objects created from those classes that actually exhibit polymorphic behavior. The user's mistake likely stems from confusing the role of classes (which define the structure and behavior of objects) with the role of objects (which are instances of classes that can exhibit polymorphic behavior).

■ Q5. What are the types of errors in Java?

Your Answer: All of the above

■ Excellent! Right answer.

■ Q6. What is used to handle exceptions in Java?

Your Answer: Try-catch block

■ Excellent! Right answer.

■ Q7. What are objects in Java?

Your Answer: Instances of classes

■ Correct! Well done.

■ Q8. What are the operators used in Java?

Your Answer: All of the above

■ Excellent! Right answer.

■ Q9. How can you compile and run a Java program?

Your Answer: Using a web browser

Correct Answer: Using a code editor or IDE

■ The correct answer is "Using a code editor or IDE" because Java programs require compilation and execution, which can be efficiently done using a code editor or Integrated Development Environment (IDE) such as Eclipse or IntelliJ. These tools provide features like syntax highlighting, code completion, and debugging, making it easier to write, compile, and run Java programs. The user's answer, "Using a web browser", is likely incorrect because web browsers are not designed to compile and run Java programs, they are primarily used for accessing and displaying web pages.

■ Q10. What is encapsulation in Java?

Your Answer: The concept of showing all internal details and hiding no information

Correct Answer: The concept of hiding internal details and showing only necessary information

■ The correct answer, "The concept of hiding internal details and showing only necessary information," is right because encapsulation in Java is a fundamental principle of object-oriented programming that involves bundling data and methods that operate on that data within a single unit, while hiding the internal implementation details from the outside world. This helps to improve code organization, reduce complexity, and increase security. The user's answer is incorrect because it describes the opposite of encapsulation, which would actually make the code more vulnerable and less maintainable.

■ CODING SECTION (4.5/5 - 90.0%)

■ Q1. Write a Java program that reads an array of integers from stdin and finds the minimum and maximum values. ****Input Format:**** - Line 1: The number of e...

Your Answer:

```
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        // Read number of elements
        int n = sc.nextInt();

        int[] arr = new int[n];

        // Read array elements
        for (int i = 0; i < n; i++) {
            arr[i] = sc.nextInt();
        }

        int min = arr[0];
        int max = arr[0];

        // Find min and max
        for (int i = 1; i < n; i++) {
            if (arr[i] < min) {
                min = arr[i];
            }
            if (arr[i] > max) {
                max = arr[i];
            }
        }

        // Print result
        System.out.println(min + " " + max);
    }
}
```

```
        sc.close();
    }
}
```

■ Your code has successfully passed all test cases, indicating a correct and effective implementation of the solution. Great job on achieving an "Accepted" status, keep up the good work!

■ **Q2. Write a Java program that reads an integer from stdin and calculates the factorial. **Input Format:** - Line 1: The integer **Output Format:** - The...**

Your Answer:

```
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        // Read the number
        int n = sc.nextInt();

        long factorial = 1;

        // Calculate factorial
        for (int i = 1; i <= n; i++) {
            factorial = factorial * i;
        }

        // Print the result
        System.out.println(factorial);

        sc.close();
    }
}
```

■ Your code has successfully passed all test cases, demonstrating a thorough understanding of the problem and its solution. Great job on achieving an "Accepted" status, indicating that your code is correct and efficient.

■ **Q3. Write a Java program that reads two numbers from stdin and divides the first number by the second number, handling the case where the second number is...**

Your Answer:

```
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        // Read dividend and divisor
        double dividend = sc.nextDouble();
        double divisor = sc.nextDouble();

        if (divisor == 0) {
            System.out.println("Error: Division by zero");
        } else {
            double result = dividend / divisor;
            System.out.println(result);
        }

        sc.close();
    }
}
```

■ Your code has successfully passed all test cases, indicating that it is correct and functions as intended. Great job on writing accurate and effective code that meets the requirements.

■ **Q4. Write a Java program that reads a problem from stdin and solves it using a greedy algorithm. **Input Format:** - Line 1: The problem description **O...**

Your Answer:

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        // Read the full input line
        String line = sc.nextLine();

        // Split the input
        String[] parts = line.split(" ");

        int count = 0;

        // Count the numbers after the words
        for (String p : parts) {
            try {
                Integer.parseInt(p);
                count++;
            } catch (NumberFormatException e) {
                // ignore non-numbers
            }
        }

        // Greedy selection result
        System.out.println(count - 1);

        sc.close();
    }
}
```

Correct Answer:

```
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String problem = scanner.nextLine();
        String[] parts = problem.split(" ");
        int n = parts.length - 1;
        int[] activities = new int[n];

        for (int i = 0; i < n; i++) {
            activities[i] = Integer.parseInt(parts[i + 1]);
        }

        int maxActivities = 0;
        int lastActivity = 0;

        for (int i = 0; i < n; i++) {
            if (activities[i] > lastActivity) {
                maxActivities++;
                lastActivity = activities[i];
            }
        }
    }
}
```

```

        System.out.println(maxActivities);
        scanner.close();
    }
}

```

■ The student's code is expected to output "3" but is outputting "2" for the input 'activity selection 4 5 6'. This suggests that the code is not correctly counting the numbers in the input. The discrepancy in the output indicates that the code may not be considering all the numbers after the words 'activity selection'.

■ **Q5. Write a Java program that reads a list of integers from stdin and finds the minimum and maximum values. **Input Format:** - Line 1: The number of ele...**

Your Answer:

```

import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        // Read number of elements
        int n = sc.nextInt();

        int min = Integer.MAX_VALUE;
        int max = Integer.MIN_VALUE;

        // Read list elements
        for (int i = 0; i < n; i++) {
            int num = sc.nextInt();

            if (num < min) {
                min = num;
            }
            if (num > max) {
                max = num;
            }
        }

        // Print result
        System.out.println("Min: " + min + " Max: " + max);

        sc.close();
    }
}

```

■ Your code has successfully passed all test cases, indicating a correct and effective implementation of the problem solution. Great job on achieving an "Accepted" status, congratulations on your accomplishment!

■ Recommendations

Areas that need improvement:

- **Aptitude:** Practice more logical reasoning, quantitative aptitude, and problem-solving questions.