

STATIC ROUTE -LAB

ASSIGN IP ADDRESS ALL THE CISCO ROUTERS:-

PNETLab | Topology x Static Route x ChatGPT x (18) WhatsApp x Notes/CCNA/SN-CA-B x Untitled x Ask Gemini

R1

```
R1#sh ip int bri
```

Interface	IP-Address	OK?	Method	Status	Prot
Ethernet0/0	10.0.0.1	YES	NVRAM	up	up
Ethernet0/1	20.0.0.1	YES	NVRAM	up	up
Ethernet0/2	unassigned	YES	NVRAM	down	down
Ethernet0/3	unassigned	YES	NVRAM	down	down

R1#

R2

```
R2#sh ip int bri
```

Interface	IP-Address	OK?	Method	Status	Prot
Ethernet0/0	20.0.0.2	YES	NVRAM	up	up
Ethernet0/1	30.0.0.1	YES	NVRAM	up	up
Ethernet0/2	unassigned	YES	NVRAM	down	down
Ethernet0/3	unassigned	YES	NVRAM	down	down

R2#

R3

```
R3#sh ip int bri
```

Interface	IP-Address	OK?	Method	Status	Prot
Ethernet0/0	40.0.0.1	YES	manual	up	up
Ethernet0/1	30.0.0.2	YES	manual	up	up
Ethernet0/2	unassigned	YES	NVRAM	down	down
Ethernet0/3	unassigned	YES	NVRAM	down	down

R3#

Static Route

Physical + - 01 : 00 : 00 START

34°C Partly sunny

Search

Win-2 40.0.0.10

17:11 23-08-2026

ADD STATIC ROUTES FOR MISSING ROUTES IN ALL THREE ROUTER'S:-

PNETLab | Topology Static Route ChatGPT (18) WhatsApp Notes/CCNA/SN-CA-B Untitled Ask Gemini

R1

Ethernet0/3 unassigned YES NVRAM down down

```
R1#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from Pfr

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    10.0.0.0/8 is directly connected, Ethernet0/0
L    10.0.0.1/32 is directly connected, Ethernet0/0
C    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    20.0.0.0/8 is directly connected, Ethernet0/1
L    20.0.0.1/32 is directly connected, Ethernet0/1
S    30.0.0.0/8 [1/0] via 20.0.0.2
S    40.0.0.0/8 [1/0] via 20.0.0.2
R1#
```

R2

Ethernet0/3 unassigned YES NVRAM down down

```
R2#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from Pfr

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 20.0.0.1
C    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    20.0.0.0/8 is directly connected, Ethernet0/0
L    20.0.0.2/32 is directly connected, Ethernet0/0
C    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    30.0.0.0/8 is directly connected, Ethernet0/1
L    30.0.0.1/32 is directly connected, Ethernet0/1
S    40.0.0.0/8 [1/0] via 30.0.0.2
R2#
```

R3

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from Pfr

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 30.0.0.1
S    20.0.0.0/8 [1/0] via 30.0.0.1
C    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    30.0.0.0/8 is directly connected, Ethernet0/1
L    30.0.0.2/32 is directly connected, Ethernet0/1
C    40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    40.0.0.0/8 is directly connected, Ethernet0/0
L    40.0.0.1/32 is directly connected, Ethernet0/0
R3#
```

Win-1 10.0.0.10

Win-2 40.0.0.10

Static Route

Physical 01 : 00 : 00 START

34°C Partly sunny Search 17:12 23-08-2026

PC1 TO PC2 REACHABILITY OUTPUT:-

