



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401358
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 100
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 280 (+0% Tol.)
Load losses at 120 °C	[W] 2050 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 52

Preliminary dimensions and weight IP00

Length	[mm] 1120
Width	[mm] 630
Height	[mm] 1200
Roller distance (c/c)	[mm] 520 x 520
Total weight	[kg] 740

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401358
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 160
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 400 (+0% Tol.)
Load losses at 120 °C	[W] 2900 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 54

Preliminary dimensions and weight IP00

Length	[mm] 1310
Width	[mm] 700
Height	[mm] 1280
Roller distance (c/c)	[mm] 520 x 520
Total weight	[kg] 1250

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401358
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 250
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 520 (+0% Tol.)
Load losses at 120 °C	[W] 3800 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 57

Preliminary dimensions and weight IP00

Length	[mm] 1310
Width	[mm] 670
Height	[mm] 1440
Roller distance (c/c)	[mm] 520 x 520
Total weight	[kg] 1180

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 400
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 750 (+0% Tol.)
Load losses at 120 °C	[W] 5500 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 60

Preliminary dimensions and weight IP00

Length	[mm] 1400
Width	[mm] 760
Height	[mm] 1470
Roller distance (c/c)	[mm] 670 x 670
Total weight	[kg] 1640

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 500
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 902 (+0% Tol.)
Load losses at 120 °C	[W] 6413 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 61

Preliminary dimensions and weight IP00

Length	[mm] 1460
Width	[mm] 760
Height	[mm] 1570
Roller distance (c/c)	[mm] 670 x 670
Total weight	[kg] 1710

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 630
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 1100 (+0% Tol.)
Load losses at 120 °C	[W] 7600 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 62

Preliminary dimensions and weight IP00

Length	[mm] 1520
Width	[mm] 770
Height	[mm] 1610
Roller distance (c/c)	[mm] 670 x 670
Total weight	[kg] 1870

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 800
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 1300 (+0% Tol.)
Load losses at 120 °C	[W] 8000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 64

Preliminary dimensions and weight IP00

Length	[mm] 1540
Width	[mm] 760
Height	[mm] 1860
Roller distance (c/c)	[mm] 670 x 670
Total weight	[kg] 2070

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 1000
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 1550 (+0% Tol.)
Load losses at 120 °C	[W] 9000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 65

Preliminary dimensions and weight IP00

Length	[mm] 1700
Width	[mm] 790
Height	[mm] 1900
Roller distance (c/c)	[mm] 670 x 670
Total weight	[kg] 2970

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 1250
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 1800 (+0% Tol.)
Load losses at 120 °C	[W] 11000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 67

Preliminary dimensions and weight IP00

Length	[mm] 1700
Width	[mm] 810
Height	[mm] 2080
Roller distance (c/c)	[mm] 670 x 670
Total weight	[kg] 3105

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 1600
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 2200 (+0% Tol.)
Load losses at 120 °C	[W] 13000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 68

Preliminary dimensions and weight IP00

Length	[mm] 1860
Width	[mm] 980
Height	[mm] 2190
Roller distance (c/c)	[mm] 820 x 820
Total weight	[kg] 4310

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes



CCP Number: 16Qxxxxxx

Date: x/x-2016

Technical Specification

Product name	Dry Type Vacuum Cast Coil Transformer
Product type id.	9AAF401365
Application	Distribution
Country of origin	Spain
Rated power	[kVA] 2000
Primary voltage	[V] 10000
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 400
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temperature rise (HV/LV)	[K/K] 100 / 100
Environmental, climatic, fire class	E2, C2, F1
Temperature class (HV/LV)	F/F
Altitude (a.s.l.)	[m] < 1000
Location	Indoor

Performance values

Standards	IEC 60076, EN 50588-1:2015
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 2600 (+0% Tol.)
Load losses at 120 °C	[W] 16000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 70

Preliminary dimensions and weight IP00

Length	[mm] 1900
Width	[mm] 980
Height	[mm] 2400
Roller distance (c/c)	[mm] 820 x 820
Total weight	[kg] 4745

Type of design IP00

Cooling	AN
Primary winding conductor material	AL
Secondary winding conductor material	AL
Winding manufacturing (HV/LV)	Encapsulated / Impregnated

Standard Features/Accessories

Off circuit tap changer on primary winding
Aluminum rating plate in English
1xPT100P/phase
T-154 Temperature Control Unit
Bi-Directional wheels
Drawing for information
Documents in English
Lifting lugs & Pulling Eyes