



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 100
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 145 (+0% Tol.)
Load losses	[W] 1750 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 41

Preliminary dimensions and weight

Length	[mm] 1000
Width	[mm] 650
Height	[mm] 1310
Roller distance (c/c)	[mm]
Oil weight	[kg] 155
Total weight	[kg] 770

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 200
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 250 (+0% Tol.)
Load losses	[W] 2750 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 44

Preliminary dimensions and weight

Length	[mm] 1060
Width	[mm] 710
Height	[mm] 1220
Roller distance (c/c)	[mm] 520 x 520
Oil weight	[kg] 200
Total weight	[kg] 990

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 400
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 430 (+0% Tol.)
Load losses	[W] 4600 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 45

Preliminary dimensions and weight

Length	[mm] 1150
Width	[mm] 810
Height	[mm] 1450
Roller distance (c/c)	[mm] 670 x 670
Oil weight	[kg] 270
Total weight	[kg] 1470

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 630
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 4 (±10% Tol.)
No load losses	[W] 600 (+0% Tol.)
Load losses	[W] 6500 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 52

Preliminary dimensions and weight

Length	[mm] 1250
Width	[mm] 920
Height	[mm] 1560
Roller distance (c/c)	[mm] 670 x 670
Oil weight	[kg] 360
Total weight	[kg] 1930

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket

ABB

Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 800
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 650 (+0% Tol.)
Load losses	[W] 8400 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 53

Preliminary dimensions and weight

Length	[mm] 1520
Width	[mm] 900
Height	[mm] 1630
Roller distance (c/c)	[mm] 670 x 670
Oil weight	[kg] 450
Total weight	[kg] 2400

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket

ABB

Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 1000
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 770 (+0% Tol.)
Load losses	[W] 10500 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 55

Preliminary dimensions and weight

Length	[mm] 1670
Width	[mm] 990
Height	[mm] 1660
Roller distance (c/c)	[mm] 820 x 820
Oil weight	[kg] 520
Total weight	[kg] 2770

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 1250
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 950 (+0% Tol.)
Load losses	[W] 11000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 51

Preliminary dimensions and weight

Length	[mm] 1730
Width	[mm] 990
Height	[mm] 1770
Roller distance (c/c)	[mm] 820 x 820
Oil weight	[kg] 660
Total weight	[kg] 3620

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 1600
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 1200 (+0% Tol.)
Load losses	[W] 14000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 53

Preliminary dimensions and weight

Length	[mm] 1830
Width	[mm] 1100
Height	[mm] 1815
Roller distance (c/c)	[mm] 820 x 820
Oil weight	[kg] 710
Total weight	[kg] 3850

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket



Technical Specification

Product name	Oil Insulated Hermetically sealed transformer
Product type id.	9AAC30400745
Application	Distribution - EcoDesign Tier 1
Country of origin	Poland
Rated power	[kVA] 2000
Primary voltage	[V] 10500
Primary tapplings	+5%, +2.5%, 0%, -2.5%, -5%
Secondary voltage at no load	[V] 420
Primary insulation level	[kV] LI 75 / AC 28 / Um 12
Secondary insulation level	[kV] LI - / AC 3 / Um 1.1
Frequency	[Hz] 50
Number of phases	3
Vector group	Dyn 5 or 11
Ambient temperature	°C 40 / 30 / 20
max./monthly/annual average	
Max. average temp. rise (Oil/Winding)	[K/K] 60/65
Surface Treatment	C5-M, RAL 7033
Altitude (a.s.l.)	[m] < 1000
Location	Outdoor

Performance values

Standards	IEC 60076
Impedance	[%] 6 (±10% Tol.)
No load losses	[W] 1450 (+0% Tol.)
Load losses	[W] 18000 (+0% Tol.)
Sound power level (LWA)	[dB(A)] 53

Preliminary dimensions and weight

Length	[mm] 1990
Width	[mm] 1270
Height	[mm] 1910
Roller distance (c/c)	[mm] 1070 x 1070
Oil weight	[kg] 860
Total weight	[kg] 4820

Type of design IP00

Tank construction	Hermetically sealed
Winding material (Primary)	AL
Winding material (Secondary)	AL

Standard Features/Accessories

Off circuit tap changer on primary winding
HV orcelain bushings
LV porcelain bushings
LV connection flags
Safety valve without contacts
Wheels
Liquid level indicator
2 x thermometer pocket