

Question 1

Search Strategy	Advantage	Disadvantage
Depth-first Search	Requires relatively little memory space	Will go into an infinite loop if the search space is cyclical
Depth-first search with iterative deepening	Requires relatively little memory space	Needs to recompute many paths when depth limit is increased
Breadth-first search		Stores many possible paths and can thus require a lot of space
A*	Will find a reasonable solution but not necessarily the best solution.	Has to keep a number of candidate nodes in memory and also keep their heuristic function in memory

Question 2

Question 3.1

S=[clear(a).clear(b), clear(c),clear(d),on(a,1),on(b,2),on(c,3),on(d,4)]

Our Goal: on(d,1)

On(d,1) does not hold so we propose move(d,From,1)

Preconditions:[clear(d),clear(1),on(d,From)]

clear(d) holds

clear(1) does not hold

new goal clear(1)

Propose action: move(Block,1,To)

Preconditions:[clear(Block),clear(To),on(Block,1)]

clear(Block) holds for Block = a

clear(To) holds for To = b

on(Block,1) holds for Block = a

Action move(a,1,b)

After deletions $S=[\text{clear}(a), \text{clear}(c), \text{clear}(d), \text{on}(b,2), \text{on}(c,3), \text{on}(d,4)]$

After additions $S=[\text{clear}(a), \text{clear}(c), \text{clear}(d), \text{clear}(1), \text{on}(b,2), \text{on}(c,3), \text{on}(d,4), \text{on}(a,b)]$

Back to goal $\text{on}(d,1)$

Proposed move($d, \text{From}, 1$)

Preconditions: $[\text{clear}(d), \text{clear}(1), \text{on}(d, \text{From})]$

$\text{clear}(d)$ holds

$\text{clear}(a)$ holds

$\text{on}(d, \text{From})$ holds for $\text{From} = 4$

Action move($d, 4, 1$)

After deletions $S=[\text{clear}(a), \text{clear}(c), \text{clear}(d), \text{on}(b,2), \text{on}(c,3), \text{on}(a,b)]$

After additions $S=[\text{clear}(a), \text{clear}(c), \text{clear}(d), \text{clear}(4), \text{on}(b,2), \text{on}(c,3), \text{on}(d,1), \text{on}(a,b)]$

Plan: $[\text{move}(a,1,b) \text{ move}(d,4,1)]$

Question 3.2

$S=[\text{clear}(a), \text{clear}(b), \text{clear}(c), \text{clear}(d), \text{on}(a,1), \text{on}(b,2), \text{on}(c,3), \text{on}(d,4)]$

Our Goal: $\text{on}(d,1)$

$\text{on}(d,1)$ does not hold so we propose move($d, \text{From}, 1$)

Preconditions: $[\text{clear}(d), \text{clear}(1), \text{on}(d, \text{From})]$

$\text{clear}(d)$ holds

$\text{clear}(1)$ does not hold

new goal $\text{clear}(1)$

Propose action: move($\text{Block}, 1, \text{To}$)

Preconditions: $[\text{clear}(\text{Block}), \text{clear}(\text{To}), \text{on}(\text{Block}, 1)]$

$\text{clear}(\text{Block})$ holds for $\text{Block} = a$

$\text{clear}(\text{To})$ holds for $\text{To} = b$

$\text{on}(\text{Block}, 1)$ holds for $\text{Block} = a$

Action move(a,1,b)

After deletions S=[clear(a), clear(c),clear(d),on(b,2),on(c,3),on(d,4)]

After additions S=[clear(a), clear(c),clear(d), clear(1), on(b,2),on(c,3),on(d,4),on(a,b)]

Protected goal list: [clear(1)]

Back to goal on(d,1)

Proposed move(d,From,1)

Preconditions: [clear(d),clear(1),on(d,From)]

clear(d) holds

clear(a) holds

on(d,From) holds for From = 4

Action move(d,4,1)

After deletions S=[clear(a), clear(c),clear(d), on(b,2),on(c,3),on(a,b)]

After additions S=[clear(a), clear(c),clear(d),clear(4), on(b,2),on(c,3),on(d,1),on(a,b)]

Plan:[move(a,1,b) move(d,4,1)]

Question 4

Initial state S = [clear(a),clear(b),clear(c),clear(d),on(a,1),on(b,2),on(c,3),on(d,4)]

Goal on(a,2)

Propose move(a,From,2)

Preconditions: [clear(a),clear(2),on(a,From)]

Clear(a) holds

Clear(2) fails

Regression list [clear(a),clear(2), on(a,From)]

Instantiate From = 1

New sub-goal : clear(2)

Propose move move(Block(2,To)

Precondition:[clear(Block),clear(To),on(Block,2)]

Instantiate Block to b

Proposed regressed goal list [clear(b),clear(To),on(b,2),clear(a),clear(2),on(a,2)]

Our preconditions were [clear(b), clear(To), on(b,2)

Delete list is [clear(To),on(b,2)]

New regressed goal list is [clear(b),clear(a),clear(2).on(a,2)]

Clear(To) succeeds with To = c

Action move(b,2,c)

After deletion S = [clear(a),clear(b),clear(d),on(a,1),on(c,3),on(d,4)]

After addition S= [clear(a),clear(b),clear(d),clear(2),on(a,1),on(c,3),on(d,4), on(b,c)]

Back to initial goal on(a,2)

Propose move(a,From,2)

Preconditions: [clear(a),clear(2),on(a,From)]

Regression can be performed

Instantiate From to 1

Action move(a,1,2)

After deletion S= [clear(a),clear(b),clear(d),on(c,3),on(d,4), on(b,c)]

After addition S= [clear(a),clear(b),clear(d),clear(1),on(a,2),on(c,3),on(d,4), on(b,c)]

Our goal has bee achieved with moves:[move(b,2,c),move(a,1,2)]