

Base

PowerEdge R860

Trusted Platform Module

Trusted Platform Module 2.0 V3

Chassis Configuration

2.5" Chassis with up to 24 Drives (16 SAS/SATA + 8 NVMe Direct), 4CPU, PERC12

Processor

2x Intel® Xeon® Gold 6448H 2.4G, 32C/64T, 16GT/s, 60M Cache, Turbo, HT (250W) DDR5-4800

Additional Processor

2x Intel® Xeon® Gold 6448H 2.4G, 32C/64T, 16GT/s, 60M Cache, Turbo, HT (250W) DDR5-4800

Processor Thermal Configuration

Heatsink 4 CPU Config(more than 205W under 250W for x8 x16,less than or equal to 250W for x24 chassi

Memory Configuration Type

Performance Optimized

Memory DIMM Type and Speed

4800MT/s RDIMMs

Memory Capacity

(8) 128GB RDIMM, 4800MT/s Quad Rank

RAID Configuration

C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)

RAID/Internal Storage Controllers

Front PERC H965i Rear Load (for 2.5" x8/16/32 SAS/SATA chassis)

Hard Drives

3.84TB SSD SAS Read Intensive up to 24Gbps SED FIPS-140 512e 2.5in Hot-Plug AG Drive

Hard Drives (PCIe SSD/Flex Bay)

15.36TB Enterprise NVMe Read Intensive AG Drive U.2 Gen4 with carrier

BIOS and Advanced System Configuration Settings

Performance BIOS Setting

Advanced System Configurations

UEFI BIOS Boot Mode with GPT Partition

Advanced System Configurations

No Energy Star

Power Supply

Dual, Fault Tolerant Redundant(1+1), Hot-Plug, Power Supply, 1400W MM,R860 Only

Power Cords

(4) NBR 14136 2P+T to C13, 250V, 10A, 2m, Brazil Power Cord

PCIe Riser

Riser Config 0, Half Length, 4x8 FH Slots (Gen4)

Motherboard

PowerEdge R860 Motherboard, MX

OCP 3.0 Network Adapters

Broadcom 57504 Quad Port 10/25GbE,SFP28, OCP NIC 3.0

Additional Network Adapters

Broadcom 5720 Dual Port 1GbE LOM

Additional Network Adapters

Broadcom 57414 Dual Port 10/25GbE SFP28 Adapter, PCIe Full Height, V2

Fibre Channel Adapters

Emulex LPe36002 Dual Port FC64 Fibre Channel HBA, PCIe Full Height

Bezel

PowerEdge 2U LCD Bezel

Boot Optimized Storage Cards

BOSS-N1 controller card + with 2 M.2 480GB (RAID 1)

Optics & Cables for Network Cards

(4) SFP+ SR Optic, 10GbE, for all SFP+ ports except high temp validation warning cards

Optics & Cables for Network Cards

(4) Dell Networking, Cable, SFP+ to SFP+, 10GbE, Copper Twinax Direct Attach Cable, 3 Meter

Operating System

VMware ESXi 8.0 Embedded Image (License Not Included)

OS Media Kits

No Media Required

Embedded Systems Management
OpenManage Enterprise Advanced

Embedded Systems Management
iDRAC9, Datacenter 16G

Quick Sync
No Quick Sync

Password
iDRAC,Factory Generated Password

IDRAC Service Module
iDRAC Service Module (ISM), Pre-Installed in OS

Group Manager
iDRAC Group Manager, Enabled

Rack Rails
2U Combo Drop-In/Stab-In Rails With Cable Management Arm

Server Accessories
Keyboard and Optical Mouse, USB, Black, English

Server Accessories
Internal USB 3.0 Card

Server Accessories
8X DVD-ROM, USB, External

Server Accessories
Optional Serial Card (COM), Full Height

System Documentation
No Systems Documentation, No OpenManage DVD Kit

SHIPPING
PowerEdge R860 Shipping

Shipping Material
PowerEdge R860 Shipping Material

Regulatory
PowerEdge R860 CE Marking, No BIS or CCC Marking on 2.5" Chassis

Service

Basic Next Business Day 36 Months, 36 Month(s)

Extended Service

NO WARRANTY UPGRADE SELECTED, 36 Month(s)

Infrastructure Deployment Svcs

Select Legacy ProDeploy Suite from module 714 or 200437

Differential Discounting - Deployment Services

Basic Deployment Dell Server R Series 1U/2U

Education Services

Education Services Training Credits 1000 - Redeem at education.dellemc.com Expires 1yr from order

Warranty & Support

Basic Next Business Day 36 Months, 36 Month(s)