

---

# **Systems Notes**

## **Computer Science**

---

Alex Norton

ajn123@vt.edu

Beginning 9 February 2014



# Contents

<b>Chapter 8: Shell</b>	<b>1</b>
1 Process . . . . .	1
2 Context switching . . . . .	1
3 File Descriptor . . . . .	1
4 Signal . . . . .	2
5 Pipelining . . . . .	2
6 Fork . . . . .	5
7 reentrant . . . . .	5
8 PID-process identifier . . . . .	6
<b>Thread Pool</b>	<b>7</b>
1 Threads . . . . .	7
<b>Saturday, 27 March 2010</b>	<b>8</b>
1 Bulleted list example . . . . .	8
2 This is an example experiment . . . . .	8
3 This is another example experiment . . . . .	8



# Chapter 8: Shell

## 1 Process

The first thing to understand is that a **computer program** is a passive collection of instructions; a **process** is the actual execution of those instructions.

A **process** in user mode is not allowed to execute privileged instructions. The only way for the process to change from user mode to kernel mode is via an exception such as an **interrupt**, a **fault** or a **trapping system call**.

## 2 Context switching

In computing, a **context switch** is the process of storing and restoring the state (context) of a process so that execution can be resumed from the same point at a later time. This enables multiple processes to share a single CPU and is an essential feature of a multitasking operating system. What constitutes the context is determined by the processor and the operating system.

A context switch follows these 3 steps:

1. saves the contents of the current process.
2. restores the saved context of some previously preempted process
3. passes control to this newly restored process

## 3 File Descriptor

A file descriptor is an indicator for a way of accessing a file.

## 4 Signal

A **signal** is a message that notifies a process that an event of some type has occurred in the system (just like when you press a button on your phone, a message is sent to the operating system). Each signal corresponds to some kind of system event. For example, a signal can be used to cancel background jobs.

Integer Value	Name
0	Standard Input (Stdin)
1	Standard Output (Stdout)
2	Standard Error (Stderr)

Table 1: Integer Values and their File descriptors

A pending signal is a signal that has been sent but not received. A process can also block a CERTAIN signal. In this case, blocked signals can be sent but will not be received until the signal is unblocked.

Signal Name	Source	Possible Actions	Default Action
SIGKILL	program		terminate
SIGTERM	program	block, catch, ignore	terminate
SIGSTOP	program		stop
SIGINT (C-c)	terminal	block, catch, ignore	terminate
SIGQUIT (C-\)	terminal	block, catch, ignore	terminate
SIGTSTP (C-z)	terminal	block, catch, ignore	stop
SIGCHLD	kernel	block, catch, ignore	ignore

Figure 1: Table of possible signals

## 5 Pipelining

Pipelining works by setting the standard output(1) of the first command to the standard input(0) of the second command in the pipeline. here are a couple

of system calls that you may be interested to understand what is happening in more detail, in particular, `fork(2)`, `execve(2)`, `pipe(2)`, `dup2(2)`, `read(2)` and `write(2)`.

- The `dup2` function takes two parameters *dup2(old, new)* The pointer of old will replace the pointer of new when the function is called. (code example below)

```
1      #include <stdio.h>
2      #include <unistd.h>
3      #include <sys/types.h>
4
5      #define IN 0
6      #define OUT 1
7
8      int main(void)
9      {
10         char string[] = "Hello, world!\n";
11         char readbuffer[80];
12
13         // Creates the pipe using the integer array of size two.
14         int fd[2];
15         pipe(fd);
16
17         // Fork new process
18         if(fork() == 0)
19         {
20             // Copy the write end of pipe to standard out.
21             dup2( fd[OUT], OUT );
22             // Close read and write end of pipe.
23             close( fd[IN] );
24             close( fd[OUT] );
25             // Child Process: execute new process
26             char *cmd[] = {"ls", "-la", (char *) 0};
27             execvp("ls", cmd);
28         }
29         else
30         {
31             // Clise write end of pipe.
32             close( fd[OUT] );
33             // Parent Process: Read string from the read side of
pipe.
34             read( fd[IN], readbuffer, sizeof(readbuffer) );
35             printf("Received string: %s", readbuffer);
36         }
37         return(0);
38     }
```

---



## 6 Fork

This is an example of the fork method in C. `fork()` clones a process from a process. This new process can be used to execute another process or do other things. NOTE: Once you clone a process you have no idea which order your clones will run in, your code should not depend on the order. Another thing to remember is that fork returns twice, once in the parent and once in the child (the new process you just created). The cloned process is exactly the same except for the return value of `fork()`. In the child process fork will always return 0 and in the parent it will return the process ID of itself so your code can just check for the child process with `== 0` and the parent with an else.

Fork returns the PROCESS ID OF ITS CHILD to the parent process, so that the parent knows its PID of the child to keep track of it. `Fork()` returns 0 to the child, you don't need it.

---

```
#include <unistd.h>
#include <stdio.h>

int main(){
    int x = 1;

    int pid = fork();// pid contains the childs pid for the
        parent process.
    if (pid== 0)
    { // only child executes this
        printf("Child, x = %d\n", ++x);
    }
    else {
        // only parent executes this
        printf("Parent, x = %d\n", --x);
    } // parent and child execute this
    printf("Exiting with x = %d\n", x);
    return 0;
}
```

---

## 7 reentrant

A computer program in **reentrant** if it can be interrupted in the middle of its execution and then safely called again. An interruption can come from a signal

or a jump. Once the reentered invocation completes, the previous invocations will resume correct execution.

- `Printf()` is a NON reentrant function, meaning that it is not safe to interrupt.

## **8 PID-process identifier**

A number used to temporarily uniquely identify a process.

One may use the command "ps j" to see PPID (parent process ID), PID (process ID), PGID (process group ID) and SID (session ID) of processes.

experimentP Threads- POSIX threads

# Thread Pool

## 1 Threads

threads share all the same data structures, processes DO NOT.

When you have multiple processes

Groups	Treatment X	Treatment Y
1	0.2	0.8
2	0.17	0.7
3	0.24	0.75
4	0.68	0.3

Table 1: The effects of treatments X and Y on the four groups studied.

Table 1 shows that groups 1-3 reacted similarly to the two treatments but group 4 showed a reversed reaction.

# Saturday, 27 March 2010

## 1 Bulleted list example

This is a bulleted list:

- Item 1
- Item 2
- ... and so on

## 2 This is an example experiment

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

## 3 This is another example experiment

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

---

## Formulae and Media Recipes

---

# Media

## Media 1

Compound	1L	0.5L
Compound 1	10g	5g
Compound 2	20g	10g

Table 1: Ingredients in Media 1.

# Formulae

## Formula 1 - Pythagorean theorem

$$a^2 + b^2 = c^2$$