

C++ PROGRAM DESIGN TEST DRIVEN DEVELOPMENT

Problem Solving with Computers-I

<https://ucsb-cs16-wi17.github.io/>

C++

```
#include <iostream>
using namespace std;

int main(){
    cout<<"Hola Facebook\n";
    return 0;
}
```



ASCII Art: Write a program to draw a house of stars!

- Inputs: Dimensions of the house (width, height)
- Output: Drawing of a house made of ascii '*'

Step 1: Top-down design

- Break down the problem into subtasks
- Design your functions

```
string getBody(int width, int height);  
string getRoof(int rheight);  
string getHouse(string roof, string body);
```

Step 2: Implement and test each part

- Test code drives implementation- you are in control because you can....
 - measure your progress
 - write code systematically
 - debug systematically
 - automate testing

How to do TDD?

- Test suite: Bunch of tests

- **Case 1:** `ls getRoof(0) == '*'`
- **Case 2:** `ls getRoof(1) ==`
- **Case 3:** `ls getRoof(2) ==`

```
string getRoof(int rheight);
```

- Test harness: Functions to report PASS/FAIL

If expected == actual, report **TEST PASSED!**
else report **TEST FAILED!**

What is returned by getRoof(1)

```
string getRoof(int height){
    int numSpaces;
    int numStars;
    string result;
    string spaces="";
    string stars="";

    for(int row = 0 ; row <=height;row++){
        numSpaces=0;
        numStars=1;
        spaces=stars="";

        for(int i=0;i<numSpaces;i++){
            spaces+=" ";
        }
        for(int i=0;i<numStars;i++){
            stars+="*";
        }

        result= result+spaces+stars+spaces+"\n";
    }
    return result;
}
```

A

*

B

*

C

*

*

D

None of the above

Choose the replacement code to return the correct number of stars on each row for getRoof(1)

```
string getRoof(int height){  
    int numSpaces;  
    int numStars;  
    string result;  
    string spaces="";  
    string stars="";  
  
    for(int row = 0 ; row <=height;row++){  
        numSpaces=0;  
        numStars=1;  
        spaces=stars="";  
  
        for(int i=0;i<numSpaces;i++){  
            spaces+=" ";  
        }  
        for(int i=0;i<numStars;i++){  
            stars+="*";  
        }  
  
        result= result+spaces+stars+spaces+"\n";  
    }  
    return result;  
}
```

*

A numStars=row;

B numStars=height-row;

C numStars=2*row+1;

D numStars=2*height+1;

Choose replacement code to return the correct output for getRoof(0) and getRoof(1)

```
string getRoof(int height){
    int numSpaces;
    int numStars;
    string result;
    string spaces="";
    string stars="";

    for(int row = 0 ; row <=height;row++){
        numSpaces=0;
        numStars=          ;
        spaces=stars="";

        for(int i=0;i<numSpaces;i++){
            spaces+=" ";
        }
        for(int i=0;i<numStars;i++){
            stars+="*";
        }

        result= result+spaces+stars+spaces+"\n";
    }
    return result;
}
```

```
      *          *
      *          *
      ***
```

- A** numSpaces=row;
- B** numSpaces=height-row;
- C** numSpaces=2*row+1;
- D** numSpaces=2*height+1;

Modify the code to make a hollow body

```
string getBody(int width, int height){  
    string result;  
    for(int row = 0;row <height;row++){  
        for(int col =0; col<width;col++){  
            result+='*';  
  
        }  
        result+="\n";  
    }  
    return result;  
  
}
```

Next time

- Separate compilation with makefiles
- Pointers