

Vim Cheat Sheet

Global

:h[elp] keyword - open help for keyword

:sav[eas] file - save file as

:clo[se] - close current pane

:ter[минаl] - open a terminal window

K - open man page for word under the cursor

Cursor movement

h - move cursor left

j - move cursor down

k - move cursor up

l - move cursor right

gj - move cursor down (multi-line text)

gk - move cursor up (multi-line text)

H - move to top of screen

M - move to middle of screen

L - move to bottom of screen

w - jump forwards to the start of a word

W - jump forwards to the start of a word (words can contain punctuation)

e - jump forwards to the end of a word

E - jump forwards to the end of a word (words can contain punctuation)

b - jump backwards to the start of a word

B - jump backwards to the start of a word (words can contain punctuation)

ge - jump backwards to the end of a word

gE - jump backwards to the end of a word (words can contain punctuation)

% - move to matching character (default supported pairs: '()', '{}', '[]' - use **:h matchpairs** in vim for more info)

Editing

r - replace a single character.

R - replace more than one character, until **ESC** is pressed.

J - join line below to the current one with one space in between

gJ - join line below to the current one without space in between

gwap - reflow paragraph

g~ - switch case up to motion

gu - change to lowercase up to motion

gU - change to uppercase up to motion

cc - change (replace) entire line

c\$ or **C** - change (replace) to the end of the line

ciw - change (replace) entire word

cw or **ce** - change (replace) to the end of the word

s - delete character and substitute text

S - delete line and substitute text (same as cc)

xp - transpose two letters (delete and paste)

u - undo

U - restore (undo) last changed line

Ctrl + r - redo

. - repeat last command

Marking text (visual mode)

v - start visual mode, mark lines, then do a command (like y-yank)

V - start linewise visual mode

O - move to other end of marked area

Ctrl + v - start visual block mode

Macros

qa - record macro a

q - stop recording macro

@a - run macro a

@@ - rerun last run macro

Cut and paste

yy - yank (copy) a line

2yy - yank (copy) 2 lines

yw - yank (copy) the characters of the word from the cursor position to the start of the next word

yiw - yank (copy) word under the cursor

yaw - yank (copy) word under the cursor and the space after or before it

ys or **Y** - yank (copy) to end of line

p - put (paste) the clipboard after cursor

P - put (paste) before cursor

gp - put (paste) the clipboard after cursor and leave cursor after the new text

gP - put (paste) before cursor and leave cursor after the new text

dd - delete (cut) a line

2dd - delete (cut) 2 lines

dw - delete (cut) the characters of the word from the cursor position to the start of the next word

diw - delete (cut) word under the cursor

daw - delete (cut) word under the cursor and the space after or before it

d\$ or **D** - delete (cut) to the end of the line

x - delete (cut) character

Indent text

>> - indent (move right) line one shiftwidth

<< - de-indent (move left) line one shiftwidth

Working with multiple files

:e[dit] file - edit a file in a new buffer

:bn[ext] - go to the next buffer

:bp[revious] - go to the previous buffer

:bd[elete] - delete a buffer (close a file)

:b[uffer]# - go to a buffer by index #

:b[uffer] file - go to a buffer by file

:ls or **:buffers** - list all open buffers

:sp[lit] file - open a file in a new buffer and split window

:vs[plit] file - open a file in a new buffer and vertically split window

:vert[ical] ba[ll] - edit all buffers as vertical windows

:tab ba[ll] - edit all buffers as tabs

Ctrl + ws - split window

Ctrl + wv - split window vertically

Ctrl + ww - switch windows

Ctrl + wq - quit a window

Ctrl + wx - exchange current window with next one

Ctrl + w= - make all windows equal height & width

Ctrl + wh - move cursor to the left window (vertical split)

Ctrl + wl - move cursor to the right window (vertical split)

Ctrl + wj - move cursor to the window below (horizontal split)

Ctrl + wk - move cursor to the window above (horizontal split)

Ctrl + wH - make current window full height at far left (leftmost vertical window)

Ctrl + wL - make current window full height at far right (rightmost vertical window)

Ctrl + wJ - make current window full width at the very bottom (bottommost horizontal window)

Ctrl + wK - make current window full width at the very top (topmost horizontal window)

Diff

zf - manually define a fold up to motion

zd - delete fold under the cursor

za - toggle fold under the cursor

zo - open fold under the cursor

0 - jump to the start of the line

^ - jump to the first non-blank character of the line

\$ - jump to the end of the line

g_ - jump to the last non-blank character of the line

gg - go to the first line of the document

G - go to the last line of the document

5gg or **5G** - go to line 5

gd - move to local declaration

gD - move to global declaration

fx - jump to next occurrence of character x

tx - jump to before next occurrence of character x

Fx - jump to the previous occurrence of character x

Tx - jump to after previous occurrence of character x

; - repeat previous f, t, F or T movement

, - repeat previous f, t, F or T movement, backwards

} - jump to next paragraph (or function/block, when editing code)

{ - jump to previous paragraph (or function/block, when editing code)

ZZ - center cursor on screen

Ctrl + e - move screen down one line (without moving cursor)

Ctrl + y - move screen up one line (without moving cursor)

Ctrl + b - move back one full screen

Ctrl + f - move forward one full screen

Ctrl + d - move forward 1/2 a screen

Ctrl + u - move back 1/2 a screen

O - move to other corner of block

aw - mark a word

ab - a block with ()

aB - a block with {}

at - a block with <> tags

ib - inner block with ()

iB - inner block with {}

it - inner block with <> tags

Esc - exit visual mode

Visual commands

> - shift text right

< - shift text left

y - yank (copy) marked text

d - delete marked text

~ - switch case

u - change marked text to lowercase

U - change marked text to uppercase

Registers

:reg[isters] - show registers content

"xy - yank into register x

"xp - paste contents of register x

"+y - yank into the system clipboard register

"+p - paste from the system clipboard register

Marks and positions

:marks - list of marks

ma - set current position for mark A

`a - jump to position of mark A

y`a - yank text to position of mark A

`0 - go to the position where Vim was previously exited

`" - go to the position when last editing this file

`. - go to the position of the

>% - indent a block with () or {} (cursor on brace)

>ib - indent inner block with ()

>at - indent a block with <> tags

3== - re-indent 3 lines

=% - re-indent a block with () or {} (cursor on brace)

=iB - re-indent inner block with {}

gg=G - re-indent entire buffer

]p - paste and adjust indent to current line

Exiting

:w - write (save) the file, but don't exit

:w !sudo tee % - write out the current file using sudo

:wq or **:X** or **ZZ** - write (save) and quit

:q - quit (fails if there are unsaved changes)

:q! or **ZQ** - quit and throw away unsaved changes

:wqa - write (save) and quit on all tabs

Search and replace

/pattern - search for pattern

?pattern - search backward for pattern

\vpattern - 'very magic' pattern: non-alphanumeric characters are interpreted as special regex symbols (no escaping needed)

n - repeat search in same direction

N - repeat search in opposite direction

:%s/old/new/g - replace all old with new throughout file

:%s/old/new/gc - replace all old with new throughout file with confirmations

:noh[lsearch] - remove highlighting of

zc - close fold under the cursor

zr - reduce (open) all folds by one level

zm - fold more (close) all folds by one level

zi - toggle folding functionality

]c - jump to start of next change

[c - jump to start of previous change

do or **:diffg[et]** - obtain (get) difference (from other buffer)

dp or **:diffpu[t]** - put difference (to other buffer)

:diffthis - make current window part of diff

:dif[fupdate] - update differences

:diffo[ff] - switch off diff mode for current window

Insert mode - inserting/appending text	last change in this file	search matches
i - insert before the cursor	` ` - go to the position before the last jump	Search in multiple files
I - insert at the beginning of the line	:ju[mps] - list of jumps	:vim[grep] /pattern/ {`{file}`} - search for pattern in multiple files
a - insert (append) after the cursor	Ctrl + i - go to newer position in jump list	:cn[ext] - jump to the next match
A - insert (append) at the end of the line	Ctrl + o - go to older position in jump list	:cp[revious] - jump to the previous match
o - append (open) a new line below the current line	:changes - list of changes	:cope[n] - open a window containing the list of matches
O - append (open) a new line above the current line	g, - go to newer position in change list	:ccl[ose] - close the quickfix window
ea - insert (append) at the end of the word	g; - go to older position in change list	
Ctrl + h - delete the character before the cursor during insert mode	Ctrl +] - jump to the tag under cursor	Tabs
Ctrl + w - delete word before the cursor during insert mode		:tabnew or :tabnew {page.words.file} - open a file in a new tab
Ctrl + j - begin new line during insert mode		Ctrl + wT - move the current split window into its own tab
Ctrl + t - indent (move right) line one shiftwidth during insert mode		gt or :tabn[ext] - move to the next tab
Ctrl + d - de-indent (move left) line one shiftwidth during insert mode		gT or :tabp[revious] - move to the previous tab
Ctrl + n - insert (auto-complete) next match before the cursor during insert mode		#gt - move to tab number #
Ctrl + p - insert (auto-complete) previous match before the cursor during insert mode		:tabm[ove] # - move current tab to the #th position (indexed from 0)
Ctrl + rx - insert the contents of register x		:tabc[lose] - close the current tab and all its windows
Ctrl + ox - Temporarily enter normal mode to issue one normal-mode command x.		:tabo[nly] - close all tabs except for the current one
Esc - exit insert mode		:tabdo command - run the command on all tabs (e.g. :tabdo q - closes all opened tabs)