FLIGHT-RESEARCH CASE STUDY / ABOUT 10 MINUTES

2026-10-18 | VS&A Daily |

X-56A: stable flight does not prove passive stability



X-56A beginning a research mission, June 11, 2019. Its flexible wings made active flutter suppression a flight-research objective. Photo: NASA/Jim Ross, AFRC2019-0113-08; NASA source [5]. This is not a photograph of an identified flutter test point.

NASA deliberately flew X-56A beyond its uncontrolled flutter boundary during the 2018-2019 campaign. Feedback kept the aircraft stable. In carefully bounded demonstrations, control-surface commands were briefly frozen; the unstable motion grew, then decayed when control resumed [1]. The achievement was not a stronger passive wing. It was a stable *controlled system*.

Today’s objective is to distinguish those two claims, understand how feedback phase changes modal energy, and identify the evidence needed before crediting active suppression. For a VS&A engineer, the practical issue is where structural validation ends and coupled-system validation begins.

01 / THE CONTROLLER IS PART OF THE DYNAMICS

A quiet response can conceal an unstable plant

Flutter is self-excited motion: the aerodynamic interaction can supply more energy per cycle than the system dissipates. It does not require a periodic external force tuned to a structural resonance. A gust may start the response, but continued growth can be sustained by the coupled system itself.

For X-56A, the documented mechanism was body-freedom flutter: the short-period pitch motion interacted with the first symmetric wing-bending mode [1]. Treating the fuselage as a fixed boundary would remove part of that mechanism. The aircraft's rigid-body and elastic coordinates belong in the same model.




Figure 1. Original conceptual feedback loop, not the X-56A control architecture. Each block contributes dynamics; arrows show causality, not measured gains.

"Open loop" here means the uncontrolled airframe at a specified flight condition, including its aerodynamic coupling. "Closed loop" adds sensors, signal processing, the control law, and actuator behavior. A well-damped closed-loop response tells you about the assembled loop. It cannot, by itself, establish that the uncontrolled aircraft is stable.

That distinction changes how we use a modal test. NASA reports X-56A structural testing at empty and full fuel conditions, with both landing-gear and suspended configurations. Support coupling required iterations of the suspension arrangement [2]. These tests constrained the structural model; they were not substitutes for in-flight aerodynamic or control-system validation.

The same boundary question arises on spacecraft with flexible appendages and on actively controlled laboratory structures. Before accepting a damping estimate, ask which feedback paths were operating, which signals were measured, and which physical system the identified poles actually describe. "Damping increased" is incomplete without that configuration.

02 / WATCH THE SIGN OF THE WORK

Damping is a timing relationship

Consider one generalized coordinate q, scaled in metres, with modal mass m, stiffness k, and effective open-loop damping coefficient c_a. At a chosen flight condition, c_a may be negative because it represents net aeroelastic behavior, not the material damping alone. An idealized feedback force opposes a delayed modal velocity:

$$m\ddot{q} + c_a\dot{q} + kq = F_c(t)$$

$$F_c(t) = -c_f\dot{q}(t-\tau)$$

$$\omega_n = \sqrt{\frac{k}{m}} \qquad \zeta_a = \frac{c_a}{2m\omega_n} \qquad \zeta_f = \frac{c_f}{2m\omega_n}$$

Here c_a and c_f are in N·s/m, and delay τ is in seconds. The feedback coefficient c_f is positive. With zero delay, force opposes instantaneous velocity and removes energy. The command's sign is correct, but delay can make its timing wrong.

For prescribed harmonic motion $q = Q\cos(\omega t)$, multiply the force by velocity and average over a cycle. The result is exact for that harmonic motion and ideal delayed-velocity law:

$$\overline{P_c} = -\frac{c_f(\omega Q)^2}{2}\cos(\omega\tau)$$

Mean power is in watts. Negative power removes modal energy; positive power adds it. At zero phase lag the feedback is fully dissipative. At 90 degrees it does no net work over the cycle. Beyond 90 degrees, over the first half-turn of lag, it excites rather than damps this motion.

This is an energy argument, not a universal 90-degree stability-margin rule. The airframe may already have negative damping, so the loop can lose net stabilization well before that point. Feedback also has a component in phase with displacement, changing the effective stiffness and oscillation frequency. Multiple modes, non-collocated sensors, and aerodynamic phase further complicate the result.

NASA's IAWTM control-design study illustrates the implementation problem: actuator and measurement dynamics introduced phase loss, and compensation was needed to obtain useful stabilizing gains [3]. That is a separate wind-tunnel-model analysis, not an X-56A flight result.

03 / AN EIGHT-HERTZ SCREEN, NOT FLIGHT TELEMETRY

Twenty milliseconds can matter

Choose an illustrative nominal mode at 8 Hz with open-loop damping ratio −0.02 and ideal zero-delay feedback contribution +0.06. Near the nominal frequency, an equivalent-damping screen is:

$$\zeta_{\text{screen}} = \zeta_a + \zeta_f \cos(2\pi f \tau)$$

The damping ratios are defined on page 3; the nominal angular frequency is 2π times the frequency in hertz. Evaluate at 8 Hz, keeping the feedback gain fixed. All values below are constructed examples, not identified X-56A parameters.

Delay	Phase lag at 8 Hz	Damping screen
0 ms	0°	+4.00%
10 ms	28.8°	+3.26%
20 ms	57.6°	+1.21%
30 ms	86.4°	−1.62%




Figure 2 and table. Original harmonic energy screen. The zero crossing is not a certified delay margin; no eigenvalue or nonlinear stability claim is made by this curve.

At 20 ms, the feedback still removes energy, but much of its nominal damping benefit is gone. At 30 ms it remains weakly dissipative, yet cannot overcome the assumed negative airframe damping. Setting the screen to zero gives a phase of arccos(1/3), or 70.5 degrees: about 24.5 ms at 8 Hz.

Do not turn that number into a requirement. A true delay margin requires the full characteristic equation or an appropriate robust-stability analysis, including frequency shifts and other poles. The calculation is a useful warning: unchanged gain does not mean unchanged protection.

04 / FROM A MODAL MODEL TO EVIDENCE

Validate the paths that supply the damping

Start with the coupled plant, not a structural model followed by an assumed damping bonus. Preserve the rigid-body coordinates that participate in the mechanism, relevant elastic modes, unsteady aerodynamics, and mass-property variations. Validate modal frequencies and shapes, but also check the transfer paths from each actuator to each feedback sensor. A frequency match alone does not establish the sign, phase, or authority of those paths.

Next measure the implementation. Include sensor filters, sampling, computation, communication, actuator dynamics, and surface response. A pure delay is only one model of phase loss; filters also change magnitude. Check the frequency band around uncertain modes, not only the nominal flutter frequency. Apply realistic rate and position limits, deadband, and saturation in nonlinear simulations. A controller that looks dissipative at small signal may have inadequate authority during a finite disturbance.

Then separate performance evidence from identification evidence. A rapid closed-loop decay is useful evidence of controlled behavior at that configuration. To infer the bare-airframe dynamics while feedback remains active, use an identification method that accounts for feedback and multiple inputs. Grauer and Boucher demonstrated such frequency-response estimation with designed multisine inputs, simulations, and X-56A flight data [4]. Their method depends on adequate signal-to-noise ratio and sufficiently stationary, small-perturbation data; feedback does not make these conditions optional.

The X-56A campaign used incremental envelope expansion, response checks, loop-margin evaluation, and model identification. Its brief open-loop demonstrations were explicitly high-risk tests, not routine checkout procedures [1]. The transferable lesson is the layered evidence, not a recommendation to disable a protective loop on another vehicle.

In a design review, make three configurations visible: nominal closed loop; the credible degraded or failed loop; and the recovery path between them. Evaluate uncertainty in plant dynamics and implemented control together. Check what happens during sensor faults, actuator loss, mode switching, or reversion, using the approved system-safety process. A stable nominal eigenvalue set does not demonstrate safe transitions.

Neither the 8 Hz calculation nor X-56A’s project criteria establish a universal aerospace acceptance threshold. Active flutter suppression credit, required margins, failure cases, and flight-test limits belong to the applicable program and certification basis. A research demonstration is valuable evidence of feasibility, not blanket approval for operational use.

05 / THE DESIGN-REVIEW QUESTION

What is actually keeping the mode stable?

1. Name the system. Closed-loop stability and passive airframe stability are different claims. Record the active feedback configuration with every identified damping value.

2. Preserve phase, not just gain. A force intended to damp motion can lose its energy-removal benefit through delay and implementation dynamics. Net stabilization can disappear before a 90-degree lag.

3. Build evidence across the boundary. Ground structural correlation, coupled-model validation, implemented-loop measurements, and fault/recovery analysis answer different questions. None replaces the others.

A short reflection

A feedback-on ring-down gives positive damping at a flight condition. Does that show the aircraft would remain stable if the flutter-suppression function failed?

Answer: No. It identifies the controlled response under the tested conditions. The uncontrolled or degraded plant needs separate evidence. The illustrative model makes the distinction concrete: −2% open-loop damping becomes +4% with ideal feedback, without changing the underlying passive structure.

Primary sources and figure credits

[1] J. Schaefer et al., Flying Beyond Flutter with the X-56A Aircraft, NASA/TM-20220012337, March 2023, printed pp. 1-5 and 10-11. Report-cover date used, rather than catalog acquisition date.

[2] NASA Armstrong, Efficient Air Transportation Systems, “X-56A Controllers” and “Structural Dynamics Ground Testing.” Public project summary; accessed October 18, 2026.

[3] J. A. Grauer and J. M. Waite, Design of a Collocation-Based Active Flutter Suppression Control Law for the IAWTM Wind Tunnel Model, AIAA SciTech 2024, Section IV.C, pp. 8-10. Analysis/design study, not flight evidence.

[4] J. A. Grauer and M. J. Boucher, Real-Time Estimation of Bare-Airframe Frequency Responses from Closed-Loop Data and Multisine Inputs, JGCD 43(2), 2020, pp. 288-298; NASA-hosted manuscript, conclusions.

[5] NASA, X-56A Completes Flight Series, December 11, 2019. Opening photo dated June 11, 2019; NASA/Jim Ross, AFRC2019-0113-08. U.S. government photograph.

Figures 1-2 and the table are original explanatory material. The worked example is not an X-56A reconstruction. Model preference: this run could not verify or select GPT-6 Astra.