

Assignment 3

This assignment focuses on getting comfortable with working with multidimensional data and linear regression. Key items include:

- Creating random n-dimensional data
- Creating a Model that can handle the data
- Plot a subset of the data along with the prediction
- Using a Dataset to read in and choose certain columns to produce a model
- Create several models from various combinations of columns
- Plot a few of the results


```
In [20]: import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

1. Create a 4 dimensional data set with 64 elements and show all 4 scatter 2D plots of the data x_1 vs. y , x_2 vs. y , x_3 vs. y , x_4 vs. y

```
In [51]: n = 64
x = np.linspace(0, 1, n) + np.random.rand(4, n)
x = np.vstack([x, np.ones(len(x.T))]).T
y = np.linspace(0, 1, n) + np.random.rand(n) - 1
```


```
In [52]: plt.scatter(x.T[0], y)
```

```
Out[52]: <matplotlib.collections.PathCollection at 0x24dcca18a0>
```




```
In [53]: plt.scatter(x.T[1], y)
```

```
Out[53]: <matplotlib.collections.PathCollection at 0x24dccf37c40>
```




```
In [54]: plt.scatter(x.T[2], y)
```

```
Out[54]: <matplotlib.collections.PathCollection at 0x24dccfa2ef0>
```



```
In [55]: plt.scatter(x.T[3], y)
```

```
Out[55]: <matplotlib.collections.PathCollection at 0x24dcd16af80>
```



2. Create a Linear Regression model (LIKE WE DID IN CLASS) to fit the data. *Use the example from Lesson 3*

and DO NOT USE a library that calculates automatically. We are expecting 5 coefficients to describe the linear model.

After creating the model (finding the coefficients), calculate a new column $y_p = \sum \beta_n \cdot x_n$

```
In [70]: beta = np.linalg.lstsq(x, y)[0]
         beta
```

C:\Users\jorda\AppData\Local\Temp\ipykernel_48204\4087615102.py:1: FutureWarning: `rcond` parameter will change to the default of machine precision times ``max(M, N)`` where M and N are the input matrix dimensions.

To use the future default and silence this warning we advise to pass `rcond=None`, to keep using the old, explicitly pass `rcond=-1`.

```
beta = np.linalg.lstsq(x, y)[0]
```


```
Out[70]: array([ 0.22729526,  0.18837653,  0.33780781,  0.23293845, -0.94804625])
```

```
In [57]: pred = np.dot(x, beta)
```

3. Plot the model's prediction as a different color on top of the scatter plot from Q1 in 2D for all 4 of the dimensions ($x_1 \rightarrow y_p, x_2 \rightarrow y_p, x_3 \rightarrow y_p, x_4 \rightarrow y_p$)


```
In [58]: plt.scatter(x.T[0], pred, c = 'red')
         plt.scatter(x.T[0], y, c = 'purple')
```

```
Out[58]: <matplotlib.collections.PathCollection at 0x24dcd1f22c0>
```




```
In [59]: plt.scatter(x.T[1], pred, c = 'red')  
plt.scatter(x.T[1], y, c = 'purple')
```

```
Out[59]: <matplotlib.collections.PathCollection at 0x24dcd2825c0>
```




```
In [60]: plt.scatter(x.T[2], pred, c = 'red')  
plt.scatter(x.T[2], y, c = 'purple')
```

Out[60]: <matplotlib.collections.PathCollection at 0x24dcd2c6b90>



```
In [61]: plt.scatter(x.T[3], pred, c = 'red')  
plt.scatter(x.T[3], y, c = 'purple')
```

Out[61]: <matplotlib.collections.PathCollection at 0x24dcd39d5a0>



4. Read in `mlnn/data/Credit.csv` with Pandas and build a Linear Regression model to predict Credit Rating (Rating). Use only the numeric columns in your model, but feel free to experiment which which columns you believe are better predictors of Credit Rating (Column Rating)

```
In [62]: import pandas as pd
import numpy as np
credit = pd.read_csv('Credit.csv')
credit.head()
```

```
Out[62]:
```

	Unnamed: 0	Income	Limit	Rating	Cards	Age	Education	Gender	Student	Married	Ethnicity
0	1	14.891	3606	283	2	34	11	Male	No	Yes	Caucasian
1	2	106.025	6645	483	3	82	15	Female	Yes	Yes	Asian
2	3	104.593	7075	514	4	71	11	Male	No	No	Asian
3	4	148.924	9504	681	3	36	11	Female	No	No	Asian
4	5	55.882	4897	357	2	68	16	Male	No	Yes	Caucasian

Choose multiple columns as inputs beyond `Income` and `Limit` but clearly, don't use `Rating`

```
In [87]: columns = ['Income', 'Limit', 'Cards', 'Age', 'Education', 'Balance']
x2 = credit[columns].values
x2 = np.vstack([x2.T, np.ones(len(x2))]).T
x2
```

```
Out[87]: array([[1.48910e+01, 3.60600e+03, 2.00000e+00, ..., 1.10000e+01,
3.33000e+02, 1.00000e+00],
[1.06025e+02, 6.64500e+03, 3.00000e+00, ..., 1.50000e+01,
9.03000e+02, 1.00000e+00],
[1.04593e+02, 7.07500e+03, 4.00000e+00, ..., 1.10000e+01,
5.80000e+02, 1.00000e+00],
...,
[5.78720e+01, 4.17100e+03, 5.00000e+00, ..., 1.20000e+01,
1.38000e+02, 1.00000e+00],
[3.77280e+01, 2.52500e+03, 1.00000e+00, ..., 1.30000e+01,
0.00000e+00, 1.00000e+00],
[1.87010e+01, 5.52400e+03, 5.00000e+00, ..., 7.00000e+00,
9.66000e+02, 1.00000e+00]])
```

```
In [88]: y2 = credit['Rating']
y2
```

```
Out[88]:
0      283
1      483
2      514
3      681
4      357
...
395    307
396    296
397    321
398    192
399    415
Name: Rating, Length: 400, dtype: int64
```

```
In [89]: beta2 = np.linalg.lstsq(x2, y2)[0]
beta2
```

C:\Users\jorda\AppData\Local\Temp\ipykernel_48204\1242549579.py:1: FutureWarning: `rcond` parameter will change to the default of machine precision times ``max(M, N)`` where M and N are the input matrix dimensions.
To use the future default and silence this warning we advise to pass `rcond=None`, to keep using the old, explicitly pass `rcond=-1`.

```
beta2 = np.linalg.lstsq(x2, y2)[0]
```


```
Out[89]: array([ 9.48157743e-02,  6.42304413e-02,  4.67706085e+00,  8.06617460e-03,
        -2.30863025e-01,  8.18115721e-03,  3.10522106e+01])
```

```
In [90]: pred2 = np.dot(x2, beta2)
```

5. Plot your results using scatter plots (just like in class). Show as many of your columns vs. credit rating that you can.


```
In [92]: plt.scatter(x2.T[0], pred2, c = 'red')
plt.scatter(x2.T[0], y2, c = 'purple')
```

```
Out[92]: <matplotlib.collections.PathCollection at 0x24dce7da6b0>
```


```
In [93]: plt.scatter(x2.T[1], pred2, c = 'red')
plt.scatter(x2.T[1], y2, c = 'purple')
```

```
Out[93]: <matplotlib.collections.PathCollection at 0x24dce77f640>
```




```
In [94]: plt.scatter(x2.T[2], pred2, c = 'red')
plt.scatter(x2.T[2], y2, c = 'purple')
```

Out[94]: <matplotlib.collections.PathCollection at 0x24dce43c370>




```
In [95]: plt.scatter(x2.T[3], pred2, c = 'red')  
plt.scatter(x2.T[3], y2, c = 'purple')
```

Out[95]: <matplotlib.collections.PathCollection at 0x24dcfa03550>



```
In [96]: plt.scatter(x2.T[4], pred2, c = 'red')  
plt.scatter(x2.T[4], y2, c = 'purple')
```

```
Out[96]: <matplotlib.collections.PathCollection at 0x24dccf4c640>
```



```
In [97]: plt.scatter(x2.T[5], pred2, c = 'red')  
plt.scatter(x2.T[5], y2, c = 'purple')
```

```
Out[97]: <matplotlib.collections.PathCollection at 0x24dcd370700>
```

