

Create a dictionary called `grade_thresholds` with letter grades as keys and minimum scores as values:

- "A" maps to 90
- "B" maps to 80
- "C" maps to 70
- "D" maps to 60
- "F" maps to 0

Create an empty list called `scores` to store entered grades

Ask the user to enter their name and store it as `student_name`

Display "Welcome, `student_name`! Enter your scores one at a time."

Loop:

- Ask the user to enter a score or type "done" to finish

- If the user typed "done":

- Break out of the loop

- Try:

- Convert the input to a number and store it as `score`

- If `score` is less than 0 or greater than 100:

- Display "Invalid score. Please enter a number between 0 and 100"

- Otherwise:

- Add `score` to `scores` list

- Display "Score added: `score`"

- Except (if input could not be converted to a number):

- Display "Invalid input. Please enter a numerical score only"

Define a function called `get_letter_grade` that takes `average` as a parameter:

- Check `average` against `grade_thresholds`:

- If `average` is 90 or above, return "A"

- If `average` is 80 or above, return "B"

- If `average` is 70 or above, return "C"

- If `average` is 60 or above, return "D"

- Otherwise return "F"

If `scores` list is empty:

- Display "No scores were entered"

Otherwise:

Calculate the average by dividing the sum of scores by the count of scores

Call `get_letter_grade` with average, store the result as `letter_grade`

Display `student_name`'s final average formatted to two decimals

Display the corresponding `letter_grade`

If `letter_grade` is "D" or "F":

    Display "Status: Failing"

Otherwise:

    Display "Status: Passing"