



US008077963B2

(12) **United States Patent**
Wang et al.

(10) **Patent No.:** **US 8,077,963 B2**
(45) **Date of Patent:** ***Dec. 13, 2011**

(54) **MOBILE ROBOT WITH A HEAD-BASED
MOVEMENT MAPPING SCHEME**

(76) Inventors: **Yulun Wang**, Goleta, CA (US); **Charles S. Jordan**, Santa Barbara, CA (US); **Keith P. Laby**, Santa Barbara, CA (US); **Jonathan Southard**, Santa Barbara, CA (US); **Marco Pinter**, Santa Barbara, CA (US); **Brian Miller**, Santa Barbara, CA (US)

4,709,265 A	11/1987	Silverman et al.
4,733,737 A	3/1988	Falamak
4,751,658 A	6/1988	Kadonoff et al.
4,777,416 A	10/1988	George, II et al.
4,797,557 A	1/1989	Ohman
4,803,625 A	2/1989	Fu et al.
4,847,764 A	7/1989	Halvorson
4,875,172 A	10/1989	Kanayama
4,974,607 A	12/1990	Miwa
4,977,971 A	12/1990	Crane, III et al.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1114 days.

This patent is subject to a terminal disclaimer.

CA

2289697 A1 11/1998

(Continued)

FOREIGN PATENT DOCUMENTS

OTHER PUBLICATIONS

Han et al., "Construction of an Omnidirectional Mobile Robot Platform Based on Active Dual-Wheel Caster Mechanisms and Development of a Control Simulator," 2000, Kluwer Academic Publishers, vol. 29, pp. 257-275.*

(Continued)

(21) Appl. No.: **10/890,891**

(22) Filed: **Jul. 13, 2004**

(65) **Prior Publication Data**

US 2006/0013469 A1 Jan. 19, 2006

(51) **Int. Cl.**
G06K 9/00 (2006.01)

(52) **U.S. Cl.** **382/153**; 901/8; 901/16; 700/245;
318/568.12

(58) **Field of Classification Search** 382/153
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,821,995 A	7/1974	Aghnides
4,413,693 A	11/1983	Derby
4,471,354 A	9/1984	Smith
4,519,466 A	5/1985	Shiraishi
4,638,445 A	1/1987	Mattaboni
4,697,472 A	10/1987	Hiyane

Primary Examiner — John Lee

(74) *Attorney, Agent, or Firm* — InTouch Technologies, Inc.; Paul Evans

(57) **ABSTRACT**

A robotic system that includes a mobile robot and a remote input device. The input device may be a joystick that is used to move a camera and a mobile platform of the robot. The system may operate in a mode where the mobile platform moves in a camera reference coordinate system. The camera reference coordinate system is fixed to a viewing image provided by the camera so that movement of the robot corresponds to a direction viewed on a screen. This prevents disorientation during movement of the robot if the camera is panned across a viewing area.

5 Claims, 8 Drawing Sheets

