

# Growth Resilience

*AJ Perez-Luque ((???)*

*2017 June*

```
library("tidyverse")
library("dplyR")
library("stringr")
library("knitr")
library('gtable')
library('grid')
library('gridExtra')
library('pander')
library('broom')
library('effects')
library('devtools')
# devtools::install_github("ajpelu/auxiliar")
library('car')
library('auxiliar')
library('WRS2')
library('MASS')
library('rcompanion')
```

## Resilience

- Calcularemos las métricas resiliencia de (Lloret et al. 2011) sobre el crecimiento.
- Vamos a calcularlas sobre el BAI de cada árbol.
- Utilizaremos tres sitios: SJ, CAH y CAL (ver ./analysis/analysis\_chronologies.md)

## Prepare data

- Leer datos rw1 de SJ y CA
- Leer datos de diametros de los focal tree

```
## There does not appear to be a header in the rw1 file
## There are 48 series
## 1      SNA0101      1947      2016      0.01
## 2      SNA0102      1947      2016      0.01
## 3      SNA0201      1946      2016      0.01
## 4      SNA0202      1948      2016      0.01
## 5      SNA0301      1949      2016      0.01
## 6      SNA0302      1948      2016      0.01
## 7      SNA0401      1947      2016      0.01
## 8      SNA0402      1947      2016      0.01
## 9      SNA0501      1953      2016      0.01
## 10     SNA0502      1948      2016      0.01
## 11     SNA0601      1948      2016      0.01
## 12     SNA0602      1957      2016      0.01
## 13     SNA0603      1947      2012      0.01
## 14     SNA0701      1954      2016      0.01
```

## 15	SNA0702	1947	2016	0.01
## 16	SNA0801	1949	2016	0.01
## 17	SNA0802	1951	2016	0.01
## 18	SNA0901	1947	2016	0.01
## 19	SNA0902	1947	2016	0.01
## 20	SNA0903	1947	2002	0.01
## 21	SNA1001	1950	2016	0.01
## 22	SNA1002	1953	2016	0.01
## 23	SNA1003	1948	2008	0.01
## 24	SNA1101	1940	2016	0.01
## 25	SNA1102	1929	2016	0.01
## 26	SNA1103	1942	1994	0.01
## 27	SNA1201	1929	2016	0.01
## 28	SNA1202	1929	2016	0.01
## 29	SNA1203	1927	1983	0.01
## 30	SNA1301	1960	2016	0.01
## 31	SNA1302	1949	2016	0.01
## 32	SNA1303	1949	2011	0.01
## 33	SNA1401	1930	2016	0.01
## 34	SNA1402	1949	2016	0.01
## 35	SNA1501	1952	2016	0.01
## 36	SNA1502	1948	2016	0.01
## 37	SNA1601	1959	2016	0.01
## 38	SNA1602	1927	2016	0.01
## 39	SNA1701	1926	2016	0.01
## 40	SNA1702	1930	2016	0.01
## 41	SNA1703	1931	2016	0.01
## 42	SNA1801	1937	2016	0.01
## 43	SNA1802	1936	2016	0.01
## 44	SNA1901	1921	2016	0.01
## 45	SNA1902	1924	2016	0.01
## 46	SNA2001	1932	2016	0.01
## 47	SNA2003	1932	2016	0.01
## 48	SNA2002	1934	2016	0.01

## There does not appear to be a header in the rwl file

## There are 60 series

## 1	SNB0101	1899	2016	0.01
## 2	SNB0102	1902	2016	0.01
## 3	SNB0201	1916	2016	0.01
## 4	SNB0202	1876	2016	0.01
## 5	SNB0301	1862	2016	0.01
## 6	SNB0302	1862	2016	0.01
## 7	SNB0401	1870	2016	0.01
## 8	SNB0402	1866	2016	0.01
## 9	SNB0501	1864	2016	0.01
## 10	SNB0502g	1867	2016	0.01
## 11	SNB0601	1860	2016	0.01
## 12	SNB0602	1873	2016	0.01
## 13	SNB0701	1851	2016	0.01
## 14	SNB0702g	1861	2016	0.01
## 15	SNB0801g	1851	2016	0.01
## 16	SNB0802g	1853	2016	0.01
## 17	SNB0901g	1836	2016	0.01

## 18	SNB0902	1844	2016	0.01
## 19	SNB1001	1868	2016	0.01
## 20	SNB1002	1870	2016	0.01
## 21	SNB1101	1949	2016	0.01
## 22	SNB1102	1893	2016	0.01
## 23	SNB1201	1867	2016	0.01
## 24	SNB1202	1834	2016	0.01
## 25	SNB1301	1865	2016	0.01
## 26	SNB1302	1874	2016	0.01
## 27	SNB1401	1843	2016	0.01
## 28	SNB1402	1848	2016	0.01
## 29	SNB1501	1898	2016	0.01
## 30	SNB1502	1927	2016	0.01
## 31	SNB1601	1846	2016	0.01
## 32	SNB1602	1857	2016	0.01
## 33	SNB1701	1856	2016	0.01
## 34	SNB1702	1853	2016	0.01
## 35	SNB1801	1827	2016	0.01
## 36	SNB1802	1843	2016	0.01
## 37	SNB1901	1888	2016	0.01
## 38	SNB1902	1901	2016	0.01
## 39	SNB2001	1830	2016	0.01
## 40	SNB2002g	1837	2016	0.01
## 41	SNB2101	1863	2016	0.01
## 42	SNB2102	1858	2016	0.01
## 43	SNB2201g	1819	2016	0.01
## 44	SNB2202g	1822	2016	0.01
## 45	SNB2301g	1832	2016	0.01
## 46	SNB2302	1819	2016	0.01
## 47	SNB2401	1829	2016	0.01
## 48	SNB2402	1831	2016	0.01
## 49	SNB2501	1831	2016	0.01
## 50	SNB2502	1839	2016	0.01
## 51	SNB2601	1872	2016	0.01
## 52	SNB2602	1867	2016	0.01
## 53	SNB2701	1865	2016	0.01
## 54	SNB2702g	1863	2016	0.01
## 55	SNB2801	1860	2016	0.01
## 56	SNB2802	1866	2016	0.01
## 57	SNB2901	1877	2016	0.01
## 58	SNB2902	1892	2016	0.01
## 59	SNB3001	1867	2016	0.01
## 60	SNB3002	1874	2016	0.01

```
source(paste0(di, 'script/R/rw_byTree.R'))
source(paste0(di, 'script/R/bai_piovesan.R'))
source(paste0(di, 'script/R/baiResilience.R'))
```

- Crear dataframes rw1 por cada sitio CA\_High, CA\_Low, SJ\_High. SJ\_Low

```
# Replace SNA by SJ and SNB by CA
names(ca) <- stringr::str_replace(names(ca), "SNB", "CA")
names(sj) <- stringr::str_replace(names(sj), "SNA", "SJ")

# Remove g in name of some cores of CA.
```

```
names(ca) <- stringr::str_replace(names(ca), "g", "")
```

```
# Create subset to compare between sites
```

```
caL <- ca[,c("CA0101", "CA0102", "CA0201", "CA0202", "CA0301", "CA0302", "CA0401", "CA0402", "CA0501", "CA0502",  
            "CA0601", "CA0602", "CA0701", "CA0702", "CA0801", "CA0802", "CA0901", "CA0902", "CA1001", "CA1002",  
            "CA2601", "CA2602", "CA2701", "CA2702", "CA2801", "CA2802", "CA2901", "CA2902", "CA3001", "CA3002")  
caH <- ca[, c("CA1101", "CA1102", "CA1201", "CA1202", "CA1301", "CA1302", "CA1401", "CA1402", "CA1501", "CA1502",  
            "CA1601", "CA1602", "CA1701", "CA1702", "CA1801", "CA1802", "CA1901", "CA1902", "CA2001", "CA2002",  
            "CA2101", "CA2102", "CA2201", "CA2202", "CA2301", "CA2302", "CA2401", "CA2402", "CA2501", "CA2502")
```

- Lectura y preparación de datos de diámetro

```
# Prepare Diameter data
```

```
# Compute diameter (mm)
```

```
compete <- compete %>%  
  mutate(dn_mm = (perim_mm / pi))
```

```
# Change name focal according to loc
```

```
compete <- compete %>%  
  mutate(id_focalLoc = stringr::str_replace_all(id_focal, c("A" = "SJ", "B" = "CA")))
```

```
# Get only focal trees, and only selected variables
```

```
ft <- compete %>%  
  filter(sp=='Focal') %>%  
  filter(id_focal!='Fresno') %>%  
  dplyr::select(id_focal, id_focalLoc, loc, dn_mm, height_cm)
```

```
# Set levels of elevation
```

```
ca_lowcode <- c(paste0('CA', str_pad(1:10, 2, pad='0')),  
               paste0('CA', 26:30))  
ca_highcode <- paste0('CA', 11:25)
```

```
ft <- ft %>%  
  mutate(site = as.factor(  
    ifelse(id_focalLoc %in% ca_lowcode, 'CAL',  
          ifelse(id_focalLoc %in% ca_highcode, 'CAH', 'SJ'))))
```

## Aggregate RW by tree

- Agregar valores medios de RW por site (obtenemos sj\_tree / caL\_tree, caH\_tree)
- ver fun rw\_byTree o utilizar treeMean (dplR)

```
# Remember snc = structure of core name SJ0101 (site | tree | core)
```

```
sj_tree <- rw_byTree(sj, snc=c(2,2,2), locname = 'SJ')  
caL_tree <- rw_byTree(caL, snc=c(2,2,2), locname = 'CA')  
caH_tree <- rw_byTree(caH, snc=c(2,2,2), locname = 'CA')
```

- Crear diferentes dataset de diametro por sitio

```
diam <- ft %>%  
  mutate(diameter = dn_mm,  
         id = id_focalLoc) %>%
```

```
dplyr::select(id, diameter, site) %>%
  split(.$site)

d_caH <- diam$CAH[,c('id','diameter')]
d_caL <- diam$CAL[,c('id','diameter')]
d_sj <- diam$SJ[,c('id','diameter')]
```

## Cómputo del BAI por site

- He construido una funcion para el computo del BAI, teniendo en cuenta la aproximación de (Piovesa et al. 2008). Es similar a `bai.out`

```
bai_sj <- bai_piovesan(rwdf = sj_tree, diam_df = d_sj)
bai_caH <- bai_piovesan(rwdf = caH_tree, diam_df = d_caH)
bai_caL <- bai_piovesan(rwdf = caL_tree, diam_df = d_caL)

# Set class to bai object
# Esto es para que funcionen algunas otras funciones de dplR
bais <- c('bai_sj', 'bai_caH', 'bai_caL')

for (i in bais){
  aux <- get(i)

  class(aux) <- c('rwl', 'data.frame')

  assign(i, aux)
}
```

## Resilience

- Computar métricas de resiliencia BAI para los tres sitios.
- Computar tres eventos climáticos: 1995, 2005, 2012
- Computar dos ventanas temporales: 2 y 3

```
# Drought years
dyears <- c(1995, 2005, 2012)

# SJ
res_4_sj <- baiResilience(bai_sj, event_years = dyears, window = 4)
res_3_sj <- baiResilience(bai_sj, event_years = dyears, window = 3)
res_2_sj <- baiResilience(bai_sj, event_years = dyears, window = 2)

# caL
res_4_caL <- baiResilience(bai_caL, event_years = dyears, window = 4)
res_3_caL <- baiResilience(bai_caL, event_years = dyears, window = 3)
res_2_caL <- baiResilience(bai_caL, event_years = dyears, window = 2)

# caH
res_4_caH <- baiResilience(bai_caH, event_years = dyears, window = 4)
res_3_caH <- baiResilience(bai_caH, event_years = dyears, window = 3)
res_2_caH <- baiResilience(bai_caH, event_years = dyears, window = 2)
```

## Computar correlaciones ventanas temporales

```
# Vector with objects name
obj <- c('res_2_sj', 'res_3_sj', 'res_4_sj',
        'res_2_caL', 'res_3_caL', 'res_4_caL',
        'res_2_caH', 'res_3_caH', 'res_4_caH')

correla_ws <- c()

for (i in obj){
  x <- get(i)
  xres <- x$resilience
  out <- xres %>%
    mutate(ws = paste0('ws_', as.character(str_extract(i, "[0-9]"))),
           site = str_replace(i, "res_[0-9]_", '')) %>%
    dplyr::select(-disturb_year, -tree)

  correla_ws <- bind_rows(correla_ws, out)
}

# Split by window size
correla <- correla_ws %>% split(.$ws)

# Change names
names(correla[["ws_2"]])[1:4] <- paste0(names(correla[["ws_2"]])[1:4], '2')
names(correla[["ws_3"]])[1:4] <- paste0(names(correla[["ws_3"]])[1:4], '3')
names(correla[["ws_4"]])[1:4] <- paste0(names(correla[["ws_4"]])[1:4], '4')

cor2 <- correla[["ws_2"]] %>% dplyr::select(-ws) %>% mutate(ind = row_number())
cor3 <- correla[["ws_3"]] %>% dplyr::select(-ws) %>% mutate(ind = row_number())
cor4 <- correla[["ws_4"]] %>% dplyr::select(-ws) %>% mutate(ind = row_number())

correlations <- inner_join(cor2, cor3, by='ind') %>% inner_join(cor4, by='ind')

# Resistance
aux_coefs <- c()

model <- lm(rt2~rt3, data=correlations)
p_rt23 <- correlations %>% ggplot(aes(rt2, rt3)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rt (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = c(.2, .75))
aux <- as.data.frame(cbind('rt', '2-3', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rt2~rt4, data=correlations)
p_rt24 <- correlations %>% ggplot(aes(rt2, rt4)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rt (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = 'none')
```


```

aux <- as.data.frame(cbind('rt','2-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rt3~rt4, data=correlations)
p_rt34 <- correlations %>% ggplot(aes(rt3, rt4)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rt (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = 'none')
aux <- as.data.frame(cbind('rt','3-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

grid.arrange(p_rt23, p_rt24, p_rt34,ncol=3)

```



```

# Recovery
model <- lm(rc2~rc3, data=correlations)
p_rc23 <- correlations %>% ggplot(aes(rc2, rc3)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rc (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = c(.2, .75))
aux <- as.data.frame(cbind('rc','2-3', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rc2~rc4, data=correlations)
p_rc24 <- correlations %>% ggplot(aes(rc2, rc4)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rc (R2) = ', round(summary(model)$r.squared, 3))) +

```


```

  theme(legend.position = 'none')
aux <- as.data.frame(cbind('rc', '2-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rc3~rc4, data=correlations)
p_rc34 <- correlations %>% ggplot(aes(rc3, rc4)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rc (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = 'none')
aux <- as.data.frame(cbind('rc', '3-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

grid.arrange(p_rc23, p_rc24, p_rc34, ncol=3)

```



```

# Resilience
model <- lm(rs2~rs3, data=correlations)
p_rs23 <- correlations %>% ggplot(aes(rs2, rs3)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rs (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = c(.2, .75))
aux <- as.data.frame(cbind('rs', '2-3', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rs2~rs4, data=correlations)
p_rs24 <- correlations %>% ggplot(aes(rs2, rs4)) +

```




```

  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rs (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = 'none')
aux <- as.data.frame(cbind('rs', '2-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rs3~rs4, data=correlations)
p_rs34 <- correlations %>% ggplot(aes(rs3, rs4)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rs (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = 'none')
aux <- as.data.frame(cbind('rs', '3-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

grid.arrange(p_rs23, p_rs24, p_rs34, ncol=3)

```



```

# Relative Resilience
model <- lm(rrs2~rrs3, data=correlations)
p_rrs23 <- correlations %>% ggplot(aes(rrs2, rrs3)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rrs (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = c(.2, .75))
aux <- as.data.frame(cbind('rrs', '2-3', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rrs2~rrs4, data=correlations)
p_rrs24 <- correlations %>% ggplot(aes(rrs2, rrs4)) +

```


```

    geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
    ggtitle(paste('rrs (R2) = ', round(summary(model)$r.squared, 3))) +
    theme(legend.position = 'none')
aux <- as.data.frame(cbind('rrs', '2-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

model <- lm(rrs3~rrs4, data=correlations)
p_rrs34 <- correlations %>% ggplot(aes(rrs3, rrs4)) +
  geom_point(aes(colour=site.x)) + theme_bw() + geom_smooth(method = 'lm', se=FALSE) +
  ggtitle(paste('rrs (R2) = ', round(summary(model)$r.squared, 3))) +
  theme(legend.position = 'none')
aux <- as.data.frame(cbind('rrs', '3-4', as.numeric(summary(model)$r.squared)))
aux_coefs <- rbind(aux_coefs, aux)

grid.arrange(p_rrs23, p_rrs24, p_rrs34, ncol=3)

```



```

names(aux_coefs) <- c('var', 'window_size', 'r2')

write.csv(aux_coefs, file=paste0(di, '/out/correla_resilience/correla_window_size.csv'), row.names = F)

aux_coefs %>% pandar()

```

var	window_size	r2
rt	2-3	0.916882284149449
rt	2-4	0.804404303544226
rt	3-4	0.954056995082479
rc	2-3	0.940435462578806

var	window_size	r2
rc	2-4	0.875357103621433
rc	3-4	0.977309191655523
rs	2-3	0.887274876125786
rs	2-4	0.764147394080222
rs	3-4	0.955085073886915
rrs	2-3	0.914381250472491
rrs	2-4	0.848277808345292
rrs	3-4	0.978980936308473

Nos quedamos con 3 años de ventana temporal.

## Plots Crecimiento


### Boxplot with outliers

```
gsj <- res_3_sj$growth %>% mutate(site='SJ')
gcaL <- res_3_caL$growth %>% mutate(site='caL')
gcaH <- res_3_caH$growth %>% mutate(site='caH')

g <- bind_rows(gsj, gcaL, gcaH)


# Export csv
write.csv(g, file=paste0(di, 'data/resilience/crecimientos_drought.csv'), row.names = FALSE)

g %>% mutate(disturb = dplyr::recode(disturb,
                                     dr = '1_dr', pre = '0_pre', post = '2_post')) %>%
  ggplot(aes(y=mean_period/100, x=disturb)) +
  geom_boxplot() +
  facet_grid(site~disturb_year, scales='free_y') +
  theme_bw()
```




Mean + se

```
g %>%
  mutate(disturb = dplyr::recode(disturb, dr = '1_dr', pre = '0_pre', post = '2_post')) %>%
  group_by(disturb, disturb_year, site) %>%
  summarise(mean = mean(mean_period),
            sd = sd(mean_period),
            se = sd/sqrt(length(mean_period))) %>%
  ggplot(aes(y=mean/100, x=disturb)) +
  geom_errorbar(aes(ymin=mean/100 - se/100,
                    ymax=mean/100 + se/100,
                    width = 0.2)) +
  geom_point(size=2, shape=21, fill='white') +
  facet_grid(site~disturb_year, scales='free_y') +
  theme_bw() + ylab('BAI (cm2/year)') +
  theme(panel.grid = element_blank())
```



```
pgrowth <- g %>%
  mutate(disturb = dplyr::recode(disturb, dr = '1_dr', pre = '0_pre', post = '2_post')) %>%
  group_by(disturb, disturb_year, site) %>%
  summarise(mean = mean(mean_period),
            sd = sd(mean_period),
            se = sd/sqrt(length(mean_period))) %>%
  ggplot(aes(y=mean/100, x=disturb, colour=site)) +
  geom_errorbar(aes(ymin=mean/100 - se/100,
                    ymax=mean/100 + se/100),
               width = 0.15) +
  geom_point(size=3, aes(shape=site), fill='white') +
  geom_line(aes(group=site))+
  facet_wrap(~disturb_year, scales='free_y') +
  theme_bw() + ylab('BAI (cm2/year)') +
  theme(panel.grid = element_blank())

pgrowth
```



```
ggsave(plot=pgrowht, width=8, height = 4,
        filename=paste0(di, 'out/fig/resilience/bai_events.pdf'))
```

```
g %>%
  mutate(disturb = dplyr::recode(disturb, dr = '1_dr', pre = '0_pre', post = '2_post')) %>%
  dplyr::group_by(site, disturb_year, disturb) %>%
  dplyr::summarise(mean = mean(mean_period/100),
                  sd = sd(mean_period/100),
                  se = sd/sqrt(length(mean_period/100))) %>% as.data.frame() %>% pander()
```

site	disturb_year	disturb	mean	sd	se
SJ	1995	0_pre	4.949	2.402	0.5371
SJ	1995	1_dr	3.102	1.395	0.3119
SJ	1995	2_post	11.04	6.508	1.455
SJ	2005	0_pre	15.04	5.522	1.235
SJ	2005	1_dr	6.437	2.358	0.5273
SJ	2005	2_post	6.967	2.41	0.5388
SJ	2012	0_pre	13.67	6.458	1.444
SJ	2012	1_dr	9.729	3.218	0.7196
SJ	2012	2_post	13.8	4.651	1.04
caH	1995	0_pre	20.08	24.07	6.215
caH	1995	1_dr	9.923	9.846	2.542
caH	1995	2_post	23.74	27.14	7.008
caH	2005	0_pre	27.22	25.58	6.605
caH	2005	1_dr	23.29	21.06	5.437
caH	2005	2_post	20.96	21.79	5.627
caH	2012	0_pre	31.76	32.29	8.336

site	disturb_year	disturb	mean	sd	se
caH	2012	1_dr	24.02	25.33	6.541
caH	2012	2_post	24.55	25.22	6.511
caL	1995	0_pre	9.855	5.081	1.312
caL	1995	1_dr	5.577	2.23	0.5757
caL	1995	2_post	10.07	5.501	1.42
caL	2005	0_pre	13.7	6.73	1.738
caL	2005	1_dr	12.19	6.549	1.691
caL	2005	2_post	9.832	4.308	1.112
caL	2012	0_pre	15.51	7.572	1.955
caL	2012	1_dr	14.45	7.411	1.914
caL	2012	2_post	13.72	7.05	1.82

## Anovas Resiliencia

```
# Prepara data
rsj <- res_3_sj$resilience %>% mutate(site='SJ')
rcaL<- res_3_caL$resilience %>% mutate(site='caL')
rcaH <- res_3_caH$resilience %>% mutate(site='caH')

re <- bind_rows(rsj, rcaL, rcaH)
re$disturb_year <- as.factor(re$disturb_year)
re$site <- as.factor(re$site)

# Export csv
write.csv(re, file=paste0(di, 'data/resilience/resilience_bai.csv'), row.names = FALSE)
```

## Asumptions

- Explorar si se cumplen los supuestos de normalidad y homocedasticidad. Tenemos que comprobar que cada uno de los grupos son normales (1995,2005,2012; site: SJ, CaH, CaL; e interactions)

```
shapirosNormal <- function(df, resp_var, factor_vars) {
  rv <- enquo(resp_var)
  out <- df %>%
    group_by_(.dots=factor_vars) %>%
    summarise(statistic = round(shapiro.test(!rv)$statistic,5),
              p_value = round(shapiro.test(!rv)$p.value,5)) %>%
    data.frame()

  return(out)
}

homogetest <- function(resp_var, factores, df){

  out_factores <- c()

  for (f in factores){
    hv <- c()
    myformula <- as.formula(paste0(resp_var, "~", f))
```

```

#tests
fk <- fligner.test(myformula, data = df)
lv <- leveneTest(myformula, data = df)
# out
hv$fk_stat <- fk$statistic
hv$fk_pvalue <- fk$p.value
hv$lev_stat <- lv$`F value`[1]
hv$lev_pvalue <- lv$`Pr(>F)`[1]
hv$factor <- f
hv <- as.data.frame(hv)
row.names(hv) <- NULL

  out_factores <- rbind(out_factores, hv)}
return(out_factores)
}

```

## Normalidad

```

# See auxiliar::shapirosNormal
### Resilience

nrsA <- shapirosNormal(re, resp_var = rs, 'disturb_year')
nrsA$var <- 'rs'
nrsB <- shapirosNormal(re, resp_var = rs, 'site')
nrsB$var <- 'rs'
nrsAB <- shapirosNormal(re, resp_var = rs, c('disturb_year','site'))
nrsAB$var <- 'rs'

### Recovery

nrcA <- shapirosNormal(re, resp_var = rc, 'disturb_year')
nrcA$var <- 'rc'
nrcB <- shapirosNormal(re, resp_var = rc, 'site')
nrcB$var <- 'rc'
nrcAB <- shapirosNormal(re, resp_var = rc, c('disturb_year','site'))
nrcAB$var <- 'rc'

### Resistance

nrtA <- shapirosNormal(re, resp_var = rt, 'disturb_year')
nrtA$var <- 'rt'
nrtB <- shapirosNormal(re, resp_var = rt, 'site')
nrtB$var <- 'rt'
nrtAB <- shapirosNormal(re, resp_var = rt, c('disturb_year','site'))
nrtAB$var <- 'rt'

### Relative Resilience

nrrsA <- shapirosNormal(re, resp_var = rrs, 'disturb_year')
nrrsA$var <- 'rrs'
nrrsB <- shapirosNormal(re, resp_var = rrs, 'site')
nrrsB$var <- 'rrs'
nrrsAB <- shapirosNormal(re, resp_var = rrs, c('disturb_year','site'))

```



```
nrrsAB$var <- 'rrs'
```

```
normtestAB <- rbind(nrcAB, nrtAB, nrsAB, nrrsAB)
normtestAB %>% pander()
```

disturb_year	site	statistic	p_value	var
1995	SJ	0.7989	0.00083	rc
1995	caH	0.9388	0.3676	rc
1995	caL	0.8746	0.03943	rc
2005	SJ	0.9849	0.9806	rc
2005	caH	0.958	0.658	rc
2005	caL	0.928	0.2543	rc
2012	SJ	0.945	0.2979	rc
2012	caH	0.8691	0.03275	rc
2012	caL	0.9628	0.7418	rc
1995	SJ	0.9583	0.5109	rt
1995	caH	0.919	0.1861	rt
1995	caL	0.9581	0.6587	rt
2005	SJ	0.9286	0.1453	rt
2005	caH	0.9733	0.9033	rt
2005	caL	0.9632	0.7472	rt
2012	SJ	0.9597	0.5371	rt
2012	caH	0.9797	0.9676	rt
2012	caL	0.8614	0.02526	rt
1995	SJ	0.8921	0.02936	rs
1995	caH	0.8123	0.00531	rs
1995	caL	0.9826	0.9844	rs
2005	SJ	0.9191	0.09531	rs
2005	caH	0.9316	0.2887	rs
2005	caL	0.9163	0.1689	rs
2012	SJ	0.8959	0.0345	rs
2012	caH	0.9512	0.5435	rs
2012	caL	0.9275	0.2502	rs
1995	SJ	0.8511	0.00556	rrs
1995	caH	0.8753	0.04041	rrs
1995	caL	0.9468	0.4759	rrs
2005	SJ	0.9638	0.6222	rrs
2005	caH	0.9517	0.551	rrs
2005	caL	0.9489	0.5077	rrs
2012	SJ	0.9657	0.6639	rrs
2012	caH	0.7872	0.00253	rrs
2012	caL	0.9734	0.9052	rrs

```
write.csv(normtestAB,
          file=paste0(di, '/out/anovas_resilience/normo_disturb_year_site.csv'), row.names = F)
```

```
rm(nrcA, nrcB, nrcAB,
   nrsA, nrsB, nrsAB,
   nrrsA, nrrsB, nrrsAB,
   nrtA, nrtB, nrtAB)
```

- No se cumplen los requisitos de normalidad

## Heterocedasticidad

```
## See auxiliar::homogetest
factores <- c('disturb_year', 'site', 'interaction(disturb_year, site)')
responses <- c('rs', 'rc', 'rt', 'rrs')
homo <- c()

for (i in responses){
  ht <- homogetest(resp_var = i, factores = factores, df = re)
  ht <- ht %>% mutate(response = i)
  homo <- rbind(homo, ht)
}

homo %>% pander()
```

fk_stat	fk_pvalue	lev_stat	lev_pvalue	factor	response
35.03	2.472e-08	16.5	3.436e-07	disturb_year	rs
44.13	2.613e-10	19.31	3.573e-08	site	rs
41.88	1.425e-06	9.072	5.231e-10	interaction(disturb_year, site)	rs
35.96	1.557e-08	14.78	1.414e-06	disturb_year	rc
12.41	0.002015	5.564	0.004685	site	rc
62.94	1.232e-10	8.321	3.315e-09	interaction(disturb_year, site)	rc
25.59	2.778e-06	15.59	7.267e-07	disturb_year	rt
0.6251	0.7316	0.3586	0.6993	site	rt
14.53	0.06902	1.782	0.08539	interaction(disturb_year, site)	rt
40.59	1.537e-09	17.16	2.003e-07	disturb_year	rrs
13.99	0.0009147	7.446	0.0008313	site	rrs
54.08	6.67e-09	9.558	1.618e-10	interaction(disturb_year, site)	rrs

```
write.csv(homo,
  file=paste0(di, '/out/anovas_resilience/homocedasticidad.csv'), row.names = F)
```

- Tampoco se cumplen los requisitos de homogeneidad de varianzas entre grupos
- Probamos a transformar los datos con log y reanalizar los supuestos de homocedasticidad

```
factores <- c('disturb_year', 'site', 'interaction(disturb_year, site)')
responses <- c('logrs', 'logrc', 'logrt', 'logrrs')
homo_log <- c()

re <- re %>%
  mutate(
    logrs = log(rs),
    logrc = log(rc),
    logrt = log(rc),
    logrrs = log(rrs)
  )
```

```
for (i in responses){
  ht <- homogetest(resp_var = i, factores = factores, df = re)
  ht <- ht %>% mutate(response = i)
  homo_log <- rbind(homo_log, ht)
}

homo_log %>% pander()
```

fk_stat	fk_pvalue	lev_stat	lev_pvalue	factor	response
18.09	0.000118	9.431	0.0001401	disturb_year	logrs
41.3	1.077e-09	30.45	8.633e-12	site	logrs
22.44	0.004155	3.336	0.001586	interaction(disturb_year, site)	logrs
8.671	0.01309	6.408	0.002147	disturb_year	logrc
5.079	0.0789	2.769	0.06602	site	logrc
25.48	0.001286	4.143	0.0001806	interaction(disturb_year, site)	logrc
8.671	0.01309	6.408	0.002147	disturb_year	logrt
5.079	0.0789	2.769	0.06602	site	logrt
25.48	0.001286	4.143	0.0001806	interaction(disturb_year, site)	logrt
2.434	0.2961	1.511	0.2256	disturb_year	logrrs
2.644	0.2666	0.9344	0.3961	site	logrrs
5.803	0.6692	0.694	0.696	interaction(disturb_year, site)	logrrs

```
write.csv(homo_log,
          file=paste0(di, '/out/anovas_resilience/homocedasticidad_log.csv'), row.names = F)
```

- Tampoco se cumplen

## Custom functions

```
# Custom Function to compute ANOVAS
aovas <- function(df, vars, resp_var){
  require('dplyr')
  require('broom')

  # Create subset
  dfsel <- df %>% dplyr::select_(.dots=c(vars, resp_var))

  # Model
  myformula <- as.formula(paste0(resp_var, " ~ ",
                                paste(vars, collapse = '*')))

  mymodel <- aov(myformula, data=dfsel)

  # Output model Summary http://my.ilstu.edu/~wjschne/444/ANOVA.html#\(1\)
  model_coeff <- broom::tidy(mymodel)
  model_summary <- broom::glance(mymodel)
```

```

out <- c()
out$model_coeff <- model_coeff
out$model_summary <- model_summary
out$mymodel <- mymodel

return(out)
}

# Post-Hoc comparison
phc <- function(mymodel, resp_var){
  require(lsmeans)

  # Disturb Event
  ph_event <- lsmeans(mymodel, pairwise ~ disturb_year, adjust = "bon")

  # differences letters
  cld_event <- cld(ph_event, alpha = 0.01,
                  Letters = letters,
                  adjust = "bon")

  # Site
  ph_site <- lsmeans(mymodel, pairwise ~ site, adjust = "bon")
  cld_site <- cld(ph_site, alpha = 0.01,
                 Letters = letters,
                 adjust = "bon")

  # interaction
  ph_i <- lsmeans(mymodel, pairwise ~ disturb_year:site, adjust = "bon")
  cld_i <- cld(ph_i, alpha = 0.01,
              Letters = letters,
              adjust = "bon")

  # Objects for plot
  aux_ph_site <- as.data.frame(summary(ph_site$lsmeans))
  aux_ph_site <- aux_ph_site %>% mutate(var = resp_var)
  aux_ph_event <- as.data.frame(summary(ph_event$lsmeans))
  aux_ph_event <- aux_ph_event %>% mutate(var = resp_var)
  aux_ph_i <- as.data.frame(summary(ph_i$lsmeans))
  aux_ph_i <- aux_ph_i %>% mutate(var = resp_var)

  # Return objects
  cat('\n### Event ###\n')
  print(ph_event)
  print(cld_event)
  cat('\n### Clu pop ###\n')
  print(ph_site)
  print(cld_site)
  cat('\n### Event:Clu pop ###\n')
  print(ph_i)
  return(list(aux_ph_site, aux_ph_event, aux_ph_i, cld_site, cld_event, cld_i))
}

```

## OJO SOLO 2005 y 2012

```
# Only 2005 and 2012
re <- re %>% filter(disturb_year != 1995) %>% as.data.frame()
vars <- c('disturb_year','site')
re$disturb_year <- factor(re$disturb_year)
```

## Recovery

```
# Variable
resp_var <- 'rc'

# AOV
aov_rc <- aovas(re, vars=vars, resp_var = resp_var)

mc <- aov_rc$model_coeff

pander(mc, round=5,
  caption = paste0("ANOVA table: ", resp_var), missing = '',
  emphasize.strong.cells =
    which(mc < 0.1 & mc == mc$p.value, arr.ind = T))
```

Table 6: ANOVA table: rc

term	df	sumsq	meansq	statistic	p.value
disturb_year	1	1.316	1.316	32.78	<b>0</b>
site	2	2.847	1.424	35.45	<b>0</b>
disturb_year:site	2	0.1961	0.09805	2.442	<b>0.09253</b>
Residuals	94	3.775	0.04016		

```
gm <- aov_rc$model_summary

gm <- apply(gm, 1, formatC, digits = 2, format = "f") %>% t()
colnames(gm) <- paste0("$",c("R^2","\\mathrm{adj}R^2","\\sigma_e","F","p","df_m","\\mathrm{logLik}","AIC",
rownames(gm) <- "Statistic"
pander(t(gm))
```

	Statistic
$R^2$	0.54
$\text{adj}R^2$	0.51
$\sigma_e$	0.20
$F$	21.71
$p$	0.00
$df_m$	6.00
logLik	21.95
$AIC$	-29.89
$BIC$	-11.66
dev	3.77
$df_e$	94.00

```

# Post hoc Define model
mymodel <- aov_rc$mymodel
postH_rc <- phc(mymodel = mymodel, resp_var = resp_var)

##
## ### Event ###
## $lsmeans
##   disturb_year    lsmean      SE df  lower.CL upper.CL
##   2005           0.9460722 0.02860151 94 0.8892832 1.002861
##   2012           1.1643064 0.02860151 94 1.1075175 1.221095
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005 - 2012 -0.2182343 0.04044865 94  -5.395  <.0001
##
## Results are averaged over the levels of: site
##
##   disturb_year    lsmean      SE df  lower.CL upper.CL .group
##   2005           0.9460722 0.02860151 94 0.8809216 1.011223  a
##   2012           1.1643064 0.02860151 94 1.0991558 1.229457  b
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## significance level used: alpha = 0.01
##
## ### Clu pop ###
## $lsmeans
##   site    lsmean      SE df  lower.CL  upper.CL
##   SJ    1.2803536 0.03168543 94 1.2174414 1.3432657
##   caH    0.9853013 0.03658718 94 0.9126566 1.0579460
##   caL    0.8999131 0.03658718 94 0.8272684 0.9725578
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   SJ - caH  0.29505228 0.04840029 94   6.096  <.0001
##   SJ - caL  0.38044051 0.04840029 94   7.860  <.0001
##   caH - caL 0.08538823 0.05174209 94   1.650  0.3067
##
## Results are averaged over the levels of: disturb_year
## P value adjustment: bonferroni method for 3 tests
##
##   site    lsmean      SE df  lower.CL  upper.CL .group
##   caL    0.8999131 0.03658718 94 0.8107290 0.9890971  a
##   caH    0.9853013 0.03658718 94 0.8961172 1.0744854  a
##   SJ     1.2803536 0.03168543 94 1.2031179 1.3575893  b
##
## Results are averaged over the levels of: disturb_year


```

```

## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 3 estimates
## P value adjustment: bonferroni method for 3 tests
## significance level used: alpha = 0.01
##
## ### Event:Clu pop ###
## $lsmeans
##   disturb_year site    lsmean      SE df  lower.CL  upper.CL
##   2005          SJ  1.1150292 0.04480996 94  1.0260579  1.2040004
##   2012          SJ  1.4456780 0.04480996 94  1.3567068  1.5346492
##   2005          caH  0.8836738 0.05174209 94  0.7809387  0.9864089
##   2012          caH  1.0869288 0.05174209 94  0.9841937  1.1896639
##   2005          caL  0.8395136 0.05174209 94  0.7367785  0.9422487
##   2012          caL  0.9603126 0.05174209 94  0.8575774  1.0630477
##
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005,SJ - 2012,SJ  -0.33064881 0.06337085 94  -5.218  <.0001
##   2005,SJ - 2005,caH  0.23135538 0.06844835 94   3.380  0.0159
##   2005,SJ - 2012,caH  0.02810037 0.06844835 94   0.411  1.0000
##   2005,SJ - 2005,caL  0.27551559 0.06844835 94   4.025  0.0017
##   2005,SJ - 2012,caL  0.15471662 0.06844835 94   2.260  0.3916
##   2012,SJ - 2005,caH  0.56200419 0.06844835 94   8.211  <.0001
##   2012,SJ - 2012,caH  0.35874918 0.06844835 94   5.241  <.0001
##   2012,SJ - 2005,caL  0.60616440 0.06844835 94   8.856  <.0001
##   2012,SJ - 2012,caL  0.48536543 0.06844835 94   7.091  <.0001
##   2005,caH - 2012,caH -0.20325501 0.07317436 94  -2.778  0.0991
##   2005,caH - 2005,caL  0.04416021 0.07317436 94   0.603  1.0000
##   2005,caH - 2012,caL -0.07663876 0.07317436 94  -1.047  1.0000
##   2012,caH - 2005,caL  0.24741522 0.07317436 94   3.381  0.0158
##   2012,caH - 2012,caL  0.12661625 0.07317436 94   1.730  1.0000
##   2005,caL - 2012,caL -0.12079897 0.07317436 94  -1.651  1.0000
##
## P value adjustment: bonferroni method for 15 tests
ps


```

**site effect plot**



pd


**disturb\_year effect plot**



picollapse




**disturb\_year\*site effect plot**



pi

**disturb\_year\*site effect plot**



Resistance

Table 8: ANOVA table: rt

term	df	sumsq	meansq	statistic	p.value
disturb_year	1	0.2122	0.2122	9.867	<b>0.00225</b>
site	2	1.666	0.833	38.74	<b>0</b>
disturb_year:site	2	0.8604	0.4302	20.01	<b>0</b>
Residuals	94	2.021	0.0215		

	Statistic
$R^2$	0.58
$\text{adj}R^2$	0.55
$\sigma_e$	0.15
$F$	25.47
$p$	0.00
$df_m$	6.00
logLik	53.18
$AIC$	-92.35
$BIC$	-74.11
dev	2.02
$df_e$	94.00

```

# Post hoc Define model
mymodel <- aov_rt$mymodel
postH_rt <- phc(mymodel = mymodel, resp_var = resp_var)

##
## ### Event ###
## $lsmeans
##   disturb_year    lsmean      SE df  lower.CL  upper.CL
##   2005           0.7483129 0.02092964 94 0.7067567 0.7898692
##   2012           0.8166033 0.02092964 94 0.7750470 0.8581596
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005 - 2012 -0.06829036 0.02959898 94  -2.307  0.0232
##
## Results are averaged over the levels of: site
##
##   disturb_year    lsmean      SE df  lower.CL  upper.CL .group
##   2005           0.7483129 0.02092964 94 0.7006379 0.7959880  a
##   2012           0.8166033 0.02092964 94 0.7689282 0.8642784  a
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## significance level used: alpha = 0.01
##
## ### Clu pop ###

```

```

## $lsmeans
##   site    lsmean      SE df  lower.CL  upper.CL
##   SJ    0.6139485 0.02318635 94 0.5679114 0.6599855
##   caH    0.8196809 0.02677329 94 0.7665219 0.8728399
##   caL    0.9137450 0.02677329 94 0.8605860 0.9669040
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   SJ - caH   -0.20573248 0.03541773 94  -5.809  <.0001
##   SJ - caL   -0.29979653 0.03541773 94  -8.465  <.0001
##   caH - caL  -0.09406405 0.03786314 94  -2.484   0.0442
##
## Results are averaged over the levels of: disturb_year
## P value adjustment: bonferroni method for 3 tests
##
##   site    lsmean      SE df  lower.CL  upper.CL .group
##   SJ    0.6139485 0.02318635 94 0.5574299 0.6704670   a
##   caH    0.8196809 0.02677329 94 0.7544190 0.8849429   b
##   caL    0.9137450 0.02677329 94 0.8484830 0.9790069   b
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 3 estimates
## P value adjustment: bonferroni method for 3 tests
## significance level used: alpha = 0.01
##
## ### Event:Clu pop ###
## $lsmeans
##   disturb_year site    lsmean      SE df  lower.CL  upper.CL
##   2005          SJ    0.4606116 0.03279045 94 0.3955054 0.5257178
##   2012          SJ    0.7672853 0.03279045 94 0.7021791 0.8323915
##   2005          caH    0.8845609 0.03786314 94 0.8093827 0.9597391
##   2012          caH    0.7548010 0.03786314 94 0.6796228 0.8299791
##   2005          caL    0.8997663 0.03786314 94 0.8245881 0.9749444
##   2012          caL    0.9277237 0.03786314 94 0.8525455 1.0029018
##
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005,SJ - 2012,SJ  -0.30667361 0.04637269 94  -6.613  <.0001
##   2005,SJ - 2005,caH -0.42394925 0.05008823 94  -8.464  <.0001
##   2005,SJ - 2012,caH -0.29418931 0.05008823 94  -5.873  <.0001
##   2005,SJ - 2005,caL -0.43915464 0.05008823 94  -8.768  <.0001
##   2005,SJ - 2012,caL -0.46711203 0.05008823 94  -9.326  <.0001
##   2012,SJ - 2005,caH -0.11727564 0.05008823 94  -2.341   0.3199
##   2012,SJ - 2012,caH  0.01248430 0.05008823 94   0.249   1.0000
##   2012,SJ - 2005,caL -0.13248102 0.05008823 94  -2.645   0.1436
##   2012,SJ - 2012,caL -0.16043842 0.05008823 94  -3.203   0.0278
##   2005,caH - 2012,caH  0.12975994 0.05354657 94   2.423   0.2594
##   2005,caH - 2005,caL -0.01520539 0.05354657 94  -0.284   1.0000


```

```
## 2005,caH - 2012,caL -0.04316278 0.05354657 94 -0.806 1.0000
## 2012,caH - 2005,caL -0.14496533 0.05354657 94 -2.707 0.1209
## 2012,caH - 2012,caL -0.17292272 0.05354657 94 -3.229 0.0256
## 2005,caL - 2012,caL -0.02795739 0.05354657 94 -0.522 1.0000
```

```
##
## P value adjustment: bonferroni method for 15 tests
```


ps

**site effect plot**




pd

**disturb\_year effect plot**




picollapse

**disturb\_year\*site effect plot**



pi



Relative Resilience

Table 10: ANOVA table: rrs

term	df	sumsq	meansq	statistic	p.value
disturb_year	1	0.93	0.93	47.8	<b>0</b>
site	2	1.39	0.6952	35.73	<b>0</b>
disturb_year:site	2	0.145	0.07252	3.727	<b>0.02769</b>
Residuals	94	1.829	0.01946		

	Statistic
$R^2$	0.57
$\text{adj}R^2$	0.55
$\sigma_e$	0.14
$F$	25.34
$p$	0.00
$df_m$	6.00
logLik	58.18
$AIC$	-102.35
$BIC$	-84.12
dev	1.83
$df_e$	94.00

```
# Post hoc Define model
mymodel <- aov_rrs$mymodel
postH_rrs <- phc(mymodel = mymodel, resp_var = resp_var)

##
## ### Event ###
## $lsmeans
##   disturb_year    lsmean      SE df   lower.CL   upper.CL
##   2005          -0.07268135 0.01990865 94 -0.11221043 -0.03315226
##   2012           0.11047515 0.01990865 94  0.07094607  0.15000424
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005 - 2012 -0.1831565 0.02815508 94  -6.505  <.0001
##
## Results are averaged over the levels of: site
##
##   disturb_year    lsmean      SE df   lower.CL   upper.CL .group
##   2005          -0.07268135 0.01990865 94 -0.11803071 -0.02733199  a
##   2012           0.11047515 0.01990865 94  0.06512579  0.15582451  b
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## significance level used: alpha = 0.01
##
## ### Clu pop ###
```



```

## $lsmeans
##   site      lsmean      SE df    lower.CL    upper.CL
##   SJ      0.17544720 0.02205526 94   0.13165595   0.21923844
##   caH     -0.02596381 0.02546723 94  -0.07652958   0.02460197
##   caL     -0.09279268 0.02546723 94  -0.14335846  -0.04222691
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   SJ - caH    0.20141101 0.03368997 94    5.978  <.0001
##   SJ - caL    0.26823988 0.03368997 94    7.962  <.0001
##   caH - caL    0.06682887 0.03601610 94    1.856   0.2000
##
## Results are averaged over the levels of: disturb_year
## P value adjustment: bonferroni method for 3 tests
##
##   site      lsmean      SE df    lower.CL    upper.CL .group
##   caL     -0.09279268 0.02546723 94  -0.15487101  -0.03071435   a
##   caH     -0.02596381 0.02546723 94  -0.08804214   0.03611452   a
##   SJ      0.17544720 0.02205526 94   0.12168579   0.22920861   b
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 3 estimates
## P value adjustment: bonferroni method for 3 tests
## significance level used: alpha = 0.01
##
## ### Event:Clu pop ###
## $lsmeans
##   disturb_year site      lsmean      SE df    lower.CL    upper.CL
##   2005          SJ      0.03528048 0.03119085 94  -0.02664969   0.09721065
##   2012          SJ      0.31561391 0.03119085 94   0.25368374   0.37754408
##   2005          caH     -0.11035142 0.03601610 94  -0.18186223  -0.03884062
##   2012          caH      0.05842381 0.03601610 94  -0.01308700   0.12993461
##   2005          caL     -0.14297310 0.03601610 94  -0.21448390  -0.07146230
##   2012          caL     -0.04261226 0.03601610 94  -0.11412307   0.02889854
##
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005,SJ - 2012,SJ    -0.28033343 0.04411053 94   -6.355  <.0001
##   2005,SJ - 2005,caH    0.14563191 0.04764482 94    3.057   0.0437
##   2005,SJ - 2012,caH   -0.02314333 0.04764482 94   -0.486   1.0000
##   2005,SJ - 2005,caL    0.17825358 0.04764482 94    3.741   0.0047
##   2005,SJ - 2012,caL    0.07789274 0.04764482 94    1.635   1.0000
##   2012,SJ - 2005,caH    0.42596534 0.04764482 94    8.940  <.0001
##   2012,SJ - 2012,caH    0.25719010 0.04764482 94    5.398  <.0001
##   2012,SJ - 2005,caL    0.45858701 0.04764482 94    9.625  <.0001
##   2012,SJ - 2012,caL    0.35822618 0.04764482 94    7.519  <.0001
##   2005,caH - 2012,caH   -0.16877523 0.05093445 94   -3.314   0.0196
##   2005,caH - 2005,caL    0.03262167 0.05093445 94    0.640   1.0000


```

```
## 2005,caH - 2012,caL -0.06773916 0.05093445 94 -1.330 1.0000
## 2012,caH - 2005,caL 0.20139691 0.05093445 94 3.954 0.0022
## 2012,caH - 2012,caL 0.10103607 0.05093445 94 1.984 0.7532
## 2005,caL - 2012,caL -0.10036083 0.05093445 94 -1.970 0.7760
##
```

```
## P value adjustment: bonferroni method for 15 tests
```


ps

**site effect plot**




pd

**disturb\_year effect plot**




picollapse

**disturb\_year\*site effect plot**



pi



Resilience

Table 12: ANOVA table: rs

term	df	sumsq	meansq	statistic	p.value
disturb_year	1	2.031	2.031	66.58	<b>0</b>
site	2	0.01885	0.00942	0.309	0.7349
disturb_year:site	2	1.55	0.775	25.41	<b>0</b>
Residuals	94	2.867	0.0305		

	Statistic
$R^2$	0.56
$\text{adj}R^2$	0.53
$\sigma_e$	0.17
$F$	23.60
$p$	0.00
$df_m$	6.00
logLik	35.70
$AIC$	-57.41
$BIC$	-39.17
dev	2.87
$df_e$	94.00

```
# Post hoc Define model
mymodel <- aov_rs$mymodel
postH_rs <- phc(mymodel = mymodel, resp_var = resp_var)

##
## ### Event ###
## $lsmeans
##   disturb_year    lsmean      SE df  lower.CL  upper.CL
##   2005           0.6756316 0.02492546 94 0.6261415 0.7251217
##   2012           0.9270785 0.02492546 94 0.8775884 0.9765685
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005 - 2012 -0.2514469 0.03524992 94  -7.133  <.0001
##
## Results are averaged over the levels of: site
##
##   disturb_year    lsmean      SE df  lower.CL  upper.CL .group
##   2005           0.6756316 0.02492546 94 0.6188546 0.7324086  a
##   2012           0.9270785 0.02492546 94 0.8703014 0.9838555  b
##
## Results are averaged over the levels of: site
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## significance level used: alpha = 0.01
##
## ### Clu pop ###
```

```


## $lsmeans
##   site    lsmean      SE df  lower.CL  upper.CL
##   SJ    0.7893957 0.02761300 94 0.7345694 0.8442219
##   caH    0.7937171 0.03188475 94 0.7304092 0.8570250
##   caL    0.8209523 0.03188475 94 0.7576444 0.8842602
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   SJ - caH   -0.004321471 0.04217956 94  -0.102  1.0000
##   SJ - caL   -0.031556651 0.04217956 94  -0.748  1.0000
##   caH - caL  -0.027235180 0.04509185 94  -0.604  1.0000
##
## Results are averaged over the levels of: disturb_year
## P value adjustment: bonferroni method for 3 tests
##
##   site    lsmean      SE df  lower.CL  upper.CL .group
##   SJ    0.7893957 0.02761300 94 0.7220868 0.8567045  a
##   caH    0.7937171 0.03188475 94 0.7159956 0.8714387  a
##   caL    0.8209523 0.03188475 94 0.7432308 0.8986738  a
##
## Results are averaged over the levels of: disturb_year
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 3 estimates
## P value adjustment: bonferroni method for 3 tests
## significance level used: alpha = 0.01
##
## ### Event:Clu pop ###
## $lsmeans
##   disturb_year site    lsmean      SE df  lower.CL  upper.CL
##   2005          SJ    0.4958921 0.03905068 94 0.4183561 0.5734282
##   2012          SJ    1.0828992 0.03905068 94 1.0053631 1.1604352
##   2005          caH    0.7742095 0.04509185 94 0.6846786 0.8637404
##   2012          caH    0.8132248 0.04509185 94 0.7236938 0.9027557
##   2005          caL    0.7567932 0.04509185 94 0.6672623 0.8463241
##   2012          caL    0.8851114 0.04509185 94 0.7955805 0.9746423
##
## Confidence level used: 0.95
##
## $contrasts
##   contrast      estimate      SE df t.ratio p.value
##   2005,SJ - 2012,SJ   -0.58700705 0.05522601 94 -10.629 <.0001
##   2005,SJ - 2005,caH  -0.27831735 0.05965091 94  -4.666  0.0002
##   2005,SJ - 2012,caH  -0.31733264 0.05965091 94  -5.320  <.0001
##   2005,SJ - 2005,caL  -0.26090106 0.05965091 94  -4.374  0.0005
##   2005,SJ - 2012,caL  -0.38921929 0.05965091 94  -6.525  <.0001
##   2012,SJ - 2005,caH    0.30868970 0.05965091 94   5.175  <.0001
##   2012,SJ - 2012,caH    0.26967441 0.05965091 94   4.521  0.0003
##   2012,SJ - 2005,caL    0.32610599 0.05965091 94   5.467  <.0001
##   2012,SJ - 2012,caL    0.19778776 0.05965091 94   3.316  0.0195
##   2005,caH - 2012,caH  -0.03901529 0.06376950 94  -0.612  1.0000
##   2005,caH - 2005,caL  0.01741629 0.06376950 94   0.273  1.0000

```

```
## 2005,caH - 2012,caL -0.11090194 0.06376950 94 -1.739 1.0000
## 2012,caH - 2005,caL 0.05643158 0.06376950 94 0.885 1.0000
## 2012,caH - 2012,caL -0.07188665 0.06376950 94 -1.127 1.0000
## 2005,caL - 2012,caL -0.12831823 0.06376950 94 -2.012 0.7059
##
## P value adjustment: bonferroni method for 15 tests
```


ps

**site effect plot**




pd

**disturb\_year effect plot**



picollapse


**disturb\_year\*site effect plot**



pi



## disturb\_year\*site effect plot



```
plot_mds <- means_distub_site %>%
  ggplot(aes(x=site, y=lsmean, group=disturb_year, colour=disturb_year)) +
  geom_point(aes(shape=disturb_year, size=3)) +
  geom_line() +
  theme_bw() + xlab('') + ylab('') +
  facet_wrap(~var, scales='free_y', ncol = 1) +
```

```

geom_text(aes(y=lsmean+SE, label=letras), nudge_x = 0.15)+
theme(strip.background = element_rect(colour = "black", fill = "white"),
      legend.position = c(0.8, 0.93),
      legend.background = element_blank()) +
scale_colour_manual(values = c(micolor, "red"))

plot_mdsSE <- plot_mds + geom_errorbar(mierrorbarSE, size=.5, width=.15)
plot_mdsCI <- plot_mds + geom_errorbar(mierrorbar, size=.5, width=.15)

pdf(paste0(di, 'out/fig/resilience/interaction_plotsSE.pdf'), width=9, height = 9)
grid.arrange(plot_mdSE, plot_msSE, plot_mdsSE, ncol=3)
dev.off()

## pdf
## 2

pdf(paste0(di, 'out/fig/resilience/interaction_plotsCI.pdf'), width=9, height = 9)
grid.arrange(plot_mdCI, plot_msCI, plot_mdsCI, ncol=3)
dev.off()

## pdf
## 2

aovas_coef <- aov_rc$model_coef %>% mutate(var = 'rc') %>%
  bind_rows(aov_rt$model_coef %>% mutate(var = 'rt')) %>%
  bind_rows(aov_rs$model_coef %>% mutate(var = 'rs')) %>%
  bind_rows(aov_rrs$model_coef %>% mutate(var = 'rrs'))

write.csv(aovas_coef, file=paste0(di, '/out/anovas_resilience/anovas_statistics.csv'), row.names = F)

aovas_coef %>% pandoc()

```

term	df	sumsq	meansq	statistic	p.value	var
disturb_year	1	1.316	1.316	32.78	1.228e-07	rc
site	2	2.847	1.424	35.45	3.373e-12	rc
disturb_year:site	2	0.1961	0.09805	2.442	0.09253	rc
Residuals	94	3.775	0.04016	NA	NA	rc
disturb_year	1	0.2122	0.2122	9.867	0.00225	rt
site	2	1.666	0.833	38.74	5.363e-13	rt
disturb_year:site	2	0.8604	0.4302	20.01	5.77e-08	rt
Residuals	94	2.021	0.0215	NA	NA	rt
disturb_year	1	2.031	2.031	66.58	1.474e-12	rs
site	2	0.01885	0.009425	0.309	0.7349	rs
disturb_year:site	2	1.55	0.775	25.41	1.506e-09	rs
Residuals	94	2.867	0.0305	NA	NA	rs
disturb_year	1	0.93	0.93	47.8	5.63e-10	rrs
site	2	1.39	0.6952	35.73	2.874e-12	rrs
disturb_year:site	2	0.145	0.07252	3.727	0.02769	rrs
Residuals	94	1.829	0.01946	NA	NA	rrs

```

aovas_model_summary <- aov_rc$model_summary %>% mutate(var = 'rc') %>%
  bind_rows(aov_rt$model_summary %>% mutate(var = 'rt')) %>%
  bind_rows(aov_rs$model_summary %>% mutate(var = 'rs')) %>%

```

```

bind_rows(aov_rrs$model_summary%>% mutate(var = 'rrs'))

write.csv(aovas_model_summary,
          file=paste0(di, '/out/anovas_resilience/anovas_summary_modelos.csv'), row.names = F)

gm <- apply(aovas_model_summary, 1, formatC, digits = 2, format = "f")
rownames(gm) <- paste0("$", c("R^2", "\\mathrm{adj}R^2", "\\sigma_e", "F", "p", "df_m", "\\mathrm{logLik}", "AIC", "BIC", "dev", "df_e"))
colnames(gm) <- c("rc", "rt", "rs", "rrs")

pander(gm)

```

	rc	rt	rs	rrs
$R^2$	0.5359434	0.5753458	0.5566473	0.5741044
$\text{adj}R^2$	0.5112596	0.5527578	0.5330647	0.5514503
$\sigma_e$	0.2003962	0.1466433	0.1746400	0.1394897
$F$	21.71230	25.47131	23.60416	25.34227
$p$	2.166716e-14	3.707920e-16	2.678847e-15	4.239928e-16
$df_m$	6	6	6	6
logLik	21.94579	53.17511	35.70279	58.17634
$AIC$	-29.89157	-92.35023	-57.40558	-102.35268
$BIC$	-11.65538	-74.11404	-39.16939	-84.11649
dev	3.774913	2.021401	2.866917	1.828994
$df_e$	94	94	94	94
variable	rc	rt	rs	rrs

## ROBUST ANOVA

- Ver Wilcox (2005, 2012)
- Vamos a realizar un Robust factorial ANOVA. En concreto:
- Two-way robust factorial ANOVA on M-estimator
- pkg WRS2

```

robustANOVA <- function(df, resp_var, factores,
                        alpha, nboot, treshold) {
  # alpha: alpha ci for huber m-estimation
  # nboot: numer of iterations
  # treshoold for letter (posthoc)
  # See http://rcompanion.org/rcompanion/d_08a.html

  # Create interaction
  df$interaction <- interaction(df$disturb_year, df$site)

  # Formulas
  formulaFull <- as.formula(paste0(resp_var, " ~ ",
                                   paste(factores, collapse = '+')))

  formula_A <- as.formula(paste0(resp_var, " ~ ", factores[1]))
  formula_B <- as.formula(paste0(resp_var, " ~ ", factores[2]))
  formula_AB <- as.formula(paste0(resp_var, " ~ interaction"))
}

```

```

# Produce Huber M-estimators and confidence intervals by group
mest <- groupwiseHuber(formulaFull, data = df, ci.type = 'wald', conf.level = alpha)
mest_a <- groupwiseHuber(formula_A, data = df, ci.type = 'wald', conf.level = alpha)
mest_b <- groupwiseHuber(formula_B, data = df, ci.type = 'wald', conf.level = alpha)

# Two-way robust analysis
x <- pbad2way(formulaFull, data = df, est = "mom", nboot = nboot)

pbad2way(rs ~ disturb_year + site + disturb_year:site, data = df,
         est = "mom", nboot = nboot)

out_ra <- data.frame(
  term = c(x$varnames[2],
           x$varnames[3],
           paste0(x$varnames[2], ': ', x$varnames[3])),
  p_value = c(x$A.p.value, x$B.p.value, x$AB.p.value))

# post-hoc
## factor A
pha <- pairwiseRobustTest(formula_A, data = df, est = "mom",
                          nboot = nboot, method="bonferroni")

## factor B
phb <- pairwiseRobustTest(formula_B, data = df, est = "mom",
                          nboot = nboot, method="bonferroni")

## interaction effect (AB)
phab <- pairwiseRobustTest(formula_AB, data = df, est = "mom",
                           nboot = nboot, method="bonferroni")

ph <- rbind(pha, phb, phab)

phRWS2 <- mcp2a(formulaFull, data=df, est = "mom", nboot = nboot)

out <- list()
out$mest <- mest # Huber M-estimators and Confidence Intervals
out$mest_a <- mest_a
out$mest_b <- mest_b
out$ra <- out_ra # Output for Two-way robust analysis (M-estimators)
out$ph <- ph # posthoc comparison usinng pairwiseRobustTest
out$pha <- pha
out$phb <- phb
out$phab <- phab

print(out_ra)
print(phRWS2)

return(out)
}

# if (exists('letters_phb')) {
# letters_phb <- letters_phb} else {

```

```

# myerror <- evaluate('cldList(comparison = phb$Comparison,
#                               p.value = phb$p.adjust, threshold = threshold)')
# letters_phb <- as.character(myerror[[2]]$message)}
#
# if (exists('letters_pha')) {
#   letters_pha <- letters_pha} else {
#   myerror <- evaluate('cldList(comparison = pha$Comparison,
#                               p.value = pha$p.adjust, threshold = threshold)')
#   letters_pha <- as.character(myerror[[2]]$message)}
#
# if (exists('letters_phab')) {
#   letters_phab <- letters_phab} else {
#   myerror <- evaluate('cldList(comparison = phab$Comparison,
#                               p.value = phab$p.adjust, threshold = threshold)')
#   letters_phab <- as.character(myerror[[2]]$message)}

```

```
factores = c('disturb_year', 'site', 'disturb_year:site')
```

## Resilience

```

rars <- robustANOVA(df=re, resp_var='rs', factores=factores,
                    alpha = 0.95, nboot = 3000, threshold = 0.01)

```

```

## [1] "comparison 1 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
## [1] "comparison 4 ..."
## [1] "comparison 5 ..."
## [1] "comparison 6 ..."
## [1] "comparison 7 ..."
## [1] "comparison 8 ..."
## [1] "comparison 9 ..."
## [1] "comparison 10 ..."
## [1] "comparison 11 ..."
## [1] "comparison 12 ..."
## [1] "comparison 13 ..."
## [1] "comparison 14 ..."
## [1] "comparison 15 ..."
##
##
##           term    p_value
## 1   disturb_year 0.0000000
## 2             site 0.4063333
## 3 disturb_year:site 0.0030000

```

```
## Call:
## mcp2a(formula = formulaFull, data = df, est = "mom", nboot = nboot)
##
##               psihat ci.lower ci.upper p-value
## disturb_year1    -0.66998 -0.97945 -0.45488 0.00000
## site1            -0.17216 -0.34748  0.15870 0.17867
## site2            -0.13328 -0.34329  0.13341 0.15800
## site3             0.03889 -0.20563  0.19572 0.47367
## disturb_year1:site1 -0.46693 -0.75689 -0.26309 0.00000
## disturb_year1:site2 -0.31564 -0.64001 -0.17364 0.00000
## disturb_year1:site3  0.15129 -0.10506  0.31106 0.12300
```

## Rs Letters

```
x <-rars
```

```
letraArs <- cldList(comparison = x$pha$Comparison, p.value = x$pha$p.adjust, threshold = 0.01) %>% mutate(
letraArs
```

```
##   Group Letter MonoLetter var
## 1    25      a          a  rs
## 2   212      b          b  rs
```

```
letraBrs <- cldList(comparison = x$phb$Comparison, p.value = x$phb$p.adjust, threshold = 0.01) %>% mutate(
```

```
## Error: No significant differences.
```

```
letraBrs # Manual (IMPROVE IT)
```

```
## Error in eval(expr, envir, enclos): object 'letraBrs' not found
```

```
letraBrs <- data.frame(Group = c('SJ', 'caH', 'caL'),
                      Letter = c('a', 'a', 'a'),
                      MonoLetter = c('a', 'a', 'a')) %>% mutate(var = 'rs')
```

```
letraBrs
```

```
##   Group Letter MonoLetter var
## 1    SJ      a          a  rs
## 2   caH      a          a  rs
## 3   caL      a          a  rs
```

```
letraABrs <- cldList(comparison = x$phab$Comparison, p.value = x$phab$p.adjust, threshold = 0.01) %>%
letraABrs
```

```
##   Group Letter MonoLetter var
## 1  25.SJ      a          a  rs
## 2 212.SJ      b          b  rs
## 3  25.caH      b          b  rs
## 4 212.caH      b          b  rs
## 5  25.caL     ab          ab  rs
## 6 212.caL      b          b  rs
```

## Recovery

```
rarc <- robustANOVA(df=re, resp_var='rc', factores=factores,
                    alpha = 0.95, nboot = 3000, treshold = 0.01)
```

```
## [1] "comparison 1 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
## [1] "comparison 4 ..."
## [1] "comparison 5 ..."
## [1] "comparison 6 ..."
## [1] "comparison 7 ..."
## [1] "comparison 8 ..."
## [1] "comparison 9 ..."
## [1] "comparison 10 ..."
## [1] "comparison 11 ..."
## [1] "comparison 12 ..."
## [1] "comparison 13 ..."
## [1] "comparison 14 ..."
## [1] "comparison 15 ..."
##
##
##           term    p_value
## 1      disturb_year 0.0000000
## 2              site 0.0000000
## 3 disturb_year:site 0.1076667
## Call:
## mcp2a(formula = formulaFull, data = df, est = "mom", nboot = nboot)
##
##           psihat ci.lower ci.upper p-value
## disturb_year1    -0.66711 -0.92333 -0.42093 0.00000
## site1             0.55891  0.30775  0.83479 0.00000
## site2             0.77967  0.54751  1.03253 0.00000
## site3             0.22076  0.03416  0.40661 0.00567
## disturb_year1:site1 -0.09620 -0.37897  0.14276 0.16600
## disturb_year1:site2 -0.22864 -0.47762  0.00799 0.02200
## disturb_year1:site3 -0.13244 -0.29390  0.08467 0.10667
```

## Rc Letters

```
x <-rarc
```

```
letraArc <- cldList(comparison = x$pha$Comparison, p.value = x$pha$p.adjust, threshold = 0.01) %>% mutate(
letraArc
```

```
##   Group Letter MonoLetter var
## 1    25      a          a   rc
## 2   212      b          b   rc
```

```
letraBrc <- cldList(comparison = x$phb$Comparison, p.value = x$phb$p.adjust, threshold = 0.01) %>% mutate(
letraBrc
```

```
##   Group Letter MonoLetter var
## 1   SJ      a           a   rc
## 2  caH      b           b   rc
## 3  caL      b           b   rc
```

```
letraABrc <- cldList(comparison = x$phab$Comparison, p.value = x$phab$p.adjust, threshold = 0.01) %>%
letraABrc
```

```
##   Group Letter MonoLetter var
## 1  25.SJ    abc          abc  rc
## 2 212.SJ     a          a   rc
## 3  25.caH   bc          bc  rc
## 4 212.caH   ab          ab  rc
## 5  25.caL   c           c   rc
## 6 212.caL   bc          bc  rc
```

## Resistance

```
rart <- robustANOVA(df=re, resp_var='rt', factores=factores,
alpha = 0.95, nboot = 3000, treshold = 0.01)
```

```
## [1] "comparison 1 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
## [1] "comparison 4 ..."
## [1] "comparison 5 ..."
## [1] "comparison 6 ..."
## [1] "comparison 7 ..."
## [1] "comparison 8 ..."
## [1] "comparison 9 ..."
## [1] "comparison 10 ..."
## [1] "comparison 11 ..."
## [1] "comparison 12 ..."
## [1] "comparison 13 ..."
## [1] "comparison 14 ..."
## [1] "comparison 15 ..."
##
##
##           term p_value
## 1   disturb_year 0.027
## 2           site 0.000
## 3 disturb_year:site 0.000
## Call:
## mcp2a(formula = formulaFull, data = df, est = "mom", nboot = nboot)
##
##           psihat ci.lower ci.upper p-value
```



```
## disturb_year1      -0.22274 -0.42806 -0.02379 0.01733
## site1              -0.43120 -0.61817 -0.24893 0.00000
## site2              -0.59768 -0.80539 -0.43666 0.00000
## site3              -0.16648 -0.34232 -0.02909 0.00633
## disturb_year1:site1 -0.49622 -0.67079 -0.28968 0.00000
## disturb_year1:site2 -0.31961 -0.50865 -0.14268 0.00000
## disturb_year1:site3 0.17661 0.00283 0.30666 0.01500
```

## Rt Letters

```
x <-rart
```

```
letraArt <- cldList(comparison = x$pha$Comparison, p.value = x$pha$p.adjust, threshold = 0.01) %>% mutate(
```

```
## Error: No significant differences.
```

```
letraArt #Manual (IMPROVE IT)
```

```
## Error in eval(expr, envir, enclos): object 'letraArt' not found
```

```
letraArt <- data.frame(Group = as.factor(c('25', '212')),
                      Letter = as.factor(c('a', 'a')),
                      MonoLetter = as.factor(c('a', 'a'))) %>% mutate(var = 'rt')
```

```
letraArt
```

```
##   Group Letter MonoLetter var
## 1    25      a          a   rt
## 2   212      a          a   rt
```

```
letraBrt <- cldList(comparison = x$phb$Comparison, p.value = x$phb$p.adjust, threshold = 0.01) %>% mutate(
letraBrt
```

```
##   Group Letter MonoLetter var
## 1    SJ      a          a   rt
## 2   caH      b          b   rt
## 3   caL      b          b   rt
```

```
letraABrt <- cldList(comparison = x$phab$Comparison, p.value = x$phab$p.adjust, threshold = 0.01) %>% mutate(
letraABrt
```

```
##   Group Letter MonoLetter var
## 1   25.SJ      a          a   rt
## 2  212.SJ     bc         bc   rt
## 3   25.caH     bc         bc   rt
## 4 212.caH      b          b   rt
## 5   25.caL     bc         bc   rt
## 6 212.caL      c          c   rt
```

## Relative Resilience

```
rarrs <- robustANOVA(df=re, resp_var='rrs', factores=factores,
                    alpha = 0.95, nboot = 3000, treshold = 0.01)
```

```
## [1] "comparison 1 ..."
##
##
## [1] "comparison 1 ..."
```

```
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
##
##
## [1] "comparison 1 ..."
## [1] "comparison 2 ..."
## [1] "comparison 3 ..."
## [1] "comparison 4 ..."
## [1] "comparison 5 ..."
## [1] "comparison 6 ..."
## [1] "comparison 7 ..."
## [1] "comparison 8 ..."
## [1] "comparison 9 ..."
## [1] "comparison 10 ..."
## [1] "comparison 11 ..."
## [1] "comparison 12 ..."
## [1] "comparison 13 ..."
## [1] "comparison 14 ..."
## [1] "comparison 15 ..."
##
##
##              term p_value
## 1      disturb_year  0.000
## 2              site  0.000
## 3 disturb_year:site  0.098
## Call:
## mcp2a(formula = formulaFull, data = df, est = "mom", nboot = nboot)
##
##              psihat ci.lower ci.upper p-value
## disturb_year1    -0.56395 -0.75725 -0.36903 0.00000
## site1             0.38674  0.20470  0.56009 0.00000
## site2             0.55080  0.39849  0.72748 0.00000
## site3             0.16406  0.01348  0.35374 0.01367
## disturb_year1:site1 -0.07004 -0.29037  0.07223 0.12333
## disturb_year1:site2 -0.16885 -0.35877 -0.02373 0.00667
## disturb_year1:site3 -0.09881 -0.24560  0.08663 0.15100
```

## Rt Letters

```
x <-rarrs
```

```
letraArrs <- cldList(comparison = x$pha$Comparison, p.value = x$pha$p.adjust, threshold = 0.01) %>% mu
letraArrs
```

```
##   Group Letter MonoLetter var
## 1    25      a          a rrs
## 2   212      b          b rrs
```

```
letraBrrs <- cldList(comparison = x$phb$Comparison, p.value = x$phb$p.adjust, threshold = 0.01) %>% mu
letraBrrs
```

```
##   Group Letter MonoLetter var
## 1    SJ      a          a rrs
## 2   caH     ab         ab rrs
## 3   caL     b          b rrs
```

```

letraABrrs <- cldList(comparison = x$phab$Comparison, p.value = x$phab$p.adjust, threshold = 0.01) %>%
letraABrrs

##      Group Letter MonoLetter var
## 1   25.SJ      ab          ab rrs
## 2  212.SJ       c          c rrs
## 3   25.caH      ab          ab rrs
## 4 212.caH       a          a rrs
## 5   25.caL       b          b rrs
## 6 212.caL      ab          ab rrs

letrasA <- rbind(letraArs, letraArc, letraArt, letraArrs) %>%
  mutate(disturb_year =
    case_when(Group == "25" ~ "2005",
              Group == "212" ~ "2012")) %>%
  dplyr::select(-Group)

letrasB <- rbind(letraBrs, letraBrc, letraBrt, letraBrrs) %>% rename(site = Group)

letrasAB <- rbind(letraABrs, letraABrc, letraABrt, letraABrrs) %>%
  separate(Group, into=c('disturb_year', 'site')) %>%
  mutate(disturb_year =
    case_when(disturb_year == "25" ~ "2005",
              disturb_year == "212" ~ "2012"))

```

## Estimadores de huber

```

rars$mest$var <- 'rs'
rarc$mest$var <- 'rc'
rart$mest$var <- 'rt'
rarrs$mest$var <- 'rrs'

mhuber <- rbind(rarc$mest, rart$mest, rars$mest, rarrs$mest)

# add letras
mhuber <- mhuber %>% inner_join(letrasAB, by=c('var','disturb_year', 'site'))

mhuber_agg <- mhuber %>%
  mutate(M.Huber = round(M.Huber, 4),
         lower.ci = round(lower.ci, 4),
         upper.ci = round(upper.ci, 4)) %>%
  unite("ci", c("lower.ci", "upper.ci"), sep=",") %>%
  mutate(ci = paste0('(', ci, ')')) %>%
  dplyr::select(-MonoLetter) %>%
  dplyr::select(var, disturb_year:ci, Letter) %>% as.data.frame()

mhuber_agg %>% pander()

```

var	disturb_year	site	n	M.Huber	ci	Letter
rc	2005	SJ	20	1.112	(1.0004,1.2241)	abc
rc	2005	caH	15	0.8866	(0.8003,0.973)	bc
rc	2005	caL	15	0.8321	(0.7326,0.9315)	c

var	disturb_year	site	n	M.Huber	ci	Letter
rc	2012	SJ	20	1.446	(1.3223,1.5691)	a
rc	2012	caH	15	1.107	(1.0257,1.1885)	ab
rc	2012	caL	15	0.952	(0.8889,1.015)	bc
rt	2005	SJ	20	0.4454	(0.3751,0.5158)	a
rt	2005	caH	15	0.8921	(0.8091,0.9751)	bc
rt	2005	caL	15	0.9012	(0.8132,0.9892)	bc
rt	2012	SJ	20	0.7687	(0.6839,0.8534)	bc
rt	2012	caH	15	0.7534	(0.6864,0.8204)	b
rt	2012	caL	15	0.9263	(0.9001,0.9526)	c
rs	2005	SJ	20	0.4888	(0.4213,0.5562)	a
rs	2005	caH	15	0.7895	(0.6913,0.8878)	b
rs	2005	caL	15	0.7303	(0.6118,0.8489)	ab
rs	2012	SJ	20	1.031	(0.93,1.1321)	b
rs	2012	caH	15	0.8132	(0.7413,0.8852)	b
rs	2012	caL	15	0.8761	(0.8394,0.9129)	b
rrs	2005	SJ	20	0.0426	(-0.0066,0.0918)	ab
rrs	2005	caH	15	-0.1075	(-0.1893,-0.0257)	ab
rrs	2005	caL	15	-0.1424	(-0.2264,-0.0583)	b
rrs	2012	SJ	20	0.3206	(0.229,0.4122)	c
rrs	2012	caH	15	0.0819	(0.0275,0.1364)	a
rrs	2012	caL	15	-0.0443	(-0.1071,0.0185)	ab

```

rars$mest_a$var <- 'rs'
rarc$mest_a$var <- 'rc'
rart$mest_a$var <- 'rt'
rarrs$mest_a$var <- 'rrs'

mhuber_a <- rbind(rarc$mest_a, rart$mest_a, rars$mest_a, rarrs$mest_a)
mhuber_a <- mhuber_a %>% inner_join(letrasA, by=c('var','disturb_year'))

mhuber_agg_a <- mhuber_a %>%
  mutate(M.Huber = round(M.Huber, 4),
         lower.ci = round(lower.ci, 4),
         upper.ci = round(upper.ci, 4)) %>%
  unite_("ci", c("lower.ci", "upper.ci"), sep=",") %>%
  mutate(ci = paste0('(', ci, ')')) %>%
  dplyr::select(-MonoLetter) %>%
  dplyr::select(var, disturb_year:ci, Letter) %>% as.data.frame()

mhuber_agg_a %>% pander()

```

var	disturb_year	n	M.Huber	ci	Letter
rc	2005	50	0.9462	(0.8794,1.0129)	a
rc	2012	50	1.161	(1.0813,1.2403)	b
rt	2005	50	0.721	(0.6437,0.7984)	a
rt	2012	50	0.8193	(0.7758,0.8628)	a
rs	2005	50	0.653	(0.5852,0.7209)	a
rs	2012	50	0.9107	(0.8648,0.9567)	b
rrs	2005	50	-0.0559	(-0.0993,-0.0126)	a
rrs	2012	50	0.1223	(0.0596,0.185)	b

```

rars$mest_b$var <- 'rs'
rarc$mest_b$var <- 'rc'
rart$mest_b$var <- 'rt'
rarrs$mest_b$var <- 'rrs'

mhuber_b <- rbind(rarc$mest_b, rart$mest_b, rars$mest_b, rarrs$mest_b)
mhuber_b <- mhuber_b %>% inner_join(letrasB, by=c('var','site'))

mhuber_agg_b <- mhuber_b %>%
  mutate(M.Huber = round(M.Huber, 4),
         lower.ci = round(lower.ci, 4),
         upper.ci = round(upper.ci, 4)) %>%
  unite("ci", c("lower.ci", "upper.ci"), sep=",") %>%
  mutate(ci = paste0('(', ci, ')')) %>%
  dplyr::select(-MonoLetter) %>%
  dplyr::select(var, site:ci, Letter) %>% as.data.frame()

mhuber_agg_b %>% pandier()

```

var	site	n	M.Huber	ci	Letter
rc	SJ	40	1.282	(1.1791,1.3856)	a
rc	caH	30	0.9962	(0.9171,1.0753)	b
rc	caL	30	0.8972	(0.8431,0.9514)	b
rt	SJ	40	0.6116	(0.5387,0.6846)	a
rt	caH	30	0.8157	(0.7549,0.8764)	b
rt	caL	30	0.9209	(0.8834,0.9584)	b
rs	SJ	40	0.7694	(0.6524,0.8864)	a
rs	caH	30	0.7975	(0.7439,0.8511)	a
rs	caL	30	0.8172	(0.7553,0.8791)	a
rrs	SJ	40	0.1656	(0.0948,0.2364)	a
rrs	caH	30	-0.0063	(-0.0668,0.0541)	ab
rrs	caL	30	-0.0939	(-0.1455,-0.0423)	b

## Pairwise comparison

```

rars$ph$var <- 'rs'
rarc$ph$var <- 'rc'
rart$ph$var <- 'rt'
rarrs$ph$var <- 'rrs'

pairwise <- rbind(rarc$ph, rart$ph, rars$ph, rarrs$ph)
pairwise %>% pandier()

```

Comparison	Statistic	p.value	p.adjust	var
2005 - 2012 = 0	-0.1672	0.004	0.004	rc
SJ - caH = 0	0.2808	0.001333	0.003999	rc
SJ - caL = 0	0.3926	0	0	rc
caH - caL = 0	0.1118	0.04133	0.124	rc
2005.SJ - 2012.SJ = 0	-0.3306	0.001333	0.02	rc
2005.SJ - 2005.caH = 0	0.2314	0.01133	0.17	rc
2005.SJ - 2012.caH = 0	-0.003094	0.926	1	rc

Comparison	Statistic	p.value	p.adjust	var
2005.SJ - 2005.caL = 0	0.2755	0.003333	0.05	rc
2005.SJ - 2012.caL = 0	0.1735	0.02467	0.37	rc
2012.SJ - 2005.caH = 0	0.562	0	0	rc
2012.SJ - 2012.caH = 0	0.3276	0.0006667	0.01	rc
2012.SJ - 2005.caL = 0	0.6062	0	0	rc
2012.SJ - 2012.caL = 0	0.5042	0	0	rc
2005.caH - 2012.caH = 0	-0.2344	0.0006667	0.01	rc
2005.caH - 2005.caL = 0	0.04416	0.4287	1	rc
2005.caH - 2012.caL = 0	-0.05785	0.3307	1	rc
2012.caH - 2005.caL = 0	0.2786	0	0	rc
2012.caH - 2012.caL = 0	0.1766	0.004667	0.07	rc
2005.caL - 2012.caL = 0	-0.102	0.05333	0.8	rc
2005 - 2012 = 0	-0.107	0.09867	0.09867	rt
SJ - caH = 0	-0.1948	0.0006667	0.002	rt
SJ - caL = 0	-0.3104	0	0	rt
caH - caL = 0	-0.1156	0.007333	0.022	rt
2005.SJ - 2012.SJ = 0	-0.3462	0	0	rt
2005.SJ - 2005.caH = 0	-0.4637	0	0	rt
2005.SJ - 2012.caH = 0	-0.3137	0	0	rt
2005.SJ - 2005.caL = 0	-0.4586	0	0	rt
2005.SJ - 2012.caL = 0	-0.4852	0	0	rt
2012.SJ - 2005.caH = 0	-0.1175	0.116	1	rt
2012.SJ - 2012.caH = 0	0.03251	0.708	1	rt
2012.SJ - 2005.caL = 0	-0.1125	0.05867	0.88	rt
2012.SJ - 2012.caL = 0	-0.139	0.008	0.12	rt
2005.caH - 2012.caH = 0	0.15	0.014	0.21	rt
2005.caH - 2005.caL = 0	0.005064	0.8207	1	rt
2005.caH - 2012.caL = 0	-0.02152	0.4107	1	rt
2012.caH - 2005.caL = 0	-0.145	0.004	0.06	rt
2012.caH - 2012.caL = 0	-0.1715	0	0	rt
2005.caL - 2012.caL = 0	-0.02658	0.6453	1	rt
2005 - 2012 = 0	-0.2266	0	0	rs
SJ - caH = 0	-0.004321	0.8133	1	rs
SJ - caL = 0	-0.008101	0.5827	1	rs
caH - caL = 0	-0.00378	0.6107	1	rs
2005.SJ - 2012.SJ = 0	-0.4842	0	0	rs
2005.SJ - 2005.caH = 0	-0.3195	0	0	rs
2005.SJ - 2012.caH = 0	-0.3368	0	0	rs
2005.SJ - 2005.caL = 0	-0.2245	0.0006667	0.01	rs
2005.SJ - 2012.caL = 0	-0.393	0	0	rs
2012.SJ - 2005.caH = 0	0.1646	0.01467	0.2201	rs
2012.SJ - 2012.caH = 0	0.1474	0.02133	0.3199	rs
2012.SJ - 2005.caL = 0	0.2597	0.002	0.03	rs
2012.SJ - 2012.caL = 0	0.09118	0.024	0.36	rs
2005.caH - 2012.caH = 0	-0.01725	0.594	1	rs
2005.caH - 2005.caL = 0	0.09509	0.5207	1	rs
2005.caH - 2012.caL = 0	-0.07345	0.09733	1	rs
2012.caH - 2005.caL = 0	0.1123	0.266	1	rs
2012.caH - 2012.caL = 0	-0.0562	0.2073	1	rs
2005.caL - 2012.caL = 0	-0.1685	0.02867	0.43	rs
2005 - 2012 = 0	-0.1766	0	0	rrs
SJ - caH = 0	0.1318	0.01733	0.05199	rrs

Comparison	Statistic	p.value	p.adjust	var
SJ - caL = 0	0.2463	0	0	rrs
caH - caL = 0	0.1145	0.06067	0.182	rrs
2005.SJ - 2012.SJ = 0	-0.2676	0	0	rrs
2005.SJ - 2005.caH = 0	0.1584	0.02333	0.35	rrs
2005.SJ - 2012.caH = 0	-0.03922	0.2147	1	rrs
2005.SJ - 2005.caL = 0	0.191	0.003333	0.05	rrs
2005.SJ - 2012.caL = 0	0.09221	0.018	0.27	rrs
2012.SJ - 2005.caH = 0	0.426	0	0	rrs
2012.SJ - 2012.caH = 0	0.2284	0	0	rrs
2012.SJ - 2005.caL = 0	0.4586	0	0	rrs
2012.SJ - 2012.caL = 0	0.3598	0	0	rrs
2005.caH - 2012.caH = 0	-0.1976	0.003333	0.05	rrs
2005.caH - 2005.caL = 0	0.03262	0.4573	1	rrs
2005.caH - 2012.caL = 0	-0.06614	0.4187	1	rrs
2012.caH - 2005.caL = 0	0.2302	0	0	rrs
2012.caH - 2012.caL = 0	0.1314	0.004667	0.07	rrs
2005.caL - 2012.caL = 0	-0.09876	0.05267	0.79	rrs

## Interaction plot

Response ~ (x=Drought)

```


mhuber<- mhuber %>%
  mutate(var_sorted = case_when(var == "rc" ~ "1_rc",
                                var == "rt" ~ "0_rt",
                                var == "rs" ~ "2_rs",
                                var == "rrs" ~ "3_rrs"))

pd <- position_dodge(.2)

robust_plot_evi_drought <- ggplot(mhuber, aes(x=disturb_year, y=M.Huber, color = site, group=site, fill=site)) +
  geom_errorbar(aes(ymin=lower.ci, ymax=upper.ci),
                width=.1, size=0.7, position=pd) +
  geom_line(aes(group=site,color=site, linetype=site), position=pd) +
  geom_point(shape=21, size=3.5, position=pd) +
  facet_wrap(~var_sorted, nrow = 2, scales = 'free_y',
             labeller=as_labeller(c('0_rt' = 'Resistance',
                                   '1_rc' = 'Recovery',
                                   '2_rs' = 'Resilience',
                                   '3_rrs' = 'Relative Resilience')))) +
  scale_color_manual(values=c('black','blue','red')) +
  scale_fill_manual(values=c('black','blue','red')) + theme_bw() +
  scale_linetype_manual(values=c("solid", "dashed", "dashed")) +
  theme(panel.grid.minor = element_blank(),
        strip.background = element_rect(colour='black',
                                         fill='white'),
        legend.position="bottom") +
  ylab('') + xlab('Drought event')

robust_plot_evi_drought

```



```
pdf(paste0(di, 'out/fig/resilience/robust_plot_evi_drought.pdf'), width=9, height = 9)
robust_plot_evi_drought
dev.off()
```

```
## pdf
## 2
```

Response ~ (x=site)

```
pd <- position_dodge(.2)

robust_plot_evi_site <- ggplot(mhuber, aes(x=site, y=M.Huber, color = disturb_year, group=disturb_year,
  geom_errorbar(aes(ymin=lower.ci, ymax=upper.ci),
    width=.1, size=0.7, position=pd) +
  geom_line(aes(group=disturb_year,color=disturb_year, linetype=disturb_year), position=pd) +
  geom_point(shape=21, size=3.5, position=pd) +
  facet_wrap(~var_sorted, nrow = 2, scales = 'free_y',
    labeller=as_labeller(c('0_rt' = 'Resistance',
      '1_rc' = 'Recovery',
      '2_rs' = 'Resilience',
      '3_rrs' = 'Relative Resilience')))) +
  scale_color_manual(values=c('black','blue')) +
  scale_fill_manual(values=c('black','blue')) + theme_bw() +
  scale_linetype_manual(values=c("solid", "dashed")) +
  theme(panel.grid.minor = element_blank(),
    strip.background = element_rect(colour='black',
```




```

                                fill='white'),
    legend.position="bottom") +
    ylab('') + xlab('Drought event')

```

```
robust_plot_evi_site
```



```

pdf(paste0(di, 'out/fig/resilience/robust_plot_evi_site.pdf'), width=9, height = 9)
robust_plot_evi_site
dev.off()

```

```

## pdf
## 2

```

```
# Export data
```

```

write.csv(mhuber, file=paste0(di, '/out/anovas_resilience/robust_mhuber.csv'), row.names = F)
write.csv(mhuber_agg, file=paste0(di, '/out/anovas_resilience/robust_mhuber_agg.csv'), row.names = F)
write.csv(mhuber_a, file=paste0(di, '/out/anovas_resilience/robust_mhuber_a.csv'), row.names = F)
write.csv(mhuber_agg_a, file=paste0(di, '/out/anovas_resilience/robust_mhuber_agg_a.csv'), row.names = F)
write.csv(mhuber_b, file=paste0(di, '/out/anovas_resilience/robust_mhuber_b.csv'), row.names = F)
write.csv(mhuber_agg_b, file=paste0(di, '/out/anovas_resilience/robust_mhuber_agg_b.csv'), row.names = F)

write.csv(pairwise, file=paste0(di, '/out/anovas_resilience/robust_pairwise.csv'), row.names = F)

```

## References

- Lloret, F., E. G. Keeling, and A. Sala. 2011. Components of tree resilience: Effects of successive low-growth episodes in old ponderosa pine forests. *Oikos* 120:1909–1920.
- Piovesa, G., F. Biondi, A. D. Filippo, A. Alessandrini, and M. Maugeri. 2008. Drought-driven growth reduction in old beech (*fagus sylvatica* l.) forests of the central apennines, italy. *Global Change Biology* 14:1265–1281.