
VLMs for Reward Hacking Mitigation

Joe Gauchó
UC Santa Barbara
jgauchó@ucsb.edu

Joe Gauchó
UC Santa Barbara
jgauchó@ucsb.edu

Abstract

Choosing good reward functions in reinforcement learning (RL) is notoriously difficult. Oftentimes, the true reward function is very sparse, as in a game of chess that gives a reward signal only when the agent wins. In other scenarios, such as preference optimization for large language models (LLMs) using algorithms like reinforcement learning from human feedback (RLHF) [2], the true reward function—alignment to human preferences—is impossible to specify. As a result, RL techniques typically employ proxy rewards, which provide finer-grained feedback loops and are easier to learn. However, these proxy rewards can be misspecified; RL agents that exploit misspecifications in the proxy reward function can exhibit undesirable and potentially harmful behaviors. According to [4], this type of behavior—where an agent attains a high proxy reward but does not accomplish the human-intended goal—is referred to as *reward hacking*. In this work, we investigate the problem of reward hacking and propose a novel approach that improves the approximation of the true reward function by incorporating feedback from Vision-Language Models (VLMs) into the training loss.

1 Introduction

Reinforcement learning has led to breakthroughs in areas such as robotics, game-playing, and LLMs. However, one of its fundamental challenges is the design of reward functions that effectively capture the human-intended objectives of a task. In many cases, the true reward function is either sparse or difficult to specify explicitly, necessitating the use of proxy rewards. Use of such proxies, however, introduces the concept of reward hacking, where an agent discovers unintended strategies to maximize reward without accomplishing the underlying goal.

Reward hacking can manifest in both benign and harmful ways. In some cases, agents discover novel but unintended strategies that still achieve high rewards, such as finding new methods for robot locomotion. However, it is more problematic when agents exploit bugs, manipulate physics engines, cheat, or even engage in deceptive behavior [3]. Mitigating reward hacking is essential for deploying RL in high-trust settings, where unintended behaviors could compromise safety, reliability, or ethical standards.

In this work, we propose an approach that leverages *Vision-Language Models (VLMs)* to mitigate reward hacking at training time. VLMs, which process both visual and textual information, have shown strong generalization capabilities in tasks requiring multimodal reasoning. We explore how feedback from VLMs can be integrated into the RL training pipeline to improve alignment between proxy rewards and the true underlying objective. By incorporating VLM-based signals into the training loss, we aim to reduce instances of reward hacking and enhance the overall robustness of RL agents.

2 Background

2.1 Formalizing Reward Hacking

Skalse et al. [4] formally define reward hacking as a situation where a policy improves according to the proxy reward, while worsening according to the true reward. They demonstrate that unhackable reward functions are rare, as any reward function designed for practical use is susceptible to some degree of exploitation.

2.2 VLMs in Reinforcement Learning

Recent work has explored the potential of VLMs as reward sources for reinforcement learning, as they can provide meaningful, human-aligned evaluations of agent behavior without requiring manually crafted reward functions.

A recent study by Baumli et al. [1] investigates the feasibility of using off-the-shelf VLMs as sources of reward signals in RL. Their findings suggest that larger VLMs provide more accurate and generalizable rewards, leading to improved agent performance in visually guided tasks. This approach presents a compelling alternative to traditional proxy rewards, as VLMs inherently capture semantic and contextual understanding of tasks. However, challenges remain in ensuring the reliability of VLM-derived rewards, as these models can exhibit inconsistencies in certain environments.

2.3 Using VLMs to Mitigate Reward Hacking

Given their strong reasoning capabilities, VLMs offer a promising avenue for improving reward design in RL. Unlike traditionally-defined rewards, which are prone to misspecification, VLMs provide an adaptive and context-aware evaluation mechanism. Baumli et al. demonstrate that VLMs can effectively assess whether an agent’s behavior aligns with an objective specified in natural language. By incorporating VLM-based feedback into the reward function, we hypothesize that RL agents can be guided toward behaviors that better align with human intention. By integrating VLM-based signals into the RL pipeline, we aim to establish a more reliable and scalable method for mitigating reward hacking.

3 Project Retrospective

3.1 Initial Project Goal

Our initial project idea was to use anomaly detection techniques as a means of detecting and flagging reward hacking during training time. We had hoped to create a dataset of healthy trajectories (i.e., those that do not exhibit reward hacking), and use a CNN-based anomaly detector to vet learned trajectories at training time.

As we started to experiment with different tasks, we realized that it would be difficult and time-consuming to come up with representative datasets to train the anomaly detector on. Additionally, we realized that this wouldn’t necessarily be as generalizable as we had hoped, as some tasks have enough variance in their healthy trajectories that it would make anomaly detection challenging.

Given these challenges, we began exploring alternative approaches that could provide a more generalizable and easily-scalable solution. Instead of relying on manually curated datasets of healthy trajectories, we sought a method that could leverage external knowledge to evaluate behaviors with more flexibility. This led us to consider VLMs, which are pre-trained on vast amounts of real-world data and encode a rich understanding of physical dynamics, common-sense reasoning, and human expectations about movement and behavior. Additionally, since VLMs can process both visual and textual inputs, they offered a promising way to incorporate human-like evaluation into the reinforcement loop, but without the human.

Unlabeled Section

Lorem

References

- [1] Kate Baumli, Satinder Baveja, Feryal Behbahani, Harris Chan, Gheorghe Comanici, Sebastian Flennerhag, Maxime Gazeau, Kristian Holsheimer, Dan Horgan, Michael Laskin, Clare Lyle, Hussain Masoom, Kay McKinney, Volodymyr Mnih, Alexander Neitz, Dmitry Nikulin, Fabio Pardo, Jack Parker-Holder, John Quan, Tim Rocktäschel, Himanshu Sahni, Tom Schaul, Yannick Schroecker, Stephen Spencer, Richie Steigerwald, Luyu Wang, and Lei Zhang. Vision-language models as a source of rewards, 2024.
- [2] Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences, 2023.
- [3] Joel Lehman, Jeff Clune, Dusan Misevic, Christoph Adami, Lee Altenberg, Julie Beaulieu, Peter J. Bentley, Samuel Bernard, Guillaume Beslon, David M. Bryson, Patryk Chrabaszcz, Nick Cheney, Antoine Cully, Stéphane Doncieux, Fred C. Dyer, Kai Olav Ellefsen, Robert Feldt, Stephan Fischer, Stephanie Forrest, Antoine Frénoy, Christian Gagné, Leni K. Le Goff, Laura M. Grabowski, Babak Hodjat, Frank Hutter, Laurent Keller, Carole Knibbe, Peter Krcak, Richard E. Lenski, Hod Lipson, Robert MacCurdy, Carlos Maestre, Risto Miikkulainen, Sara Mitri, David E. Moriarty, Jean-Baptiste Mouret, Anh Nguyen, Charles Ofria, Marc Parizeau, David P. Parsons, Robert T. Pennock, William F. Punch, Thomas S. Ray, Marc Schoenauer, Eric Schulte, Karl Sims, Kenneth O. Stanley, François Taddei, Danesh Tarapore, Simon Thibault, Westley Weimer, Richard A. Watson, and Jason Yosinski. The surprising creativity of digital evolution: A collection of anecdotes from the evolutionary computation and artificial life research communities. *CoRR*, abs/1803.03453, 2018.
- [4] Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krasheninnikov, and David Krueger. Defining and characterizing reward hacking, 2022.