Example – openPDC on Raspberry Pi Zero, Raspbian Jessie Lite

This implementation summary uses the following software and hardware:

- Grid Protection Alliance openPDC Product Release Latest Stable Version 2.2.70.0
- Raspberry Pi Zero, V 1.2
- Raspbian Jessie compatible wireless network USB adapter
- ➤ HDMI monitor for use until networking is configured
- Raspbian Jessie Lite 2016-05-27
- Mono 4.4.2.11

Raspberry Pi Setup

- 33. Download Raspbian Jessie Lite image from: https://downloads.raspberrypi.org/raspbian lite latest
- 34. Write the image to an SD card.

https://www.raspberrypi.org/documentation/installation/installing-images/README.md

35. Boot the Raspberry Pi using the SD card. Run the Raspbian desktop Menu / Preferences / Raspberry Pi Configuration.

```
sudo raspi-config
```

- A. Expand the Filesystem
- B. Change the **pi** user's password from *raspberry* to a new password.
- C. Set the Internationalization Options for Locale and Timezone
- D. Set the Advanced Options to enable SSH and set the Pi's Hostname. This document uses the hostname: *openpdc-piz*
- E. Finish the raspi-config program
- F. Edit the /etc/default/keyboard file to set the keyboard configuration parameters. raspi-config does not reliably do this.

```
sudo nano /etc/default/keyboard
  # KEYBOARD CONFIGURATION FILE
  # Consult the keyboard(5) manual page.
  XKBMODEL="pc104"
  XKBLAYOUT="us"
  XKBVARIANT=""
  XKBOPTIONS=""
BACKSPACE="guess"
```

- G. Reboot the Pi
- 36. Configure the Pi's Ethernet to connect to the network. This example uses a third party USB wireless adapter.
 - A. Review the /etc/network/interfaces file to find the path to the wifi supplicant configuration file for the wlan# interface. Edit the supplicant configuration file to add the network SSID and PSK pass phrase.

```
cat /etc/network/interfaces
...
allow-hotplug wlan0
iface wlan0 inet manual
    wpa-conf /etc/wpa_supplicant/wpa_supplicant.conf
```

```
sudo nano /etc/wpa_supplicant/wpa_supplicant.conf
country=US
ctrl_interface=DIR=/var/run/wpa_supplicant GROUP=netdev
update_config=1
network={
    ssid="your-wifi-ssid"
    psk="your-wifi-passphrase"
}
```

- B. Reboot the Pi
- C. Make a note of the Pi's IP address sudo ifconfig -a
- D. Raspbian wireless setup details can be found at: https://www.raspberrypi.org/documentation/configuration/wireless-wireless-cli.md
- 37. By default, the Pi can now be accessed by remotely using a terminal running ssh
 - A. Remotely ping test the network connection. You may need to configure your DNS or PC's hosts file to associate the IP address to the new hostname.

```
ping <the Pi's IP address>
ping openpdc-piz
```

- B. For example, use **ssh** in a **git-bash** session in Windows ssh pi@openpdc-piz
- C. Run the standard update commands.

```
sudo apt-get update
sudo apt-get upgrade
```

38. Optional: Install git:

```
# Switch to Home folder
cd ~
# Install Git prerequisites - this takes a while
sudo apt-get install build-essential libssl-dev libcurl4-openssl-dev libexpat1-dev tk-
dev gettext -y
# Get
wget https://www.kernel.org/pub/software/scm/git/git-2.9.3.tar.gz
tar xzvf git-2.9.3.tar.gz
cd git-2.9.3
# Make Git takes a while, Install Git is quick
make prefix=/usr/local all
sudo make prefix=/usr/local install
# Test Git
git --version
```

39. Install unzip

sudo apt-get install unzip

Mono Installation on the Raspberry Pi Zero

40. Build Mono from a release tarball⁴³ Note: This process takes many hours.

```
A. Install dependencies. Our earlier git build procedure installed some of these. sudo apt-get install build-essential gettext -y sudo apt-get install libtool automake autoconf mono-devel -y
```

B. Download the source code tarball file and extract it

```
cd ~
wget http://download.mono-project.com/sources/mono/mono-4.4.2.11.tar.bz2
tar -xvjf mono-4.4.2.11.tar.bz2
cd mono-4.4.2
```

C. Configure the source code

```
./configure --prefix=/usr/local
```

2) Configure Results:

```
Engine:
```

```
Host: armv6l-unknown-linux-gnueabihf
Target: armv6l-unknown-linux-gnueabihf
```

GC: sgen and Included Boehm GC with typed GC and parallel mark

TLS: __thread

SIGALTSTACK: yes

Engine: Building and using the JIT

oprofile: no BigArrays: no DTrace: no

LLVM Back End: no (dynamically loaded: no)

Libraries:

.NET 4.6: yes
Xamarin.Android: no
Xamarin.iOS: no
Xamarin.WatchOS: no
Xamarin.TVOS: no
Xamarin.Mac: no

JNI support: IKVM Native

libgdiplus: assumed to be installed

zlib: system zlib

D. Run make to build and install

```
make
sudo make install
mono --version

Mono JIT compiler version 4.4.2 (Stable 4.4.2.11/f72fe45 Wed Aug 10 21:41:34
EDT 2016)
Copyright (C) 2002-2014 Novell, Inc, Xamarin Inc and Contributors. www.mono-
project.com

TLS:
__thread
SIGSEGV:
normal
Notifications: epoll
Architecture: armel,vfp+hard
Disabled:
none
```

⁴³ Derived from the procedures described on http://www.mono-project.com/docs/compiling-mono/linux/

Misc: softdebug

LLVM: supported, not enabled.

GC: sgen

openPDC Server openPDC Software Installation

41. Install openPDC

A. Download and run the installation script file using the Preservation option -p

cd ~/ mkdir GPA cd GPA

wget http://www.gridprotectionalliance.org/Products/openPDC/Scripts/installonenPDC sh

sudo bash install-openPDC.sh -p

42. Test openPDC

sudo mono /opt/openPDC/openPDC.exe -RunAsConsole

While the console is running, type **version** to verify the openPDC version, the type **exit** to quit.

43. Register openPDC to run automatically

sudo bash register-openPDC.sh

44. Test openPDC control commands. Test them one at a time and wait for each to complete before testing the next command.⁴⁴

sudo /opt/openPDC/openPDC stop
sudo /opt/openPDC/openPDC start
sudo /opt/openPDC/openPDC restart
sudo /opt/openPDC/openPDC pause
sudo /opt/openPDC/openPDC resume

- 45. Start openPDC on the openPDC Server and use **openPDCConsole** to assure openPDC is running mono /opt/openPDC/openPDCConsole.exe
 - A. Type **version** to check the openPDC version

App Domain: openPDCShell.exe, running on .NET 4.0.30319.42000 Machine Name: openpdc-piz

OS Version: Unix 4.4.13.0

Product Name: Raspbian GNU/Linux 8 (jessie) using Mono

Working Memory: 62.5939 MiB Execution Mode: 32-bit

Processors: 1

Code Base: opt/openPDC/openPDCShell.exe


Build Date: 8/14/2016 8:19:36 AM

Version: 2.2.70.0

- B. Type exit to quit openPDC
- 46. Enable Root Login for SSH. This is needed to copy files from Windows to the openPDC Server's data folder on the Pi.
 - A. Edit the server's /etc/ssh/sshd_config file:

sudo nano /etc/ssh/sshd_config

⁴⁴ If these command are executed in quick succession in a script, the abuse may result in openPDC not clearing its process lock file, *openPDC.pid*. In testing, this condition, was fixable by rebooting the Pi device.



Change: PermitRootLogin witout-password

To: PermitRootLogin yes

B. Restart the ssh service: sudo /etc/init.d/ssh restart

C. See: https://linuxconfig.org/enable-ssh-root-login-on-debian-linux-server for details.

47. Install **sqlite3** used for running the openPDC *add-user.sh* script sudo apt-get install sqlite3