

Deck



a Go package for presentations

DECK: a package for presentations

Deck is a package written in Go

That uses a singular markup language

With elements for text, lists, code, and graphics

All layout and sizes are expressed as percentages

Clients are interactive or create formats like PDF or SVG

Elements

Hello, World

A block of text, word-wrapped to a specified width.
You may specify size, font, color, and opacity.

```
package main
import "fmt"
func main() {
    fmt.Println("Hello, World")
}
```

<text>...</text>

bullet

- Point A
- Point B
- Point C
- Point D

plain

First item

Second item

The third item

the last thing

number

1. This

2. That

3. The other

4. One more

<list>...</list>


height



width

```
<image ... />
```


height (relative
to element
or canvas
width)



width


```
<rect ... />
```

height (relative
to element
or canvas
width)




width

```
<ellipse ... />
```

`<line ... />`



angle2 (90 deg)

The diagram shows a gray arc on a white background. The arc starts at a point on the right and curves upwards and to the left. The starting point is labeled 'x, y' and 'angle1 (0 deg)'. The ending point is labeled 'angle2 (90 deg)'.


x, y angle1 (0 deg)

<arc . . . />

control

start

end



<curve ... />

Markup and Layout

Start the deck	<code><deck></code>
Set the canvas size	<code><canvas width="1024" height="768" /></code>
Begin a slide	<code><slide bg="white" fg="black"></code>
Place an image	<code><image xp="70" yp="60" width="256" height="179" name="work.png" caption="Desk"/></code>
Draw some text	<code><text xp="20" yp="80" sp="3">Deck uses these elements</text></code>
Make a bullet list	<code><list xp="20" yp="70" sp="2" type="bullet"></code> <code>text, list, image</code> <code>line, rect, ellipse</code> <code>arc, curve</code>
End the list	<code></list></code>
Draw a line	<code><line xp1="20" yp1="10" xp2="30" yp2="10"/></code>
Draw a rectangle	<code><rect xp="35" yp="10" wp="4" hr="75" color="rgb(127,0,0)"/></code>
Draw an ellipse	<code><ellipse xp="45" yp="10" wp="4" hr="75" color="rgb(0,127,0)"/></code>
Draw an arc	<code><arc xp="55" yp="10" wp="4" hp="3" a1="0" a2="180" color="rgb(0,0,127)"/></code>
Draw a quadratic bezier	<code><curve xp1="60" yp1="10" xp2="75" yp2="20" xp3="70" yp3="10" /></code>
End the slide	<code></slide></code>
End of the deck	<code></deck></code>


Anatomy of a Deck

Deck uses these elements

- text, list, image
- line, rect, ellipse
- arc, curve



Desk



Text and List Markup

Position, size	<code><text xp="..." yp="..." sp="..."></code>
Block of text	<code><text ... type="block"></code>
Lines of code	<code><text ... type="code"></code>
Attributes	<code><text ... color="..." opacity="..." font="..." align="..."></code>
<hr/>	
Position, size	<code><list xp="..." yp="..." sp="..."></code>
Bullet list	<code><list ... type="bullet"></code>
Numbered list	<code><list ... type="number"></code>
Attributes	<code><list ... color="..." opacity="..." font="..." align="..."></code>


Common Attributes for text and list

<code>xp</code>	horizontal percentage
<code>yp</code>	vertical percentage
<code>sp</code>	font size percentage
<code>type</code>	"bullet", "number" (list), "block", "code" (text)
<code>align</code>	"left", "middle", "end"
<code>color</code>	SVG names ("maroon"), or RGB "rgb(127,0,0)"
<code>opacity</code>	percent opacity (0-100, transparent - opaque)
<code>font</code>	"sans", "serif", "mono"

Graphics Markup




```
<line xp1="5" yp1="75" xp2="20" yp2="70" sp="0.2"/>
```




```
<rect xp="10" yp="60" wp="15" hr="66.6" color="red"/>
```

```
<rect xp="15" yp="55" wp="10" hr="100" color="blue" opacity="30"/>
```




```
<ellipse xp="10" yp="35" wp="15" hr="66.66" color="green"/>
```

```
<ellipse xp="15" yp="30" wp="10" hr="100" color="blue" opacity="30"/>
```



```
<curve xp1="5" yp1="10" xp2="15" yp2="20" xp3="15" yp3="10" sp="0.3" color="red"/>
```

```
<arc xp="22" yp="10" wp="10" wp="10" a1="0" a2="180" sp="0.2" color="blue"/>
```



102030405060708090

908070605040302010

Percent Grid


10%, 50%

Hello

50%, 50%



90%, 50%



Percentage-based layout

bullet

- Point A
- Point B
- Point C
- Point D

plain

First item
Second item
The third item
the last thing

number

1. This
2. That
3. The other
4. One more

<list>...</list>

bullet

- Point A
- Point B
- Point C
- Point D

plain

First item

Second item

The third item

the last thing

number

1. This
2. That
3. The other
4. One more

```
<list>...</list>
```

Design Examples



hello, world

Top

Left

Right

Bottom

20%

30%

70%

20%

Header (top 20%)

Summary
(30%)

Detail
(70%)

Footer (bottom 20%)

BOS



Virgin America 351

Gate B38

8:35am

SFO

On Time

JFK



IND

US Airways 1207

Gate C31C

5:35pm

Delayed

AAPL	503.73	-16.57 (3.18%)
AMZN	274.03	+6.09 (2.27%)
GOOG	727.58	-12.41 (1.68%)

Two Columns

One

Two

Three

Four



Tree and Sky

Five

Six


Seven

Eight



Rocks

This is not a index card



Rich

Can't buy me love

Bliss

Worse

Better

Misery

We have each other

Poor

Code


```
package main
import (
    "github.com/ajstarks/svggo"
    "os"
)

func main() {
    canvas := svg.New(os.Stdout)
    width, height := 500, 500
    a, ai, ti := 1.0, 0.03, 10.0

    canvas.Start(width, height)
    canvas.Rect(0, 0, width, height)
    canvas.Gstyle("font-family:serif;font-size:144pt")

    for t := 0.0; t <= 360.0; t += ti {
        canvas.TranslateRotate(width/2, height/2, t)
        canvas.Text(0, 0, "i", canvas.RGBA(255, 255, 255, a))
        canvas.Gend()
        a -= ai
    }
    canvas.Gend()
    canvas.End()
}
```

Output



A few months ago, I had a look at the brainchild of a few serious heavyweights working at Google. Their project, the Go programming language, is a static typed, c lookalike, semicolon-less, self formatting, package managed, object oriented, easily parallelizable, cluster fuck of genius with an unique class inheritance system. It doesn't have one.

The Go Programming Language

is a static typed,
c lookalike,
semicolon-less,
self formatting,
package managed,
object oriented,
easily parallelizable,
cluster fuck of genius
with an unique class inheritance system.

The Go Programming Language

is a static typed,
c lookalike,
semicolon-less,
self formatting,
package managed,
object oriented,
easily parallelizable,
cluster fuck of genius
with an unique class inheritance system.

The Go Programming Language

is a static typed, c lookalike, semicolon-less, self formatting,
package managed, object oriented, easily parallelizable,
cluster fuck of genius with an unique class inheritance system.

It doesn't have one.

So, the next time you're about to
make a subclass, think hard and ask
yourself

what would Go do

Andrew Mackenzie-Ross, <http://pocket.co/sSc56>



Python and Ruby programmers come to Go because they don't have to surrender much expressiveness, but gain performance and get to play with concurrency.

Less is exponentially more
Rob Pike

The image features a full-page background of a sky with dark, textured blue clouds. A bright sunburst is visible in the upper center, with light rays breaking through the cloud cover. A horizontal band of dark grey color spans the middle of the image, serving as a backdrop for the text.

You must not blame me if I do talk to the clouds.

FOR, LO,


the winter is past,

the rain is over and gone;

The flowers appear on the earth;

the time for the singing of birds is come,

and the voice of the turtle is heard in our land.



Clients

```
package main
import (
    "log"
    "github.com/ajstarks/deck"
)
func main() {
    presentation, err := deck.Read("deck.xml", 1024, 768) // open the deck
    if err != nil {
        log.Fatal(err)
    }
    for _, slide := range presentation.Slide {           // for every slide...
        for _, t := range slide.Text {                  // process the text elements
            x, y, size := deck.Dimen(presentation.Canvas, t.Xp, t.Yp, t.Sp)
            slideText(x, y, size, t)
        }
        for _, l := range slide.List {                  // process the list elements
            x, y, size := deck.Dimen(presentation.Canvas, l.Xp, l.Yp, l.Sp)
            slideList(x, y, size, l)
        }
    }
}
```

A Deck Client


Process

deck code

interactive

PDF

SVG




```

func main() {
    benchmarks := []Bardata{
        {"Macbook Air", 154.701},
        {"MacBook Pro (2008)", 289.603},
        {"BeagleBone Black", 2896.037},
        {"Raspberry Pi", 5765.568},
    }
    ts := 2.5
    hts := ts / 2
    x := 10.0
    bx1 := x + (ts * 12)
    bx2 := bx1 + 50.0
    y := 60.0
    maxdata := 5800.0
    linespacing := ts * 2.0
    text(x, y+20, "Go 1.1.2 Build and Test Times", ts*2, "black")
    for _, data := range benchmarks {
        text(x, y, data.label, ts, "rgb(100,100,100)")
        bv := vmap(data.value, 0, maxdata, bx1, bx2)
        line(bx1, y+hts, bv, y+hts, ts, "lightgray")
        text(bv+0.5, y+(hts/2), fmt.Sprintf("%.1f", data.value), hts, "rgb(127,0,0)")
        y -= linespacing
    }
}


```

Generating a Barchart

Go 1.1.2 Build and Test Times



```
$ (echo '<deck><slide>'; go run deckbc.go; echo '</slide></deck>')
```



```
go get github.com/ajstarks/deck/vgdeck
```



```
go get github.com/ajstarks/deck/pdfdeck
```



```
go get github.com/ajstarks/deck/svgdeck
```

pdfdeck [options] file.xml...

- sans, -serif, -mono [font] specify fonts
- pagesize [w,h, or Letter, Legal, Tabloid, A2-A5, ArchA, Index, 4R, Widescreen]
- stdout (output to standard out)
- outdir [directory] directory for PDF output
- fontdir [directory] directory containing font information
- author [author name] set the document author
- title [title text] set the document title
- grid [percent] draw a percent grid on each slide

`svgdeck [options] file.xml...`

- `-sans, -serif, -mono [font]` specify fonts
- `-pagesize [Letter, Legal, A3, A4, A5]`
- `-pagewidth [canvas width]`
- `-pageheight [canvas height]`
- `-stdout` (output to standard out)
- `-outdir [directory]` directory for PDF output
- `-title [title text]` set the document title
- `-grid [percent]` draw a percent grid on each slide

`vgdeck [options] file.xml...`

`-loop [duration]` loop, pausing [duration] between slides

`-slide [number]` start at slide number

`-w [width]` canvas width

`-h [height]` canvas height

`-g [percent]` draw a percent grid

vgdeck Commands

`+, Ctrl-N, [Return]`

Next slide

`-, Ctrl-P, [Backspace]`

Previous slide

`^, Ctrl-A`

First slide

`$, Ctrl-E`

Last slide

`r, Ctrl-R`

Reload

`x, Ctrl-X`

X-Ray

`/, Ctrl-F [text]`

Search

`s, Ctrl-S`

Save

`q`

Quit

github.com/ajstarks/deck



ajstarks@gmail.com
@ajstarks