




For Information Displays

Anthony Starks
@ajstarks



Go is great on the back end



But sometimes it's about the picture

Information Displays

Packages and Tools

Lots of pictures

Why Go?



Edward Tufte

Display data for precise, effective, quick analysis,
Small multiples, optimizing the data-ink ratio
Visual and beautiful evidence.



Nigel Holmes

Designing for the context: The data visualizer
asks: “What’s the data?”, the infographics
designer: “What’s the Story?”

An interesting arrangement
of text and graphics, designed
to convey a message

I hate pushing pixels

Programs are much
better at it



Precise

Efficient

Consistent



Fatih Arslan

@fatih

Following



If you don't learn your tool in and out,
the tool will block you during the
progress. Don't let the tool disrupt you.
If there is too much disruption, it's time
to switch to a new tool. If there is no
such tool, it's time to write your own.


4:43 AM - 12 Apr 2018

SVGo




[go get github.com/ajstarks/svgo/...](https://github.com/ajstarks/svgo/)

OpenVG



[go get github.com/ajstarks/openvg](https://github.com/ajstarks/openvg)

Deck



[go get github.com/ajstarks/deck/](https://github.com/ajstarks/deck/)
[go get github.com/ajstarks/deck/generate](https://github.com/ajstarks/deck/generate)
[go get github.com/ajstarks/deck/cmd/pdfdeck/](https://github.com/ajstarks/deck/cmd/pdfdeck/)
[go get github.com/ajstarks/deck/cmd/dchart/](https://github.com/ajstarks/deck/cmd/dchart/)





Scale



Roundrect



rgb(164,198,57)

Line

Circle

Arc

Line

Rect


Element

Arguments

Rect (100,200,250,125)

```
<rect x="100" y="200" width="250" height="125"/>
```

(100, 200)



125

250

Element

Rect (100,200,250,125,

"fill:gray;stroke:blue")

CSS Style

```
<rect x="100" y="200" width="250" height="125"  
      style="fill:gray;stroke:blue"/>
```

(100, 200)



125

250

Element

Rect (100,200,250,125,

`id='box'`, `fill='gray'`, `stroke='blue'`)

Arguments

Attributes

```
<rect x="100" y="200" width="250" height="125"  
      id='box' fill='gray' stroke='blue' />
```

(100, 200)



125

250

```
package main

import (
    "github.com/ajstarks/svg"
    "os"
)

func main() {
    canvas := svg.New(os.Stdout)
    width := 700
    height := 500
    style := "font-size:72pt;fill:white;text-anchor:middle"

    canvas.Start(width, height)
    canvas.Rect(0, 0, width, height)
    canvas.Circle(width/2, height, width/2, "fill:rgb(77, 117, 232)")
    canvas.Text(width/2, height*3/4, "hello, world", style)
    canvas.End()
}
```



localhost:1999/hwsvg.go

```
package main

import (
    "github.com/ajstarks/svg"
    "os"
)

func main() {
    canvas := svg.New(os.Stdout)
    width := 700
    height := 500
    style := "font-size:72pt;fill:white;text-anchor:middle"

    canvas.Start(width, height)
    canvas.Rect(0, 0, width, height)
    canvas.Circle(width/2, height, width/2, "fill:rgb(77, 117, 232)")
    canvas.Text(width/2, height*3/4, "hello, world", style)
    canvas.End()
}
```

(Shift-Enter to compile and run.) Compile and run after each keystroke

The screenshot shows a web-based development environment. On the left, a code editor displays a Go program named 'hwsvg.go'. The code creates a new SVG canvas from standard output, sets its width and height, draws a blue circle at the center, and prints the text 'hello, world' in white inside it. On the right, the browser's main content area shows the resulting SVG image: a large blue circle centered on a black background, with the text 'hello, world' written in white inside the circle.

```
localhost:1999/hwsvg.go
```

```
package main

import (
    "github.com/ajstarks/svggo"
    "os"
)


func main() {
    canvas := svg.New(os.Stdout)
    width := 700
    height := 500
    style := "font-size:72pt;fill:white;text-anchor:middle"

    canvas.Start(width, height)
    canvas.Rect(0, 0, width, height)
    canvas.Circle(width/2, height, width/2, "fill:rgb(255,0,0)")
    canvas.Text(width/2, height*3/4, "hello, Mars", style)
    canvas.End()
}
```


(Shift-Enter to compile and run.) Compile and run after each keystroke

The screenshot shows a web-based development environment. On the left, a code editor displays a Go program that generates an SVG visualization. The code uses the `svggo` library to create a red circle centered at (350, 375) with a radius of 350 pixels, filled with red. It also contains white text with a font size of 72pt that reads "hello, Mars". The text is positioned at the bottom-right of the circle. The browser's address bar shows the URL `localhost:1999/hwsvg.go`. The overall interface has a clean, modern look with a light gray background.

<https://ajstarks.org:1958/>




clock




rshape




face




funnel




cube



pacman



rotext




mondrian



tux



flower




lewitt



concentric

Data

```
<thing top="100" left="100" sep="100">  
  <item width="50" height="50" name="Little" color="blue">This is small</item>  
  <item width="75" height="100" name="Med"      color="green">This is medium</item>  
  <item width="100" height="200" name="Big"      color="red">This is large</item>  
</thing>
```



Little:This is small/blue

Med:This is medium/green


Big:This is large/red

Picture

```

<barchart title="2015 MacBook Benchmarks">
    <note>Source: AnandTech, April 14, 2015</note>
    <bdata scale="0,6000,1000"
        title="Mozilla Kraken 1.1 (native browser, milliseconds)">
        <bitem value="1729.7" name="Lenovo Yoga 3 Pro"/>
        <bitem value="1997.0" name="ASUS Zenbook UX305"/>
        <bitem color="steelblue" value="2589.0" name="12 inch MacBook"/>
        <bitem value="3621.7" name="Google Nexus 9"/>
        <bitem value="4014.3" name="Apple iPad Air 2"/>
        <bitem value="4296.7" name="NVIDIA Shield Tablet"/>
        <bitem value="5028.2" name="Apple iPad Air"/>
    </bdata>
</barchart>

```




2015 MacBook Benchmarks

Source: AnandTech, April 14, 2015

f50 sunset

```
https://api.flickr.com/services/rest/?  
method=flickr.photos.search  
&api_key=...  
&text=sunset  
&per_page=50  
&sort=interestingness-desc
```

```
<?xml version="1.0" encoding="utf-8"?>  
<rsp stat="ok">  
  <photos page="1" pages="105615" perpage="50" total="5280747">  
    <photo id="4671838925" ... secret="b070f3363e" server="4068" farm="5" ... />  
    <photo id="3590142202" ... secret="c46752e4d8" server="2441" farm="3" .../>  
    ...  
  </photos>  
</rsp>
```





SVGo Clients



benchpng.txt

image/png package: Go 1.3 vs Go 1.4





```
structlayout -json bytes Reader | structlayout-svg -t bytes.Reader > reader.svg
```

Go Programming Language Release History


4Q 2009




1Q 2010



2Q 2010



3Q 2010



4Q 2010





Sample Bullet Graph


The bullet graph features a single, primary measure (for example, current year-to-date revenue) compares that measure to one or more other measures to enrich its meaning, for example, compared to a target), and displays it in the context of qualitative ranges of performance, such as poor, satisfactory, and good.




PLANNING TO PLAN








Apple Purchases and Stock Price



Twitter Update Frequency



You are here



JONES

- LAYER TENNIS SEASON 4 WEEK 6 MATCH COMMENTARY BY MIKE MONTEIRO -

MONTIEL



DKNG

- LAYER TENNIS SEASON 4 WEEK 7 MATCH COMMENTARY BY JOHN GRUBER -

DDL



ANDERSON

- LAYER TENNIS SEASON 4 PLAYOFF QUARTERFINAL COMMENTARY BY BRYAN BEDELL -

DKNG



CONTINO
CASSARO



PUTNAM
STOCKS



WHITE
TAYLOR



HALL
WARREN



STRAWBERRY LUNA
DOUBLENAUT



JONES
MONTIEL



DKNG
DDL



SHAWNA X
STEVENS



TAYLOR
JONES



PUTNAM
RAJKUMAR



REYES
WHITE



ANDERSON
DKNG



TAYLOR
WHITE



RAJKUMAR
ANDERSON



ANDERSON
WHITE
















```
canvas.Def()  
canvas.Gid("unit")  
canvas.Polyline(xl, yl, "fill:none")  
canvas.Polygon(xp, yp)  
canvas.Gend()
```




```
canvas.Gid("runit")  
canvas.TranslateRotate(150, 180, 180)  
canvas.Use(0, 0, "#unit")  
canvas.Gend()  
canvas.Gend()  
canvas.DefEnd()
```



```
for y := 0; < height; y += 130 {  
    for x := 100; x < width; x+=100 {  
        canvas.Use(x, y, "#unit")  
        canvas.Use(x, y, "#runit")  
    }  
}
```

OpenVG



- Circle
- Ellipse
- Rectangle
- Rounded Rectangle
- Line
- Polyline
- Polygon
- Arc
- Quadratic Bezier
- Cubic Bezier
- Image

OpenVG on the Raspberry Pi



Why I use Go



Anthony Starks
@ejstars
ajstars@gmail.com



```
package main
import "fmt"

func main() {
    fmt.Println("hello, world")
}
```

This is the traditional hello, world program.
It's six lines long, and imports the fmt package,
leading some to be surprised at the size of the resulting binary.

```
package main

import (
    "bufio"
    "github.com/ajstarks/openvg"
    "os"
)

func main() {
    width, height := openvg.Init()

    w2 := openvg.VGfloat(width / 2)
    h2 := openvg.VGfloat(height / 2)
    w := openvg.VGfloat(width)

    openvg.Start(width, height)                      // Start the picture
    openvg.BackgroundColor("black")                  // Black background
    openvg.FillRGB(44, 100, 232, 1)                // Big blue marble
    openvg.Circle(w2, 0, w)                         // The "world"
    openvg.FillColor("white")                       // White text
    openvg.TextMid(w2, h2, "hello, world", "serif", width/10) // Greetings
    openvg.End()                                    // End the picture
    bufio.NewReader(os.Stdin).ReadBytes('\n') // Pause until [RETURN]
    openvg.Finish()                                // Graphics cleanup
}
```



OpenVG Functions

Circle (x, y, r VGfloat)

Ellipse (x, y, w, h VGfloat)

Rect (x, y, w, h VGfloat)

Roundrect(x, y, w, h, rw, rh VGfloat)

Line (x1, y1, x2, y2 VGfloat)

Polyline (x, y []VGfloat)

Polygon (x, y []VGfloat)

Arc (x, y, w, h, sa, aext VGfloat)

Qbezier (sx, sy, cx, cy, ex, ey VGfloat)

Cbezier (sx, sy, cx, cy, px, py, ex, ey VGfloat)

Image (x, y VGfloat, w, h int, s string)

Text (x, y VGfloat, s, font string, size int)

TextMid (x, y VGfloat, s, font string, size int)

TextEnd (x, y VGfloat, s, font string, size int)

Possible Light Rain

83°



90% Chance of precipitation

Thursday August 2

6:26 pm

'All I Did Was Be Black': Police Are Called on College Student Eating Lunch

Tennessee Primary Election Results

Bipartisan Senate Group Pushes 'Crushing' Punishments to Thwart Russia

Trump Officials on Russian Meddling Threat: Democracy 'Is in the Crosshairs'

Are Journalists the Enemy of the People? Ivanka Trump Says They're Not

Mostly Cloudy

47°



(feels like 45°)

Sunday March 13

3:03 am

Farhad and Mike Discuss the Apple Case and a Go-Playing Computer Program
Getting the Weather Report From Windows
The Government Answers Apple in the iPhone Case
Apple and U.S. Bitterly Turn Up Volume in iPhone Privacy Fight
F.C.C. Proposes Privacy Rules for Internet Providers



MECHANICAL DRAWING

GEOMETRICAL DRAWING

Mostly Cloudy

36° 

(feels like 29°)

29% Chance of precipitation

Tuesday February 23

9:41 pm

Justice Alito Addresses Prospect of an 8-Member Court

Michigan: State Senate Approves Aid to Help Flint Residents Pay Water Bills

Told to 'Take the Gloves Off,' John Kasich Says the Race Is Out of His Hands

Utah: Polygamist Sect Leaders Are Arrested on Fraud Charges

North Carolina: State Lawmakers Target Restroom Anti-Bias Law in Charlotte



HDMI Pi

Clear

66°



Friday April 14

5:55 pm

White House to Keep Its Visitor Logs Secret

Georgia Officers are Fired After Kicking Man at Traffic Stop

Does a Uniform Keep Officers in Line? The Baltimore Chief Thinks So

Wisconsin Man Who Mailed Manifesto to Trump Is Captured After 10-Day Manhunt

California Today: GoPros, Audiobooks and Other Perks of the Library




```
func main() {  
  
    //...  
  
    dateticker := time.NewTicker(1 * time.Minute)  
    weatherticker := time.NewTicker(5 * time.Minute)  
    headticker := time.NewTicker(10 * time.Minute)  
    sigint := make(chan os.Signal, 1)  
    signal.Notify(sigint, os.Interrupt)  
  
    for {  
        select {  
            case <-weatherticker.C:  
                canvas.weather(*location)  
            case <-dateticker.C:  
                canvas.clock(*smartcolor)  
            case <-headticker.C:  
                canvas.headlines(*section, *thumb)  
            case <-sigint:  
                openvg.Finish()  
                os.Exit(0)  
        }  
    }  
}
```




```
func main() {  
  
    //...  
  
    dateticker := time.NewTicker(1 * time.Minute)  
    weatherticker := time.NewTicker(5 * time.Minute)  
    headticker := time.NewTicker(10 * time.Minute)  
    sigint := make(chan os.Signal, 1)  
    signal.Notify(sigint, os.Interrupt)  
  
    for {  
        select {  
            case <-weatherticker.C:  
                canvas.weather(*location)  
            case <-dateticker.C:  
                canvas.clock(*smartcolor)  
            case <-headticker.C:  
                canvas.headlines(*section, *thumb)  
            case <-sigint:  
                openvg.Finish()  
                os.Exit(0)  
        }  
    }  
}
```



```
func main() {  
  
    //...  
  
    dateticker := time.NewTicker(1 * time.Minute)  
    weatherticker := time.NewTicker(5 * time.Minute)  
    headticker := time.NewTicker(10 * time.Minute)  
    sigint := make(chan os.Signal, 1)  
    signal.Notify(sigint, os.Interrupt)  
  
    for {  
        select {  
            case <-weatherticker.C:  
                canvas.weather(*location)  
            case <-dateticker.C:  
                canvas.clock(*smartcolor)  
            case <-headticker.C:  
                canvas.headlines(*section, *thumb)  
            case <-sigint:  
                openvg.Finish()  
                os.Exit(0)  
        }  
    }  
}
```



```
func main() {  
  
    //...  
  
    dateticker := time.NewTicker(1 * time.Minute)  
    weatherticker := time.NewTicker(5 * time.Minute)  
    headticker := time.NewTicker(10 * time.Minute)  
    sigint := make(chan os.Signal, 1)  
    signal.Notify(sigint, os.Interrupt)  
  
    for {  
        select {  
            case <-weatherticker.C:  
                canvas.weather(*location)  
            case <-dateticker.C:  
                canvas.clock(*smartcolor)  
            case <-headticker.C:  
                canvas.headlines(*section, *thumb)  
            case <-sigint:  
                openvg.Finish()  
                os.Exit(0)  
        }  
    }  
}
```




deck



a Go package for presentations

```
<deck>
  <slide bg="black" fg="white">
    <ellipse xp="50" yp="0" wp="100" hr="100" color="blue"/>
    <text      xp="50" yp="25" sp="10" align="c">hello, world</text>
  </slide>
</deck>
```



```
Start the deck <deck>

Set the canvas size <canvas width="1200" height="900"/>

Begin a slide <slide bg="white" fg="black">

Draw some text <text xp="50" yp="90" sp="5" align="c">Deck elements</text>

Place an image <image name="follow.jpg" caption="Dreams" xp="70" yp="60" width="640" height="480" scale="80"/>

Make a bullet list <list xp="10" yp="70" sp="3" type="bullet">

    <li>text, image, list</li>
    <li>rect, ellipse, polygon</li>
    <li>line, arc, curve</li>

End the list </list>

Draw a rectangle <rect xp="15" yp="20" wp="8" hp="6" color="rgb(127,0,0)"/>

Draw a ellipse <ellipse xp="27.5" yp="20" wp="8" hp="6" color="rgb(0,127,0)"/>

Draw a polygon <polygon xc="37 37 45" yc="17 23 20" color="rgb(0,0,127)"/>

Draw a line <line xp1="50" yp1="20" xp2="60" yp2="20"/>

Draw an arc <arc xp="70" yp="20" wp="10" hp="8" a1="0" a2="180" color="rgb(0,0,127)"/>




Draw a bezier <curve xp1="80" yp1="20" xp2="95" yp2="30" xp3="90" yp3="20"/>

End the slide </slide>

End of the deck </deck>
```

Deck elements

- text, image, list
- rect, ellipse, polygon
- line, arc, curve



Percent Grid


10%, 50%

Hello


50%, 50%



90%, 50%



Percentage-based layout



Landscape



Portrait

Scaling the canvas

Data Process

deck

PDF (pdfdeck)

PNG (pngdeck)

SVG (svgdeck)

OpenVG (vgdeck)

deck/generate text and list functions

- Text** (x, y float64, s, font string, size float64, color string, op ...float64)
- TextBlock** (x, y float64, s, font string, size, margin float64, color string, op ...float64)
- TextMid** (x, y float64, s, font string, size float64, color string, op ...float64)
- TextEnd** (x, y float64, s, font string, size float64, color string, op ...float64)
- Code** (x, y float64, s string, size, margin float64, color string, op ...float64)
- List** (x, y, size, spacing, wrap float64, items []string, ltype, font, color string)

deck/generate graphic functions

Image (x, y float64, w, h int, name, link string)

Rect (x, y, w, h float64, color string, op ...float64)

Square (x, y, w float64, color string, op ...float64)

Ellipse (x, y, w, h float64, color string, op ...float64)

Circle (x, y, w float64, color string, op ...float64)

Polygon (x, y []float64, color string, op ...float64)


Line (x1, y1, x2, y2, size float64, color string, op ...float64)

Arc (x, y, w, h, size, a1, a2 float64, color string, op ...float64)

Curve (x1, y1, x2, y2, x3, y3, size float64, color string, op ...float64)

```
func main() {
    deck := generate.NewSlides(os.Stdout, 1600, 900) // 16x9 deck to stdout
    deck.StartDeck() // start the deck
```

```
deck.StartSlide("rgb(180,180,180)")
// ...
deck.EndSlide()
```



```
deck.StartSlide("blanchedalmond")
// ...
deck.EndSlide()
```




```
deck.StartSlide("black", "white")
// ...
deck.EndSlide()
```



```
deck.EndDeck() // end the deck
}
```

```
// Text alignment
deck.StartSlide("rgb(180,180,180)")
deck.Text(50, 80, "Left", "sans", 10, "black")
deck.TextMid(50, 50, "Center", "sans", 10, "gray")
deck.TextEnd(50, 20, "Right", "sans", 10, "white")
deck.Line(50, 100, 50, 0, 0.2, "black", 20)
deck.EndSlide()
```



```
// List
items := []string{"First", "Second", "Third", "Fourth", "Fifth"}
deck.StartSlide("blanchedalmond", "black")
deck.Text(10, 80, "Important Items", "sans", 5, "")
deck.List(10, 60, 4, 1.4, 50, items, "bullet", "sans", "red")
deck.EndSlide()
```

Important Items

- First
- Second
- Third
- Fourth
- Fifth

```
// Picture with text annotation
quote := "Tony Stark was able to build this in a cave. With a box of scraps!"
deck.StartSlide("black", "white")
deck.Image(50, 50, 1600, 681, "cave.png", "https://youtu.be/MtntTvuv8Aw")
deck.Rect(70, 60, 40, 40, "black", 40)
deck.TextBlock(45, 70, quote, "sans", 5, 45, "")
deck.EndSlide()
```



Tony Stark was able
to build this in a cave.
With a box of scraps!

A View of User Experience: Designing for People

Anthony Starks / ajstarks@gmail.com / @ajstarks

Design



What works good is better than what looks good, because what works good lasts.

Ray Eames

Designing for People

title A View of User Experience: Designing for People Anthony Starks / ajstarks@gmail.com / @ajstarks

section Design gray white

caption eames.png Ray Eames What works good is better than what looks good, because what works good last

capgen slides.txt | pdfdeck ... > slides.pdf

```

deck
  canvas 1200 900
    slide "white" "black"
      ctext "Deck elements" 50 90 5
      cimage "follow.jpg" "Dreams" 70 60 640 480 50

    blist 10 70 3
      li "text, image, list"
      li "rect, ellipse, polygon"
      li "line, arc, curve"
    elist

    rect   15 20 8 6           "rgb(127,0,0)"
    ellipse 27.5 20 8 6        "rgb(0,127,0)"
    polygon "37 37 45" "17 23 20" "rgb(0,0,127)"
    line    50 20 60 20 0.2    "rgb(127,0,0)"
    arc     70 20 10 8 0 180 0.2 "rgb(0,127,0)"
    curve   80 20 95 30 90 20 0.2 "rgb(0,0,127)"

  eslide
edeck

```

Deck elements

- text, image, list
- rect, ellipse, polygon
- line, arc, curve



Dreams



decksh

Deck Web API

deckd -dir [start dir] -listen [address:port] -maxupload [bytes]

GET	/	List the API
GET	/deck/	List the content on the server
GET	/deck/?filter=[type]	List content filtered by deck, image, video
POST	/deck/content.xml?cmd=1s	Play a deck with the specified duration
POST	/deck/content.xml?cmd=stop	Stop playing a deck
POST	/deck/content.xml?slide=[num]	Play deck starting at a slide number
DELETE	/deck/content.xml	Remove content
POST	/upload/ Deck:content.xml	Upload content
POST	/table/ Deck:content.txt	Generate a table from a tab-separated list
POST	/table/?textsize=[size]	Specify the text size of the table
POST	/media/ Media:content.mov	Play the specified video



René Magritte

The False Mirror

LG



Design Examples

Top

Left

Right

Bottom

10%

30%

70%

10%

Header (top 10%)

Summary
(30%)

Detail
(70%)

Footer (bottom 10%)

My Story

Section

One

Two

Three

Four

Five

Six

Document Links

Add web and mailto links with the link attribute of the text element.

Once rendered as a PDF, clicking on the link opens the default browser or email client.

The image contains two screenshots. The top screenshot shows a PDF viewer window titled "deck-fira-4x3.pdf (page 53 of 57)". It displays a quote in white text on a dark blue background: "Python and Ruby programmers come to Go because they don't have to surrender much expressiveness, but gain performance and get to play with concurrency." Below the quote, it says "Less is exponentially more" and "Rob Pike". The bottom screenshot shows a web browser window titled "command center: Less is e...". The URL in the address bar is "commandcenter.blogspot.com/2012/06/less-is-exp...". The page content is identical to the quote in the PDF, along with some additional text and a "Read more" link.

Python and Ruby programmers come to Go because they don't have to surrender much expressiveness, but gain performance and get to play with concurrency.

Less is exponentially more
Rob Pike

What you're given is a set of powerful but easy to understand, easy to use building blocks from which you can assemble—compose—a solution to your problem. It might not end up quite as fast or as sophisticated or as ideologically motivated as the solution you'd write in some of those other languages, but it'll almost certainly be easier to write, easier to read, easier to understand, easier to maintain, and maybe safer.

To put it another way, oversimplifying of course:

Python and Ruby programmers come to Go because they don't have to surrender much expressiveness, but gain performance and get to play with concurrency.

C++ programmers *don't* come to Go because they have fought hard to gain exquisite control of their programming domain, and don't want to surrender any of it. To them, software isn't just about getting the job done, it's about doing it a certain way.

The issue, then, is that Go's success would contradict their world view.

BOS



SFO

Virgin America 351

Gate B38

8:35am

On Time

JFK



IND

US Airways 1207

Gate C31C

5:35pm


Delayed

Flight Information

Los Angeles (LAX)



New York/Newark (EWR)



Distance Traveled

1,958 mi

3,151 km

Distance to Destination


596 mi

798 km

Time to Destination

Estimated time of arrival

Local time of arrival



1:20

12:14 am

12:14 am

Ground speed




Headwind



Outside Temperature



Current Altitude



AAPL	179.98	3.04 (1.72%)
AMZN	1578.89	27.03 (1.74%)
FB	185.23	2.89 (1.58%)
GOOGL	1160.84	31.46 (2.79%)
MSFT	96.54	2.11 (2.23%)

AAPL	181.72	1.74 (0.97%)
AMZN	1598.39	19.50 (1.24%)
FB	184.76	-0.47 (-0.25%)
GOOGL	1165.93	5.09 (0.44%)
MSFT	96.77	0.23 (0.24%)

AAPL	175.30	-2.72 (-1.53%)
AMZN	1544.93	-26.75 (-1.70%)
FB	172.56	-12.53 (-6.77%)
GOOGL	1100.07	-34.35 (-3.03%)
MSFT	92.89	-1.71 (-1.81%)

```

func stockslide(deck *generate.Deck, symbols []string) {
    x := left
    y := top

    rintr := (top-bottom)/float64(len(symbols))
    size := rintr/2.5
    cintr := size*4

    var color string
    for _, s := range symbols {
        stock, err := stockapi(s)
        if err != nil || stock.Symbol == "" {
            continue
        }
        if stock.Change < 0 {
            color = negcolor
        } else {
            color = poscolor
        }
        deck.Text(x, y, stock.Symbol, "sans", size, "")
        x += cintr * 2
        deck.TextEnd(x, y, fmt.Sprintf("%.2f", stock.Price), "sans", size, "")
        x += cintr
        deck.TextEnd(x, y, fmt.Sprintf("%.2f", stock.Change), "sans", size, color)
        x += cintr
        deck.TextEnd(x, y, fmt.Sprintf("(%.2f%%)", stock.PctChange), "sans", size, color)
        x = left
        y -= rintr
    }
    deck.Text(footx, footy, time.Now().Format("2006-01-02 15:04:05"), "sans", 1.5, "yellow")
}

```

AAPL	181.72	1.74 (0.97%)
AMZN	1598.39	19.50 (1.24%)
FB	184.76	-0.47 (-0.25%)
GOOGL	1165.93	5.09 (0.44%)
MSFT	96.77	0.23 (0.24%)

2018-03-12 21:05:06

So, the next time you're
about to make a subclass,
think hard and ask yourself

what would Go do




Andrew Mackenzie-Ross



go

bug	start a bug report
build	compile packages and dependencies
clean	remove object files and cached files
doc	show documentation for package or symbol
env	print Go environment information
fix	update packages to use new APIs
fmt	gofmt (reformat) package sources
generate	generate Go files by processing source
get	download and install packages and dependencies
install	compile and install packages and dependencies
list	list packages or modules
mod	module maintenance
run	compile and run Go program
test	test packages
tool	run specified go tool
version	print Go version
vet	report likely mistakes in packages

Go Proverbs

-  Don't communicate by sharing memory, share memory by communicating.
-  Concurrency is not parallelism.
-  Channels orchestrate; mutexes serialize.
-  The bigger the interface, the weaker the abstraction.
-  Make the zero value useful.
-  interface{} says nothing.
-  Gofmt's style is no one's favorite, yet gofmt is everyone's favorite.
-  A little copying is better than a little dependency.
-  Syscall must always be guarded with build tags.
-  Cgo must always be guarded with build tags.
-  Cgo is not Go.
-  With the unsafe package there are no guarantees.
-  Clear is better than clever.
-  Reflection is never clear.
-  Errors are values.
-  Don't just check errors, handle them gracefully.
-  Design the architecture, name the components, document the details.
-  Documentation is for users.
- Don't panic.



Don't communicate
by sharing memory,
share memory by
communicating.




The bigger the interface,
the weaker the abstraction.



Make the zero
value useful.

Chapter V



Advice from a Caterpillar

THE Caterpillar and Alice looked at each other for some time in silence: at last the Caterpillar took the hookah out of its mouth, and addressed her in a languid, sleepy voice. “Who are you?” said the Caterpillar. This was not an encouraging opening for a conversation. Alice replied, rather shyly, “I—I hardly know, sir, just at present—at least I know who I was when I got up this morning, but I think I must have been changed several times since then.”



You promised to tell me our history, you know," said Alice, "and why it is you hate—C and D, she added in a whisper, half afraid that it would be offended again. Mine is a long and a sad tale!" said the Mouse, turning to Alice, and sighing. "It is a long tail, certainly," said Alice, looking down with wonder at the Mouse's tail; "but why do you call it sad?" And she kept on puzzling about it while the Mouse was speaking, so that her idea of the tale was something like this:—

Fury said to a mouse, That he met in the house,
"Let us both go to law:I will prosecute YOU—Come, I'll take no denial; We must have a trial:For really this morning I've nothing to do."
Said the mouse to the cur, "Such a trial, dear Sir, With no jury or judge, would be wasting our breath."
"I'll be judge, I'll be jury, Said cunning old Fury:
"I'll try the whole cause, and condemn you to death.'

SVGo Examples



hello.go



SVGo



rl.go



concentric.go



concentric2.go




cgrid.go




diag.go



shining.go



mondrian.go



richter.go



eclipse.go



pacman.go



pyramid.go



cloud.go



color-clouds.go



creepy.go



d4h.go



sunearth.go



conception.go



conception2.go



randbox.go




randspot.go




cube.go



schotter.go




randarc.go



reurse.go



clock.go




plotfunc.go




therm.go



pattern.go



marker.go



gradient.go




fontrange.go



uni.go



lorem.go



rotate.go



rottext.go



skewabc.go



gear.go



star.go



starx.go



swoosh.go



textpath.go



imfade.go



fe.go



artist.go



go.go

codepicdeck

```

package main

import (
    "fmt"
    "github.com/ajstarks/svggo"
    "os"
)

func main() {
    xp := []int{50, 70, 70, 50, 30, 30}
    yp := []int{40, 50, 75, 85, 75, 50}
    xl := []int{0, 0, 50, 100, 100}
    yl := []int{100, 40, 10, 40, 100}
    bgcolor := "rgb(227,78,25)"
    bkcolor := "rgb(153,29,40)"
    stcolor := "rgb(65,52,44)"
    stwidth := 12
    stylefmt := "stroke:%s;stroke-width:%d;fill:%s"
    canvas := svg.New(os.Stdout)
    width, height := 500, 500
    canvas.Start(width, height)
    canvas.Def()
    canvas.Gid("unit")
    canvas.Polyline(xl, yl, "fill:none")
    canvas.Polygon(xp, yp)
    canvas.Gend()
    canvas.Gid("runit")
    canvas.TranslateRotate(150, 180, 180)
    canvas.Use(0, 0, "#unit")
    canvas.Gend()
    canvas.Gend()
    canvas.DefEnd()
    canvas.Rect(0, 0, width, height, "fill:"+bgcolor)
    canvas.Gstyle(fmt.Sprintf(stylefmt, stcolor, stwidth, bkcolor))
    for y := 0; y < height; y += 130 {
        for x := -50; x < width; x += 100 {
            canvas.Use(x, y, "#unit")
            canvas.Use(x, y, "#runit")
        }
    }
    canvas.Gend()
    canvas.End()
}

```



shining.go [8]

```

package main

import (
    "os"
    "github.com/ajstarks/svggo"
)

var (
    canvas = svg.New(os.Stdout)
    width  = 500
    height = 500
)

// Piet Mondrian - Composition in Red, Blue, and Yellow
func main() {
    w3 := width / 3
    w6 := w3 / 2
    w23 := w3 * 2
    canvas.Start(width, height)
    canvas.Gstyle("stroke:black;stroke-width:6")
    canvas.Rect(0, 0, w3, w3, "fill:white")
    canvas.Rect(0, w3, w3, w3, "fill:white")
    canvas.Rect(0, w23, w3, w3, "fill:blue")
    canvas.Rect(w3, 0, w23, w23, "fill:red")
    canvas.Rect(w3, w23, w23, w3, "fill:white")
    canvas.Rect(width-w6, height-w3, w3-w6, w6, "fill:white")
    canvas.Rect(width-w6, height-w6, w3-w6, w6, "fill:yellow")
    canvas.Gend()
    canvas.Rect(0, 0, width, height, "fill:none;stroke:black;stroke-width:12")
    canvas.End()
}

```



mondrian.go [9]

```

package main

import (
    "os"
    "github.com/ajstarks/svg"
)

var (
    canvas = svg.New(os.Stdout)
    width  = 500
    height = 500
)

func tro() {
    canvas.Rect(100, 100, 100, 100)
    canvas.TranslateRotate(100, 100, 30)
    canvas.Grid(0, 0, width, height, 50, "stroke:lightsteelblue")
    canvas.Rect(0, 0, 100, 100, "fill:red")
    canvas.Gend()
}

func main() {
    canvas.Start(width, height)
    canvas.Grid(0, 0, width, height, 50, "stroke:lightsteelblue")
    tro()
    canvas.End()
}

```



rotate.go [36]

```

package main


import (
    "os"
    "github.com/ajstarks/svg"
)

var (
    canvas = svg.New(os.Stdout)
    width  = 500
    height = 500
)

func main() {
    a := 1.0
    ai := 0.03
    ti := 10.0

    canvas.Start(width, height)
    canvas.Rect(0, 0, width, height)
    canvas.Gstyle("font-family:serif;font-size:244pt")
    for t := 0.0; t <= 360.0; t += ti {
        canvas.TranslateRotate(width/2, height/2, t)
        canvas.Text(0, 0, "s", canvas.RGBA(255, 255, 255, a))
        canvas.Gend()
        a -= ai
    }
    canvas.Gend()
    canvas.End()
}

```



rottext.go [37]





The new masters of our universe are people who are essentially only half-educated.




They have had no exposure to the humanities or the social sciences, the academic disciplines that aim to provide some understanding of how society works, of history and of the roles that beliefs, philosophies, laws, norms, religion and customs play in the evolution of human culture

John Naughton, The Guardian, 19 November, 2017




dchart: charts for deck






```
# AAPL Volume
2017-09-01    679.879
2017-10-01    504.291
2017-11-01    600.663
2017-12-01    531.184
2018-01-01    659.181
2018-02-01    927.894
2018-03-01    713.728
2018-04-01    666.154
2018-05-01    617.408
2018-06-01    527.298
2018-07-01    393.691
2018-08-01    163.768
```

```
<deck>
  <slide>
    <text ...>AAPL Volume</text>
    <line ... color="lightsteelblue"/>
    <text ... color="rgb(127,0,0)">563.1</text>
    <text ... color="rgb(75,75,75)">2017-01-01</text>
  </slide>
</deck>
```




data | dchart | pdf

AAPL Volume



dchart AAPL.d



dchart -left=20 -right=80 -top=75 -yaxis -xlabel=2 -grid AAPL.d

Chart Types

-bar	bar chart (default true)
-wbar	word bar chart (default false)
-hbar	horizontal bar chart (default false)
-scatter	scatter chart (default false)
-dot	dot plot (default false)
-line	line chart (default false)
-vol	volume plot (default false)
-pgrid	proportional grid (default false)
-pmap	proportional map (default false)
-donut	donut chart (default false)
-radial	radial chart (default false)

Chart Elements

-grid	show gridlines on the y axis (default false)
-frame	show a frame around the chart (default "rgb(127,127,127)")
-datacond	conditional data colors (low,high,color)
-val	show values (default true)
-valpos	value position (t=top, b=bottom, m=middle) (default "t")
-pct	show computed percentage with the values (default false)
-yaxis	show a y axis (default true)
-yrange	specify the y axis labels (min,max,step)
-fulldeck	generate full deck markup (default true)
-title	show the title (default true)
-charttitle	specify the title (overriding title in the data)
- xlabel	x axis label interval (default 1, 0 to suppress all labels)
-xlast	show the last x label
-hline	horizontal line at value with label
-rline	show a regression line (default false)
-note	show annotations (default true)

Position and Scaling

-top	top of the plot (default 80)
-bottom	bottom of the plot (default 30)
-left	left margin (default 20)
-right	right margin (default 80)
-min	set the minimum value
-max	set the maximum value
-dmin	data minimum (default false, min=0)

Measures and Attributes

-barwidth	barwidth (default computed from data size)
-linewidth	linewidth (default 0.2)
-ls	linespacing (default 2.4)
-textsize	text size (default 1.5)
-color	data color (default "lightsteelblue")
-vcolor	value color (default "rgb(127,0,0)")
-volop	volume opacity (default 50)
-framecolor	frame color (default "rgb(127,127,127)")
-rlcolor	regression line color (default "rgb(127,0,0)")
-datafmt	data format for values (default "%.1f")
-noteloc	annotation location: c-center (default), r-right, l-left
-psize	diameter of the donut (default 30)
-pwidth	width of the donut or proportional map (default 3)
-pmlen	pmap label length (default 20)
-spokes	show spokes on radial charts (default false)

CSV

-csv	read CSV files (default false)
-csvcol	specify the columns to use for label,value

```

package main


import (
    "fmt"
    "math"
)

func main() {
    fmt.Println("# y=sin(x)")
    for x := 0.0; x < math.Pi*2; x += 0.1 {
        fmt.Printf("%.2f\t%.4f\n", x, math.Sin(x))
    }
}

```


	# y=sin(x)
0.00	0.0000
0.10	0.0998
0.20	0.1987
0.30	0.2955
0.40	0.3894
0.50	0.4794
0.60	0.5646
0.70	0.6442
0.80	0.7174
	...
5.80	-0.4646
5.90	-0.3739
6.00	-0.2794
6.10	-0.1822
6.20	-0.0831

$y=\sin(x)$




sine | dchart -val=f -bottom=50 -xlabel=10

$y=\sin(x)$




sine | dchart -val=f -bottom=50 -xlabel=10 -bar=f -color=steelblue -vol




```
#!/bin/sh
mopts="-fulldeck=f -bar=f -vol -top=90 -bottom 60 -left=20 -right=80 -val=f -title=f"
mfunc -f sine | dchart $mopts -color=steelblue -xlabel=10
mfunc -f cosine | dchart $mopts -xlabel=0 -color=orange
```

A record 64 million Americans live in multigenerational households


The number and share of Americans living in multi-generational family households have continued to rise, despite improvements in the U.S. economy since the Great Recession. In 2016, a record 64 million people, or 20% of the U.S. population, lived with multiple generations under one roof, according to a new Pew Research Center analysis of census data.



% of Americans in multigenerational households



Total Asian Black Hispanic Other White



Tech Stock Performance

July 2017 - July 2018

Apple

Amazon.com

Facebook

Alphabet

Microsoft

AAPL

AMZN

FB





GOOG

MSFT


Closing Price




Volume



Evolution of Baby Names in the US: 1880-2015



Evolution of Baby Names in the US: 1880-2015



What is it about Go?

fmt

func

io.Reader

io.Writer

net/http

encoding/xml

encoding/json

encoding/csv

cgo

The Community

From: Russ Cox
Subject: Re: [go-nuts] Visualizing Random Number Generators...
Date: March 5, 2010 1:14:44 EST
To: ajstarks <ajstarks@gmail.com>

are you going to share the library
or just tease us with pictures? ;-)

Thompson wanted to create a comfortable computing environment constructed according to his own design, using whatever means were available

Dennis M. Ritchie, 'The Development of the C Language'

Go is not the process of some Whiggish development process. We were just trying to get something that worked for us


Rob Pike, 'Origin of Go's interface design', golang nuts

Making Tools

Reducing the distance from
the idea to the picture




Picasso



Turing


Thank you



@ajstarks




ajstarks@gmail.com



github.com/ajstarks



speakerdeck.com/ajstarks



flickr.com/photos/ajstarks