

- If we had re-reading (i.e., regression) data, we would also have to run an analysis using the *glmer* function on those data. The code would look like:

```
model.full <- glmer(Regressions ~ Context * Sentence + (1 + Context * Sentence |  
Subject) + (1 + Context * Sentence | Item), data = RO, family = binomial)
```

- To generate the pairwise comparisons (and to report the descriptives using the original measurement scale), we would use:

```
emmeans(model.full, pairwise ~ Context * Sentence, adjust = "none", type =  
"response")
```

- If we did not set the `type` parameter, then the descriptives would be on a log odds ratio scale (and harder to interpret).

# Citing Packages

Remember to cite the packages you use, plus the version of R itself (with year info.) To find out how to cite a particular package, type:

```
> citation ("lme4")
```

To cite lme4 in publications use:

```
Douglas Bates, Martin Maechler, Ben Bolker, Steve Walker (2015). Fitting Linear Mixed-Effects Models  
Using lme4. Journal of Statistical Software, 67(1), 1-48. doi:10.18637/jss.v067.i01.
```

And to find out which version of R you are using:

```
> version
```

platform	x86_64-apple-darwin15.6.0
arch	x86_64
os	darwin15.6.0
system	x86_64, darwin15.6.0
status	
major	3
minor	4.3
year	2017
month	11
day	30
svn rev	73796
language	R
version.string	R version 3.4.3 (2017-11-30)
nickname	Kite-Eating Tree