



This repository

Search

Pull requests

Issues

Gist



ajstewartlang / Affective-Theory-of-Mind-Inferences

Watch

0

Star

0

Fork

0

Code

Issues 0

Pull requests 0

Projects 0

Wiki

Pulse

Graphs

Settings

Branch: master

Find file

Copy path

Affective-Theory-of-Mind-Inferences / Expt 1 Script and data / Expt1\_AngerFear\_script.R

ajstewartlang Tidied up code with consistent labelling

de7b584 3 hours ago

0 contributors

59 lines (46 sloc) | 3.17 KB

Raw

Blame

History



```
1 library(lme4)
2 library(lmerTest)
3 library(lsmmeans)
4 library(pbkrttest)
5 library(readr)
6 library(ggplot2)
7
8 #script for AngerFear RT and accuracy data analysis with arousal
9
10 #this is the analysis of the RT data
11 AngerFearRT <- read_csv("~/AngerFearRT.csv")
12
13 AngerFearRT$StoryEmotion <- as.factor(AngerFearRT$StoryEmotion)
14 AngerFearRT$FaceExpression <- as.factor(AngerFearRT$FaceExpression)
15
16 contrasts(AngerFearRT$StoryEmotion) <- matrix(c(.5, -.5))
17 contrasts(AngerFearRT$FaceExpression) <- matrix(c(.5, -.5))
18
19 #with Subject, Vignette, and Face as crossed random effects with arousal
20 #full model does not converge so need to drop interaction term from the random effects - in addition, Face random effect has only random in
21 modelRTAr1 <- lmer(RT ~ StoryEmotion*FaceExpression*Arousal + (1+StoryEmotion+FaceExpression|Subject) + (1+StoryEmotion+FaceExpression|Vig
22 summary(modelRTAr1)
23 modelRT <- lmer(RT ~ StoryEmotion*FaceExpression + (1+StoryEmotion+FaceExpression|Subject) + (1+StoryEmotion+FaceExpression|Vignette) + (1
24 anova(modelRTAr1, modelRT)
25
26 #difference between models not signif - arousal does not interact with effect so drop arousal from subsequent analysis
27
28 modelRTnull <- lmer(RT ~ (1+StoryEmotion+FaceExpression|Subject) + (1+StoryEmotion+FaceExpression|Vignette) + (1+FaceExpression|Face),
29 anova(modelRT, modelRTnull)
30 summary(modelRT)
```

# This is GitHub Desktop

