


Accelerated Visualization of Transparent Molecular Surfaces in Molecular Dynamics

Adam Jurcik, Jiri Sochor, Barbora Kozlikova (Masaryk University)
Julius Parulek (University of Bergen)

PacificVIS 2016
April 19, Taipei



Protein Surfaces in Biochemistry

- Proteins – in all living cells
- Protein features – delimited by surfaces
 - Molecular surface – pockets
 - Transport pathways – tunnels
 - Closed voids – cavities
- Molecular Dynamics
 - Simulation of natural motion
 - Surfaces **change**




Molecular Surface

- Solvent Accessible [Lee et al. '71]
 - Spherical patches
- Solvent Excluded [Connolly '83]
 - Spherical patches
 - Toroidal patches
 - Spherical triangles
 - reentrant



Transparent Molecular Surface


- Molecular surface using OIT [Kauker et al. '13]
 - Fragments of all atom spheres
 - CSG operations on fragments
 - **Correct** transparency
 - **High** depth complexity
 - 188 layers/10000 atoms



Our Accelerated Method


Idea: Compute and render only surface

- Method overview:
 - 1) Parallel SES computation
 - 2) Surface components analysis
 - 3) SES patches ray-casting
- Visual enhancements:
 - Cavity coloring by area
 - Opacity modulation




Contour-Buildup Algorithm

- Contour-buildup algorithm [Totrov et al. '96]
 - Accelerated and **localized** computation
- Parallelization
 - Multiple CPUs [Lindow et al. '10]
 - Single GPU [Krone et al. '11]
- Rendering SES using transparency
 - Surface of cavities – possible occlusion




Surface Graph

- Ideas:
 - Surfaces = isolated connected components (CC)
 - Spherical patches are enclosed with tori
 - Tori connect triangles
- Algorithm:
 - 1) Build adjacency list
 - 2) Find CCs – use BFS
 - 3) Find circles for patches





Extended GPU Contour-Buildup I

- Surface graph
 - Extraction of all SES patches
 - Extraction of inner cavities
 - Improved memory efficiency – contour arcs are stored in a hash table



Extended GPU Contour-Buildup II

- Ray-casting
 - Improved performance of ray-casting individual SES patches using OBBs



Results I

- Transparent SES visualization:
 - Static and dynamic structures – PDB ID
 - SES probe size = 1,4 Å

Results II

- Performance comparison
 - Resolution: 1024 x 768
 - GPU: NVIDIA GF GTX 680

		Our method		Kauker et al.		
PDB ID	Atoms	DL	FPS	DL	FPS	Speedup
1OGZ	~650	12	48.1	117	31.0	1.55
1VIS	~2500	15	34.1	135	11.2	3.04
4ADJ	~10000	19	15.5	188	6.2	2.50

Summary

- Contribution
 - Accelerated transparent dynamic SES visualization
 - Improved memory efficiency
- Limitations
 - Uneasy to perceive transparency in still images
 - Unable to detect open pathways – tunnels
- Future work
 - Detection and coloring of tunnels
 - (Employment of efficient BFS algorithm)

Thank you for your attention!