

Network Attacking Techniques

Network Security (NETSEC)

Yuhong Li

Outline

- Attacking means and procedure
- Information collection
- Network hiding
- Port and vulnerability scanning
- Actualizing attacks
- Backdoor setting and log cleaning



Network Attacking Means and Procedure


Network attacking

- Network attacking
 - Actions that harm the networks
 - Disclose information, destroy integrity, deny services, non-authorized access ...
- Basic features
 - Using certain tools
 - Having certain affects



Network attacking means

- Network scanning (reading, incl. interception)
- Operation (modification, fabrication)
- Masquerade/Spoofing: IP spoofing, ARP spoofing, DNS spoofing, phishing
- Flooding (exhausting the resources, interruption)
- Redirection (ARP redirect)
- Rootkits techniques





Information Collection




Information collection

- Preparation for attacks: collecting various information of target hosts or networks
 - Network access methods: dial-in, wireless LAN, Ethernet, VPN etc.
 - Target network information: domain name, IP range, physical location etc.
 - Network topology: router/switch types, manufactures, transmission networks etc.
 - User information: email, user account, passwords etc.
 - Personal information: occupation, contact, ...
- Approaches
 - Searching engine: google, bing, ...
 - Tools: whois, netdiscover, dnsmap, dnswalk, dig,
 - Social engineering: social information

Example: whois enquiry

- Detail information about IP, DNS
- ICANN's ASO(Address Supporting Organization)
- Regional Internet Registry-RIR, National Internet Registry-NIR
 - IP addresses (address ranges) are kept in databases of NIR or RIR
 - Each RIR knows who manages the IP address ranges
- Select any whois server
 - http://www.whois365.com/



Other tools

- Send query request to the target server
 - host, dig, nslookup dig domain +trace
- Network scanning
 - netdiscover
 - nmap
 - dnsmap
 - dnsdict6
- Brute force enumerate
 - dnsenum: recursive enumerate all the subdomains and hosts in the subdomain dnsenum [-r] [-f/usr/share/dnsenum/dns.txt] domain name
 - Dnsrecon: domain name collection tool
 - Fierce:scan target IP and hosts names, including find the domain names by inverse look up



netdiscover by using ARP

```
Currently scanning: (passive)
                                                                                            Screen View: ARP Request
root@kali:~# netdiscover --help
netdiscover: invalid option -- '-'
                                                  37915 Captured ARP Request packets, from 14387 hosts.
                                                                                                                   Total size: 2275188
Netdiscover 0.3-pre-beta7 [Active/passive arp reconnais
                                                                     At MAC Address
                                                                                            Requests IP
                                                                                                               Count
Written by: Jaime Penalba < jpenalbae@gmail.com>
                                                   192.168.1.232
                                                                     9c:14:63:53:84:d9
                                                                                            192.168.1.1
                                                                                                                  181
                                                                     fc:4d:d4:f8:84:f8
Usage: netdiscover [-i device] [-r range | -l file | -: 192.168.2.156
                                                                                            192.168.2.110
                                                                                                                  303
                                                                     ac:cb:51:03:30:c0
                                                   192.168.1.64
                                                                                            192.168.1.1
                                                                                                                  187
 -i device: your network device
 -r range: scan a given range instead of auto scan. 1:192.168.2.156
                                                                     fc:4d:d4:f8:84:f8
                                                                                            192.168.2.111
                                                                                                                  261
 -1 file: scan the list of ranges contained into the (192.168.2.156
                                                                     fc:4d:d4:f8:84:f8
                                                                                            169.254.169.254
                                                                                                                   10
                                                                     d8:38:0d:cb:3d:dc
                                                                                            192.168.101.107
                                                                                                                   72
                                                   192.168.101.4
 -p passive mode: do not send anything, only sniff
                                                  192.168.1.131
                                                                     44:47:cc:99:bd:cc
                                                                                            192.168.1.1
                                                                                                                  187
 -m file: scan the list of known MACs and host names
 -F filter: Customize pcap filter expression (default 10.72.38.4
                                                                     00:50:ba:51:5f:57
                                                                                            10.11.248.51
 -s time: time to sleep between each arp request (mil] 10.72.38.5
                                                                     00:50:ba:51:5f:58
                                                                                            10.11.248.52
                                                  10.72.38.6
                                                                                            10.11.248.53
                                                                     00:50:ba:51:5f:59
 -n node: last ip octet used for scanning (from 2
                                                   10.72 38 7 AA.5A.ha.51.5f.
                                                                     AA.5A.ha.51.5f.5a
 -c count: number of times to send each arp reques
                                                                                              Screen View: Unique Hosts
                                                   10.7
 -f enable fastmode scan, saves a lot of time, recomme
                                                        3 Captured ARP Reg/Rep packets, from 3 hosts.
                                                                                                           Total size: 180
 -d ignore home config files for autoscan and fast mod
                                                   10.7
 -S enable sleep time supression between each request
                                                   10.7
                                                                         At MAC Address
                                                                                              Count
                                                                                                             MAC Vendor
 -P print results in a format suitable for parsing by
                                                   10.7
 -N Do not print header. Only valid when -P is enabled.
                                                        192.168.100.1
                                                                         00:50:56:c0:00:08
                                                                                                             VMware, Inc.
 -L in parsable output mode (-P), continue listening after
                                                        192.168.100.2
                                                                         00:50:56:fa:d6:4e
                                                                                                             VMware, Inc.
                                                        192.168.100.254 00:50:56:fc:4f:d5
                                                                                                             VMware, Inc.
If -r, -l or -p are not enabled, netdiscover will scan for
                                                       root@kali:-#
```




Social engineering

- Collecting information from people
- Information source
 - Professionist: information about an area
 - Staffs related to the target networks: analysis from other "unuseful" information
 - garbage collection: obsolete devices, media, files ...
- Maltego
 - Highly automated information collecting tool
 - DNS severs, IP addresses, sub-domains, personal information
 - Cross platform
 - Graphical user interface (GUI)



Network topology determination

Neotrace: graphical network path tracing tools, integrated
 IP address location, Whois and map



Eavesdropping/Snooping

- Intercept SMTP, HTTP, FTP, POP3,
 TELNET messages (not encrypted)
- Network listener/sniffer
 - Listen to drivers: intercept data streams, filter them and cache
 - Capture drivers: control the network card to receive data, and put in cache
 - Cache: store the captured data
 - decryption: decrypt the obtained data
 - Data analyzer: pattern matching and analysis to the obtained data
- Tools: Wireshark、IRIS、Tcpdump/Windump、Sniffer Pro
- More tools: Cain&Abel, p0f, driftnet, ferret
- Protection from eavesdropping and snooping
 - Check if a network card in network working in the promiscuous mode
 - Use encrypted protocols
 - Secure network topology

packet sniffer packet application (e.g., www application analyzer browser, ftp client) operating Transport (TCP/UDP) system Network (IP) packet copy of all Ethernet capture Link (Ethernet) (pcap) Physical to/from network

Summary

- Whois enquiry: IP Whois, DNS Whois, Whois reverse query, IP2Location, IP2Domain
- Collection based on DNS servers: host, dig, dnsenum, dnsrecon, fierce
- Searching IP addresses in internal networks: ICMP searching, ARP searching, UDP/TCP query
- Mining based on WEB
- Social engineering
- Determine the target network topology: traceroute, Zenmap, Neotrace
- Network sniffing: Cain&Abel, p0f, driftnet and ferret




Network Hiding

Network hiding

- Hide own IP address -> cannot be traced after attacking
- IP spoofing
 - TCP/IP does not check source IP address; bypass the blacklist in ACL
- MAC spoofing
 - Change the MAC address to permissible ones
- Using agents
 - Visiting or collecting data through (multiple) agents,
- Impersonate a user
 - Eavesdropping or break account or password of users
- zombies
 - Control zombies to attack other machines

IP spoofing -1


- TCP/IP only check the validity of destination IP: change IP and bypass the host's or network's access control
- Relative easy when C and A are in the same LAN
- When C and A are not in the same LAN, UDP spoofing is relatively easy





IP spoofing -2

- If A and B use TCP, a little complex for the attacker C
- Procedure
 - Stop A's receiving data
 - Guess the ISN (initiating sequence number)
 - Time-dependent
 - Random
 - Fixed
 - Established a deceiving connection to B





Countermeasures

- Prerequisite: identify a host by its IP address + successfully guess the ISN
- Countermeasures
 - Use encryption-based protocols, e.g., IPSec, SSH
 - Use password or certificate for authentication
 - Use random ISN
 - Use packet filtering on routers: make sure source IP addresses is accordant to the network topology
 - Don't use trust policies based on IP addresses

MAC spoofing

- Access control based on MAC
- Access control based on IP and MAC
- Soft modification
 - Card driver reads MAC address from the system and writes it to the hardware's memory
- Hard modification
 - Change the original MAC address stored in ROM



Network address translation (NAT)


- Private address <-> public address, transparent to end users
 - netstat –an
- Static: one to one, fixed
 - Mapping between internal and external networks
- Dynamic: select from an address pool randomly
 - Can be used e.g., for OSPF
- Port address translation (PAT): mapping both IP address and port number
 - Sharing the same IP address, for TCP and UDP communications
 - Address translating table: setup an entry recording the mapping when a communication begins, delate the entry when ends
 - Each entry: bind a session



Hiding through agents

- Agent: "act" on behalf of hosts -> communicate with target hosts indirectly through an agent
 - Separate the direct communication into two segments/processes
 - isolate internal network and external network
 - What will happen if the agent is vulnerable?
- Forward agent
 - Send request to the agent, the agent answers and forwards the request to the destination host
 - Must know the IP address of the agent and the port
- Backward agent
 - Can be seen as the front-end of a server, can be used to protect the sever.
 - The client does not know the exist of the agent

Working procedure





Frequently used proxies

- HTTP agent, normally port 80, 8080
- SSL agent, standard port 443
- HTTP CONNECT agent
- HTTP TUNNEL agent
- FTP agent, normally port 21, 2121
- POP3 agent, normally port 110
- Telnet agent, normally port 23
- Socks agent, standard port 1080
- Tools
 - Burpsuite, ZAP, Sockcaps64, Proxychains, Squid, Subgraph Vega ...



Summary

- TCP-based IP Spoofing: need to guess TCP ISN, relatively difficult
- MAC Spoofing: used in LAN, break the ACL-based access control
- NAT: trace each message based on address translation (static and dynamic)
- Agent: attackers can attack the target machine indirectly
- Multiple agents + zombies: very difficult to trace



Port and Vulnerability Scanning



Network scanning -1

- Technique based on remote service discovery and system vulnerabilities scanning.
 - The open services on the target host (i.e., the ports)
 - The developer of the services and versions
 - OS type and version
 - Vulnerabilities of the services that can be utilized
 - Vulnerabilities of the OS
 - Sensitive information like accounts and passwords
- General steps of network scanning
 - Scan service connections as many as possible -> open services
 - Scan the services -> type and version
 - Scan vulnerability -> attack

Network scanning -2

- Host-based scanning
 - Run on the scanned host
 - Detect the wrong configurations, weak passwords, configurations violating security policies...
 - Need access right to the scanned host: system security scanning based on passive policy
- Network-based scanning
 - Send probing packets to the remote hosts, collect the responses, decoding and analyzing the data
 - System security scanning based on active policy
- According to the purpose of network scanning
 - Port scanning, type and version scanning, vulnerability scanning, weak password scanning, Web vulnerability scanning, configuration scanning.


Port scanning

- To find the open ports and services on the target devices -> preparing for the attacks
- Slow-scanning: irregular and long interval scanning on discrete ports
- Out-of-order scanning: short interval scanning on continuous ports
- TCP-port scanning: connection scanning, SYN scanning, FIN scanning, ACK scanning, NULL scanning, XMAS scanning, TCP window scanning, self-defined scanning
 - System log can only record the connection scanning
- UDP-port scanning



Connection Scanning


 Attempt to setup a TCP connection with the target device by invoking the transport layer API






SYN scanning


• To finish two handshakes when attempting to setup a TCP connection with the target port, no record is made in logs



Dumb scanning

- Need cooperation by a third device with less traffic
- Dumb scanning of IP header
 - A sends consecutive ICMP requests to B, then analyze the ID in the IP header
 - A send connection request (SYN) to the specified port of C, impersonating B
 - If the port is open, C responses B with SYN+ACK.
 - If the port is closed, C responses B with RST.
 - From B's response, i.e., ID in the IP header
 - If the port at C is open, ID increases by a big value, not 1
 - If the port at C is closed, ID increases by 1 regularly





The accuracy is dependent on B, B should have no connection with other devices.

Vulnerability scanning

- To find the security holes in the applications and services in target networks -> key for conducting attacks!
- Vulnerabilities
 - OS: Windows, Linux, Mac OS, Unix
 - Applications and services: types, applications/services, and versions
 - Configurations: systems, applications/services, versions
- Approaches
 - Match the scanning results with known bases
 - Tentative attacks: probe if a security hole exists according to the known features or certain configurations
- Techniques
 - Vulnerability databases
 - Add-ons

Vulnerability databases

- CVE program and platform: https://www.cve.org/ (http://cve.mitre.org/)
 - Common Vulnerabilities and Exposures
 - Unique name to each vulnerability
- American National Vulnerability Database: https://nvd.nist.gov/
- https://vuldb.com/
- https://bugtraq.securityfocus.com/archive
- http://cvescan.com
- https://www.exploit-db.com/
- https://ics-cert.us-cert.gov/advisories
- National Computer Emergency Response Teams (CERTs) around the world (e.g., JP-CERT, CERT-US, and CERT-SE) usually publishes information about the latest critical vulnerabilities.


₩CVE-2021-45472 Detail

RECEIVED

This vulnerability has been received by the NVD and has not been analyzed

Description

In MediaWiki through 1.37, XSS can occur in Wikibase because an external identifier property can have a URL format that includes a \$1 formatter substitution marker, and the javascript: URL scheme (among others) can be used.



References to Advisories, Solutions, and Tools

By selecting these links, you will be leaving NIST webspace. We have provided these links to other web sites because they may have information that would be of interest to you. No inferences should be drawn on account of other sites being referenced, or not, from this page. There may be other web sites that are more appropriate for your purpose. NIST does not necessarily endorse the views expressed, or concur with the facts presented on these sites. Further, NIST does not endorse any commercial products that may be mentioned on these sites. Please address comments about this page to nvd@nist.gov.

Hyperlink	Resource
https://gerrit.wikimedia.org/r/q/l37ece1dfdc80d38055067c9c4fa73ba591acd8bd	
https://phabricator.wikimedia.org/T297570	

Weakness Enumeration

CWE-ID	CWE Name	Source

Change History




Tools

- Shadow Security Scanner: from Russia
- Nessus: system vulnerability scanning and analysis software
 - C/S, graphical interface
 - The server returns scanning results to the client
 - Add-ons: NASL(NESSUS Attack Scripting Language)
- OpenVAS: open vulnerability evaluation system



OpenVAS





Web vulnerability scanning

- Security holes published by OWASP 2013
 - Injection flaw: e.g., SQL, OS, LDAP injection.
 - Wrong authentication and session management: bypass the authentication based on passwords, keys or tokens etc.
 - Cross-site vulnerability: e.g., session-hijacking
 - Insecure, direct object access: download password files, sensitive directories and databases
 - Mistakes in security configuration
 - Sensitive data leak: credit card information
 - Mistakes in access control
 - Fabricated cross-site request: log into the victim's browser (remotely), visit a web site, obtaining the session cookie and ID and other authentication information
 - Using components with known vulnerabilities
 - Unverified redirection: phishing



Tools for web vulnerability scanning -paid

- Accunetix
 - Provide Online scanning
 - Good at SQL injection and XSS
- Appscan, IBM
 - Scan e.g., XSS, HTTP response splitting, falsified parameters, hidden fields processing, buffer overflow
- N-STALKER (originally N-Stealth) https://www.nstalker.com/alliance/
 - WebApp Security Scan to search for vulnerabilities such as SQL Injection, XSS, and known attacks.
 - 39,000 Web Attack Signature database along with a patent-pending Component-oriented Web Application Security Assessment technology



Tools for web vulnerability scanning – free

- Nikto: scanning the known vulnerabilities on web server
- Golismero: Framework for web vulnerability scanning written in Python, integrated tools like Nikto, theharvester, sqlmap, OpenVAS
- VEGA: from Subgraph, Web program security test platform, effective for SQL injection, XSS, sensitive information leak and others
- Skipfish: from google, Web program evaluation tool, fast & low CPU occupation
- Sqlmap: written in Python, specialized for scanning and making use of SQL injection
- W3af: web attacking and evaluating tool written in Python



Summary

- Network scanning: port, vulnerability (web vulnerability)
- Port scanning: full connection, half connection, dump
- Vulnerability scanning: approaches, techniques
- Web scanning



Expected learning outcomes

- Describe the general procedure for performing network attacks
- Understand and explain the basic principles for information collection, network hiding and port and vulnerability scanning
- Acquaint yourself with some tools (the names and their major functions)



Thank you!